

### COMPANY SURGEONS

*Dr. Abbott Skinner, Chf. Med. Officer	St. Paul, Minn.
*Dr. Charles T. Eginton, Asst. to Chf. Med. Officer	St. Paul, Minn.
*Dr. Darrell E. Westover	St. Paul, Minn.
*Dr. John F. Alden	St. Paul, Minn.
*Dr. Ernest R. Anderson	Minneapolis, Minn.
*Dr. Victor E. Ekblad	Superior, Wis.
Dr. Milton Finn	Superior, Wis.
Dr. Fred Johnson	Superior, Wis.
Dr. E. G. Stack	Superior, Wis.
Dr. Raymond J. Spurzem	Anoka, Minn.
Dr. Leroy J. Larson	Bagley, Minn.
*Dr. Einar W. Johnson	Bemidji, Minn.
Dr. T. P. Groschupf	Bemidji, Minn.
Dr. Wm. T. Nygren	Braham, Minn.
Dr. W. W. Will	Bertha, Minn.
Dr. G. E. Larson	Cambridge, Minn.
Dr. G. W. Schossow	Erskine, Minn.
Dr. George A. Sather	Fosston, Minn.
Dr. N. F. Musachio	Foley, Minn.
Dr. C. E. Norberg	Cloquet, Minn.
Dr. Gordon C. MacRae	Duluth, Minn.
*Dr. C. H. Coombs	Cass Lake, Minn.
Dr. R. W. Brockway	Grand Rapids, Minn.
*Dr. John B. Evensta	Grand Rapids, Minn.
Dr. B. S. Adams	Hibbing, Minn.
Dr. Clarence Jacobson	Hibbing, Minn.
Dr. John J. Muller	Hibbing, Minn.
Dr. R. L. Christie	Long Prairie, Minn.
Dr. Paul J. Keith	Milaca, Minn.
Dr. E. G. Hubin	Sandstone, Minn.
*Dr. H. W. Goehrs	St. Cloud, Minn.
Dr. G. H. Goehrs	St. Cloud, Minn.
*Dr. J. F. DuBois	Sauk Centre, Minn.
*Dr. Julian F. DuBois, Jr.	Sauk Centre, Minn.
*Dr. John C. Grant	Sauk Centre, Minn.
Dr. E. N. Peterson	Virginia, Minn.
Dr. J. Arnold Malmstrom	Virginia, Minn.
*Dr. Charles J. Mock	Virginia, Minn.
*Dr. Luther F. Davis	Wadena, Minn.
Dr. O. F. Ringle	Walker, Minn.

\*Designates also Examining Surgeon.

### OPHTHALMIC SURGEONS

(Eye Doctors)

Dr. Edward P. Burch	St. Paul, Minn.
Dr. Charles E. Stanford	Minneapolis, Minn.
Dr. Malcolm A. McCannel	Minneapolis, Minn.
Dr. John E. Power, Jr.	Duluth, Minn.
Dr. T. J. Doyle	Superior, Wis.
Dr. Roger T. Thompson	Superior, Wis.
Dr. W. T. Wenner	St. Cloud, Minn.

**J. CHRISTIANSON,**  
Chief Dispatcher.

**C. W. HAMMER,**  
Chief Dispatcher.

**R. R. McENARY,**  
Trainmaster.

**W. E. RICHTER,**  
Trainmaster.

**W. T. SLOAN,**  
Trainmaster.

**T. G. HOOKER,**  
Trainmaster.

Scanned from the Dean Ogle Collection

# GREAT NORTHERN RAILWAY COMPANY

## MESABI DIVISION TIME TABLE 78

EFFECTIVE 12:01 A. M.

CENTRAL TIME

Tuesday, September 5, 1961

E. F. OVIATT, Superintendent.

R. N. WHITMAN, General Manager.

A. W. CAMPBELL, General Superintendent Transportation.

Printed in U.S.A.

2 WESTWARD

FIRST SUBDIVISION

EASTWARD

Shorts Numbers	Car Capacity		SECOND CLASS		FIRST CLASS		Distance from Duluth	Time Table No. 78			Telegraph Code	Distance from St. Paul	SIGNS	FIRST CLASS		SECOND CLASS	
	Sleepers	Other Tracks	407		19	23		Effective September 5, 1961						24	20	408	
			Daily	Daily	Daily	STATIONS			Daily	Daily				Daily			
J 139	82				L 4.45Pm	L 7.40Am	2.37	DULUTH	DU	159.97	RKDNXB	A 1.50Am	A 7.45Pm				
					A 4.51Pm	A 7.46Am	2.37	BRIDGE SWITCH		157.60		L 1.40Am	L 7.39Pm				

TRAINS BETWEEN ELEVATOR STATION AND DULUTH TERMINAL DEPOT ARE GOVERNED BY NORTHERN PACIFIC, LAKE SUPERIOR DIVISION TIME TABLE

Shorts Numbers	Car Capacity	Distance from Duluth	Stations	Telegraph Code	Distance from St. Paul	Signs	First Class	Second Class
J 136	Yard 5689	3.23	ELEVATOR STATION	BY	156.74	RKPBXC	s 11.34	s 7.30
J 131	32	4.22	SUPERIOR		155.75	PX		
		5.41	25TH ST.		154.56	V		
		8.40	CENTRAL AVE.		151.57			

FIRST CLASS TRAINS BETWEEN CENTRAL AVE. TOWER AND DULUTH TERMINAL DEPOT ARE GOVERNED BY NORTHERN PACIFIC, LAKE SUPERIOR DIVISION TIME TABLE

Shorts Numbers	Car Capacity	Distance from Duluth	Stations	Telegraph Code	Distance from St. Paul	Signs	First Class	Second Class
J 430	Yard 297	8.67	CENTRAL AVE. TOWER	SU	151.30	RIDNPXJ	A 11.24Am	A 7.13Pm
J 125		10.37	SAUNDERS	B	149.60	RIDNPXJ	11.22	7.11
J 121	96 7	13.43	BOYLSTON		146.54	PJ	11.19	7.08
J 113	127 10	18.54	DEHAM		141.43	P	11.13	11.54
J 103	139 3	24.71	POXBORO		135.26	P	11.06	6.56
J 99	4	36.74	NICKERSON	NS	123.23	NP	10.53	6.46
J 96	12	40.65	DUQUETTE		119.32	P	10.49	
J 91	110 14	43.18	KERRICK	K	116.79	DP	10.45	11.16
J 82	135 25	48.93	BRUNO		111.04	P	10.38	11.08
J 76	134 226	57.31	ASKOV	RD	102.66	DP	10.29	6.30
J 67	22	63.17	SANDSTONE	NA	96.80	DINPWX	10.21	6.24
	146 16	71.99	HICKLEY	H	87.98	DP	10.11	10.31
		72.36	HICKLEY TOWER	HT	87.61	DNPI	10.08	10.30
J 59	167 8	80.21	BROOK PARK		79.76	P	9.59	6.07
GA54	16 4	80.54	BROOK PARK JCT.		79.43	PJ	9.58	6.06
GA49	107 28	86.01	HENRIETTE		73.96	P	9.52	10.08
GA43	59 32	91.45	GRASSTON		68.52	P	9.46	5.57
GA40	15	96.72	BRAM	RA	63.25	DP	9.40	5.52
GA38	27	100.15	STANCHFIELD		59.82	P	9.36	9.46
GA33	104 126	102.64	GRANDY		57.33	P	9.32	9.40
GA27	65	107.52	SAMBRIDGE	CG	52.45	DNP	9.27	5.43
GA21	97 45	113.17	ISANTI	IS	46.80	DP	9.17	9.24
GA15	17	119.19	BETHEL	BE	40.78	DP	9.10	5.34
GA 9	82 8	125.34	GEDAR		34.63	P	9.04	9.04
G 13		131.03	ANDOVER		28.94	P	8.59	5.24
		136.99	COON CREEK JCT.	CN	22.98	JRDNPV	L 8.54Am	L 5.19Pm

TRAINS BETWEEN COON CREEK JUNCTION AND NORTHTOWN ARE GOVERNED BY NORTHERN PACIFIC TIME TABLE

TRAINS BETWEEN NORTHTOWN AND ST PAUL ARE GOVERNED BY TWIN CITY TERMINALS TIME TABLE

Shorts Numbers	Car Capacity	Distance from Duluth	Stations	Telegraph Code	Distance from St. Paul	Signs	First Class	Second Class
		159.97	ST. PAUL		22.98		L 8.10Am	L 4.30Pm
		4.0			2.26			
		32.1			56.3			
		3.16			41.9			
		Time Over Subdivision			46.8		2.56	2.26
		Average Speed Per Hour			46.8		56.3	3.27

Westward trains are superior to eastward trains of the same class.  
SEE ADDITIONAL SPECIAL INSTRUCTIONS PAGES 8 THROUGH 11.



**4 WESTWARD THIRD SUBDIVISION EASTWARD**

Station Numbers	Car Capacity		SECOND CLASS	Distance from Sauk Centre	Time Table No. 78 Effective September 5, 1961	STATIONS	Telegraph Calls	SIGNS	SECOND CLASS
	Sidings	Other Tracts	523						Daily Ex. Sun.
.....	.....	.....	L 5.15Am	0.14		PARK RAPIDS JCT.	.....	JPX	A 11.55Am
K-18	39	63	5.55	18.58	0.14	LONG PRAIRIE	NE	D	11.15
K-24	.....	53	6.40	26.44	7.86	BROWERVILLE	VI	D	10.50
K-32	.....	31	7.10	31.82	5.38	CLARISSA	RU	D	10.20
K-36	34	32	7.45	36.51	4.69	EAGLE BEND	GD	D	9.55
K-44	.....	27	8.15	44.02	7.51	BERTHA	BR	D	9.30
K-56	.....	52	A 9.00 L 9.50	56.19	12.17	WADENA	WD	DI	L 9.00 A 8.35
K-70	23	30	10.10	70.44	14.25	SEBEKA	SK	DW	A 8.15
K-79	.....	27	10.30	79.17	8.73	MENAHGA	MH	D	7.50
K-91	30	116	11.05	91.17	12.00	PARK RAPIDS	J	D	7.20
K-103	.....	29	11.35	103.07	11.90	NEVIS	N	D	6.10
K-109	.....	27	11.50	109.32	6.25	AKELEY	AY	D	5.50
K-119	.....	32	12.10Pm	118.81	9.49	WALKER	K	DV	5.20
Y-106	Yard	681	A 1.00Pm	140.38	2.11	N. P. RY. CROSSING	.....	U	.....
			7.45 18.11		19.46	CASS LAKE ★	CS	JBRKDN WXPYO	L 4.30Am
						Time Over Subdivision Average Speed Per Hour			7.25 18.92

**WESTWARD FOURTH SUBDIVISION EASTWARD**

Station Numbers	Car Capacity		Distance from Dormer Jct.	Time Table No. 78 Effective September 5, 1961	STATIONS	Telegraph Calls	SIGNS
	Sidings	Other Tracts					
YC8	.....	.....	0.00		DORMER JCT.	.....	PX
YC7	45	.....	0.29		LUCKNOW	.....	PX
.....	.....	.....	2.03		SHERWOOD JCT.	.....	JXV
YC6	80	60	2.26		BUHL	BU	DPX
.....	.....	.....	3.18		FRAZER YARD	.....	PXV
.....	39	.....	5.71		ELBERN SIDING	.....	PX
YD61	.....	.....	6.14		ST. CLAIR JCT.	.....	JPXV
YD60	.....	.....	6.61		WILPEN JCT.	.....	JPXV
YD59	Yard	150	9.19		EMMERT TOWER ★	.....	PIX
YB31	.....	.....	9.90		NORTH MITCHELL	.....	PX
YB30	.....	.....	10.75		RUBY JCT.	.....	JPXV
YB29	.....	139	11.73		HIBBING	.....	PX
.....	.....	.....	12.31		SCRANTON	.....	IX
YB 25	Yard	1327	15.41		KELLY LAKE ★	KY	BRKDNP WXYJO
YD 64	.....	14	19.43		KEEWATIN	KW	DPX
YD 69	90	45	20.27		MOORE	.....	PX
YD 74	.....	520	25.00		NASHWAUK ★	NK	DPX
YD 76	31	.....	27.08		KEVIN	.....	P
YD 80	.....	375	31.60		CALUMET	CU	JDPXV
YD 82	.....	5	32.48		MARBLE	RB	DPX
YD 86	.....	.....	35.99		HOLMAN JCT.	.....	JPI
YD 87	.....	.....	37.01		TACONITE JCT.	NI	JPV
YD 88	.....	56	38.84		BOVEY	BY	DPX
YD 91	.....	300	41.60		CANISTEO ★	.....	PXY
Y 161	142	178	46.84		GUNN	GU	JPYIX

**WESTWARD FIFTH SUBDIVISION EASTWARD**

Station Numbers	Car Capacity		SECOND CLASS	Distance from Elk River	Time Table No. 78 Effective September 5, 1961	STATIONS	Telegraph Calls	SIGNS	SECOND CLASS
	Siding	Other Tracts	305						Daily Ex. Sunday
G-28	.....	.....	L 7.20Am	0.00		ELK RIVER	ER	JRDNW	A 12.05Pm
<b>TRAINS BETWEEN N. P. RY. JCT. AND ELK RIVER ARE GOVERNED BY N. P. RY. TIME TABLE</b>									
.....	.....	.....	7.22Am	0.74		N. P. RY. JCT.	.....	IV	11.55Am
H-20	29	116	s 8.35	19.16	0.74	PRINCETON	CT	DX	s 11.00
H-29	.....	20	s 9.10	28.58	9.42	PEASE	EA	D	s 10.25
.....	.....	.....	A 9.20Am	32.56	3.98	MILACA JCT.	.....	JP	L 10.10Am
			2.0 16.28			Time Over Subdivision Average Speed Per Hour			1.55 16.96

**WESTWARD SIXTH SUBDIVISION EASTWARD**

Station Numbers	Car Capacity		Distance from Brookston	Time Table No. 78 Effective September 5, 1961	STATIONS	Telegraph Calls	SIGNS
	Sidings	Other Tracts					
Y 213	129	95	.....		BROOKSTON ★	BN	JPXY
YD 11	145	5	10.92		BADEN	.....	P
.....	145	5	24.99		FERMOY	.....	P
YA 12	144	5	39.88		ONEGA	.....	P
YB 25	Yard	1327	50.32		KELLY LAKE ★	KY	BRKDNP OJWYX

Westward trains are superior to eastward trains of the same class on the Third, Fourth, Fifth and Sixth Subdivisions.

SEE ADDITIONAL SPECIAL INSTRUCTIONS PAGES 8 THROUGH 11.

**WESTWARD SEVENTH SUBDIVISION EASTWARD**

Station Numbers	Car Capacity		FIRST CLASS		Distance from Brook Park Jct.	Time Table No. 78 Effective Sept. 5, 1961	SIGNS	FIRST CLASS	
	Sidings	Other Tracks	11	3				12	4
			Daily	Daily					
.....	.....	.....	.....	.....	.....	<b>BROOK PARK JCT.</b>	JP	.....	.....
J48	.....	59	.....	.....	11.39	11.39 MORA	DP	.....	.....
J41	89	31	.....	.....	18.49	7.10 OGILVIE	DP	.....	.....
J28	90	71	.....	.....	30.59	12.10 MILACA	BRDPX	.....	.....
.....	.....	.....	.....	.....	31.23	0.64 MILACA JCT.	PJX	.....	.....
J14	89	38	.....	.....	44.68	13.45 FOLEY	DP	.....	.....
G63	.....	182	L 7.00pm	L 9.42am	58.15	13.47 EAST ST. CLOUD	DNPIX RKDNW BXYO	A 11.31am	A 6.48pm
73	Yard	1501	A 7.08pm	A 9.50am	59.69	1.54 ST. CLOUD	★	L 11.23am	L 6.40pm
			0.08 11.5	0.08 11.5	Time Over Subdivision Average Speed Per Hour			0.08 11.5	0.08 11.5

Westward trains are superior to eastward trains of the same class.  
SEE ADDITIONAL SPECIAL INSTRUCTIONS PAGES 5 THROUGH 11.

**SPECIAL INSTRUCTIONS**

**ALL SUBDIVISIONS**

**1. SPEED RESTRICTIONS GENERAL.**

The following speed limits apply to trains and engines operating under the conditions outlined, unless rules or conditions require a further reduction.

50 MPH—Diesel engines light or with caboose only.

35 MPH—Trains or engines on main routes, actuating the points of spring switches;

Trains or engines thru No. 20 turnouts at following locations.

Saunders .....Crossover	Brookston .....Jct.
Boylston .....Crossover	Brookston .....End Dbl. Trk.
Dedham .....Siding	Paupores .....Siding
Askov .....Siding	Floodwood .....Siding
Hinckley Tower .....Siding	Island .....Siding
Brook Park .....Siding	Swan River .....Jct.
Brook Park Jct. ....Jct.	Swan River .....Siding
Grasston .....Siding	Philbin .....Siding
Coon Creek Jct. ....Jct.	Baden .....Siding
Coon Creek .....Crossover	Fermoy .....Siding
Brookston .....Crossover	Onega .....Siding

30 MPH—On Main lines, when handling following equipment in trains, not in actual service but on own wheels, derricks, cranes, pile drivers, Jordan spreaders, shovels, wedge plows, scale test car, also ore cars series 80000 thru 94250 and air dump cars X-2000 thru X-2096, X-7000 thru X-7049 when such cars are loaded with ore or gravel.

25 MPH—Trains handling logs;  
Trains or engines moving in facing point direction at spring switches without facing point lock;

Trains or engines thru No. 15 turnouts at following locations:

Cent. Ave. Tower .....Crossover	Boylston .....Jct.
Saunders .....Jct.	Bridge 29 .....Gantlet
Br. 1.3 .....End Dbl. Trk.	Gunn .....Jct.

20 MPH—Trains handling the following equipment on Branch Lines or on 6 degree or sharper curves of Main Lines, scale test car, ore cars series 80000 thru 94250, air dump cars X-2000 thru X-2096, X-7000 thru X-7049 when such cars are loaded with ore or gravel.

15 MPH—Trains handling the following equipment on Branch Lines or on 6 degree or sharper curves of Main Lines, derricks, cranes, pile drivers, Jordan spreaders, shovels and wedge plows.

Trains or engines moving thru interlockings against the current of traffic on double track;

Trains or engines thru all other turnouts, except equilateral turnouts, and those shown previously in this item.

1(a). Rule 240-W of the Consolidated Code of Operating Rules is modified to permit handling Great Northern cars 60276 thru 60279, 61500 thru 61524 and 61000 thru 61009 in passenger trains at passenger train speeds.

**2. MOVEMENT OF ENGINES DEAD IN TRAINS.**

Engine 2350 must be handled on rear of freight and mixed trains.

Diesel engines 1 thru 196 or any road switcher unit not equipped with alignment control couplers must be towed as single units. On engines 550 thru 599, coupler alignment control lock blocks must be 'DOWN' when coupled in multiple unit operation.

Following road switcher engines are equipped with alignment control couplers: 200 thru 218; 220 thru 230; 550 thru 599 (lock blocks); 600 thru 699; 700 thru 734; 900 thru 915 and 2000 thru 2035.

Single unit diesel engines, or multiple unit groups (When such groups consist of road freight, road passenger, or engines with alignment control couplers), when towed dead in freight trains, are to be handled not less than five (5) cars nor more than fifteen (15) cars behind the road engine. There should not be more than five (5) units in a group. Additional such units or groups of units must be separated by not less than five (5) cars. When towing diesel engines dead in trains the following speeds must not be exceeded:

MAXIMUM SPEED	ENGINE NUMBER
50 MPH.....	1 thru 10, 14 thru 16, 24 thru 28, 75 thru 162, 165 thru 170
79 MPH.....	350 thru 375, 500 thru 512, 679, 680, 2350
65 MPH.....	All other diesel engine units

3. Except at points where it is necessary to classify trains, open cars loaded with poles, piling, lumber, timber, pipe, or other lading which might shift, should be placed as close as possible to the head end of train, but not next to engine, caboose, occupied outfit car or passenger car. Loaded trailer-on-flat cars are not included in this category. In double track territory, trains handling such cars must use extreme care to avoid slack running in or out when passing or being passed by other trains. In single track territory, trains handling such cars must be at stop when on siding or other track to meet or be passed by other trains, except when have more cars than siding will hold, it is permissible for such trains to pull by each other at restricted speed. Loaded dump cars should not be handled on double track after dark, but if necessary to do so, close watch must be maintained by members of the crew, and if a car dumps its load, train must be stopped at once and protection provided as prescribed by the rules.

4. Brakemen with less than one year of experience should not be used as flagmen except in emergency, and then Superintendent will be notified by wire.

5. When operating snow machines in non-block signal territory no train should be permitted to follow closer than a station apart, when that cannot be done they will be blocked not less than thirty minutes apart.

After severe blizzard or dirt storm, employes on first train over road must exercise care to avoid accident caused by striking drift without first having drifts faced with hand shovels, cutting

in far enough to get beyond the hard snow and giving a perpendicular wall to strike against instead of slope or wedge-like shape. When operating snow dozer, conductor in charge will ride in the dozer.

On snow and dirt dozers every precaution must be taken to see that cage, flangers and wings clear all obstacles when in service and are properly secured when in through trains, and dozers properly turned. Hand screws must be tightened to raise flanger on dozers as high as possible before making a back-up movement, and must not be released until the dozing work is actually to start. Hand screws holding the cage on dozers must be tightened or chains otherwise fastened except when dozer has air in cylinders and is attended by an employe.

6. Due to limited overhead clearance at tunnels and structures, employes are warned to keep off top of cars of extreme height and width when handled in trains and yards, except in emergency. In absence of previous advice on such cars, wire proper officer for instructions.

7. Placarded loaded tank cars handled in through freight or mixed trains shall not be nearer than 6th car from engine, occupied caboose or passenger car.

Cars placarded "Explosives", "Flammable", "Corrosive Liquids", or "Poison Gas" handled in through freight trains, local and mixed trains, shall not be nearer than 16th car from engine, occupied caboose or passenger car.

When length of train will not permit handling of cars as prescribed above—ANY PLACARDED CAR, loaded with above commodities—shall be placed near middle of train, but not nearer than 2nd car from engine, occupied caboose or passenger car.

When switching such cars in terminal yards they must be separated from engine by at least one non-placarded car.

When placarded cars described above are handled in freight trains made up in "blocks" or classifications, placarded car or cars shall be placed near middle of the "block" or classification, but not nearer than 6th car from engine, occupied caboose or passenger car.

When such placarded cars are placed in trains they must not be placed next to each other, next to refrigerators equipped with gas-burning heaters, stoves or lanterns, or next to loaded flat cars, or gondola cars containing lading higher than ends of car that is liable to shift.

Carload express shipments of explosives, sealed and placarded, may be handled on passenger trains; LCL shipments may be made in so-called peddler car with messenger in charge when such car is assigned to the handling of express and baggage exclusively.

Terminal or pick-up points enroute must furnish conductor and engineer Form 250 showing consecutively location in train of all cars placarded "Explosives". At points other than terminals where crews change, notice will be transferred from crew to crew.

Employes will be guided by further instructions governing handling of loaded tank cars, Explosives, Flammables, Corrosive Liquids, and Poison Gas found in I.C.C. Regulations and Consolidated Code Rules 727 and 811.

8. Trains departing from stations, either from siding or main track in trailing point movement actuating points of spring switches, a member of crew must observe indication of governing signal in opposite direction after rear end of train has passed through switch to ascertain if switch points return to normal position. If this signal indicates Stop and no immediate train movement or other cause is evident, report the fact to Superintendent from first available point of communication. During and immediately following snow storms or violent wind storms, spring switches must be operated by hand and relined in normal position before heading out through switch in trailing point movement, actuating switch points, to insure switch is in proper operating condition.

9. Facing point locks on hand operated switches are indicated by a six-inch yellow stripe painted on target staff. Be positive locking device is restored to normal position after using. A running switch must not be made through this type switch.

10. Rule 3(C) of the Consolidated Code of Operating Rules is amended as follows: Employes governed by time service rules must not wear wrist watches while on duty unless such watches are of an approved type. Approved type wrist watches are: Elgin, B. W. Raymond Model, 13/0 size, 23 jewels.

11. Regarding Consolidated Code Rule 103. In addition to complying with the provisions of this rule, members of a crew will be governed by the following: When an engine, with or without cars, is about to move over a public crossing not protected by a watchman, by gates or by crossing signals in operation, a member of the crew must be on the ground at the crossing to provide protection.

12. Before picking up cars of peeled pulpwood from industry at any station, conductor must examine lading; if lading is not protected with woven wire to prevent sliding out on sides, or, when wire is not available, with boards and stakes, then car must not be moved from industry. The fact must be promptly reported by wire to the Superintendent.

13. Whistle Signals for Routes at Junctions and Interlockings:

Routes	Whistles
Main Track .....	2 short, 1 long
Diverging route .....	2 long
Siding .....	4 short
Against current of traffic .....	1 long, 1 short

14. The Consolidated Code of Operating Rules, Edition of 1959, in addition to the following instructions will govern Great Northern employes while operating on Minnesota Transfer Railway Co. and St. Paul Union Depot Company trackage:

(a) All trackage of the Minnesota Transfer Railway Company is defined as a system of tracks within yard limits over which movements must be made at restricted speed and are not authorized by time table or train order, but subject to prescribed signals and rules, or special instructions.

The limits of the St. Paul Union Depot Co. property extend from connection with the Northern Pacific Ry. and Great Northern Ry. tracks at Third Street and connection with the CMStP&P-CB&Q R.R. tracks opposite depot roundhouse on the east, to connection with the CGW Ry. and CMStP&P R.R. tracks at Robert Street on the west.

(b) The time table of the St. Paul Union Depot Company is for information only. Employes of railroads using the tracks of this Company will be governed by current time table of their respective companies only as to arriving and departing time of trains.

(c) Where in the rules of the Consolidated Code reference is made to trains, such rules will also apply to yard movements and engines.

(d) Under Rule 15, the use of torpedoes is prohibited.

(e) Under Rule 11, burning fuseses must not be used except in case of emergency and then only when held in hand and must be extinguished before leaving.

#### THE FOLLOWING RULES APPLY ONLY ON THE ST. PAUL UNION DEPOT COMPANY:

(f) There is no superiority of trains within the limits of St. Paul Union Depot Company property.

(g) Within the limits of the St. Paul Union Depot Company property, trains and engines must move at restricted speed and must not exceed ten (10) miles per hour through crossovers, turnouts and puzzle switches.

The entrance to, and all movements on this property, will be made only on authority of hand signals from switch tenders. No train or engine may foul any track or puzzle switch without authority of hand signals from switch tenders in control of such movements, except that short interior switching movements may be made through crossovers connecting shed tracks when authorized by train director.

Any lead or track may be used for the make-up of trains on authority of train director. The movement of trains should be given preference.

(h) When indicated by the ringing of the bell, flashing of headlight, hand or light signal that a train or engine is ready to move,

the switch tender in charge of the shed track on which the movement is standing will handle as follows: at west end of station the switch tender will control the movement by hand or light signal; at the east end of station the switch tender will inform the train director, who will route the movement by instructions over the public address system. Switch tenders will be governed by these instructions, relaying such instructions by hand or light signal to the next switch tender in the direction of the movement. Each must receive an acknowledgment before signalling the movement. Signals must not be acknowledged or acted upon unless the signal corresponds with instructions from the train director and is definitely understood.

(i) When backing, the back-up air brake valve on passenger trains must be operated by the conductor, except in the movement of empty equipment it may be operated by a competent trainman or yardman. When practicable, conductors must see that trainmen are stationed so hand or light signals may be used in case of any emergency. When backing a train, the engine brake valve must be in running position. An application of the brakes must be made with back-up air brake valve before starting and it must be known that the brakes are in operative condition. Movement must not be started until the proper signal is given. A running test must be made with the back-up air brake valve before the train has moved 300 feet. If the running test is not made within 300 feet the engineer must stop the train and ascertain cause. The speed of train must not exceed eight (8) miles per hour; and train must be under such control that it can be stopped short of train or obstruction, and short of bumping post on stub tracks.

(j) Headlights must be dimmed while on shed tracks.

## FIRST SUBDIVISION

(Main Line)

### 1. MAXIMUM PERMISSIBLE SPEED FOR TRAINS.

Between	Passenger	Freight
Central Ave. Tower and Boylston .....	75 MPH	50 MPH
Boylston and Foxboro .....	60 MPH	40 MPH
Foxboro and Coon Creek Jct. ....	79 MPH	50 MPH

### 2. SPEED RESTRICTIONS.

Duluth Terminal Bridge to G.N. Rices Point and G.N. connection to Seventh Ave. freight house, trains and engines at restricted speed not exceeding .....	20 MPH
Bridge 14.2, Boylston .....	Passenger 35 MPH Freight 10 MPH
Long lead, west end Sandstone Yard.....	15 MPH

### 3. TRAIN REGISTER EXCEPTIONS.

All trains register by ticket at Central Ave. Tower and Coon Creek Jct.

Trains originating at Allouez register by ticket at Saunders.

Eastward freight trains will throw off register check at Saunders giving all information called for in train register except arrival and tie up.

### 4. CLEARANCE PROVISIONS AND EXCEPTIONS RULE 83(B).

(a) At Boylston, Brook Park Jct., trains for which these points are initial stations may proceed on authority of clearance under which such trains arrive.

(b) Mesabi Division clearance received by first class trains and passenger extras at Minneapolis, and by other trains at Minneapolis Jct., will clear train at Coon Creek Jct. when train order signal indicates proceed.

### 5. RESTRICTED CLEARANCES.

Superior, bents under Fifteenth St. viaduct will not clear man on side of car or engine.

### 6. Hinckley, automatic block signal 72.1 governing westward trains, is located on left hand side of main track about 500 feet west of depot.

### 7. SPEED TEST BOARDS.

Engineers shall test speed of their trains passing following point as compared with Speed Table:

Westward, between MP 76 and MP 77 approximately 4 miles west of Hinckley Tower.

Eastward, between MP 77 and MP 76 approximately 3 miles east of Brook Park.

### 8. CROSSOVERS ON DOUBLE TRACK.

Facing Point	Trailing Point
Saunders, east crossover	Central Ave.
Boylston	Saunders, at tower.
	Boylston

### 9. SPRING SWITCHES WITH FACING POINT LOCK.

Dedham .....	siding	Grasston .....	siding
Nickerson .....	siding	Cambridge .....	siding
Askov .....	siding	Bethel .....	siding

Normal position is for main track.

### 10. SPRING SWITCHES WITHOUT FACING POINT LOCK.

Superior, east switch of Eastward and Westward incoming tracks. Normal position is for incoming tracks and all other roundhouse lead switches, when not in use, must be left lined for roundhouse lead.

Elevator "X", east and west of car unloader on unloading track. Normal position of switch west of unloader is for unloading track.

Normal position of switch east of unloader is for runaround track.

### 11. DRAGGING EQUIPMENT DETECTOR INDICATOR.

Eastward trains on Signal 15.6 between Boylston and Dedham. Westward trains on Signal 61.1 between Askov and Sandstone.

### 12. MANUAL INTERLOCKINGS.

Central Ave. Tower .....	N. P. Ry. crossing
Coon Creek Jct. ....	junction with N. P. Ry.

### 13. MANUAL INTERLOCKINGS WITH DUAL CONTROL SWITCHES.

Sandstone .....	east and west yard switch
-----------------	---------------------------

### 14. AUTOMATIC INTERLOCKINGS.

Superior 73rd St., .....	MStP&SSM. RR. Crossing
-----------------------------	------------------------

### 15. Arrange to stop No. 19 daily, except Sunday, at Brook Park at a point accessible to mail messenger so mail pouches can be placed in RPO car door.

### 16. Great Northern Transfers going to Great Northern Rices Point Yard will use C&NW track from bridge switch to switch in C&NW main track leading to new connection to Great Northern Rices Point Yard. Authority to use C&NW track will be given by clear signal at Minnesota Draw.

For movement from Great Northern Rices Point Yard to Superior, authority to use C&NW track must be obtained from Minnesota Draw by telephone—from phone located in booth just north of Birch Street between Great Northern and C&NW tracks—before leaving Rices Point Yard.

## SECOND SUBDIVISION

(Main Line)

### 1. MAXIMUM PERMISSIBLE SPEED FOR TRAINS.

Between	Passenger	Freight
Boylston and Paupores .....	50 MPH	40 MPH
Paupores and Tilden Jct. ....	59 MPH	45 MPH

### 2. SPEED RESTRICTIONS.

Between Home Signals of Interlockings at: ..... 20 MPH  
 Bridge 29, westward.  
 Bemidji.  
 Erskine.

Cass Lake, on all tracks over footwalk crossing located just west of mainline switch to roundhouse ..... 8 MPH

Whistle signal must be sounded as prescribed by rule. Crossing must be cut immediately. When this crossing is blocked by coupling up train, trainmen must remain at the crossing to prevent pedestrians from crawling through the cars.

### 3. TRAIN REGISTER EXCEPTIONS.

Tilden Jct. is register station only for trains directed by train order to register there.

### 4. CLEARANCE PROVISIONS AND EXCEPTIONS RULE 83(B).

At Boylston, Brookston and Gunn, trains for which these points are initial stations may proceed on authority of clearance under which such trains arrive.

All trains must obtain clearance Form A at Cass Lake.

Mesabi Division clearance received at Crookston will clear train at Tilden Jct. Rule 83(B) does not apply at Tilden Jct.

At Soo Jct., Soo Line Trains may proceed to Cass Lake without obtaining clearance Form A.

### 5. SPEED TEST BOARDS.

Engineers shall test speed of their trains passing following point as compared with Speed Table:

Westward, between MP 86 and MP 87 approximately 4½ miles west of Island.

Eastward, between MP 87 and MP 86 approximately 2 miles east of Wawina.

Eastward, between MP 86 and MP 87 approximately 2 miles east of Wilton.

Westward, between MP 87 and MP 86 approximately 3 miles west of Bemidji.

### 6. Cloquet, derails located near east end storage tracks Nos. 1 and 2 are not provided with derail signs.

Cloquet, when setting out cars on either end of No. 1 track be sure cars are shoved down far enough to clear N. P. Ry. crossovers.

Cloquet, cars left on G.N. tracks must not be closer than 60 ft. each way from 10th Street crossing east of depot.

### 7. Grand Rapids, when setting out cars, eastward freight trains will stop and leave train west of west switch; westward trains will stop east of the first public crossing.

Grand Rapids, at Hawkinson Addition Crossing MP 110, trains stopped to make set-outs at Grand Rapids must clear this crossing.

### 8. Lengby, Till Avenue Crossing, just west of depot:

McIntosh, Cleveland Avenue Crossing, 200 ft. east of depot: Industry tracks do not include automatic road crossing protection and all train and engine movements over these crossings on industry tracks must be flagged by trainman on the ground.

### 9. International Refinery, Alford, while switching, do not handle cars over drip pans with brakes set as sparks from brakes create a fire hazard.

Cabooses with fires in stoves not permitted on any of the plant tracks and crews working in the vicinity will refrain from smoking.

Tail hose located in telephone booth must be used on end of cuts shoved to Old No. 1 and Old No. 2 tracks with air coupled

into it so that trainmen taking position on rear car of cut being shoved can control the movement over crossing immediately ahead of the unloading rack, as well as being able to stop cut of cars short of end of these two spur tracks.

### 10. CROSSOVERS ON DOUBLE TRACK.

Facing Point	Trailing Point
State Line, west crossover	State Line, east crossover
Carlton, east crossover	Alford
Cloquet, west crossover	Carlton, west crossover
Brookston, east crossover	Cloquet, east crossover

### 11. SPRING SWITCHES WITH FACING POINT LOCK.

Cass Lake, east yard switch.

Normal position is for main track.

### 12. SPRING SWITCHES WITHOUT FACING POINT LOCK.

Cass Lake, west crossover switch to roundhouse lead  
 incoming roundhouse track  
 outgoing roundhouse track

Normal position is for tracks named.

### 13. DRAGGING EQUIPMENT DETECTOR INDICATOR.

Eastward trains, on signal 30.2 approximately one mile west of Bridge 29.

Westward trains on Signal 28.1 approximately 1 mile east of Bridge 29.

### 14. MANUAL INTERLOCKINGS.

State Line Tower .....	N. P. Ry. crossing
Carlton .....	N. P. Ry. crossing
Erskine .....	MStP&SSM. RR. crossing

### 15. MANUAL INTERLOCKINGS WITH DUAL CONTROL SWITCHES.

Gunn ..... junction with 4th Subdivision

### 16. AUTOMATIC INTERLOCKINGS.

Bemidji .....	N. P. Ry. crossing
Bridge 29 .....	gantlet
Bridge 29:	

Release for westward route on westward track is located in release box at eastward home signal.

Release for eastward route on eastward track is located in release box at westward home signal.

Cranks for hand operation of smashboards are attached by chains to the mechanism.

### 17. CTC—SOO JCT. TO CASS LAKE.

Telephones for communication with the control operator are located at the east end of CTC section and at the spring switch, east end of Cass Lake Yard, 1000 feet west of west end of CTC section. Westward Soo Line trains will call the operator at Cass Lake on phone for authority to enter G.N. main line. The following will govern in case of failure of communications: Soo Line crew will unlock switch and attempt to line for their movement. If switch will line and signal clears, this will be their authority to leave Soo Jct., and proceed to Cass Lake.

## THIRD SUBDIVISION

(Park Rapids Line)

### 1. MAXIMUM PERMISSIBLE SPEED FOR TRAINS.

Between	Passenger	Freight
Park Rapids Jct. and Cass Lake .....	35 MPH	30 MPH

### 2. SPEED RESTRICTIONS.

Between Home Signals of Interlockings at: ..... 20 MPH  
 Park Rapids Jct.  
 Wadena.

### 3. TRAIN REGISTER EXCEPTIONS.

All Third Subdivision trains will register at Sauk Centre.

### 4. CLEARANCE PROVISIONS AND EXCEPTIONS RULE 83(B).

Mesabi Division clearance received at Sauk Centre will clear train at Park Rapids Jct.



5. Cass Lake, normal position south wye switch is for east leg of wye.
6. **AUTOMATIC INTERLOCKINGS.**  
 Park Rapids Jct., 0.52 miles west of ..... N. P. Ry. crossing  
 Wadena, 0.23 miles west of ..... N. P. Ry. crossing

## FOURTH SUBDIVISION

(Gunn-Dormer Jct. Line)

1. **MAXIMUM PERMISSIBLE SPEED FOR TRAINS.**
- | Between                     | Passenger | Freight |
|-----------------------------|-----------|---------|
| Gunn and Emmert .....       | 45 MPH    | 35 MPH  |
| Emmert and Dormer Jct. .... | 35 MPH    | 30 MPH  |
2. **SPEED RESTRICTIONS.**  
 Between Home Signals of Interlockings at ..... 20 MPH  
 Hill Annex Spur. Hibbing.  
 Majorca Mine Spur. North Mitchell.  
 Emmert Tower.
3. **CLEARANCE PROVISIONS AND EXCEPTIONS RULE 83(B).**  
 At Kelly Lake, trains arriving from Sixth Subdivision (Casco Line) destined to Fourth Subdivision (Gunn Line) may proceed to Keewatin on authority of clearance under which such trains arrive.
4. Between Calumet and Oil Spur, located 1.47 miles west of Bovey, main track will be used jointly by G.N. and DM&IR. Rys. and authority for train movements is controlled by G.N. Ry. and G.N. rules and Special Instructions will govern.
5. St. Paul Mine Spur, Third Avenue, Keewatin, trains will not exceed a speed of 12 MPH through the approach circuits of the signal system covering crossing signals for Highway No. 169.
6. Harrison Mine Spur, Nashwauk, trains will not exceed a speed of 12 MPH northbound into the mine or 6 MPH southbound out of the mine through the approach circuits of the signal system covering crossing signals for Highway No. 169 crossing.
7. Telephone in service at Buckeye, Canisteo and Danube Mines switch. Crews coming from Buckeye, Canisteo and Danube Mines will communicate with the dispatcher and know that way is clear on the main track before proceeding with train down the descending grade on both legs of the wye.
8. Block signal located at Mesabi Chief Mine spur normally displays indication, Rule 240(B) and governs movements from spur to main track; after lining switch, if no conflicting movement is evident on main track, movement may be made in accordance with signal indication after complying with Rule 513.
9. Trains and engines will run with the current of traffic between Kelly Lake and Emmert Tower without train orders or clearance, and must keep to the left unless otherwise provided.
10. Between Emmert Tower and DM&IR. Jct. east of Scranton, G. N. double track will be used jointly by DM&IR. trains. G. N. rules and special instructions will govern.
11. Between Wilpen Jct. and St. Clair Jct., and between Buhl and Dormer Jct., DM&IR. trains will use G.N. main track jointly and be governed by G.N. rules and special instructions. Normal position of switches at Wilpen Jct., St. Clair Jct., and Dormer Jct., is for G.N. 4th Subdivision.
12. Between St. Clair Jct. and Chisholm Jct., main track will be used jointly by G. N. and DM&IR. Rys. and authority for train movements is controlled by DM&IR. Ry. and DM&IR rules will govern.
13. Train and engine movements from main line on new Hull Crusher Spur over Kelly Lake road crossing must be protected by a member of the crew due to restricted view approaching this crossing.
14. Susquehanna Shaft, necessary to shove all empties under the head frame, which will not clear a man on top or side of ore car. Crews must stop before shoving under the head frame and brakemen will walk by the shaft to a point where they can give signals in shoving empties onto the tail tracks.  
 When placing empties for shaft loading, fill the north tail track through the crossover first, as an engine will not go over this crossover. Then fill the south tail track. When placing empties for screener loading, fill the south tail track first, then the north tail track as an engine cannot move through the crossover into the south screener tail track.
15. Boeing crude ore unloading pocket, located five (5) feet east of No. 1 tail track switch, Boeing Mine, open between rails and on north side of track. Use caution when working in vicinity of this pocket and walk on south side of track.
16. Signal protection in service at Danube Mine Spur switch and crossover from Balkan Mining Company track to Danube Mine Tracks. Movements over this crossing will be governed by dwarf color-light signals, displaying indication Figure 6 of Rule 240-A or Figure 4 of Rule 240-H except eastward color-light signal for Balkan Mining Company will display Figure 3 of Rule 240-A or Figure 2 of Rule 240-H, all of the Consolidated Code. Normal position of switches is for Balkan Mining Company and for G. N. Ry. track from Danube Mine to washing plant. Signals will clear automatically for Balkan Mining Company and for G. N. Ry. from Danube Mine to washing plant. To obtain signal to crossover the Balkan Mining Company track, G. N. Ry. trainmen should make sure there is no approaching conflicting movement, then line all three switches in the route to clear signal before proceeding. After crossover movement has been made, all three switches must be restored to normal position for Balkan Mining Company track and G. N. Ry. washing plant track.
17. Normal position of Gunn Line Switch at East leg of wye, Kelly Lake, will be for Fourth Subdivision.
18. **CROSSOVERS ON DOUBLE TRACK.**
- | Facing Point | Trailing Point          |
|--------------|-------------------------|
| Hull Crusher | Mahoning                |
| Ruby Jct.    | Agnew                   |
|              | Scranton                |
|              | Hibbing, east crossover |
|              | Hibbing, west crossover |
|              | North Mitchell          |
19. **SPRING SWITCHES WITH FACING POINT LOCK.**  
 Nashwauk, west north storage track switch.  
 west south storage track switch.  
 Calumet, west new yard switch.  
 Canisteo, west new yard switch.  
 Normal position is for main track.
20. **SPRING SWITCHES WITHOUT FACING POINT LOCK.**  
 Kelly Lake, west switch transfer cinder pit track,  
 Normal position is for mallet cinder pit track.  
 roundhouse wye tracks.  
 Normal position east switch is for mallet cinder pit track,  
 south switch is for east leg of wye.  
 west switch is for west leg of wye.  
 Kelly Lake, west wye switch,  
 Normal position is for 4th subdivision.
21. **SEMI-AUTOMATIC INTERLOCKINGS.**  
 Emmert Tower ..... D. M. & I. R. Ry. crossing  
 Calumet, 0.60 miles east of ..... Hill Annex Spur  
 Complete instructions for operation of electric lock and gates at semi-automatic interlocking are located at "Release" boxes.

## 22. AT VIRGINIA.

G. N. Ry. trains to and from Virginia operate via D. M. & I. R. Ry. tracks between Emmert and Virginia.

**SPEED RESTRICTIONS.**

(a) Between Home Signals of Interlockings at: ..... 20 MPH  
D. W. & P., Virmount Tower.  
D. W. & P., Crescent Ave.

(b) Highway No. 53 crossing, 6th Avenue West, leading to Columbia Mine.

Trains must not exceed a speed of 10 MPH through the approach circuits of this crossing.

(c) Trains and engines must stop before passing over crossing U. S. Highway No. 53 leading to depot, and a member of crew on ground at the crossing will protect movement.

## 23. AUTOMATIC INTERLOCKINGS.

Virginia, 0.47 miles west of ..... D. W. & P. Ry. crossing  
1.20 miles west of ..... D. W. & P. Ry. crossing

**FIFTH SUBDIVISION**

(Princeton Line)

## 1. MAXIMUM PERMISSIBLE SPEED FOR TRAINS.

Between ..... Freight  
Elk River and Milaca Jct. .... 20 MPH

## 2. SPEED RESTRICTIONS.

Between Home Signals of Interlocking at Elk River.... 20 MPH

## 3. CLEARANCE PROVISIONS AND EXCEPTIONS RULE 83(B).

At Milaca Jct., trains for which this point is initial station may proceed on authority of clearance under which such trains arrive.

## 4. SEMI-AUTOMATIC INTERLOCKINGS.

Elk River, 0.74 miles west of ..... N. P. Ry. Jct.

**SIXTH SUBDIVISION**

(Casco Line)

## 1. MAXIMUM PERMISSIBLE SPEED FOR TRAINS.

Between ..... Passenger Freight  
Brookston and Kelly Lake ..... 45 MPH 45 MPH

## 2. AUTOMATIC INTERLOCKINGS.

Onega, 5.95 miles west of ..... D. M. & I. R. Ry. crossing

## 3. DRAGGING EQUIPMENT DETECTOR INDICATOR.

Eastward Trains, on iron mast approximately 6400 feet east of Signal 62.2 about 2.5 miles west of Brookston.

**SEVENTH SUBDIVISION**

(Milaca Line)

## 1. MAXIMUM PERMISSIBLE SPEED FOR TRAINS.

Between ..... Passenger Freight  
Brook Park Jct. and East St. Cloud ..... 50 MPH 40 MPH

## 2. SPEED RESTRICTIONS.

Bridge 46.3, Mora ..... 20 MPH  
Bridge 54.2, Quamba ..... 20 MPH  
Between Home Signals of Interlockings at: ..... 20 MPH  
Brook Park Jct.  
East St. Cloud.

## 3. CLEARANCE PROVISIONS AND EXCEPTIONS RULE 83(B).

(a) At Brook Park Jct., trains for which this point is initial station may proceed on authority of clearance under which such trains arrive.

(b) Trains originating at East St. Cloud may proceed without a clearance.

## 4. At St. Cloud, eastward freight trains must know before leaving there that route is clear at N. P. Ry. crossing, East St. Cloud.

## 5. MANUAL INTERLOCKINGS.

East St. Cloud ..... N. P. Ry. crossing

**SPEED TABLE**

Time	Per Mile	Miles	Time	Per Mile	Miles
Min.	Sec.	Per Hour	Min.	Sec.	Per Hour
			1	12	50.0
			1	14	48.6
			1	16	47.4
			1	18	46.2
			1	20	45.0
			1	22	43.9
			1	24	42.9
			1	26	41.9
			1	28	40.9
			1	30	40.0
			1	33	38.7
			1	36	37.5
			1	39	36.4
			1	42	35.3
			1	45	34.3
			1	50	32.7
			1	55	31.3
			2	—	30.0
			2	10	27.7
			2	20	25.7
			2	30	24.0
			2	40	22.5
			3	—	20.0
			3	30	17.1
			4	—	15.0
			5	—	12.0
			6	—	10.0
			7	—	8.6
			8	—	7.5
			9	—	6.7
			10	—	6.0
	46	78.3			
	47	76.6			
	48	75.0			
	49	73.5			
	50	72.0			
	51	70.6			
	52	69.2			
	53	67.9			
	54	66.7			
	55	65.5			
	56	64.3			
	57	63.2			
	58	62.1			
	59	61.0			
1	0	60.0			
1	1	59.0			
1	2	58.1			
1	3	57.1			
1	4	56.3			
1	5	55.4			
1	6	54.5			
1	7	53.7			
1	8	52.9			
1	9	52.2			
1	10	51.4			

**WATCH INSPECTORS**

Yano Bros., 1121 Tower Avenue ..... Superior, Wis.  
Marcus Co., 728 Tower Avenue ..... Superior, Wis.  
Charles Thoele Jeweler, 611 New York Building ..... St. Paul, Minn.  
Oscar P. Gustafson Co., 410 Nicollet Avenue... Minneapolis, Minn.  
Pomerleau & Son, 227 East Hennepin Avenue... Minneapolis, Minn.  
Lindman's Jewelry, Elk's Building ..... Bemidji, Minn.  
Paul E. Teske ..... Hibbing, Minn.  
Geary Jewelry Co. .... Hibbing, Minn.  
Randall's Jewelry & Gift Store ..... Grand Rapids, Minn.  
Weber Jewelry & Music Co.,  
714 St. Germain Street ..... St. Cloud, Minn.

## Business Tracks not shown as stations on Time Table

Name	Location	Car Capacity	Switch Opens
<b>First Subdivision</b>			
North Central Public Service Spur.....	2.25 miles east of Coon Creek Jct.....	7	W
Rural Coop. Power Ass'n Spur.....	2.42 miles east of Cambridge..	6	E
<b>Second Subdivision</b>			
International Refineries.....	Alford.....	45	E
Lindsay Pit.....	1.69 miles west of Carlton....	70	E
Flint Pit.....	2.33 miles east of Brookston..	120	E
Mirbat.....	5.37 miles east of Floodwood..	12	E
Wawina.....	12.90 miles west of Floodwood	11	E
Cohasset Mill & Lumber Co.....	0.37 miles east of Cohasset....	9	E
Minn. Power and Light Spur.....	0.98 miles west of Cohasset....	106	E
Chippewa Wood Processing Spur.....	0.13 miles east of Deer River..	16	W
Webster Lumber Co.....	5.26 miles west of Schley.....	17	E
Farris.....	4.13 miles west of Cass Lake..	15	E & W
Airport Spur.....	2.25 miles west of Bemidji.....	19	W
Minnesota Pipeline Co.....	2.50 miles east of Bagley.....	50	E & W
Dugdale.....	0.90 miles east of Tilden Jct....	12	W
<b>Third Subdivision</b>			
Little Sauk.....	10.24 miles west of Park Rapids Jct.....	5	W
Round Prairie.....	13.70 miles west of Park Rapids Jct.....	12	E & W
Peters Meat Products Spur.....	0.40 miles west of Long Prairie	10	W
Redwood Rendering Co.....	1.61 miles west of Long Prairie	35	E
Midland Co-op. Spur.....	1.68 miles west of Long Prairie	6	E
Hewitt.....	4.03 miles west of Bertha.....	22	E & W
Leaf River.....	4.32 miles west of Wadena....	24	E & W
Land O'Lakes Creamery Spur.....	0.58 miles west of Sebeka.....	19	W
Dorset.....	6.57 miles west of Park Rapids	11	E & W
Leech Lake.....	3.27 miles west of N.P. Ry. Crossing.....	10	E & W
Wilkinson.....	10.12 miles west of N.P. Ry. Crossing.....	8	E & W
<b>Fourth Subdivision</b>			
Coal Spur.....	2.47 miles east of Buhl.....	3	E
Service Station Inc. Spur.....	0.90 miles east of Hibbing....	4	E
Oil Track.....	1.42 miles east of Hibbing....	18	E & W
Douglas Shop Spur.....	2.18 miles east of Emmert....	9	W
Wacootah Storage Track.....	3.67 miles west of Virginia....	25	E & W
Keewatin Saw Mill Spur.....	1.92 miles west of Kelly Lake..	14	E
Mid-Range Builders Supply.....	0.15 miles east of Nashwauk..	7	W
Minn. Power & Light Spur.....	1.09 miles east of Nashwauk..	15	E
Ryan and Gillis Spur.....	0.93 miles west of Kevin.....	29	W
Oil Spur.....	1.19 miles east of Canisteo....	35	W
<b>Fifth Subdivision</b>			
Zimmerman.....	9.50 miles west of N.P. Ry. Jct.	15	E & W
Long's Siding.....	4.05 miles west of Princeton..	4	W
<b>Sixth Subdivision</b>			
Arlberg.....	5.42 miles west of Brookston..	17	E
Casco.....	5.84 miles west of Fermoy....	36	E
<b>Seventh Subdivision</b>			
Quamba.....	5.06 miles west of Brook Park Jct.....	8	E
Kanabec Hdwe. Co. Spur.....	1.0 miles east of Mora.....	5	W
Bock.....	6.88 miles west of Ogilvie....	12	W
R. E. A. Oil Spur.....	0.5 miles east of Milaca.....	3	W
Foreston.....	2.65 miles west of Milaca Jct..	29	E & W
Oaks.....	8.37 miles west of Milaca Jct..	26	E & W
Ronneby.....	11.14 miles west of Milaca Jct.	11	W
Parent.....	4.30 miles west of Foley.....	28	E & W

## Mine Spurs

Name	Location	Switch Opens
Stevenson, Lambertson, Mahoning Concentrate, Warren.....	0.53 miles east of Kelly Lake....	W
Mahoning, N. Uno, Mahoning Grp IV, So. Agnew, Carmi.....	0.72 miles east of Kelly Lake....	W
Hull Crusher.....	1.80 miles east of Kelly Lake....	W
Morton.....	1.98 miles east of Kelly Lake....	E
Scranton, Alworth.....	2.42 miles west of North Mitchell	W
Susquehanna, Weggum, Boeing..	0.03 miles west of North Mitchell	E
Webb, Albany, Longyear.....	0.81 miles east of North Mitchell	E
Dunwoody.....	0.99 miles east of Emmert....	W
Chataco.....	0.74 miles west of Chisholm....	W
Elbern.....	2.87 miles west of Buhl.....	W
Judson, Michael.....	1.35 miles west of Buhl.....	W
Grant.....	1.22 miles west of Buhl.....	W
North Shiras.....	0.78 miles east of Buhl.....	E
Margaret.....	0.96 miles east of Buhl.....	E
Wanless.....	1.38 miles east of Buhl.....	E
Kinney, Atkins, Wade.....	0.68 miles east of Dormer Jct....	E
Elliott Siding.....	1.18 miles east of Dormer Jct....	E & W
Hanna B, Pilot.....	2.64 miles west of Virginia....	E
Enterprise.....	0.83 miles west of Virginia....	E
Columbia.....	0.47 miles west of Virginia....	W
Bennett-Russell, Carlz.....	2.57 miles west of Kelly Lake....	E
St. Paul.....	0.25 miles east of Keewatin....	E
Chieftan.....	0.35 miles west of Moore.....	W
Mesabi Chief Washer, Aromac, Perry, Mississippi.....	1.17 miles west of Moore.....	W
O'Brien.....	1.57 miles east of Nashwauk....	W
Hawkins Fines.....	0.37 miles east of Nashwauk....	E
York, Galbraith.....	0.15 miles east of Nashwauk....	W
Hawkins (MacKilican).....	0.13 miles east of Nashwauk....	E
Harrison, Harrison Fines.....	0.78 miles west of Nashwauk....	W
Patrick A, Patrick C.....	2.26 miles west of Nashwauk....	W
Hill Annex Creta.....	1.38 miles east of Calumet....	E
Hill Annex Washer.....	0.60 miles east of Calumet....	E
Hill Annex Fines, Hill Trumbull Washer.....	0.69 miles east of Calumet....	E
Hill Spur.....	0.37 miles west of Calumet....	E
Rhude Media Spur.....	0.57 miles east of Holman Jct....	E
Arcturas.....	0.25 miles east of Holman Jct....	W
Holman.....	Taconite Jct.....	W
Hunner.....	0.83 miles west of Bovey.....	E
Canisteo, Buckeye, Danube.....	Canisteo.....	E & W
West Hill.....	0.20 miles west of Canisteo....	W
Jessie.....	1.60 miles west of Canisteo....	E
Greenway.....	2.42 miles west of Canisteo....	W
Tioga.....	0.24 miles east of Seyton.....	W

Page 12 (outside rear cover) is blank.