

COMPANY SURGEONS

*Dr. Abbott Skinner, Chief Medical Officer St. Paul, Minn.
*Dr. Charles T. Eginton, Asst. to Chief Medical Officer
St. Paul, Minn.
Dr. James N. Berbos Aberdeen, S. D.
*Dr. Carson B. Murdy Aberdeen, S. D.
Dr. William C. Kaufman Appleton, Minn.
*Dr. R. P. Griffin Benson, Minn.
Dr. Donald F. Holm Benson, Minn.
*Dr. Clarence V. Bateman Breckenridge, Minn.
*Dr. Louis T. O'Brien Breckenridge, Minn.
Dr. C. W. Jacobson Breckenridge, Minn.
Dr. Theodore Greenfield Cokato, Minn.
Dr. Joseph C. Houts Dassel, Minn.
*Dr. A. G. Maercklein Ellendale, N. D.
Dr. Earl E. Suckow Garretson, S. D.
Dr. I. L. Oliver Graceville, Minn.
Dr. M. S. Nelson Granite Falls, Minn.
Dr. Carl L. Lundell Granite Falls, Minn.
Dr. M. L. Ransom Hancock, Minn.
Dr. William H. Thomas Howard Lake, Minn.
*Dr. W. H. Saxton Huron, S. D.
Dr. O. W. Scholpp Hutchinson, Minn.
Dr. V. S. Irvine Lidgerwood, N. D.
Dr. Karl A. Danielson Litchfield, Minn.
*Dr. B. C. Ford Marshall, Minn.
Dr. F. D. Gray Marshall, Minn.
Dr. W. W. Yeager Marshall, Minn.
Dr. J. E. Eckdale Marshall, Minn.
*Dr. Ernest R. Anderson Minneapolis, Minn.
*Dr. Fred W. Behmler Morris, Minn.
Dr. Jack Guy New London, Minn.
Dr. T. J. Bloedel Osseo, Minn.
Dr. C. R. Myre Paynesville, Minn.
*Dr. H. W. Goehrs St. Cloud, Minn.
Dr. G. H. Goehrs St. Cloud, Minn.
Dr. Vernon E. Nells St. Cloud, Minn.
*Dr. John F. Alden St. Paul, Minn.
*Dr. Darrel E. Westover St. Paul, Minn.
*Dr. A. L. McGilvra Sioux Center, Iowa
Dr. Arch F. O'Donoghue Sioux City, Iowa
*Dr. H. E. Rudersdorf Sioux City, Iowa
*Dr. S. A. Donahoe Sioux Falls, S. D.
*Dr. G. Robert Bartron Watertown, S. D.
*Dr. Walter E. Hinz Willmar, Minn.
*Dr. A. M. McCarthy Willmar, Minn.
*Dr. R. P. Michels Willmar, Minn.
Dr. Chester B. McVay Yankton, S. D.

*Designates also Examining Surgeon.

OPHTHALMIC SURGEONS

(Eye Doctors)

Dr. Charles E. Stanford Minneapolis, Minn.
Dr. Malcolm A. McCannel Minneapolis, Minn.
Dr. Edward P. Burch St. Paul, Minn.
Dr. W. T. Wenner St. Cloud, Minn.
Dr. James E. Reeder Sioux City, Iowa
Dr. Sidney F. Becker Sioux Falls, S. D.
Dr. Stanley S. Chunn Willmar, Minn.

ROENTGENOLOGIST

(X-Ray only)

Dr. Rolf M. Iverson Minneapolis, Minn.
Dr. David A. Burlingame St. Paul, Minn.
O. J. LORINSER, Chief Dispatcher.
F. L. HENRY, Trainmaster.
A. D. POWERS, Trainmaster.
P. B. RASMUSSEN, Trainmaster.
A. C. OOTHOUT, Trainmaster.
A. R. McKEEN, Trainmaster.
J. H. BOYD, Asst. Superintendent.
J. G. TOOMEY, Asst. Superintendent.
E. S. PINKERTON, Genl. Supervisor of Terminals.

Scanned from the Dean Ogle Collection.

GREAT NORTHERN RAILWAY COMPANY

WILLMAR DIVISION

TIME TABLE 93

EFFECTIVE 12:01 A. M.

CENTRAL TIME

Sunday, May 10, 1959

H. J. SURLS, Superintendent.

R. N. WHITMAN, General Manager.

A. W. CAMPBELL,
General Superintendent Transportation.

Printed in U.S.A.

2 WESTWARD

FIRST SUBDIVISION

EASTWARD

Station Numbers	Car Capacity		SECOND CLASS	FIRST CLASS					Distance from St. Paul	Time Table No. 93 Effective May 10, 1959	STATIONS	Telegraph Calls	SIGNS	FIRST CLASS					SECOND CLASS
	Sidings	Other Tracks	(326)	31	9	27	185	51						32	28	186	10	52	(325)
			329	Daily	Daily Ex. Sat.	Daily	Daily Ex. Sun.	Daily Ex. Sun.											Daily
0				L 9.10Pm	L 8.45Pm	L 9.30Am				ST. PAUL	A	K	A 7.00Am	A 9.55Pm		A 6.45Am			
11				9.40Pm	9.30Pm	10.03Am		10.57	10.57	MINNEAPOLIS	S	K	6.30Am	9.30Pm		6.20Am			

TRAINS BETWEEN ST. PAUL AND LYNDALE JCT. ARE GOVERNED BY TWIN CITY TERMINALS TIME TABLE.

Station	Yard	Capacity	Time	Time	Time	Time	Time	Time	Station	Code	Code	Time	Time	Time	Time	Time	Time
A 24	W 80	35	L 9.43Pm	L 9.34Pm	L 10.07Am		12.17	12.17	LYNDALE JCT. ★	UD	DNJ PX	A 6.18Am	A 9.15Pm		A 5.59Am		
			9.56	f 9.47	10.20		23.90	23.90	WAYZATA	WA	DNPR	6.00	8.54		s 5.30		
							24.23	24.23	HUTCHINSON JCT.		PJ						
A 27	E 79	19		f 9.51	10.24		27.00	27.00	LONG LAKE	ON	DP	5.56	8.50		s 5.20		
A 32	W 103	19		s 9.59	10.29		31.37	31.37	MAPLE PLAIN	MA	DP	5.51	8.45		s 5.11		
A 39	80	54		s 10.10	10.35		38.36	38.36	DELANO ★	DA	DNP	5.43	8.37		s 4.57		
A 45		23		f 10.18			45.06	45.06	MONTROSE		P				s 4.45		
A 48		26		f 10.21			47.83	47.83	WAVERLY	WY	DP				s 4.38		
A 53	307	59		s 10.32			52.84	52.84	HOWARD LAKE	RD	DP				s 4.29		
A 59	148	155		s 10.44	10.53		59.15	59.15	COKATO	CT	DP		8.15		s 4.17		
A 65	168	86		s 10.56			64.94	64.94	DASSEL	DS	DP				s 4.05		
A 70	47	19		f 11.03			70.04	70.04	DARWIN	DN	DP				s 3.55		
A 76	171	156		s 11.17	s 11.08		76.18	76.18	LITCHFIELD ★	FD	DNP	5.07	s 7.57		s 3.45		
A 84	160	53		f 11.26			83.86	83.86	GROVE CITY	G	DP				f 3.30		
A 89	307	70		f 11.31	11.25		88.99	88.99	ATWATER	WR	DP		7.43		f 3.20		
A 97		33		f 11.38			96.35	96.35	KANDIYOHI	KD	DP				s 3.09		
A 102	Yard	1661	L 11.10	L 11.12	L 11.40	L 11.45	L 1.30Am	L 1.00Am	WILLMAR ★	W	ORDNK BXWZ	L 4.40	L 7.25	A 7.00Pm	L 2.57	A 11.40Pm	
							A 1.05Am	102.66	SIoux CITY LINE JCT.		JPX	A 4.37	A 7.18	A 7.00Pm	A 2.32	L 11.37Pm	
A 109	37	19				s 1.42	108.79	108.79	PENNOCK	K	DP				s 6.45	f 2.23	
A 116	173	47				s 1.55	116.23	116.23	KERKHOVEN	KH	DP				s 6.32	f 2.15	
A 121		32				s 2.05	120.71	120.71	MURDOCK	CK	DP				s 6.23	f 2.07	
A 125	138	39				s 2.15	125.27	125.27	DE GRAFF	DG	DP				s 6.14	f 2.00	
A 133	140	272		11.39	s 12.42	s 12.15Pm	A 2.30Am	132.78	BENSON ★	BN	DNPRK	4.05	s 6.44	L 6.00Pm	s 1.50		
A 138	139	38		s 12.50			138.45	138.45	CLONTARF		P				f 1.23		
A 149	76	49		s 1.04			148.67	148.67	HANCOCK	NC	DP DN YTP				f 1.10		
A 157	400	300		12.01Am	s 1.26	s 12.41	157.52	157.52	MORRIS ★	MR	DP	3.40	s 6.15		s 12.59		
A 166	145	41		s 1.39			165.74	165.74	DONNELLY	DY	DP				s 12.44		
A 176	135	51		s 1.53			176.20	176.20	HERMAN	HR	DP				s 12.30		
A 181	143	30		12.21	s 2.01	1.05	181.09	181.09	NORCROSS	RC	DP	3.16	5.50		s 12.21		
A 187		24					187.56	187.56	CHARLESVILLE		P						
A 193	150	64			s 2.15		192.59	192.59	TINTAH	QN	DP				f 12.08		
			L 10.10Pm		2.18		195.39	195.39	ABERDEEN LINE JCT.		PJ				12.03Am		A 8.50Am
A 200	264	108	s 10.25		f 2.22		199.81	199.81	CAMPBELL ★	CB	DP				f 11.59		s 8.35
A 207		21	s 10.35	12.42	f 2.29	1.32	206.97	206.97	DORAN	OD	DP RDNWB YOKXZ	2.51	5.24		f 11.53		s 8.10
A 214	Yard	1143	A 11.00Pm	A 12.53Am	A 2.40Am	A 1.45Pm	214.85	214.85	BRECKENRIDGE ★	BR	DP	L 2.42Am	L 5.15Pm		L 11.45Pm		L 8.00Am
			.50	3.10	5.06	3.38	1.00	.05	Time Over Subdivision			3.36	4.00	1.00	6.14	.03	.50
			23.35	64.00	39.74	55.78	30.59	5.64	Average Speed Per Hour			56.30	50.67	30.59	32.51	9.4	23.35

Westward trains are superior to eastward trains of the same class.
Automatic Block Signals are in service on this Subdivision.
SEE ADDITIONAL SPECIAL INSTRUCTIONS PAGES 8 THROUGH 15.

4 WESTWARD

THIRD SUBDIVISION

EASTWARD

Station Numbers	Car Capacity		SECOND CLASS		FIRST CLASS		Distance from Willmar	Time Table No. 93			Telegraph Calls	SIGNS	FIRST CLASS		SECOND CLASS	
	Sidings	Other Tracks	419		51			Effective May 10, 1959					52		420	
			Daily	Ex. Sunday	Daily	Ex. Sunday		STATIONS					Daily	Ex. Sunday	Daily	Ex. Sunday
A-102			L 9.30Am		L 1.00Am		W	BDNKOR WXZ	A 11.40Pm		A 9.35Pm	

TRAINS BETWEEN SIOUX CITY LINE JUNCTION AND WILLMAR ARE GOVERNED BY FIRST SUBDIVISION SCHEDULES

			L 9.35Am		L 1.05Am	0.47	JPX		A 11.37Pm		A 9.25Pm	
			9.50		f 1.13	5.97	P		f 11.29		9.16	
I-64	55	12	s 1.23	11.99	RA	DP	s 11.22		9.07	
I-70	50	32	s 1.37	19.55	CA	IDP	s 11.10		8.55	
I-77	116	47						
I-83	61	38	s 1.48	25.48	MY	DP	s 10.59		8.45	
I-87	35	f 1.53	29.21		P	f 10.53		8.35	
I-92	97	130	s 2.08	34.59	GX	DPI	s 10.46		8.23	
I-97	49	11	f 2.15	40.02			f 10.27		8.13	
I-102	58	35	s 2.26	44.22	HY	DPI	s 10.21		8.06	
I-109	50	37	s 2.37	50.39	C	DP	s 10.06		7.57	
I-116	35	s 2.48	57.70	GV	DP	s 9.56		7.45	
I-121	148	144	s 2.56	63.07	MD	DNXP	s 9.47		7.35	
								
								
I-128	51	32	s 3.21	69.76	YD	DP	s 9.27		7.18	
I-134	50	38	s 3.32	76.01	RS	DP	s 9.17		7.09	
I-142	38	s 3.45	83.88	F	DP	s 9.05		6.58	
I-147	100	56	s 3.56	88.89	RV	DP	s 8.55		6.50	
I-155	37	s 4.10	96.73	HD	DP	s 8.42		6.35	
								
I-164	30	69	s 4.47	105.53	NE	DNP	s 8.29		6.20	
I-170	120	35	s 5.00	112.27		P	s 8.08		6.05	
I-175	53	108	s 5.09	116.88	JA	DP	s 7.59		5.55	
I-183	50	35	s 5.24	124.58	FS	DP	s 7.47		5.42	
I-186	145	220	A 5.30Am	127.90	JC	BDNK PRXY	L 7.40Pm		5.35	
IA-7	49		134.11		P			4.58	
IA-17	100	37		145.23	HS	DPI			4.42	
IA-23	100	43		151.65		IP			4.32	
IA-30	101	34		158.55	AD	DP			4.23	
IA-36	50	31		164.24	DO	DP			4.10	
IA-45	19		173.20		P			3.58	
IA-52	100	72		180.78	UX	DNP			3.45	
IA-61	2		188.82		P			3.33	
IA-66	41	29		193.96	SB	DP			3.22	
IA-78	43	51		206.50		P			3.00	
				211.96	GS	DNIP				
IA-85	51	30		213.32	HI	DP			2.50	
IA-97	Yard	A 4.15Pm		222.77	SX	BDNKOW RXZ			L 2.30Pm	
			6.40 33.34		4.25 28.85								3.57 32.26		6.55 32.14	
Time Over Subdivision Average Speed Per Hour																

Westward trains are superior to eastward trains of the same class.
SEE ADDITIONAL SPECIAL INSTRUCTIONS PAGES 8 THROUGH 15.

6 WESTWARD

SEVENTH SUBDIVISION

EASTWARD

Station Numbers	Car Capacity		SECOND CLASS		FIRST CLASS		Distance from Benson	Time Table No. 93			Telegraph Calls	SIGNS	FIRST CLASS		SECOND CLASS	
	Siding	Other Tracks	529	531	185	186		Effective May 10, 1959					186	530	532	
			Daily Ex. Sunday	Daily Ex. Sunday				STATIONS								Daily Ex. Sunday
A133			L 7.55Am		L 2.35Am		0.78	BENSON.....★	BN	BDNPKR	A 5.55Pm		A 8.10Pm			
C 9	34		s 8.00		s 2.37	0.78	0.78	WATERTOWN LINE JCT...	JPY	s 5.53		8.05			
C 16	33		s 8.30		s 2.52	7.88	7.10	DANVERS.....	DR	D	s 5.40		7.50			
C 22	45	167	s 9.00		s 3.06	15.83	7.95	HOLLOWAY.....	OW	D	s 5.27		7.30			
C 30	34		s 1.30		s 3.20	21.96	6.13	APPLETON.....	AU	DNX1	s 5.15		7.15			
C 37	44	26	s 12.15Pm		s 3.36	30.65	8.69	LOUISBURG.....	BG	D	s 4.57		6.45			
C 46	35		s 12.50		s 3.48	37.14	6.49	BELLINGHAM.....	BA	D	s 4.45		6.30			
C 52	45	26	s 1.30		s 4.03	46.34	9.20	NASSAU.....	NA	D	s 4.32		6.10			
C 58	36		s 2.05		s 4.15	51.82	5.48	ALBEE.....	s 4.22		5.55			
C 66	15		s 2.45		s 4.30	57.98	6.16	LA BOLT.....	BO	D	s 4.12		5.40			
C 73	43	31	s 4.00		s 4.47	65.57	7.59	STOCKHOLM.....	SK	D	s 4.00		5.20			
C 86	35		s 5.00		s 5.03	72.82	7.25	SOUTH SHORE.....	VR	D	s 3.48		5.00			
			f 5.30		f 5.25	86.08	13.26	RAUVILLE.....	f 3.26		4.30			
						91.49	5.41	M. & ST. L. RY. CROSSING.						
						91.80	0.31	C. & N. W. RY. CROSSING.						
C 92	Yard	324	A 5.50Pm	L 5.45Am	A 5.35Am	91.99	0.19	WATERTOWN.....	WN	BDNK ORX	L 3.15Pm		L 4.15Pm	A 3.00Pm		
C102	34			s 6.10		93.26	1.27	W. & S. F. JCT.....	JX						
C109	37			s 6.30		101.89	8.63	GROVER.....			s 2.25			
						108.24	6.35	HAZEL.....	Z	D			s 2.05			
						115.16	6.92	C. M. ST. P. & P. RY. CROS.						
C116	41			s 6.55		115.17	0.01	VIENNA.....	VA	D			s 1.45			
C124	35			s 7.20		124.05	8.88	WILLOW LAKE.....	WK	D			s 1.15			
C136	35			s 7.50		136.19	12.14	BANCROFT.....	BF	D			s 12.40			
C141	35			s 8.05		140.64	4.45	OSCEOLA.....	SC	D			s 12.25			
C149	36			s 8.25		148.36	7.72	YALE.....	YA	D			s 12.05Pm			
C162	Yard	202	A 9.15Am			161.83	13.47	HURON.....	HU	IBDRY			L 11.30Am			
			9.55	3.30	3.00			Time Over Subdivision			2.40		3.55	3.30		
			9.27	19.95	30.66			Average Speed Per Hour			34.49		23.49	19.95		

Westward trains are superior to eastward trains of the same class.

SEE ADDITIONAL SPECIAL INSTRUCTIONS PAGES 8 THROUGH 15.

ALL SUBDIVISIONS

1. SPEED RESTRICTIONS GENERAL.

(a) Where Automatic Block and Interlocking Rules and Signal Indications require movement at RESTRICTED SPEED, such movement must be made prepared to stop short of train, obstruction, or switch not properly lined and on the lookout for broken rail or anything that may require the speed of a train to be reduced; but not exceeding 15 MPH or as much slower as necessary; and where conditions require the movement must be controlled so stop can be made in time to avoid accident.

(b) Maximum permissible speed of passenger, freight and mixed trains will be designated by distinctive reflectorized roadway signs set in an upward angle of 45 degrees.

Except as directly affected by speed restrictions prescribed in Item 1—ALL SUBDIVISIONS—and other speed restrictions covered by Item 2 under individual Subdivisions, the 45 degree signs designate zone speed territories and the numerals thereon indicate in miles per hour the maximum permissible speed which will govern until the next zone sign is reached.

When the movement is from a higher to a lower speed zone, the zone sign is located approximately one mile from the point where the lower speed becomes effective. At the end of this one mile is located a reflectorized angular Restricting Sign, yellow background with black stripes, indicating the point where lower speed becomes effective. Lower speed to govern until entire train passes next zone sign.

When the movement is from a lower to a higher speed zone, the 45 degree sign is located at the point where speed may be increased.

In double track territory when trains or engines are operated against the current of traffic or when one of the tracks is used as single track, in either case if the track being used is not signaled for traffic in the direction of the movement, the maximum permissible speed is Passenger Freight
59 MPH 49 MPH

This does not modify Rule 93. Further, trains and engines operating under the above conditions must not exceed the maximum permissible speed prescribed by the 45 degree signs with the current of traffic.

On Subdivisions where both passenger and freight trains are operated, the 45 degree sign has two sets of figures, the numerals preceded with the letter "P" apply to passenger trains. The numerals preceded with the letter "F" apply to freight trains and mixed trains, and to passenger trains when handling freight cars, except cars equipped with steel wheels, air signal and steam heat lines. On Subdivisions where normally only freight or mixed trains are operated, the 45 degree sign may have just one set of figures preceded with the letter "F", which applies to all trains.

(c) Speed shown on Speed Limit Plate on engines must not be exceeded.

(d) Diesel engines light or with caboose only 50 MPH

When cabooses are handled in passenger service trains will not exceed speed of:
when handling cabooses X-100, X-198 to X-310..... 65 MPH
caboose X-830 to X-749 50 MPH

Trains handling, not in actual service, derricks, pile drivers, ditchers, cranes, shovels, Jordan Spreaders, wedge plows, etc. on Main Lines 30 MPH

except on 6 degree curves or sharper and on branch lines 15 MPH

Trains handling ore cars or air dump cars loaded with ore or gravel and scale test car on Main Lines..... 30 MPH

except on 6 degree curves or sharper, and on Branch Lines 20 MPH

Unless conditions require a further speed restriction, trains or engines, moving against the current of traffic on double track through interlockings 15 MPH

Trains or engines moving on main routes actuating points of spring switches 35 MPH

Trains or engines moving in facing point direction at spring switches without facing point lock 25 MPH

Trains or engines through No. 20 turnouts..... 35 MPH

End of double track at:

Delano.

End of two main tracks at:

Two miles west of Atwater, Pennock and Doran.

Crossovers at:

Two miles east of depot at Delano.

Two miles west of depot at Atwater.

Willmar, just west of Stock Yards.

Benson, east crossover switches.

Howard Lake, east and west switches.

Cokato, east and west switches.

Dassel, east and west switches of control siding.

Darwin, east switch of siding.

Litchfield, east switch of control siding.

Grove City, west switch of control siding.

Atwater, east switch of control siding.

Kerkhoven, east and west switches.

Benson, east switch control siding.

Morris, east and west switches of control siding.

Donnelly, east and west switches.

Herman, east and west switches.

Norcross, east and west switches.

Campbell, west switch of control siding.

Robbinsdale, east and west switches.

Sioux City, east switch 26th street yard.

Trains or engines through all other turnouts..... 15 MPH

(e) Open cars loaded with poles, piling, lumber, timber, pipe or other lading which might shift, shall be handled as far as possible in pole trains or local trains. Except at points where it is necessary to classify trains, such cars should be placed as close as possible to the head end of the train but shall not be placed immediately next to Diesel engines, or immediately next to caboose, occupied outfit or passenger cars. These commodities must not be placed in trains at such locations as will conflict with the rules governing the handling of explosives, inflammables or acids. In double track territory, engineers on trains containing such cars must at all times use extreme care to avoid slack running in or out when passing or being passed by other trains.

On single track, trains containing such cars must be at stop when on siding or adjacent track when meeting or being passed by other trains, except when there are more cars than siding will hold, it is permissible for such train to pull by other train at restricted speed.

2. MOVEMENT OF ENGINES DEAD IN TRAINS.

Diesel and Diesel-Electric engines 2303-2350 must be handled on rear of train.

Single unit switcher and road switcher type diesel engines moving dead in freight trains are to be handled not less than five (5) cars, or more than fifteen (15) cars from road engine. Additional units are to be separated by not less than five (5) cars. Multiple unit groups, not exceeding four (4) units, all equipped with alignment control couplers moving dead in freight trains, are to be handled not less than five (5) cars from road engine. Additional groups or single units are to be separated by not less than five (5) cars.

Trains handling Diesel and Diesel-Electric engines in tow dead in train will not exceed following speeds:

Engine Number	Maximum Speed
1 thru 19, 24 thru 28, 75 thru 170.....	50 MPH
20 thru 23, 29 thru 33, 175 thru 232, 247 thru 249, 254 thru 259, 262, 263, 271 thru 274, 276 thru 279, 307 thru 317, 400 thru 474, 550 thru 598, 600 thru 678, 681 thru 732, 900 thru 903....	65 MPH
260, 261, 266 thru 270, 275, 280, 281, 350 thru 365, 500 thru 512, 679, 680	79 MPH
2303 thru 2324	50 MPH
2325 thru 2350	60 MPH

3. Under Rule 24, engine number only will be displayed in indicators on engines so equipped. This will also apply when our engines are operating over Northern Pacific Tracks. Between Klamath Falls and Chemult, Southern Pacific Rules will govern.

4. When two or more Diesel units are coupled together the numerals and suffix letter, where provided, of the leading unit will be illuminated at all times when in service.

The numerals and suffix letter of trailing units must not be illuminated.

The numerals and suffix letter of the leading unit only will be used in train orders as prescribed by Consolidated Code Rule 206.

5. Air hose on engines must be hooked up in hose fastener when not in use.

6. EMPLOYES WILL BE GOVERNED AS FOLLOWS ON ENGINES, PASSENGER AND FREIGHT CARS EQUIPPED WITH ROLLER BEARINGS:

Roller bearing failures on cars or engines equipped with roller bearing journal boxes may be due to lack of oil or grease. If the box is not blazing, the oil plug in the cover should be removed and engine or valve oil added. Oil must never be added to a box that is blazing. Grease lubricated roller bearing boxes have grease plugs locked with metal strap which must be cut off with chisel before plug can be removed. After the oil has been added and plug replaced, the train should proceed at reduced speed and care exercised until it is apparent that the box will run cool. If fire develops in roller bearing box on any equipment, it must be closely watched, train moved slowly, and Superintendent notified from first available point of communication, who will prescribe for the movement.

Some engines and cars equipped with roller bearings have heat indicators or stench bombs inserted in the housing of boxes which release a strong pungent odor in the event of excessive journal box temperatures. When this odor is detected, train must be stopped at once and box located. Compare the temperature of this box with the other boxes on the same engine or car, check the oil level, and if there is no evidence of overheating, train may proceed, but if the box is overheating proceed only as instructed in the preceding paragraph.

Cars and engines equipped with roller bearings must not be allowed to stand alone, even on level track, without brakes being adequately applied.

7. COOLING AND STEAM BOILER WATERING FACILITIES FOR DIESEL ENGINES ARE PROVIDED AT THE FOLLOWING INTERMEDIATE STATIONS:

FIRST SUBDIVISION

WILLMAR—At passenger depot.

MORRIS—In frost box at west end depot platform.

SECOND SUBDIVISION

MONTICELLO—At depot.

ST. CLOUD—In frost box at depot.

THIRD SUBDIVISION

GARRETSON—In frost box east of depot.

MARSHALL—In service building east of depot.

8. Under Rule 2, watches that have been examined and certified to by a designated inspector must be used by yardmen. Rule 2A of the Consolidated Code of Operating Rules and General Instructions does not apply to employees of the Great Northern Railway.

9. Brakemen with less than one year of experience should not be used as flagman except in emergency, and then Superintendent will be notified by wire.

10. When operating snow machines in non-block signal territory, no train should be permitted to follow closer than a station apart; when that can not be done, they will be blocked not less than thirty minutes apart.

11. After severe blizzard or dirt storm, employes on first train over road must exercise care to avoid accident caused by striking drift without first having drifts faced with hand shovels, cutting in far enough to get beyond the hard snow and giving a perpendicular wall to strike against instead of slope or wedgelike shape. When operating snow dozer, conductor in charge will ride in the dozer. On snow and dirt dozers every precaution must be taken to see that cage, flangers and wings clear all obstacles when in service and are properly secured when in through trains, and dozers properly turned. Hand screws must be tightened to raise flanger on dozers as high as possible before making a back-up movement, and must not be released until the dozing work is actually to start. Hand screws holding the cage on dozers must be tightened or chains otherwise fastened except when dozer has air in cylinders and is attended by an employe.

12. Loaded dump cars should not be handled on double track after dark, but if necessary to do so, close watch must be kept by trainmen and if a car dumps its load, train must be stopped and protection afforded on the opposite track.

13. Unless otherwise provided when passenger trains are operated against current of traffic on double track or through sidings, conductors shall notify Railway Postal Clerks, train shall stop at points where U. S. mail is usually picked up and conductors are responsible for delivery of mail to Postal car.

14. Conductor will report by wire all flat spots on wheels of passenger cars. Any cars having flat spots on wheels of more than two and one-half inches long must be set out.

15. Engineers finding flat spots on Diesel engines in excess of two and one-half inches will immediately notify Superintendent, who will prescribe for their movement.

16. Due to limited overhead clearance at tunnels and structures, employees are warned to keep off top of cars of extreme height and width when handled in trains and yards, also such standing cars in electrified zone, except in emergency. In absence of previous advice on such cars, wire proper officer for instructions.

17. The Railway Company is responsible for proper handling of perishable freight on road and at points where Western Fruit Express Company do not maintain representatives. Conductors on trains handling perishable freight will ascertain from way-bills class of service required and light or extinguish heaters and manipulate vents in accordance with current instructions provided for handling perishable freight issued by the National Perishable Freight Committee.

18. Placarded loaded tank cars handled in through freight trains shall not be nearer than 6th car from engine, occupied caboose or passenger car.

Cars placarded "Explosives", "Inflammable", "Corrosive Liquids", or "Poison Gas" handled in through freight trains, local and mixed trains, shall not be nearer than 16th car from engine, occupied caboose or passenger car.

When length of train will not permit handling of cars as prescribed above—ANY PLACARDED CAR, loaded with above commodities—shall be placed near middle of train, but not nearer than 2nd car from engine, occupied caboose or passenger car.

When switching such cars in terminal yards they must be separated from engine by at least one non-placarded car.

When placarded cars described above are handled in freight trains made up in "blocks" or classifications, placarded car or cars shall be placed near middle of the "block" or classification, but not nearer than 6th car from engine, occupied caboose or passenger car.

When such placarded cars are placed in trains they must not be placed next to each other, next to refrigerators equipped with gas-burning heaters, stoves or lanterns, or next to loaded flat cars, or gondola cars containing lading higher than ends of car that is liable to shift.

Carload express shipments of explosives, sealed and placarded, may be handled on passenger trains; LCL shipments may be

made in so-called peddler car with messenger in charge when such car is assigned to the handling of express and baggage exclusively.

Terminal or pick-up points enroute must furnish conductor and engineer Form 250 showing consecutively location in train of all cars placarded "Explosives". At points other than terminals where crews change, notice will be transferred from crew to crew.

Employes will be guided by further instructions governing handling of loaded tank cars, Explosives, Inflammables, Corrosive Liquids, and Poison Gas found in I.C.C. Regulations and Consolidated Code Rules 726(C) and 808.

19. In Automatic Block Signal territory, the absence of the lunar light on a spring switch signal, Rule 501 E, page 114, of the Consolidated Code, will not be regarded as an imperfectly displayed signal, as prescribed by Rule 27, when the Automatic Block Signal governing movement over such switch indicates "Proceed." This does not modify Rule D524.

20. The normal position of a spring switch with facing point lock is identified by a color light type signal displaying a "lunar white" light for train or engine movements in a trailing point direction and for movements in facing point direction when conditions require.

The normal position of a spring switch without facing point lock is identified by a triangular yellow target on switch stand with letter "S" in black, and "lunar white" light in switch lamp in place of green light displayed in both directions through or over the switch.

Trains, departing from stations, either from siding or main track in trailing point movement actuating points of spring switches, a member of crew must observe indication of governing signal in opposite direction after rear end of train has passed through switch to ascertain if switch points return to normal position. If this signal indicates Stop and no immediate train movement or other cause is evident report the fact to Superintendent from first available point of communication.

During and immediately following snow storms or violent wind storms, spring switches must be operated by hand and relined to normal position before heading out through switch in trailing point movement, actuating switch points, to insure switch is in proper operating condition.

INDICATORS AT SPRING SWITCHES.

Spring switch indicators consisting of a red and yellow light unit or a single yellow light unit (all units normally dark) mounted on an iron mast is located at the clearance point of a siding. The switch-key-controller mounted on the mast must be operated by a member of the crew who, together with engineer, must observe and be governed by its indication before fouling main track or making movement from siding to main track through a spring switch in automatic signal territory, unless the movement is made immediately after an opposing train has passed the switch and Automatic Signal at leaving end of siding indicates "Proceed".

If Indicator displays a yellow light when switch-key-controller is operated, train or engine movement to main track may be made immediately in accordance with train rights and operating rules. Display of yellow light must continue until leading wheels have passed clearance point.

If Indicator does not display a yellow light when switch-key-controller is operated, train or engine movement to main track may be made in accordance with train rights and operating rules, after operating spring switch by hand waiting three minutes and taking every precaution to provide proper protection.

To operate Switch Indicator, insert switch key in controller and turn clockwise toward "R", hold a few seconds and remove key. If yellow light is displayed and intended movement is not made, insert switch key in controller and turn counter-clockwise toward "N" to restore signal system to normal condition to avoid delay to trains on main track.

Switch-key-controller must never be operated toward "N" after having been operated toward "R" if intended movement to main track is to be made

21. Facing point locks on hand operated switches are indicated by a six inch yellow stripe painted on target staff. Be positive locking device is restored to normal position after using. A running switch must not be made through this type switch.
22. **DRAGGING EQUIPMENT DETECTOR INDICATOR** consists of a single white light unit (normally dark) with circular background mounted on signal or other mast. When white light is displayed, train must be stopped and inspected for dragging equipment. Notify Superintendent from first available point of communication.
23. Rule 204(A) prescribes that copies of train orders will be furnished the rear trainman, such orders will only be furnished on trains designated:
Nos. 3, 4, 7, 8, 9, 10, 27, 28, 31, 32 and sections thereof; also extra passenger train whether operated as section of regular train or as a passenger extra.
24. **OSCILLATING EMERGENCY RED HEADLIGHT** will be immediately displayed by day or night when a train is disabled or stopped suddenly by an emergency application of air brakes or when engineer and conductor find it necessary to stop train due to some defect which might cause accident, over-running clearance point at meeting and waiting points, end of double track or junction.
Engineer of an approaching train observing display of emergency red headlight must stop before passing and be governed by conditions existing. If operating on adjacent track, ascertain and if safe for passage, then proceed at restricted speed until train is passed.
OSCILLATING EMERGENCY RED REAR END LIGHT is of two types—Automatic Control—Portable Manual Control—and except as otherwise provided, must be displayed by day or night each time train stops or is running at speed less than 18 MPH. Automatic Control type automatically functions in this manner. However, when train running at speed above 18 MPH and moving under circumstances in which it might be overtaken by another train or engine and during foggy and stormy weather, light may be operated manually with emergency switch and employes to afford other protection prescribed by rule.
THE USE OF EMERGENCY RED HEADLIGHT AND REAR END LIGHT DOES NOT IN ANY WAY RELIEVE ENGINE-MEN AND TRAINMEN FROM RESPONSIBILITY OF COMPLYING WITH RULES 99 AND 102.
Emergency red rear end light must be extinguished under the following conditions:
When standing at initial and final terminal of run.
When train is being switched from rear.
When train is in the clear on siding.
When operating in double track, or two or more main track territory, where another train is approaching from the rear on an adjacent main track, but not until it is known such train is not on same track.
Portable light must be removed before coupling to rear of such car.
Oscillating white light on engines will be displayed in addition to standard headlight governed by Rules 17 and 17(B). In case of headlight failure it can be used as emergency headlight or as a focus light by push button control if desired.
Enginemen and trainmen on trains and engines equipped with oscillating emergency red lights must familiarize themselves with the operation of the lights.
25. Rule D-97 is in effect on this division.
26. St. Paul Union Depot and Minneapolis, in order to facilitate the handling of patients arriving on cots in baggage cars and who require use of wheel chair or stretcher, conductors will wire Union Depot Company, St. Paul, or Stationmaster, Minneapolis, describing the class of service required.
27. Great Northern crews when making interchange on foreign line railway track will be governed by the rules and bulletins of such line.

28. This is authority to honor passes of tenant lines railways' train and engine men between Twin Cities, except on Trains 81 and 82.
29. Arrangements have been made with the M. & St. L. Railway Company to honor interline tickets reading via that line from St. Paul on our trains from St. Paul to Minneapolis, and Conductors will honor all such tickets accordingly. All such tickets honored should be endorsed "Honored, G. N. St. Paul to Minneapolis", and make notation on Form and number of tickets honored in ticket report to Auditor Passenger Receipts.
30. Rule 19 figures 2 to 9 inclusive, and Rule 19B are supplemented as follows:
When the rear car of a passenger train is equipped with built-in electric markers, or when the rear unit of an engine, moving light, is equipped with electric signal lamps, they must be lighted by day and by night to be considered as markers. The requirement for showing green to the front, or direction of movement, and green to the side will not apply.
The built-in electric markers, or electric signal lamps used as markers, must not be extinguished until the train has arrived at the final terminal of run, or is in the clear of the main track at the terminal and switch closed.

FIRST SUBDIVISION

(Main Line)

1. MAXIMUM PERMISSIBLE SPEED FOR TRAINS.

Between	Passenger	Freight
Lyndale Jct. and Breckenridge	79 MPH	50 MPH

2. SPEED RESTRICTIONS.

Delano No. 27 passing depot	40 MPH
-----------------------------------	--------

3. TRAIN REGISTER EXCEPTIONS.

Wayzata, register only for Sixth Subdivision trains.
Willmar, Nos. 31, 32, 27 and 28 will register by ticket.
Benson, register is only for trains originating and terminating.

4. CLEARANCE PROVISIONS AND EXCEPTIONS RULE 83(B).

All trains must obtain Clearance Form A at Willmar.
At Lyndale Jct., Hutchinson Jct., Sioux City Line Jct., trains for which these points are initial stations may proceed on authority of clearance under which such trains arrive, and at Lyndale Jct. only when train order signal indicates proceed.
Westward Ninth Subdivision trains will require M.St.P.&S.M. Ry. clearance at Campbell.

5. CONDITIONAL STOPS.

No. 27 stops at Wayzata to discharge passengers from Chicago and east and to pick up passengers destined Fargo and west where No. 27 is scheduled to stop.
No. 28 stops at Wayzata to discharge passengers from Fargo and west and to pick up passengers destined Chicago and east.
No. 9 Sundays stop at Montrose, Waverly, Darwin, Grove City, Atwater, Kandiyohi.

6. Lyndale Jct., eastward freight trains on Willmar Line having cars to set out at this point will stop before passing eastward Home Signal to make set-out.

7. Crossings as herein shown at the following stations are equipped with automatic signals and switch controllers. When engines or cars are standing in circuit but crossing not fouled, signals must be cleared for highway traffic by operating controllers. When crossing is to be fouled, controllers must first be operated to set signals at stop position against highway traffic. Long Lake, Crossing East of depot; and crossing two and one-half miles West. Maple Plain, Budd Street, West of depot. Dassel, 3rd & 4th Streets. Litchfield, Miller, Sibley and Holcomb Avenues. Atwater, Main Street crossing East of depot.

Pennock, Highway crossing just West of Depot.
Kerkhoven, 9th Street crossing East of Depot.
Benson State Aid Road No. 3, one and one-half miles West of Depot.
Clontarf, State Aid Road No. 13, Grace Ave.
Hancock, 6th Street crossing West of Depot.
Donnelly, 4th Street crossing West of Depot.
Norcross, Highway crossing just West of Depot.
Tintah, Highway crossing West of Depot.
Campbell, 5th Street Crossing West of Depot.
Doran, Crossing about one-fourth mile East of Depot.
Campbell.
All movements on house track over State Aid road No. 11 just west of depot must be protected by flagman.
Donnelly.
All movements on industry track over 4th Street Crossing must be protected by flagman.

8. SPEED TEST BOARDS.

Engineers shall test speed of their trains passing following points as compared with Speed Table:
Westward trains, between MP 32.1 and MP 33.1 just west of Maple Plain.
Eastward trains, between MP 87 and MP 86 two miles west of Grove City.
Westward trains between MP 110 and MP 111 one mile west of Pennock.
Eastward trains between MP 205 and MP 204 two miles east of Doran.

9. CROSSOVERS ON DOUBLE TRACK AND TWO MAIN TRACKS.

Facing Point	Trailing Point
	Mile Post 15.....400 feet west of.
	Mile Post 19.....700 feet west of.
Wayzata	Long Lake.....Just east of Depot.
	Long Lake.....Just west of Depot.
Mile Post 37.....	Maple Plain.....Just east of Depot.
1600 feet east of.	Mile Post 37.....1600 feet east of.
	Just west of end of two main tracks west of Atwater.
	KandiyohiJust east of Depot.
Willmar, double crossover just west of stockyard.	

10. Consolidated Code Rules 251, 253 and 254 are in effect on the double track between Lyndale Jct. and beginning of CTC at MP 36.7 about 2 miles east of Delano.
Oral and message instructions issued by the train dispatcher over the signature of the Superintendent must be complied with. When necessary to move trains against the current of traffic, or to provide for single track operation, or to authorize work train movements, train orders must be provided. Extra trains must be authorized by train order or by double track clearance as provided by Rule D-97.
The use of these rules does not modify Rule 99.

11. INSTRUCTIONS GOVERNING OPERATION OF TRAIN AND ENGINES WITHIN CENTRALIZED TRAFFIC CONTROL SYSTEM.

CTC extends between MP 36.7 about 2 miles east of depot Delano and mile post 212 one and one quarter miles east of N.P. Ry. crossing east of Breckenridge.
Double track extends between Lyndale Jct. and just west of depot Delano.
Two main tracks known as—NORTH MAIN and SOUTH MAIN—extends between the following points:
MP 91.1 about 2 miles west of depot Atwater and Pennock.
Doran and MP 212.
Willmar is the control station for CTC under the supervision of train dispatcher.

Controlled sidings are located at:

Howard Lake
Cokato
Dassel—South of main track.
Litchfield—South of main track.
Grove City
Atwater
Kerkhoven
DeGraff
Benson—North of main track
Clontarf
Morris
Donnelly
Herman
Norcross
Tintah
Campbell

Dwarf signals located at leaving end of controlled sidings—and Aberdeen Line Jct.—when displaying a single green indication—is not covered by interlocking rules of the Consolidated Code. Indication will be "Proceed on Main Route."

Non-controlled sidings are located at:

Delano—South of eastward main track, cap. 80 cars
Dassel—North of main track, cap. 79 cars
Darwin—Cap. 47 cars
Litchfield—North of main track, cap. 106 cars
Pennock—Cap. 37 cars
Benson—South of main track—cap. 138 cars
Hancock—Cap. 76 cars

Switches of non-controlled sidings are hand operated and equipped with electric locks. Before using non-controlled siding permission must be obtained from train dispatcher.

All Main Track switches within CTC—except as follows—are hand operated and equipped with electric locks governed by Rule 283:

All Controlled sidings
Benson—Double crossover at MP 132.
Aberdeen Line Jct.

End of two main tracks at:

Atwater
Pennock
Doran

The following signals are located adjacent to the left of the track which they govern:

EASTWARD ON NORTH MAIN TRACK

Signal 92.6
Eastward governing home signal end of two main tracks
Atwater.
Eastward governing home signal at west crossover east of Delano.

WESTWARD SOUTH MAIN TRACK

Signal 99.9

SINGLE TRACK-EASTWARD MOVEMENTS

Signal 89.6
Governing home signal east siding switch Atwater.

SIDING AT ATWATER-WESTWARD MOVEMENTS

Westward governing home signal.

Pennock—Eastward governing automatic block signal 103.6 on North Main Track.
Westward governing automatic block signal 107.5 on South Main Track.

Benson—At double crossover MP 132 for westward movements from Main Track to controlled siding—and for eastward movements from controlled siding to Main Track.

Morris—governing home signal east siding switch.

Between Doran and Breckenridge—

Eastward controlled signals on North Main Track at MP 212 and end of Two Main Tracks Doran.

Automatic block signals 210.7 and 212.1 on South Main Track for westward movements: and—Automatic block signal 208.6 on North Main Track for eastward movements.

12. MANUAL INTERLOCKINGS.

N. P. Ry. crossing1.58 miles east of Breckenridge

13. AUTOMATIC INTERLOCKINGS.

MStP&SSM. RR. crossing2.17 miles west of Tintah

SECOND SUBDIVISION

(Osseo Line)

1. MAXIMUM PERMISSIBLE SPEED FOR TRAINS.

Between	Passenger	Freight
Lyndale Junction and St. Cloud	75 MPH	50 MPH
St. Cloud and Willmar	45 MPH	40 MPH

2. SPEED RESTRICTIONS.

Between Home Signals of Interlockings at: 20 MPH
Rice Jct.
Paynesville.

3. TRAIN REGISTER EXCEPTIONS.

Lyndale Jct., all trains register by ticket.
St. Cloud, Nos. 3, 11 and 12 will register by ticket.

4. CLEARANCE PROVISIONS AND EXCEPTIONS RULE 83(B).

At Lyndale Jct., trains for which this point is initial station may proceed on authority of clearance under which such trains arrive when train order signal indicates proceed.

All trains must obtain Clearance Form A at St. Cloud.
Trains originating at Rice Jct. may proceed without a clearance.

5. Crossings as herein shown are equipped with automatic crossing

signals and switch controllers. When engines or cars are standing in circuit but crossing not fouled, signals must be cleared for highway traffic by operating controllers. When crossing is to be fouled, controllers must first be operated to set signals at stop position against highway traffic.

St. Cloud, 3rd Street North.
Monticello, Pine Street and Elm Street.
Robbinsdale, 42nd Street west of depot.
Robbinsdale, Noble Avenue, 1000 feet east of depot.
Albertville, two and one half miles east of, at Trunk Highway 241.

Robbinsdale.
All movements on industry track over Noble Avenue Crossing must be protected by flagman.

6. Track north of main track extending approximately 2 miles east-

ward from depot, St. Cloud, is known as LONG LEAD and must be kept clear for meeting and passing of trains.

7. SPRING SWITCHES WITH FACING POINT LOCK.

Robbinsdale, east and west siding switch.
Osseo, east and west siding switch.
Rogers, east and west siding switch.
Albertville, east and west siding switch.
Monticello, east and west siding switch.
Clearwater, east and west siding switch.
Normal position is for main track.

8. MANUAL INTERLOCKINGS.

MStP&SSM. RR. crossing1.34 miles west of Robbinsdale

9. AUTOMATIC INTERLOCKINGS.

M.W. Ry. crossing0.76 miles west of Lyndale Jct.
Soo Line crossing0.76 miles west of Paynesville

10 MANUAL INTERLOCKINGS WITH DUAL CONTROL SWITCHES.

Rice Jct.
This switch is electrically controlled by operator at the depot, St. Cloud.

11. INSTRUCTIONS GOVERNING OPERATION OF TRAIN AND ENGINES WITHIN CENTRALIZED TRAFFIC CONTROL SYSTEM.

CTC extends between the westward controlled signal just west of Lyndale Jct. and the controlled signals and switch at M.W. Jct. Lyndale Jct. yard office is the control station for the CTC under control of operator under supervision of train dispatcher. Eastward M.W. trains at M.W. Jct. will not require clearance Form A as prescribed by CTC Rule 271 but will be governed by signal indication.

THIRD SUBDIVISION

(Main Line)

1. MAXIMUM PERMISSIBLE SPEED FOR TRAINS.

Between	Passenger	Freight
Willmar and Merrill	55 MPH	45 MPH
Merrill and Sioux City	55 MPH	40 MPH

2. SPEED RESTRICTIONS.

Between Home Signals of Interlockings at: 20 MPH
 Clara City.
 Hanley Falls.
 Booge.
 Hills.
 Wren Tower.

Garretson, within city limits 20 MPH
 I. C. RR. Crossing, 2.89 miles east of Sioux City..... 10 MPH

3. TRAIN REGISTER EXCEPTIONS.

Garretson, Register only for trains originating and terminating.

4. CLEARANCE PROVISIONS AND EXCEPTIONS RULE 83(B).

At Sioux City Line Jct., trains for which this point is initial station may proceed on authority of clearance under which such trains arrive.

All trains must obtain Clearance Form A at Garretson.

5. Pipestone, trains and engines using CRI&P main track between G.N. interchange track switch and east end of CRI&P siding, must move at restricted speed, and must be governed by current operating rules and time table of CRI&P Ry.

6. AUTOMATIC INTERLOCKINGS.

CMStP&P. RR. crossing1.44 miles east of Granite Falls
 M&StL. Ry. crossing0.32 miles east of Hanley Falls
 C&NW. Ry. crossing4.44 miles west of Booge
 I.C. RR. crossing0.38 miles west of Hills
 CRI&P. Ry. crossing0.22 miles west of Lester
 Granite Falls, push button controls are located on east end of depot, at crossover switches, at east siding switch, and on eastward home signal. Trains and engines occupying main track at depot or lining east siding switch or crossover switches, for movements out of siding automatically set up route for eastward movement through interlocking at CMStP&P crossing, provided no conflicting movement on CMStP&P track, and will hold this set up for a period of approximately four minutes, after which, if route is not used, automatic interlocking control can be taken away by CMStP&P trains or engines approaching crossing. If an eastward train occupies main track at depot for meeting trains or station work for a period in excess of four minutes, trainman must operate push button at depot or at crossover switches to obtain interlocking route. If an eastward train occupies main track between eastward approach and home signals for a period in excess of four minutes, trainman must operate push button at east siding switch or on home signal to obtain interlocking route. Push button boxes must be kept closed and locked except when in use.

7. MANUAL INTERLOCKING.

I.C. RR. crossingWren Tower

8. SEMI-AUTOMATIC INTERLOCKINGS.

M.W. Ry. crossing.....0.46 miles east of Clara City
 If a train is stopped by a Stop-indication and no immediate conflicting train movement is evident, and both smash boards are in reverse position, trainman may signal train to proceed over the crossing after making certain that gates are set against conflicting route. If smash boards are not in reverse position, trainman shall operate them by hand with crank attached to mechanism.

9. RAILROAD CROSSINGS PROTECTED BY GATES.

I.C. RR. crossing2.89 miles east of Sioux City
 Normal position is clear for Great Northern.

10. Crossings as herein shown are equipped with automatic crossing signals and switch controllers. When engines or cars are standing in circuit but crossing not fouled, signals must be cleared for highway traffic by operating controllers. When crossing is to be fouled, controllers must first be operated to set signals at stop position against highway traffic.

Maynard, just east of depot.
 Pipestone, Main street.
 Garretson, Crossing at Dowes St.
 County Road J 3 1/2 miles west of Hinton.

11. SPEED TEST BOARDS.

Engineers shall test speed of their trains passing following points as compared with Speed Table:

Westward trains, between MP 7 and MP 8 between Priam and Raymond.

Eastward trains, between MP 121 and MP 122 between Jasper and Sherman.

Westward trains, between MP 134 and MP 135 between Booge and C.&N.W. Ry. crossing.

Eastward trains, between MP 208 and MP 209 between Merrill and Wren Tower.

FOURTH SUBDIVISION

(Yankton Line)

1. MAXIMUM PERMISSIBLE SPEED FOR TRAINS.

Between	Passenger	Freight
Garretson and Sioux Falls	40 MPH	30 MPH
Sioux Falls and Volin	40 MPH	25 MPH
Volin and Mission Hill	25 MPH	25 MPH
Mission Hill and Yankton	40 MPH	25 MPH

2. SPEED RESTRICTIONS.

Yankton, CMStP&P RR. crossing 10 MPH
 C&NW. Ry. crossing 10 MPH

Between Home Signals of Interlockings at: 20 MPH
 Sioux Falls.

Lennox.
 Davis.

Garretson, Nos. 51 and 52 will run at restricted speed within yard limits.

3. ENGINE RESTRICTIONS.

Between Sioux Falls and Yankton.....GP-9 heaviest permitted

4. CLEARANCE PROVISIONS AND EXCEPTIONS RULE 83(B).

Great Northern clearance issued to No. 293 at Volin and No. 294 at Yankton will clear train at G. N. Jct. and C. & N. W. Jct., respectively.

5. Sioux Falls, train and engine movements over Sixth and Eighth Street crossings will be protected by assigned watchmen between the hours of 5:00 A.M. and 9:00 P.M. daily, except Sunday. All train and engine movements over these crossings must be protected by a member of the crew on the ground at the crossing in advance of the movement outside of assigned hours of watchmen.

6. AUTOMATIC INTERLOCKINGS.

C&NW. Ry. crossing3.96 miles east of Sioux Falls
 CMStP&P. RR. crossing0.21 miles west of Lennox
 C&NW. Ry. crossing3.54 miles west of Davis

7. RAILROAD CROSSINGS PROTECTED BY GATES.

C&NW. Ry. crossing0.58 miles east of Yankton
 CMStP&P. RR. crossing0.88 miles east of Yankton

Normal position is clear for Great Northern.

CMStP&P. RR. crossing1.41 miles east of Yankton

Normal position is stop for Great Northern.

FIFTH SUBDIVISION

(Browns Valley Line)

1. MAXIMUM PERMISSIBLE SPEED FOR TRAINS.

Between **Freight**
 Morris and Browns Valley 25 MPH

2. ENGINE RESTRICTIONS.

GP-9heaviest permitted

SIXTH SUBDIVISION

(Hutchinson Line)

1. MAXIMUM PERMISSIBLE SPEED FOR TRAINS.

Between **Freight**
 Hutchinson Jct. and Hutchinson 25 MPH

2. ENGINE RESTRICTIONS.

GP-9heaviest permitted

3. CLEARANCE PROVISIONS AND EXCEPTIONS RULE 83(B).

At Hutchinson Jct., trains for which this point is initial station may proceed on authority of clearance under which such trains arrive.

4. SWITCH INDICATORS.

Hutchinson Jct. indicator is located near hand operated junction switch. Push buttons and instructions for their operation are in the iron box locked with a switch lock.

5. Crossing as herein shown is equipped with automatic crossing signals and switch controllers. When engines or cars are standing in circuit but crossing not fouled, signals must be cleared for highway traffic by operating controllers. When crossing is to be fouled, controllers must first be operated to set signals at stop position against highway traffic.

St. Bonifacius, Highway crossing of Trunk Highway No. 7.

SEVENTH SUBDIVISION

(Huron Line)

1. MAXIMUM PERMISSIBLE SPEED FOR TRAINS.

Between	Passenger	Freight
Benson and Mile Post 120 three miles east of Willow Lake	40 MPH	30 MPH
Mile Post 120, three miles east of Willow Lake and Huron	35 MPH	25 MPH

2. SPEED RESTRICTIONS.

Between Home Signals of Interlockings at: 20 MPH

Appleton.

Huron.

Watertown, within city limits 6 MPH

3. ENGINE RESTRICTIONS.

Between Watertown and HuronGP-9 heaviest permitted

4. CLEARANCE PROVISIONS AND EXCEPTIONS RULE 83(B).

All trains must obtain clearance form A at Watertown.

5. AUTOMATIC INTERLOCKINGS.

CMStP&P. RR. crossing0.77 miles west of Appleton

C&NW. Ry. crossing0.64 miles east of Huron

6. Crossing as herein shown is equipped with automatic crossing signals and switch controllers. When engines or cars are standing in circuit but crossing not fouled, signals must be cleared for highway traffic by operating controllers. When crossing is to be fouled, controllers must first be operated to set signals at stop position against highway traffic. Huron, S. D. Highway crossing just east of C&NW railway crossing.**EIGHTH SUBDIVISION**

(Watertown Line)

1. MAXIMUM PERMISSIBLE SPEED FOR TRAINS.

Between **Freight**
 Sioux Falls and Watertown 25 MPH

2. SPEED RESTRICTIONS.

Arlington, within city limits 10 MPH
 Between Home Signals of Interlocking at Arlington... 20 MPH

3. ENGINE RESTRICTIONS.

GP-9heaviest permitted

4. CLEARANCE PROVISIONS AND EXCEPTIONS RULE 83(B).

At W. & S. F. Jct., Sioux Falls Jct., trains for which these points are initial stations may proceed on authority of clearance under which such trains arrive.

5. Sioux Falls, train and engine movements over Sixth and Eighth Street crossings will be protected by assigned watchmen between the hours of 5:00 A.M. and 9:00 P.M. daily, except Sunday. All train and engine movements over these crossings must be protected by a member of the crew on the ground at the crossing in advance of the movement outside of assigned hours of watchmen.**6. AUTOMATIC INTERLOCKINGS.**

C&NW. Ry. crossing0.97 miles west of Arlington

7. RAILROAD CROSSINGS PROTECTED BY GATES.

C&NW. Ry. crossing0.19 miles east of Arlington

Normal position is clear for Great Northern.

NINTH SUBDIVISION

(Aberdeen Line)

1. MAXIMUM PERMISSIBLE SPEED FOR TRAINS.

Between	Freight
Soo Line Jct. and Milepost 55 Rutland	35 MPH
Milepost 55 and Milepost 83	30 MPH
Milepost 83 and Aberdeen	25 MPH

2. SPEED RESTRICTIONS.

Between Home Signals of Interlocking at Aberdeen..... 20 MPH

3. ENGINE RESTRICTIONS.

GP-9heaviest permitted

4. AUTOMATIC INTERLOCKINGS.

C&NW. Ry. crossing0.62 miles east of Aberdeen
 CMStP&P. RR. crossing0.64 miles east of Aberdeen

5. Westward Ninth Subdivision trains will require M.St.P.&S.S.M. Ry. clearance at Campbell.**TENTH SUBDIVISION**

(Forbes Line)

1. MAXIMUM PERMISSIBLE SPEED FOR TRAINS.

Between **Freight**
 Rutland and Forbes 25 MPH

2. ENGINE RESTRICTIONS.

GP-9heaviest permitted

WATCH INSPECTORS

H. W. Anderson, 1578 University Ave., St. Paul, Minn.
 Herbert B. Christensen, Inc., 144 E. 5th Street, St. Paul, Minn.
 A. T. Valleux, 894 Rice Street, St. Paul, Minn.
 O. H. Arosin Co., 414 Robert Street, St. Paul, Minn.
 Kavehar Jewelry, 2218 Central, Minneapolis, Minn.
 Oscar P. Gustafson Co., 404 Nicollet Ave., Minneapolis, Minn.
 Pomerleau & Son, 227 East Hennepin Ave., Minneapolis, Minn.
 R. F. Berens & Son, 20 East Lake Street, Minneapolis, Minn.
 Weber Jewelry & Music Co., 714 St. Germain St., St. Cloud, Minn.
 Lundman's Jewelry, 210 West 4th Street, Willmar, Minn.
 Paffrath & Son, 317 West 4th Street, Willmar, Minn.
 E. O. Kellenberger, 624 Atlantic Avenue, Morris, Minn.
 Nordahl Jewelry, 107 North 5th St., Breckenridge, Minn.
 Smith Jewelry Co., 225 So. Phillips Avenue, Sioux Falls, S. D.
 Brodkey & Goodsite, 400 4th St., Sioux City, Iowa.
 Grand Credit Jewelers, 627 4th Street, Sioux City, Iowa.
 Haugen Jewelry Co., Garretson, S. D.
 Fox Jewelry Co., Yankton, S. D.
 Haywoods Jewelry, Watertown, S. D.

SPEED TABLE

Time Min.	Per Mile Sec.	Miles Per Hour	Time Min.	Per Mile Sec.	Miles Per Hour
	46	78.3	1	18	46.2
	47	76.6	1	20	45.0
	48	75.0	1	22	43.9
	49	73.5	1	24	42.9
	50	72.0	1	26	41.9
	51	70.6	1	28	40.9
	52	69.2	1	30	40.0
	53	67.9	1	33	38.7
	54	66.7	1	36	37.5
	55	65.5	1	39	36.4
	56	64.3	1	42	35.3
	57	63.2	1	45	34.3
	58	62.1	1	50	32.7
	59	61.0	1	55	31.3
1	0	60.0	2	—	30.0
1	1	59.0	2	10	27.7
1	2	58.1	2	20	25.7
1	3	57.1	2	30	24.0
1	4	56.3	2	40	22.5
1	5	55.4	3	—	20.0
1	6	54.5	3	30	17.1
1	7	53.7	4	—	15.0
1	8	52.9	5	—	12.0
1	9	52.2	6	—	10.0
1	10	51.4	7	—	8.6
1	12	50.0	8	—	7.5
1	14	48.6	9	—	6.7
1	16	47.4	10	—	6.0

BUSINESS TRACKS

NAME	LOCATION	Capacity Cars	Switch Opens
Second Subdivision			
Tileston Mill Spur	3.50 miles east of St. Cloud	288	East
Crystal Lumber Co. Spur	1.56 miles west of Robbinsdale	8	West
Oscar Roberts Co. Inc.	1.57 miles east of Osseo	8	West
Empire Quarry Spur	2.47 miles west of Rice Jct.	141	East
North Star Granite Corp. Spur	4.28 miles west of Rice Jct.	41	West
Cold Spring Granite Spur	5.01 miles west of Rice Jct.	7	East
Gravgaard Spur	1.84 miles west of Hawick	7	E & W
New London Materials and Construction Co.	3.01 miles west of Hawick	84	E & W
New London Gravel Pit	1.73 miles east of New London	250	E & W
Steel Tanks Inc.	1.25 miles east of New London	6	East
Green Lake Ice Spur	.67 mile east of Spicer	22	East
Third Subdivision			
Readi-Mix and Oil Spur	0.58 mile west of Marshall	6	East
Fourth Subdivision			
Lawrence Spur	5.50 miles west of Corson	45	E & W
Crampton Spur	6.98 miles west of Corson	22	West
Naomi Spur	2.50 miles west of Lennox	7	East
Sixth Subdivision			
Cox Bros. Spur	0.53 miles west of Spring Park	2	West
Ninth Subdivision			
Great Northern Ry. Industry Tracks	Hankinson, N. D.	190	East on M.St.P. & S.S.M. Ry. Track
Tenth Subdivision			
Straubville	18.64 miles west of Forbes Line Jct.	34	E & W
Silver Leaf	7.09 miles west of Guelph	7	W

Page 16 (outside rear cover) is blank.