

SURGEONS AND PHYSICIANS

Alliance, Nebr..... DR. G. F. JOHNSTON..... Surgeon and Examiner.
Alliance, Nebr..... DR. J. S. BROZ..... Surgeon and Examiner.
Alliance, Nebr..... DR. F. P. SUCGANG..... Eye Specialist.
Ansley, Nebr..... DR. C. W. WILCOX..... Surgeon.
Broken Bow, Nebr..... DR. P. H. J. CAROTHERS..... Surgeon.
Broken Bow, Nebr..... DR. C. L. BOWMAN..... Surgeon.
Crawford, Nebr..... DR. B. C. BISHOP..... Surgeon.
Crawford, Nebr..... DR. R. G. BROWN..... Surgeon.
Custer, So. Dak..... DR. F. E. MANNING..... Surgeon.
Deadwood, So. Dak..... DR. F. S. HOWE..... Surgeon and Examiner.
Edgemont, So. Dak..... DR. J. R. BYRNE..... Surgeon and Examiner.
Hot Springs, So. Dak... DR. S. G. BAILEY..... Surgeon.
Hyannis, Nebr..... DR. W. L. HOWELL..... Surgeon.
Mullen, Nebr..... DR. D. A. WALKER..... Surgeon.
Ravenna, Nebr..... DR. L. E. DICKINSON..... Surgeon and Examiner.

Whenever any person other than a trespasser, sustains injuries on Company property requiring immediate medical attention, the nearest Company Surgeon should be summoned by the officer or employe of highest rank present.

In case of emergency when the attendance of the Company Surgeon cannot be had at once, the most available surgical aid should be called to serve until the Company Surgeon arrives. No important surgical operation should be made previous to the arrival of the Company Surgeon, except such as may be required for the immediate safety of the patient.

In case of injury to trespassers, a physician—the Company Surgeon when available—should be summoned only in case the injury renders the patient incapable of seeking medical attention himself. An injured trespasser should not, except in emergency, be removed from the county in which the injury occurs, but arrangements should be made to turn the patient over to the county authorities in case he cannot provide for his own care after emergency service has been rendered.

DR. O. H. HORRALL,
Chief Surgeon,
Chicago, Ill.

DR. R. B. KEPNER,
Chief Medical Officer,
Chicago, Ill.

E. L. POTARF,
General Manager, Omaha, Nebr.

W. F. GILES, Jr.
Superintendent, Alliance, Nebr.

G. B. ANDRESS
Assistant Superintendent, Sterling, Colo.

W. B. SIMMONS,
General Supt. Transportation, Chicago, Ill.

Chicago, Burlington & Quincy Railroad Company

LINES WEST OF THE MISSOURI RIVER

TIME TABLE OF THE ALLIANCE DIVISION OF THE WESTERN DISTRICT No. 55

EFFECTIVE AT 12:01 A. M.
MOUNTAIN STANDARD TIME

SUNDAY, APRIL 29, 1951

DESTROY ALL TIME TABLES OF PREVIOUS DATE

This Time Table is for the exclusive use and guidance of the employes concerned, who must carry in addition thereto the Book of Rules of the Operating Department.

Ravenna and Seneca—Subdivision

ALLIANCE DIVISION.

TIME TABLE No. 55.

EFFECTIVE APRIL 29, 1951.

WESTWARD				Signs	Distance from Lincoln	STATIONS	Capacity of		Office Open	EASTWARD					
FIRST CLASS		Daily Passenger	Daily Passenger				Siding	Other Tracks		Office Open		FIRST CLASS		Daily Passenger	Daily Passenger
P.M.	A.M.											A.M.	P.M.		
		41	43							42	44				
				B.C.K.R. T.W.	127.74	RAVENNA	Yard	Yard	Continuous.	A	A	A	A		
				F.	133.41	SWEETWATER		9	No Office.	A	A	A	A		
				F.	137.91	HAZARD	130	34	No Office.	s	s	s	s		
				F.W.	144.27	LITCHFIELD		35	No Office.			s	s		
				F.	150.00	GAVIN		130	No Office.						
				F.	153.65	MASON		34	No Office.			s	s		
				F.	160.00	ANSLEY		130	No Office.	s	s	s	s		
				F.	167.55	BERWYN		32	No Office.			s	s		
				F.C.W.	176.13	BROKEN BOW	151	Yard	No Office.	s	s	s	s		
				F.	184.72	Merna	132	45	No Office.			s	s		
				F.W.	195.62	ANSELMO	129	44	No Office.	s	s	s	s		
				F.	207.71	LINSOTT		10	No Office.						
				F.	215.47	DUNNING		75	No Office.			s	s		
				F.C.W.	225.27	HALSEY		144	No Office.	s	s	s	s		
				F.	235.18	NATICK		43	No Office.						
				F.	242.56	THEDFORD		128	No Office.			s	s		
				F.	250.64	NORWAY		132	No Office.						
				B.C.K.R. T.W.	257.61	SENECA	Yard	Yard	Continuous.	L	L	L	L		
						(129.87)				A	A	A	A		
						SCHEDULE TIME				s	s	s	s		
						AVERAGE MILES AN HOUR				s	s	s	s		

CENTRALIZED TRAFFIC CONTROL IN EFFECT BETWEEN M.P. 125.99 EAST OF RAVENNA AND M.P. 366.26.

Controlled electric switch locks on all main track switches through Ravenna yard.

Automatic electric switch locks on all hand operated main track switches at all stations except Ravenna.

Extra trains will not display classification signals between Ravenna and Seneca.

No train order signal at Ravenna and Seneca. Conductors and Enginemen must have Clearance Form A.

First class trains will register by ticket at Seneca.

At Ravenna, engines heavier than Class R-5 must not use track No. 13 which is the stub track immediately southwest of the boiler house.

Spring switches: West end of sidings Hazard, Gavin, Ansley, Merna, Anselmo, Linscott, Halsey and Thedford.
East end of siding Norway.

No. 42 stops at stations Thedford to Litchfield inclusive to discharge revenue passengers from points west of Alliance and Casper to Alliance.

Nos. 41 and 44 stop at Sweetwater on flag or at request of mail clerks to handle parcel post.

B-1, B-1-A, O-5-A, S-4, S-4-A, M-4-A engines must not be operated on following tracks:

Ravenna: Mill track, City track, Coal chute incline track, Cinder pit loading track, Boiler house track.

Mason: 300 feet west end of business track.

Ansley: Business track.

Broken Bow: Mill track.

Halsey: Coal shed track west of coal shed. Business track from west end to the crossing west of stock yards.

1-017 a+d-80
1-018 east-201-754 hr
TR #581009
Hosp 4.45

Seneca and Alliance—Subdivision

ALLIANCE DIVISION.

TIME TABLE No. 55.

EFFECTIVE APRIL 29, 1951.

WESTWARD				Signs	Distance from Lineal	STATIONS	Capacity of		Office Open	EASTWARD			
FIRST CLASS		Sidings	Other Tracks				FIRST CLASS						
Daily Passenger	Daily Passenger						Daily Passenger	Daily Passenger					
43	41								44	42			
A.M. L 4.50	A.M. L 1.20			B.C.K.R. T.W.	257.61 SENECA	Yard	Yard	Continuous.	P.M. A 12.55	A.M. A 12.25		
				F.	263.15 KELSO		75	No Office.				
s 5.04	s 1.40			F.	268.64 MULLEN	130	73	No Office.	s 12.38	s 12.09		
	f 1.54			F.W.	278.82 HECLA	137	23	No Office.	f 12.22			
5.30	s 2.14			F.C.W.	293.88 WHITMAN	141	75	No Office.	s 12.06	11.40		
					 HYANNIS	147	50	No Office.	P.M. s 11.49	s 11.25		
s 5.46	s 2.36			F.	306.88 ASHBY	128	46	No Office.	s 11.36			
	s 2.50			F.W.	315.47 BINGHAM	158	22	No Office.	s 11.25			
	s 3.03			F.	324.02 ELLSWORTH	130	35	No Office.	s 11.12	10.53		
6.14	s 3.20			F.	334.41 LAKE SIDE		81	No Office.	s 11.01			
	s 3.35			F.	341.92 ANTIOCH	129	45	No Office.	s 10.49			
	f 3.50			F.W.	350.53 BIRDSSELL	129		No Office.				
6.39	4.05			F.	359.15 ALLIANCE	Yard	Yard	Continuous.	L 10.30	L 10.20		
A 6.55	A 4.20			B.C.K.O.R. T.W.Y.	365.50 (107.89)				A.M.	P.M.		
					 SCHEDULE TIME				2:25	2:05		
2:05	3:00				 AVERAGE MILES AN HOUR				44.6	51.9		
51.9	35.9												

CENTRALIZED TRAFFIC CONTROL IN EFFECT BETWEEN M.P. 125.99 EAST OF RAVENNA AND M.P. 366.26.

Controlled electric switch locks on all main track switches through Alliance yard.

Automatic electric switch locks on all hand operated main track switches at all stations except switches at Kelso, which are manual controlled, and switches through Alliance yard.

Extra trains will not display classification signals between Seneca and Alliance.

No train order signal at Seneca and Alliance. Conductors and Enginemen must have Clearance Form A.

First class trains will register by ticket at Seneca.

All switches leading off runaround track Alliance must be lined back for the runaround track after being used.

Koester side track M. P. 363.66.

Spring switches: West end of sidings Mullen, Hecla, Whitman, Hyannis, Ashby, Bingham and Birdsell.
East end of sidings Ellsworth and Antioch.

No. 41 stops Antioch to exchange mail on flag or on request of mail clerk.

B-I, B-I-A, O-5-A, S-4, S-4-A, M-4-A engines must not be operated on following tracks:

Mullen: Business track north of main track.

Antioch: Business track.

Alliance: West leg of "Y."

Alliance and Edgemont—Subdivision

ALLIANCE DIVISION.

TIME TABLE No. 55.

EFFECTIVE APRIL 29, 1951.

WESTWARD			Office Open Week Days Except Saturday	Signs	Distance from Lincoln	STATIONS	Capacity of		Office Open Saturday and Sunday	EASTWARD	
SECOND CLASS	FIRST CLASS	Siding					Other Tracks	FIRST CLASS		SECOND CLASS	
Daily Freight	Daily Passenger							Daily Passenger		Daily Freight	
79	43								42	80	
A.M. 10.30	A.M. 7.25	Continuous.	B.C.K.O.R. T.W.Y.Yd.	365.50 ALLIANCE	Yard	Yard	Continuous.	P.M. A 9.55	P.M. A 8.20	
10.45	7.32	No Office.	F.	370.65	5.15 YALE	88		No Office.	9.46	8.05	
10.55	f 7.38	No Office.	F.	375.59	4.94 BERE A	79	20	No Office.	f 9.40	7.57	
11.15	s 7.48	7:00 am to 11:00 pm	W.Yd.	384.59	9.00 HEMINGFORD	E67 W77	85	7:00 a.m. to 11:00 p.m.	s 9.26	7.45	
11.30	f 8.01	No Office.	F.	391.34	6.75 NONPAREIL	88	15	No Office.	f 9.18	7.34	
11.40	8.07	No Office.	F.	396.49	5.15 NYE	66		No Office.	9.11	7.26	
11.50	s 8.14	7:00 a.m. to 4:00 p.m.		400.61	4.12 MARS LAND	76	106	Closed	s 9.05	7.20	
11.59	8.19	No Office.	F.	404.14	3.53 DOOLEY	68		No Office.	8.57	7.15	
P.M. 12.20	f 8.28	7:00 a.m. to 4:00 p.m.	W.	410.34	6.20 BELMONT	73	88	Closed	s 8.48	7.05	
12.35	8.38	No Office.	F.	416.41	6.07 RUTLAND			No Office.	8.34	6.40	
1.10	s 9.05	Continuous.	B.C.K. W.Y.Yd.	422.92	6.51 CRAWFORD	W88 E88	Yard	Continuous.	s 8.23	6.20	
1.22	9.12	No Office.	F.	423.12	0.20 C. & N.W. Crossing (Grade) ..			No Office.	8.04	6.05	
1.36	9.22	No Office.	F.	423.35	5.23 HORN	77	11	No Office.	7.54	5.53	
1.44	f 9.26	No Office.	F.	436.96	8.61 JODER	67	5	No Office.	f 7.50	5.48	
1.52	9.33	No Office.	F.	440.10	3.14 ORELLA	76		No Office.	7.43	5.41	
2.00	s 9.40	7:00 a.m. to 4:00 p.m.	W.	445.40	5.30 MANSFIELD	87	9	No Office.	s 7.37	5.34	
2.12	f 9.50	No Office.	F.	450.34	4.94 ARDMORE	130	55	Closed	f 7.25	5.22	
2.24	s 9.59	7:00 a.m. to 4:00 p.m.	F.	458.79	8.45 RUMFORD	72	11	No Office.	s 7.15	5.10	
2.27	10.02	No Office.		466.92	8.13 PROVO	95	11	Closed	7.10		
2.35	10.07	No Office.	F.	468.12	1.20 AREA WYE	177		No Office.	7.05	5.00	
A 2.45 P.M.	A 10.15 A.M.	Continuous.	B.C.K.O.R. T.W.Y.Yd.	472.16	4.04 DENNIS	77		No Office.	L 7.00 P.M.	L 4.50 P.M.	
4:15 26.0	2:50 39.7			476.14	3.98 EDMONT	Yard	Yard	Continuous.			
				 (110.64)						
				 SCHEDULE TIME				2:55 37.9	3:30 31.2	
				 AVERAGE MILES AN HOUR						

TRAINS EASTWARD ARE SUPERIOR TO TRAINS OF THE SAME CLASS WESTWARD.

CENTRALIZED TRAFFIC CONTROL IN EFFECT BETWEEN M. P. 366.26 WEST OF ALLIANCE AND M. P. 125.99

CONTROLLED ELECTRIC SWITCH LOCKS ON ALL MAIN TRACK SWITCHES THROUGH ALLIANCE YARD.

TRAINS HAVE NO TIME TABLE SUPERIORITY BETWEEN PASSENGER DEPOT EDMONT AND DEADWOOD LINE JCT. ALL TRAINS AND ENGINES MUST MOVE AT RESTRICTED SPEED BETWEEN THESE POINTS.

Manual Block System. Rule 318-B in effect between Alliance and Belmont; Crawford and Edgemont and on eastward advance track between Crawford and Rutland.

Automatic Block system in effect between Belmont and Crawford.

Rule 221 a in effect at all train order offices on this subdivision and is modified to include both freight and passenger trains.

No train order signal at Alliance, Crawford, and Edgemont. Conductors and Enginemen must have Clearance Form A.

All switches leading off runaround track Alliance must be lined back for the runaround track after being used.

Eastward advance track between Crawford and Rutland will be used only on train order authority.

At Crawford, westward advance siding is the first track north of main track between west subway M. P. 422.79 and west end of yard.

When first class trains meet at Edgemont, train taking siding will use first track next to depot.

No. 12 track in Edgemont yard will be used as a runaround track. All switches leading off this track must be lined back for the runaround track after being used except will not apply to eastward or westward freight trains leaving yard.

Ginn side track M.P. 370.41.

Nida side track M.P. 381.28.

B-1, B-1-A, O-5-A, S-4, S-4-A, M-4-A engines must not be operated on following tracks:

- Alliance: West leg of "Y".
- Crawford: "Y". Old transfer.
- Hemingford: Mill track.
- Ardmore: Refinite track.
- Edgemont: Wye.

Spring switches: East end advance track Rutland.
East main track switch Edgemont yard.

Telephone located: Waiting room Crawford. East end eastward siding MP 423.59. West starting signal MP 421.64. Rutland MP 416.41. Breezy Point MP 413.93. Tunnel MP 411.20. East starting signal MP 410.59.

Edgemont and Deadwood—Subdivision

ALLIANCE DIVISION.

TIME TABLE No. 55.

EFFECTIVE APRIL 29, 1951.

NORTHWARD				SOUTHWARD						
SECOND CLASS		Office Open Week Days Except Saturday	Signs	Distance from Edgemont	STATIONS	Office Open Saturday and Sunday	Capacity of		SECOND CLASS	
Sunday Tues - Thur Mixed	179						Siding	Other Tracks	Monday Wed. - Fri. Mixed	180
	P.M. L 6.30	Continuous.	B.C.K.O.R T.W.Y.Yd.	0.00 EDGEMONT	Continuous.	Yard	Yard	P.M. A 8.10	
		No Office.	F.	0.56	... DEADWOOD LINE Jct.	No Office.				
	f 6.55	No Office.	F.	8.34 CHILSON	No Office.		28	f 7.40	
	f 7.10	No Office.	F.W.Y.Yd.	15.97 MINNEKAHTA	No Office.		41	f 7.20	
	f 7.40	No Office.	F.	24.87 ARGYLE	No Office.		31	f 6.55	
	f 7.55	No Office.	F.	27.50 LORING	No Office.		18	f 6.45	
	f 8.30	No Office.	F.W.	32.31 PRINGLE	No Office.	12	13	f 6.30	
	f 8.50	No Office.	F.	37.52 MAYO	No Office.		30	f 6.10	
	f 8.55	No Office.		38.97 SANATOR	No Office.		4	f 6.05	
	s 10.00	7:00 a.m. to 4:00 p.m.	W.	44.46 CUSTER	Closed	24	60	s 5.45	
	f 10.20	No Office.	F.	50.77 BERNE	No Office.	21	6	f 5.15	
	f 10.35	No Office.	F.	54.82 OREVILLE	No Office.		17	f 5.01	
	s 11.25	7:00 a.m. to 4:00 p.m.	W.Y.Yd.	60.42 HILL CITY	Closed.	24	54	s 4.45	
	f 11.50	No Office.	F.	67.97 REDFERN	No Office.	13		f 2.01	
	f 12.15	No Office.	F.	74.82 MYSTIC	No Office.	13		f 1.40	
	f 12.40	No Office.	F.W.	82.05 ROCHFORD	No Office.	11	12	f 1.25	
	f 1.00	No Office.	F.	88.27 NAHANT	No Office.	7	9	f 1.10	
	f 1.20	No Office.	F.	93.66 DUMONT	No Office.	25	24	f 12.55	
	f 1.50	No Office.	F. W.Y.Yd.	98.55 ENGLEWOOD	No Office.	Yard	Yard	f 12.40	
	f 2.15	No Office.	F.Yd. O.	102.92 KIRK	No Office.		20	f 12.20	
	f 2.25	No Office.	F.	105.11 PLUMA	No Office.		24	f 12.10	
	A 2.30 A.M.	7:00 a.m. to 4:00 p.m.	B.K.R.T. W.Yd.	106.83 DEADWOOD	Closed.	Yard	Yard	L 12.05 P.M.	
				 (106.83)					
	8:00 13.4			 SCHEDULE TIME				8:05 13.2	
				 AVERAGE MILES AN HOUR					

TRAINS SOUTHWARD ARE SUPERIOR TO TRAINS OF THE SAME CLASS NORTHWARD.

TRAINS HAVE NO TIME TABLE SUPERIORITY BETWEEN PASSENGER DEPOT EDGEMONT AND DEADWOOD LINE JCT. ALL TRAINS AND ENGINES MUST MOVE AT RESTRICTED SPEED BETWEEN THESE POINTS.

Manual Block System. Rule 318-B In effect.

Rule 221a in effect at all train order offices on this subdivision and is modified to include both freight and passenger trains.

Rule 907 In effect.

No train order signal at Edgemont and Deadwood. Conductors and Enginemen must have Clearance Form A.

When first class trains meet at Edgemont, train taking siding will use the first track next to depot.

No. 12 track in Edgemont yard will be used as a runaround track. All switches leading off this track must be lined back for the runaround track after being used, except will not apply to eastward or westward freight trains leaving yard.

B-1, B-1-A, O-5-A, S-4, S-4-A, M-4-A engines must not be operated on Edgemont wye.

Trains will register Minnekahta, Hill City, Englewood and Kirk when instructed by dispatcher.

When trains meet at Kirk, the southward train will take siding on Kirk-Fantail line.

Northward freight trains will set up and use retaining valves on all loads when descending grades of three per cent or greater, listed.

Three percent grades: M. P. 51.09 to M. P. 54.49.

M. P. 70.00 to M. P. 73.92.

M. P. 94.41 to M. P. 104.57.

T-2 and diesel engines except diesel switch engines must not be operated on following tracks:

Wasp Spur beyond 150 feet from main track switch.

Yates Spur from first switch north of the long track to end of track.

Orohondo Spur.

Pluma: Powder house spur.

Powder Spur.

Deadwood: Standard Oil track. Silme Plant track. North of stock yards on Stock track. Pioneer Fruit Co. track from south end of platform at fruit house to north switch. Armour spur. Transfer track. Continental Oil track

SPUR TRACKS:

Lime Spur, M. P. 30.66

Nihart Spur, M. P. 35.53

OD Spur, M. P. 83.30

Wasp Spur (F), M. P. 100.77

Yates Spur (F), M. P. 102.32

Orohondo Spur, M. P. 103.40

Powder Spur, M. P. 105.65

Cinder Spur, M. P. 105.66

Minnekahta and Hot Springs Subdivision

WESTWARD	Distance from Minnekahta	Office Open Week Days Except Saturday	STATIONS	Signs	Capacity of		EASTWARD
					Sidings	Other Tracks	
	0.00	No Office. MINNEKAHTA	F.W.Y.Yd.		41	
	6.87	No Office. ERSKINE			10	
	12.90	7:30 a.m. to 4:30 p.m. HOT SPRINGS	R.W.Yd.		35	
			(13.15)				

TRAINS EASTWARD ARE SUPERIOR TO TRAINS OF THE SAME CLASS WESTWARD.
 Manual Block System. Rule 318-B in effect.
 Rule 221a in effect at all train order offices on this subdivision and is modified to include both freight and passenger trains.
 Hot Springs Quarry M. P. 7.80.
 Rule 907 in effect.
 No train order signal at Hot Springs. Conductors and Enginemen must have Clearance Form A when operator on duty.
 Mallet engines may operate Minnekahta to bridge 11.45, but must not operate over bridge 11.45.
 Office open: Hot Springs Saturday and Sunday closed.

Lead and Kirk—Subdivision

WESTWARD	Distance from Lead	Office Open Week Days Except Saturday	STATIONS	Signs	Capacity of		EASTWARD
					Sidings	Other Tracks	
	0.00	8:00 a.m. to 5:00 p.m. LEAD	R.W.Yd.	Yard	Yard	
	1.24	No Office. FANTAIL	F.		10	
	3.28	No Office. KIRK	F.Yd.		18	
			(3.28)				

TRAINS EASTWARD ARE SUPERIOR TO TRAINS OF THE SAME CLASS WESTWARD.

Manual Block System. Rule 318-B in effect. Rule 907 in effect.

Rule 221a in effect at all train order offices on this subdivision and is modified to include both freight and passenger trains.

Westward freight trains will stop at Fantail, test air and retaining valves; set up retaining valves and pull train out of Fantail with retaining valves set up.

When trains meet at Kirk, the Eastward (or Southward) train will take siding on Kirk-Fantail line.

Office open: Lead Saturday and Sunday Closed.

Keystone and Hill City—Subdivision

WESTWARD	Distance from Hill City	Office Open	STATIONS	Signs	Capacity of		EASTWARD
					Sidings	Other Tracks	
	9.45	No Office. KEYSTONE	F.O.		10	
	4.07	No Office. NELSON SPUR			2	
	1.65	No Office. TIN MILL SPUR			3	
	0.00	See Page 5 HILL CITY	W.Y.Yd.	24	54	
			(9.50)				

TRAINS EASTWARD ARE SUPERIOR TO TRAINS OF THE SAME CLASS WESTWARD.

Manual Block System. Rule 318-B in effect.
 Rule 221a in effect at all train order offices on this subdivision and is modified to include both freight and passenger trains.
 Rule 907 in effect.

Train order signal Hill City does not govern trains on Keystone and Hill City sub-division. Conductors and Enginemen must have Clearance Form A when operator is on duty.

Pine Camp Spur M. P. 7.85.
 Four percent grades: M. P. 0.46 to M. P. 1.31.
 M. P. 1.68 to M. P. 2.59.
 M. P. 4.50 to M. P. 5.00.
 M. P. 6.34 to M. P. 7.25.

Freight trains will set up and use retaining valves on all loads when descending grades of 4 percent or greater listed.
 Engines must not go on track scales at Keystone.

Englewood and Reno—Subdivision

WESTWARD	Distance from Englewood	Office Open	STATIONS	Signs	Capacity of		EASTWARD
					Sidings	Other Tracks	
	0.00	No Office. ENGLEWOOD	F.O.W. Y.Yd.	Yard	Yard	
	1.86	No Office. RENO			93	
			(1.86)				

TRAINS EASTWARD ARE SUPERIOR TO TRAINS OF THE SAME CLASS WESTWARD.

Manual Block System. Rule 318-B in effect. Rule 907 in effect.

FREIGHT TRAINS (Information Only)

WESTWARD		STATIONS	EASTWARD	
Daily Freight			Daily Freight	
75	79		78	80
L 8:00 A. M.	L 12:30 A. M. RAVENNA	A 10:45 P. M.	A 4:45 A. M.
A 12:50 P. M.	A 4:25 A. M. SENECA	L 6:15 P. M.	L 12:30 A. M.
L 1:32 P. M.	L 5:05 A. M. ALLIANCE	A 5:45 P. M.	A 11:59 P. M.
A 5:00 P. M.	A 9:30 A. M.		L 2:45 P. M.	L 9:20 P. M.

SPEED RESTRICTIONS

SPEED RESTRICTIONS

1. When a distant signal is displaying a restricting indication, trains must reduce speed at once and move at restricted speed until the indication of the next governing signal can be determined.

Clear indication of block signals does not modify the requirements of Rule 93.

When running against the current of traffic, all trains and engines must move within yard limits at restricted speed.

2. Enginemen handling light engines or engines with cabooses must approach all hazardous road crossings where the view is obscured prepared to stop and must run at restricted speed approaching, and on curves and where view is obscured between 6:30 A.M. and 6:30 P.M. and use extreme care to avoid striking motor cars.

Troop trains consisting of passenger cars only (including waycar) will be governed by speed limits designated for steam trains handling conventional equipment, except must not exceed maximum speed of 65 MPH.

Troop trains handling freight cars will be governed by speed limits designated for freight trains, except must not exceed maximum speed of 50 MPH.

Light Engines may operate at maximum speed authorized for freight trains, except must not exceed 35 miles an hour.

Diesel engines running light must not exceed speed authorized for freight trains except must not exceed 35 miles an hour, unless otherwise provided.

Passenger trains handled by single-engine-truck freight engines must not exceed maximum speed authorized for freight trains unless otherwise provided in subdivision speed restrictions or by train order.

Passenger trains handling freight equipment must not exceed maximum speed authorized for freight trains unless otherwise provided.

Gas or diesel-electric motor cars may operate on the various subdivisions at maximum speed authorized for passenger trains but must not exceed 50 miles an hour. On branch lines where steam is substituted for motor service, speed must be reduced 10 miles an hour below authorized speed for motor trains.

Gas or diesel-electric motor cars must not exceed a speed of 10 miles an hour above the speed authorized for steam engines running backward on that subdivision.

Steam switch engines not equipped with engine truck, moving over the road (outside of switching limits) must run forward when practicable, and must not exceed 20 miles per hour.

To prevent damage to traction motors, when handling electrically operated power units dead in trains the maximum speed must not exceed:

- Gas-electric motor cars.....60 M. P. H.
- Diesel-electric power units.....75 M. P. H.
- Diesel-electric switch engines.....40 M. P. H.
- Gas-electric switch engines series 9103 to 9106 inc.....30 M. P. H.

Where sub-division maximum speeds are less, they will govern.

Diesel and Gas-electric motor trains and engines must not pass through water if the water is more than three inches above top of rail and when passing through water speed must not exceed 3 miles an hour to prevent damage to traction motors.

LOCATION

Passenger
Trains
M. P. H.

Freight
Trains
M. P. H.

ALL SUBDIVISIONS

LOCATION	Passenger Trains M. P. H.	Freight Trains M. P. H.
On sidings.....	Restricted speed	Restricted speed
All crossovers and turnouts, not otherwise specified	10	10
Trailing movements through spring switches not otherwise provided.....	15	15
Handling clam shells, pile drivers, steam shovels.		
Main lines.....		30
Branch Lines.....		20
Except pile drivers 204617 and 204618 on branch lines.....		15
(See Special Instruction 13)		
Rotary Snow Plows:		
Main lines.....		25
Branch Lines.....		15
Handling scale test cars (must be handled next to waycar with air coupled.)		
Main lines.....		25
Branch Lines.....		20
20 yard air dump cars in 202650-202799 series, loaded or empty, (in rear of train when possible).....		25
Loaded 30 yard air dump cars in 202800-202884 series (in rear of train when possible)		
Main lines.....		35
Engines under steam, disconnected on one side, with main rod down.....	25	25
Wholly disconnected or dead steam engines.....		20
B, S-4 or S-4-A engines on which drivers are blocked up.....	40	40
O-5-A or M engines on which drivers are blocked up	30	25
M-2-A engines.....	40	40
T-2 engines.....	35	25

The following speed restrictions will govern when handling steam derricks:

TERRITORY	250 Ton Wrecking Derrick 204375	Other Steam Derricks
Ravenna-Belmont.....	30	30
Belmont-Edgemont.....	25	25
Edgemont-Englewood.....	20	20
Englewood-Deadwood.....	Must not operate	15
Minnekahta-Hot Springs.....	"	15
Hill City-Keystone.....	"	10

SPEED RESTRICTIONS—Concluded

LOCATION	Passenger Trains M. P. H.	Freight Trains M. P. H.	LOCATION	Passenger Trains M. P.H.	Freight Trains M. P. H.
RAVENNA AND SENECA SUBDIVISION			EDGEMONT AND DEADWOOD SUBDIVISION		
Maximum speed.....	65	50	Maximum speed.....	35	25
No. 43 passing Merna and Halsey to dispatch U.S. mail.....	35		On 3 percent descending grade.....	25	15
No. 43 passing Anselmo and Thedford Sundays to dispatch newspapers.....	35		Around curves between M. P. 6 and Dumont.....	25	25
M-4-A Engines.....	50	50	Over bridge 76.68.....	15	15
Steam Engines running backward.....	20	20	Around 16 degree curves between Englewood and Deadwood.....	15	15
Over bridge 139.29.....	50	45	600 HP diesel switch engines between Deadwood and Kirk.....	25	25
Over highway crossings from Fifth street at stock yards, to Thirteenth street, first crossing west of freight house Broken Bow.....		30	Loaded tank cars and loaded 30 yard air dump cars, series 202800-202884 (in rear of train when possible).....	..	20
			Steam engines running backward between Edgemont and Englewood.....	20	20
			Steam engines running backward between Englewood and Deadwood.....	10	10
			All trains between Deadwood Line Junction and east switch at Edgemont and between M. P. 106 and passenger depot at Deadwood.....	Restricted	Speed
SENECA AND ALLIANCE SUBDIVISION			MINNEKAHTA AND HOT SPRINGS SUBDIVISION		
Maximum speed.....	65	50	Maximum speed.....	20	20
M-4-A Engines.....	50	50	Steam engines running backward.....	10	10
Steam Engines running backward.....	20	20	Between M. P. 8 and M. P. 9 and between M. P. 11 and Hot Springs.....	15	15
			Loaded tank cars and loaded 30 yard air dump cars, series 202800-202884 (in rear of train when possible).....	15	15
ALLIANCE AND EDGEMONT SUBDIVISION			ENGLEWOOD AND RENO SUBDIVISION		
Maximum speed:.....	59	49	Maximum speed.....	10	10
Between M. P. 405 and M. P. 406.....	50	40	600 HP diesel switch engines.....	10	10
Between M. P. 417 and M. P. 417.75.....	50	40			
Between M. P. 409.4 and M. P. 410.3.....	40	40	KEYSTONE AND HILL CITY SUBDIVISION		
Between M. P. 411 and M. P. 413.25.....	30	20	Maximum speed.....	10	10
Between M. P. 413.25 and M. P. 414.75.....	20	20			
Between M. P. 414.75 and M. P. 415.25.....	30	20	LEAD AND KIRK SUBDIVISION		
M-4-A Engines on curves, M. P. 409.4 to M. P. 416.....	20	20	Maximum speed.....	15	15
Eastward advance track, between Crawford and Rutland.....	30	20	Steam engines running backward.....	10	10
M-4-A Engines.....	49	49	600 HP diesel switch engines.....	15	15
Steam Engines running backward.....	20	20			
Through No. 15 turnouts, located as follows:					
Main track movement east subway Crawford M.P. 422.70.....	30	30			
Main track movement west end yard Crawford M.P. 423.10.....	30	30			
Main track movement west end Edgemont yard M.P. 476.50.....	30	30			
All trains between Deadwood Line Junction and east switch at Edgemont.....	Restricted	Speed			

SPEED OF TRAINS

Miles per Hour	Time per Mile		Miles per Hour	Time per Mile	
	Minutes	Seconds		Minutes	Seconds
5.....	12	0	40.....	1	30
10.....	6	0	45.....	1	20
15.....	4	0	50.....	1	12
20.....	3	0	55.....	1	5
25.....	2	24	60.....	1	0
30.....	2	0	65.....	0	55
35.....	1	43	70.....	0	51

SPECIAL INSTRUCTIONS

Master Mechanic:	C. J. Harty, Alliance, Nebr.
Trainmasters:	C. R. Phillips, Alliance, Nebr. H. L. Roberts, Alliance, Nebr.
Road Foremen:	R. E. Rasser, Alliance, Nebr. C. H. Nicolai, Alliance, Nebr.
Chief Dispatcher:	B. H. Martin, Alliance, Nebr.
Asst. Chief Dispatcher:	P. S. Allen, Alliance, Nebr.
Night Chief Dispatcher:	H. E. Hillyer, Alliance, Nebr.
Train Dispatchers:	
J. T. Coldwell	E. R. McGuire
R. V. Cox	J. A. Ross
A. E. Erlison	H. M. Sayre
C. J. Hitt	R. L. Shields
F. H. Hall	L. J. Toohey
D. E. Hain	J. E. Roten

1. Where manual block system rules are in effect, light engines will be handled the same as passenger trains.

In manual block territory, permissive movement will be authorized by train dispatcher. Train dispatcher will report block when clear.

Where Rules D-251, D-252 and D-254 are in effect, freight trains stopped by train order signal, at stations where sidings are located, on or near schedule of first class trains, will clear the main track at once unless otherwise advised by signalman. Conductors must advise promptly when clear of main track and must not again enter the block without permission from signalman.

2. Rule 374 is modified as follows:

"When a train is passed by a passenger train at a non-communicating station, except in automatic block signal territory, the train passed must wait ten minutes and then proceed at restricted speed to the next available point of communication."

3. When under Rule 951, operators are instructed to handle switches for a train they must be available immediately to do so. They will maintain a position where they may be seen by the conductor and will advise him of their intention to handle switches for his train. After so advising the conductor, the operator will be responsible for the return of switches to normal position after train has passed.

4. Train order signal must indicate "Stop" in both directions at end of reverse movement, and Clearance Form A, with copy of train order delivered to train completing reverse movement unless movement is controlled by signal indication.

A train authorized by train order to move against the current of traffic must approach all interlocking and Centralized Traffic Control at restricted speed where distant signals are not provided for such movements.

Manual block system Rule 318-B in effect for trains moving against the current of traffic.

5. USE OF TRACK. Where there are two sidings for meeting or passing trains, the right hand track must be used unless otherwise provided.

When Interlocking signals operated by remote control are in stop position, train or enginemen will promptly communicate with operator or signalman and when so instructed may proceed by stop signal, examining switches and derails in route designated, assuring themselves they are in proper position.

Freight and Passenger Diesel engines may operate on any siding, yard or station track where O-1-A engines operate.

At Area Wye, the first track south of the main track, known as No. 1 track, will be the delivery track. The second track, known as No. 2 track, will be the receiving track. Capacity of No. 1 track is 38 cars, No. 2 track 34 cars. No. 3 track just inside the Area, connecting the two legs of the wye, may be used as an overflow track for cars going to or coming from the Area in the event No. 1 or No. 2 tracks are blocked. Crews of the Black Hills Ordnance Depot will come in over the west leg of the wye, moving down the lead to the west far enough to leave or take cars from these tracks. The cut off or inside crossover switches west of the wye are equipped with switch locks and must be kept locked for No. 1 storage track, except when in actual use. Derails have been installed on east wye track 100 feet west of the main track switch and on west end of No. 1 storage track and must be kept locked.

6. Trains must be identified at meeting or waiting points.

7. When a train is to be advanced as prescribed by Rule 925, the engine-man will, in acknowledgment of the signal, sound two long blasts of the whistle as provided in Rule 14(b).

8. Conductors must report by wire, storms or conditions that may render track unsafe and will tie up their trains when in their judgment it is unsafe to proceed.

9. Under Rule 103, when cars are pushed by an engine over public crossings at grade, not protected by a watchman or gates, a member of the crew must protect the crossing, unless the move is made under Rule 1012.

Should train or enginemen observe that highway crossing signals or gates are not operating properly, the fact should be reported promptly by wire to the superintendent and chief dispatcher.

10. SPRING SWITCHES. Spring switches are designated by a round target bearing the letter S.

Facing point movements over spring switches are protected by automatic home signal. When signal indicates "Stop", trains may proceed on hand signal after switch has been examined and points are found to fit properly.

Trains trailing through switch may do so without opening or closing it.

When sand or snow is blowing the switch points must be cleared before trailing move is made through switch.

When trailing through switch and train is stopped before movement is complete, backward movement must not be made until switch is set and secured in proper position. When switch is opened by hand it must be closed by hand.

For trailing moves through spring switches the speed designated in time table speed restrictions must not be exceeded.

Sand must not be used over spring switches.

Drop switch will not be made over spring switches unless specifically authorized.

Employees handling spring switch hand throw lever must keep body in clear of lever until it has reached the center position when releasing the latch on hand throw lever.

11. Sand must not be used, ash pans cleaned, water allowed to run or blow-off cocks opened over movable parts or between route signals which govern the movements through an interlocking.

Trains of three cars or less and light engines must not use excessive sand nor stand on sanded rails within the limits of Automatic Block, Centralized Traffic Control, and Interlocking nor within the control limits of Automatic Highway Crossing protection.

12. When occupied outfit cars are set out of a train at a station, or on a track between stations, or when moved from one track to another at a station, the conductor must notify the chief dispatcher from the first available point of communication as to the track on which the occupied outfit cars are left.

Under Rule 93, trains handling occupied company service cars, or carrying caretakers, must be protected as prescribed by Rule 99.

Under Rule 908, trains will be notified of occupied company service cars when such cars occupy sidings or station tracks used as sidings.

13. "Derricks, pile drivers, steam shovels, clamshells and other similar equipment moved in trains, other than work trains, upon their own wheels, leads must be lowered and securely fastened, booms disconnected, boom end and leads trailing, and boom loaded so as to be entirely free of swinging features. They must be inspected for safe side and top clearance, and should be separated from the engine by at least two cars when practicable. Company service steam wrecking derricks having specially designed idler cars are excepted.

"Derricks, steam shovels, ditchers, draglines, rail loaders and other similar equipment loaded on flat cars or other open-top cars with booms connected and handled in trains must have booms trailing and securely fastened. Cars loaded with such equipment, when picked up at intermediate stations or junctions and not properly turned, must be turned at first point where facilities are available to effect trailing position of booms.

"Spreaders to be handled in trains other than work trains must have all movable parts properly secured and when practicable must be turned in the direction which they are normally operated."

14. Train orders addressed to motor trains handling trailer, and two car branch line steam passenger trains handling blind end baggage cars must be delivered by operator to baggageman in addition to conductor and engineman.

SPECIAL INSTRUCTIONS—Concluded

15. Modifying the first paragraph of Rule 959: The standard flagging equipment for an engine or motor will be one red flag, one white lantern, one red lantern, four fuses, six torpedoes. The fuses and torpedoes to be carried in a rack in cab of steam engines and in a container in cab of Diesel-Electric motors.

On Gas-Electric motor operated trains, flagging equipment will be carried in the baggage compartment instead of in the motor room.

This modifies the second paragraph of Rule 919 so far as it applies to flagging equipment on engines or motors, and that part of the tenth paragraph of Rule 920 reading—"Normal supply for engines, three fuses and six torpedoes."

In freight and mixed train service the front brakeman is responsible with the engineer for knowing that in the cab of engine or motor there is the prescribed flagging equipment.

Rule 919 is modified to permit the use of electric lanterns.

16. Rule 916 is abolished.

17. Rule 914 is modified as follows:

A yellow signal on the right of the track indicates that the track one mile distant is safe for a speed of but 10 miles an hour, unless otherwise directed by train order. Where the one mile requirement will place the yellow signal between the switches of a siding, the signal will be carried back in advance of the siding switch.

A green signal on the right of the track signifies that the slow track has been passed, and the usual speed may be resumed. Enginemen must maintain slow speed until proceed signal is received from rear end.

Under Rule 914, on trains equipped with communicating signal system, the proceed signal will be given by one short sound of the communicating signal.

18. Grade signals changed from the aspects and instructions shown on pages 88 and 89 of rules of the operating department by replacing the yellow roundels in semaphores with red roundels, the blades red and white instead of yellow and black, and in color light signals one yellow roundel changed to red. Trains may pass grade signal displaying restrictive indication at ten miles an hour instead of five, and be governed by Rules 509-A or 509-B.

19. The use of cupola lights will be discontinued and that part of Rule D-19 reading: "A red light to the rear and a green light to the front must be displayed in cupola of caboose while on main track," is abolished.

20. Rule 1078 is modified as follows: Be thoroughly familiar with all signal rules, the arrangement of tracks where switching is required, and the movements and rights of trains using them. Be constantly on the watch for approaching trains, and be sure that the proper signal is shown to each, switch tenders using yellow flag by day and yellow light by night.

21. High or wide loads which are moving in train with restrictions on account of limited overhead or side clearance must be handled next to engine when practicable.

22. The night signals to be used under Rule 906 are modified as follows: Hot Journals—Stop signal followed by lamp swung in small vertical circle. Brakes sticking—Stop signal followed by lamp in sliding movement out from body.

23. When it is necessary for track cars to be operated during night hours, the track car operator must, when practicable, obtain an accurate line up; and where it can be done, all trains and engines entering the territory in which the cars are being operated will be notified of such track cars. When so notified, enginemen will keep a sharp lookout for track cars and use the whistle freely.

24. Conductors in all classes of service will, when practicable, personally contact and compare time with their engineers before trains are cleared from initial terminals on the subdivision.

25. Rule 1047 is modified as follows: Assist passengers, especially women, children and infirm persons, in entering and leaving the cars, or in passing from one car to another, giving special attention to their safety. Direct them on which side to leave the train, and see that platform gates and vestibule doors are opened and closed, as convenience and safety require. Do not leave the gates or car platforms until train has cleared the station platform. While the train is waiting at a station, remain at the car steps unless relieved by the conductor or train porter or when required to assume flagging duties. Use step boxes where necessary.

26. The headlights on trains handled by diesel or gas-electric engines must be burned dim during daylight hours, when in road service.

27. Red fuses will be used only in complying with the requirements of Rule 99 or for emergency stop signal. Yellow fuses will be used in giving signals as prescribed by Rules 12(a) to 12(g) inclusive, when weather conditions, or length of train make it impracticable to pass hand or lamp signals.

28. Trains carrying U. S. mail, taking siding, will stop at depot to discharge mail.

29. On single track, unless movement is made from siding on signal indication, protection must be provided as prescribed by Rule 99 before switch is opened or main track fouled. This applies to both hand operated and spring switches.

30. OSCILLATING EMERGENCY RED HEADLIGHTS. Enginemen operating engines equipped with oscillating emergency red headlights will be governed by the following:

When a train is disabled or stopped suddenly by an emergency application of the air brakes or when the engineman or conductor finds it necessary to stop train due to some defect or under circumstances which might cause derailment, fouling of adjacent track, the emergency red headlight must immediately be displayed. The red headlight is displayed and the white headlight extinguished automatically by an emergency application of the air brakes. Should the automatic feature fail to function the engineman must display the red light manually. When safety and the rules will permit the light will be extinguished manually.

The OSCILLATING EMERGENCY RED REAR END LIGHT will be displayed automatically by an emergency application of the air brakes, or manually when operating under Rule 917. Should the automatic features fail to function from an emergency application of the air brakes a trainman will display the light manually but under no circumstances will he permit the manual operation of the light to delay complying with Rules 99 and 102. When displayed, and safety and the rules will permit, the light will be extinguished manually.

Engineman on an approaching train, observing the emergency red light displayed, must stop immediately and must not pass the red light until it has been ascertained that track is safe and clear for the movement of train.

This rule is in effect at all hours.

THE USE OF THE EMERGENCY RED HEADLIGHT AND REAR END LIGHT DOES NOT IN ANY WAY RELIEVE ENGINEMEN AND TRAINMEN FROM FULL COMPLIANCE WITH RULES 99 and 102.

Where switching is to be done, cars or engines must not be coupled to the end of a car to which a portable emergency red rear end light is applied unless it is known positively that there is ample clearance to avoid damage to the light.

Enginemen and trainmen on trains or engines equipped with oscillating emergency red lights must familiarize themselves with the operation of the lights.

31. Rule 922 is modified as follows;

Cars containing explosives must be placed near the middle of train, 2 or more such cars may be placed together if desired. They must be at least 16 cars from the engine or occupied caboose, when length of train will permit.

In local freight trains, to avoid the dangers of otherwise unnecessary switching at way stations, cars containing explosives may be placed not closer than the second car from the caboose or the second car from the engine.

32. Trains and engines performing switching or other work at locations where automatic highway crossing gates are installed must approach such crossings at restricted speed and not occupy crossing until gates have lowered unless movement is protected by a member of crew.

RAILROAD CROSSINGS

CRAWFORD:

C. & N. W. trains have right to cross ahead of C. B. & Q. trains.

SPECIAL INSTRUCTIONS—CENTRALIZED TRAFFIC CONTROL

CENTRALIZED TRAFFIC CONTROL—An automatic block system upon which is superimposed manual control of certain signals and switches, which manual control is exercised by train dispatcher, or operator acting upon authority of train dispatcher.

DUAL-CONTROL SWITCH—A switch equipped with a dual-controlled switch mechanism which is provided with a hand-throw lever and a selector so arranged that when selector lever is operated, the control of switch will be transferred from the power-operated switch machine to the hand-throw lever, or from the hand-throw lever to the power-operated switch machine.

STOP SIGNAL—A fixed signal at the entrance to a route or block which is controlled both manually and automatically, and designated by the absence of a number plate.

TAKE-SIDING SIGNAL—A fixed signal located on and near the base of the signal mast, authorizing movement to siding.

LEAVE-SIDING SIGNAL—A low fixed signal, located near clearance point of siding, authorizing movement to main track and indicating condition of block.

CONTROLLED ELECTRIC SWITCH LOCK—A controlled, electrically operated mechanism with indicator that locks a switch in its normal position until released from the CENTRALIZED TRAFFIC CONTROL office. Controlled electric switch locks are designated by the letter "C" on door of case.

AUTOMATIC ELECTRIC SWITCH LOCK—An automatic, electrically operated mechanism with indicator that locks a switch in its normal position when block conditions on main track are such that it would be unsafe to reverse or use switch.

CONTROLLED SIDING—A siding having a dual-controlled switch at each end, protected by Stop or Take-siding signal, all of which are under control of the train dispatcher.

CENTRALIZED TRAFFIC CONTROL is in effect on portions of the road so specified in timetable or bulletin. Limits of CENTRALIZED TRAFFIC CONTROL are further identified by roadway signs located at the entrance to or passage from that portion of the road on which the system is in effect.

515. Within CENTRALIZED TRAFFIC CONTROL limits, signals will govern the use of blocks and movement over controlled switches; and, unless otherwise provided, their indications supersede timetable superiority and take the place of train orders. They do not dispense with the use or observance of other signals whenever or wherever they may be required.

516. **AUTOMATIC INTERMEDIATE BLOCK SIGNALS** govern the use of intermediate blocks between controlled sidings and may be Stop-and-proceed, or grade signals. Automatic block system rules are in effect for intermediate blocks governed by such signals. Stop-and-proceed signals are designated by number plate, and grade signals by purple marker.

517. Enginemen and trainmen must comply with the signal indications and also with the instructions of the train dispatcher, in all movements made within CENTRALIZED TRAFFIC CONTROL limits.

518. When a train is delayed at a Stop-signal and cause is unknown, or in case of any unusual delay, conductor or engineman must notify train dispatcher at once.

519. When a train is stopped by a Stop-signal it must stay until authorized to proceed.

520. When a Stop-signal does not clear and it is possible to communicate with the train dispatcher and the train dispatcher knows that there is no opposing train in the block, instructions may be issued to proceed under authority of Clearance Form F.

521. When a train or engine is authorized to pass a Stop-signal, which fails to clear, with a Clearance Form F, trainman or engineman must examine the switch points and observe them until leading truck of engine or car has passed the signal 50 feet.

522. Trains stopped or delayed after having passed intermediate signal displaying a clear indication, must approach the next signal at restricted speed until indication of governing signal can be determined.

523. The main track and controlled sidings must not be entered or fouled unless the movement is authorized by a signal indication, or by permission from the train dispatcher.

524. **CONTROLLED SIDINGS** are not protected by signals between clearance points. Trains must move at restricted speed, not exceeding speed authorized by timetable through turnouts and on sidings.

525. When trains meet within CENTRALIZED TRAFFIC CONTROL limits, and it is not necessary to stop for opposing train, headlight will be dimmed instead of extinguished when on siding, and opposing train may pass same, and be governed by signal indication.

526. When stopping at a signal, no part of train or engine should pass the signal.

527. A train or engine entering a block between signals, on authority of train dispatcher, must be protected as required by the rules and must proceed at restricted speed to the next governing signal.

528. A train or engine or cars on sidings or other tracks must stand clear of insulated joints placed in the track at the clearance point. When a train or engine enters a siding or other track, the main track switch must be kept open until the entire train has passed the insulated joints at the clearance point.

Trains or engines proceeding from sidings or other tracks, must remain clear of insulated joints at the clearance points on such tracks until the main track switch has been opened.

529. A train or engine having passed beyond the limits of a block must not back into that block, except by permission from the train dispatcher.

530. In foggy or stormy weather, enginemen must approach all signals with great care, prepared to comply with the indication displayed.

531. When a work extra is authorized within CENTRALIZED TRAFFIC CONTROL limits, the train dispatcher will instruct conductor either the time and place the work extra must be clear for other trains or the time to call on telephone for further instructions.

The levers controlling signals and switches at each end of the working limits must be blocked and no other train or engine permitted to enter the working limits until the work extra is clear.

Flag protection will not be required within the working limits except on two or more tracks where other tracks may be obstructed.

532. To operate a dual-control switch by hand, or to make any switch movements over a dual-control switch, trainmen or enginemen must secure permission from the train dispatcher. When permission (including time and working limits) is granted, engineman must be notified and switch must be operated by hand in the following manner:

1. Unlock switch lock on dual-selector lever.
2. Move dual-selector lever from position marked "POWER" to position marked "HAND".
3. In addition to above, when necessary to reverse the switch points, throw switch in regular manner with lever provided for that purpose.

If additional time is required, permission must be secured from the train dispatcher before the time limit has expired.

When time limit has expired or work is completed, switch must be restored to position in which originally found, and engineman notified. Train dispatcher must be advised of the location of train or engine, and the next movement desired.

When a dual-control switch is being operated by hand, or dual-selector lever is on position marked "HAND", signal indications governing movements over such switch are suspended.

The permission granted by the train dispatcher to operate a dual-control switch by hand does not authorize any part of the train or engine to move beyond the designated working limits, nor does it authorize movement over such switch except on hand signal from trainman or engineman stationed at the switch.

The selector and hand-throw lever must not be forced. They will move easily when in mesh, although some manipulation of first one and then the other may be necessary to get them in proper mesh. If the switch was lined for the siding when hand operation started, it must be again lined for siding before selector lever is restored to "POWER" position.

533. When hand-operated switches are equipped with electric locks, trainman or engineman must obtain permission from the train dispatcher before using. Switches must then be operated as follows:

1. Unlock and open door of case.
2. If the indicator shows the word "UNLOCKED", turn crank to the left until it is against its stop block, then throw switch.

When finished using switch, proceed as follows:

1. Place the switch in its normal position and lock.
2. Turn the crank of electric lock to the right until it is against its stop block.
3. Close and lock door of case.
4. Call the train dispatcher and report the completion of movement and that switch is properly locked.

534. When a train or engine is occupying the main track and has permission to operate a switch equipped with Automatic Electric Switch Lock, the leading truck of engine or car must be less than one rail length ahead of switch before Electric Switch Lock can be operated.

535. When a train or engine is using a hand-operated switch equipped with Electric Switch Lock, and the head end of train has entered the siding and portion of train is left on the main track, the Electric Switch Lock Lever MUST BE LEFT REVERSED until the head end of train has again returned to the main track. It must return to the main track through the same switch, as Electric Switch Lock on opposite end of track cannot be operated under these conditions. This applies to either Controlled or Automatic Electric Switch Lock.

536. Drop switches must not be made over power operated switches.

537. Enginemen must not permit ash pans or front end of engines to be cleaned on the tracks and switches over which the movements are governed by signal indication, except at points designated by the Superintendent. Sand must not be used, ash pans cleaned, water allowed to run or blow-off cocks opened over movable parts of controlled switches or between the signals which govern the movements, in either direction, over these switches.

