

**OPERATING INSTRUCTIONS FOR MARS
COMBINATION WHITE AND RED
FIGURE "8" HEADLIGHT**

WHITE LIGHT

To be used in figure "8" position whenever the stand-ard locomotive headlight is in operation.

RED LIGHT

When head end protection is required as provided by Rule 99, enginemen will immediately display RED HEADLIGHT. This will not relieve forward trainman or fireman from complying with fourth paragraph of Rule 99. When occupying main track meeting an opposing train, RED HEADLIGHT will be displayed approaching and while standing on main track awaiting arrival of opposing train.

THE OPERATION AND USE OF RED HEADLIGHT WILL NOT RELIEVE ENGINEMEN OR TRAINMEN FROM COMPLYING WITH RULES 99 AND 102.

**SAFETY
Is of
FIRST IMPORTANCE
in the
Discharge of Duty**

DISPATCHERS

R. E. Hagelberg, Chief Dispatcher	Oelwein, Ia.
D. F. Gifford, Night Chief Dispatcher	" "
C. K. Cole, Dispatcher.....	" "
H. Oakley, "	" "
E. G. Jordan, "	" "
N. J. Kjar, "	" "
R. L. Folkers, "	" "
P. M. Ketchum, "	" "
J. W. Nish, "	" "
J. P. Davison, "	" "
W. T. Nish, "	" "
J. L. Rueber, "	" "

**CHICAGO GREAT WESTERN
RAILWAY COMPANY**

—AND—

**CHICAGO, ROCK ISLAND AND PACIFIC
RAILROAD COMPANY**

**JOINT
TIME TABLE
No. 14**

BETWEEN

MANLY, IOWA

AND

CLEAR LAKE JUNCTION, IOWA

EFFECTIVE AT 12:01 A. M.

SUNDAY, NOVEMBER 8, 1959

FOR EMPLOYEES ONLY

B. N. HOWERY,
General Manager,
Oelwein, Iowa

H. A. PETERSON,
Superintendent,
Oelwein, Iowa

G. E. TRAYNOR,
Trainmaster,
Clarion, Iowa

MANLY TO CLEAR LAKE JUNCTION

SOUTHBOUND						JOINT TIME TABLE No. 14 Effective 12:01 A. M. Sunday, Nov. 8, 1959	Distance from Council Bluffs	Office Calls	Hours of Telegraph Service			
SECOND CLASS		FIRST CLASS			STATIONS						Monday Thru Friday	Saturdays, Sundays, Holidays
67 C.R.I. & P. Freight Depart Daily	65 C.R.I. & P. Freight Depart Daily	15 C.R.I. & P. Rocket Depart Daily	17 C.R.I. & P. Rocket Depart Daily	13 C.G.W. Passenger Depart Daily							10.40PM	260.6
	16				12.20AM	212.4	JU	Continuous	Continuous			
6.30PM	4.52AM	11.45PM	2.15PM	12.20AM	212.2							
					0.5	211.7						
6.33	4.55	11.47	2.17	12.22	0.2	204.2						
6.42	5.07	11.56PM	2.26	12.31	7.5	203.6						
					0.6	203.0	DF	8.00A-5.00PM				
6.52	5.10	12.15AM	2.28	12.45	0.6	202.1						
					0.9	201.5	K	Continuous	Continuous			
6.56PM	5.15AM	12.19AM	2.32PM	12.48AM	0.6	159.6	PO					
					41.9							
Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily	2.00AM							
.26	.23	.34	.17	.28	Time on District							

**Southbound trains are superior to northbound trains of the same class. Rule 71.
At Mason City, the time of First Class trains applies at the passenger station.**

SPEED RESTRICTIONS

LIMITS	CLASS OF SERVICE	
	Passenger Trains	Freight Trains
Main track except as otherwise restricted by yard limits, specific slow orders, slow boards, slow flags, special rules, or other proper notice:		
Between Manly and Clear Lake Jct.....	55	45
Except: Between Mason City Passenger Station and Clear Lake Jct.....	20	20

Maximum speed over railroad crossings as follows:

CROSSING	MILE	Passenger Trains	Freight Trains
C. R. I. & P.—M. & St. L.....	48.9	20	20
C. & N. W.....	57.0	20	20
C. M. St. P. & P.....	58.5	20	20
M. C. & C. L.....	59.1	20	20

Through city limits of the following towns, speed of trains is restricted as follows by city ordinance:

	MILES PER HOUR	
	Passenger Trains	Freight Trains
Mason City—street crossings.....	25	25

TRAINS HANDLING STEAM DERRICKS, PILE DRIVER, OR CRANES ON THEIR OWN WHEELS, 30 MILES PER HOUR. SCALE TEST CAR RESTRICTED TO MOVEMENT IN WAY FREIGHT TRAINS ONLY, NOT EXCEEDING 25 MILES PER HOUR.

SPECIAL RULES

MOVEMENT OF TRAINS

1. Rules of C.G.W. Ry. will govern movement of trains.
2. Superiority of trains by direction is shown at bottom of schedule pages. (See Rule 71.)
3. C.G.W. trains get their schedule date under Rule 4 from Clarion and Hayfield. C.R.I.&P. trains get their schedule date from Manly and Clear Lake Junction. Manly and Clear Lake Junction are initial stations for C.R.I.&P. trains.
4. Register Stations:
 - Manly— All trains—First-class trains will register by Form 188 except when displaying signals.
 - Mason City— All first-class trains. (For information of yard engines only.)
 - Clear Lake Junction—All trains will register by Form 188 except when displaying signals.
5. All trains must obtain clearance card, Form 14, at Manly.
6. Stations protected by yard limit boards are as follows:
 - Manly
 - West Manly
 - North Yard
 - Mason City
 - Clear Lake Junction
7. USE OF TRACKS:
 - (a) Unless otherwise instructed, trains meeting at Mason City will use the east siding.
 - (b) Designated sidings in yards:
 - North Yard—Track A-3
 - Clear Lake Junction—No. 1 track (protect against cars or engines standing on this track).

CLEAR LAKE JUNCTION TO MANLY

Capacity of Other Tracks, Location Water Tanks and Fuel Stations, Turn-Tables, Track Scales, Wyes.	Capacity of Sidings.	Distance from Hayfield.	JOINT TIME TABLE No. 14		NORTHBOUND									
			Effective 12:01 A. M. Sunday, Nov. 8, 1959		FIRST CLASS			SECOND CLASS						
			STATIONS		14 C.G.W. Passenger	16 C.R.I. & P. Rocket	18 C.R.I. & P. Rocket	66 C.R.I. & P. Freight	68 C.R.I. & P. Freight					
					Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily					
T-W-O-Y		.0	PH-R	HAYFIELD	4.55AM									
30		48.2	PH	MANLY	s 3.15AM	s 4.47AM	s 3.59PM		1.00PM	9.30PM				
Connection Interlocked		48.4		C.R.I. & P.-M. & St. L. Crossings										
	66	48.9		WEST MANLY	3.10	4.45	3.56		12.55	9.27				
Yard		55		NORTH YARD	2.58	4.37	3.47		12.23	9.03				
Connection Auto. Signal Protect		57.0		C. & N. W. Crossing										
O. S. Yard	W19 E47	57.6	PH	MASON CITY	s 2.55	s 4.35	s 3.44		12.20	9.00				
Auto. Signal Protect		58.5		C.M.St. P. & P. Crossing										
Connection Interlocked 20		59.1	PH-R	{ CLEAR LAKE JCT. } { M. C. & C. L. Crossing }	2.35AM	4.12AM	3.39PM		12.15PM	8.52PM				
T-W-O		101.0	PH-R	CLARION	1.20AM									
				Time on District	.40	.35	.20		.45	.38				

**Southbound trains are superior to northbound trains of the same class. Rule 71.
At Mason City, the time of First Class trains applies at the passenger station.**

8. The automatic block system is operated in North Yard and South Yard, Mason City.

Supplementing Rule S-509. When a train is stopped by automatic block signal in North Yard or South Yard, Mason City, it may, after sounding whistle signal 14(b), proceed without flagging in advance, but must not exceed a speed of five (5) miles per hour through the block, keeping a sharp lookout for opposing or preceding train, broken rail, open switch, or other obstruction.

9. STANDARD CLOCKS:

Manly passenger station
Clear Lake Junction passenger station

10. GENERAL ORDER BOARDS:

<p style="text-align: center;">C.G.W.</p> <p>Manly passenger station Clear Lake Jct. tower Mason City passenger station</p>	<p style="text-align: center;">C.R.I.&P.</p> <p>Des Moines passenger station Des Moines roundhouse Des Moines yard office Iowa Falls passenger station Iowa Falls yard office Manly passenger station Manly roundhouse Manly yard office Minneapolis passenger station Inver Grove yard office Inver Grove roundhouse</p>
--	--

C.G.W. Ry. General Orders affecting movement of trains between Manly and Clear Lake Junction are posted on the C.R.I.&P. General Order boards at the above locations. C.R.I.&P. train and enginemen must acquaint themselves with the contents of such General Orders before leaving those points on each trip and be governed thereby.

11. When snow plows are operated ahead of or following other trains, absolute block between open stations must be maintained

between such trains in territory involved. When necessary, dispatchers must call operators to establish necessary communications. These requirements do not modify Rule 99.

Snow plows, while in road operation, will not exceed a speed of five (5) miles per hour when meeting, passing, or being passed by a passenger train.

12. Precautions to be taken to insure safe train operation during and following severe storms:

OPERATORS—Notify Train Dispatcher promptly nature and extent of storm. Call Section Foreman, if not on duty. If so advised by Section Foreman, hold trains until it is known track is safe.

TRAIN AND ENGINEMEN—Bring train under control and proceed through territory affected by storm at a rate of speed that will insure safety; notify Train Dispatcher condition of track. If unable to communicate with Dispatcher or Section Foreman and there is a doubt as to it being safe to move, take siding and wait until advised track is safe.

TRAIN DISPATCHERS—On receipt of report of storm notify trains likely to be affected; see that Superintendent, Division Engineer and Roadmaster are notified and that Section Foremen are patrolling track and get all information necessary to protect safe movement of trains quickly as possible. If necessary, have Operator call Section Foreman.

14. The following signs placed in column provided on face of schedule pages indicate:

- W—Water
- O—Fuel for Diesel Locomotives
- S—Track Scales
- T—Turn Table
- Y—Wye
- PH—Telephone or Telegraphone
- R—Radio Base Stations

SPECIAL SAFETY CODE FOR EMPLOYEES IN TRAIN, ENGINE, AND YARD SERVICE

1. Safety is of first importance in the discharge of duty.
2. Avoid all risks. Watch for unsafe conditions and correct and report them.
3. Look both ways before crossing any track. Avoid crossing track in front of movement after signal is given to move. Do not stand or walk on track when avoidable.
4. Step over rails, frogs, switch guard rails, interlocking machinery or connections and not on them. Do not sit on rails or ties or take refuge under car.
5. Look out for approaching movements and alight outside of rails when getting off engine or car.
6. When alighting from or boarding rear end of freight train, use rear platform of caboose.
7. When boarding or alighting from a locomotive, caboose, or car face in, as on a ladder. Observe footing and clearances before alighting from moving or standing engine or car. Keep firm grip on handhold until foot is firmly placed on ground or other support when engine or car is standing.
8. Keep away from side or end while riding top of car, except for time required to operate brake or perform other duty there.
9. Do not ride on facing end of leading car or trailing end of rear car when possible to avoid it.
10. When riding side or top of car, keep a close watch for unsafe clearances.
11. Before going under or between standing cars or engines, first see or know they will not be moved. Otherwise obtain suitable protection. No signal should be given to move engine or cars when anyone is under or between.
12. One man will be permitted to ride the leading footboard of switch engine on short switch moves. He will board the footboard from a position outside of the rails, remaining in sight of engineer or fireman. He will alight from the footboard before coupling into other equipment. Enginemen will not permit their engine to couple into other equipment while a man is riding the leading footboard.
13. Employees will not attempt to board oncoming footboards when the movement is of such speed to be unsafe, or when engine is moving over frogs, crossovers, turnouts, or where a safe footing on the ground or footboards is in doubt.
14. Firm grip and safe foothold are essential to safety when on sillstep, side ladder, end platform, or in transferring or changing position.
15. When alighting from moving equipment extreme care should be exercised. Avoid getting off in an awkward manner that will result in strains or sprains.
16. When engineman sees or knows that ground man is about to get on or off, he will regulate speed down to point of assured safety. Consider the footing, visibility and other conditions.
17. In setting or releasing brakes, be alert to the hazard of slipping or losing hold, sudden lurch, stop or start of car, brake club breaking or slipping, brake chains kinking or overlapping, also grabbing or kicking of brake. (Study the peculiarities and proper handling of different types of brakes.) Pressure on brake should be exerted toward body of car. Do not hold brake tension by hand—use the dog and ratchet.
18. Leave cars in clear and tied down to avoid possibility of fouling other tracks or man on side of car. Do not leave cars standing on tracks too near street or highway crossing, preferably 60 feet away from the crossing.
19. Be prepared constantly for sudden start or stop and for the shock of brake or slack action.
20. Use cut-lever to uncouple cars. If lever is inoperative, tie the movement down before crossing to opposite side.
21. It is prohibited to use foot or hand to adjust drawbar, knuckle or lock pin while car or locomotive is in motion or when another car is approaching within a car length.
22. Angle cocks will be closed before uncoupling air hose when there is pressure in train line. When setting brakes by turning angle cock, keep firm grip on hose.
23. Do not place hands, feet, or any part of body between inside end of car and lumber, pipe, or other lading likely to shift. Keep clear of unsecured drop end doors. Do not use gate of gondola for handhold.
24. Slack cuts apart half car length before going between couplers to make adjustments of knuckles or for other purposes.
25. Do not attempt to cross track close in front of moving engine or car.
26. Wear safe shoes and other apparel, and use suitable clear (or Calobar) goggles when needful to protect against sand, cinders, or other eye hazards.
27. Keep feet in clear of the path of counterweights on ground throw switch levers. Do not handle switch stand lever when switch is being run through.
28. A habit of too much idle conversation across cab or caboose may contribute to serious accident.
29. Keep the mind on the work and have a clear and mutual understanding of the moves to be made.

DIESEL LOCOMOTIVE HAZARDS

30. Enginemen and others will use hard rubber or nonmetallic cased flashlights in and around Diesel locomotives.
31. Never place hands or face near main generator or any high voltage equipment while it is working under load.
32. Do not smoke or have open flame in engine room.
33. Rings and wrist watches will not be worn while working around electrical equipment.
34. Fuses will not be pulled while under load.
35. High voltage cabinet will not be opened while motor is running, other than idling.
36. Stepping out of side doors of moving Diesel units to elevated platform or other side elevation is prohibited.
37. At any time an engine is overheated or shut down for mechanical defect, no handhold cover plates should be removed until sufficient time has elapsed to permit engine to cool down sufficiently to prevent possibility of an explosion (minimum one hour).