E. C. PEARCESan Francisco	0
TERMINAL TRAINMASTERS	
C. H. KOONS San Francisco	
P. MOREHOUSESan Francisco	
TRAINMASTERS	
W. MACESan Francisco	,
C. H. PHELPSWatsonville Jct.	
C. E. JONESSan Luis Obispo	,
ASSISTANT TRAINMASTERS	
M. A. McINTYRESan Francisco	,
K. E. GWINNSalinas	
R. A. MILLERSalinas	3
ASSISTANT TRAINMASTER—	
DIVISION EXAMINER	
M. S. OLSENSan Francisco	,
M. S. OBBET	
ROAD FOREMEN OF ENGINES	
M. E. KETCHAMSan Francisco	
E. P. HONNERTSan Luis Obispo)
ENGINEMEN INSTRUCTOR	
L. G. COVELLSan Francisco	0
CHIEF TRAIN DISPATCHERS	
A. S. BRAINARDSan Francisco	0

TERMINAL SUPERINTENDENT

H. W. HALL, Assistant Superintendent

J. L. EMERY.....San Luis Obispo

B. S. BAUMAN, Assistant Superintendent

SOUTHERN PACIFIC COMPANY



COAST DIVISION TIMETABLE

154

AT 12:01 A. M.
PACIFIC STANDARD TIME

FOR THE GOVERNMENT AND INFORMATION OF EMPLOYES ONLY

J. W. CORBETT, General Manager.

> R. E. HALLAWELL, H. R. HUGHES, Assistant General Managers.

> > G. C. BAKER,

General Superintendent of Transportation.

C. H. GRANT, Superintendent of Transportation.

> J. J. JORDAN, Superintendent.

HOSPITAL DEPARTMENT SURGEONS

LOCATION	NAME	TITLE
San Francisco	Dr. W. W. Washburn	Chief Surgeon
San Francisco	Dr. Clinton Horn	Examiner, 65 Market Street
San Francisco	Dr. S. P. Strange	District Surgeon and Examiner, 3rd and King Sts.
Daly City	Dr. Homer Righetti	District Physician and Surgeon
South San Francisco	Dr. Edwin I. Bartlett	District Physician and Surgeon
South San Francisco	Dr. W. H. Musselman	District Physician and Surgeon
Ocean View	Dr. Harry A. Deering Dr. E. G. Gamette	Emergency Physician and Surgeon District Physician and Surgeon
Burlingame	Dr. Benjamin H. Page	District Physician and Surgeon
San Mateo	Dr. George W. Sevenman	Asst. Dist. Physician and Surgeon
Redwood City	Dr. Harper Peddicord	District Physician and Surgeon
California Ave	Dr. Granville Wood	District Physician and Surgeon
Palo Alto	・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・	
Palo Alto	Dr. D. Wood Dr. Burt L. Davis, Jr	District Physician and Surgeon District Physician and Surgeon
Los Altos	Dr. G. D. Billingsley	District Physician and Surgeon
Sunnyvale	Dr. Howard Diesner	District Physician and Surgeon
Campbell	Dr. P. A. Werthmann	District Physician and Surgeon
Los Gatos	Dr. William R. Harder Dr. Samuel B. Randall	District Physician and Surgeon District Physician and Surgeon
Santa Cruz	Dr. A. A. Cowden	Asst. Dist. Physician and Surgeon
Santa Cruz Mountain View	Dr A H Mckarlana	District Physician and Surgeon
San Jose	Dr. D. R. Threlfall	District Physician and Surgeon
San Jose	Dr. D. R. Threlfall Dr. R. C. Sheretz Dr. J. M. Hohl Dr. Philip Jordan	Asst. Dist. Physician and Surgeon Asst. Dist. Physician and Surgeon
San Jose	Dr. J. M. Hohl	Oculist and Aurist
San Jose Morganhill	Dr. J A Carv	District Physician and Surgeon
Gilroy	Dr. E. J. Chesebro	District Physician and Surgeon
Hollister Watsonville	Dr. J. A. Cary Dr. E. J. Chesebro Dr. E. N. Moore Dr. D. S. Woodard	District Physician and Surgeon
Watsonville	Dr. D. S. Woodard	District Physician and Surgeon
Watsonville	Dr. L. M. Liles Dr. O. C. Marshall Dr. M. F. Bettencourt	District Physician and Surgeon Asst. Dist. Physician and Surgeon
Watsonville	Dr. M. F. Bettencourt	Oculist and Aurist
Monterey	Dr. Mast Wollson	District Physician and Surgeon
Pacific Grove	Dr. H. S. Hoyt	District Physician and Surgeon
Salinas	Dr. E. W. Reeves.	District Physician and Surgeon District Physician and Surgeon
Salinas	Dr. Rollin Reeves Dr. A. J. Trinkle	District Physician and Surgeon
Gonzales	Dr. Gustav Eberhardt	Emergency Physician and Surgeon
King City	Dr. C. T. Bullard	District Physician and Surgeon
San Miguel	Dr. C. T. Bullard	District Physician and Surgeon
Paso Robles	Dr. H. McGarvey	District Physician and Surgeon Emergency Physician and Surgeon
Santa Margarita	Dr Harry I Coventry	Emergency Physician and Surgeon
San Luis Obispo	Dr. James B. Smith	District Physician and Surgeon
San Luis Obispo	Dr. R. T. Treadwell	District Physician and Surgeon
San Luis Obispo	Dr. George B. Kelker	Oculist and Aurist Oculist and Aurist
San Luis Obispo Santa Maria	Dr. W. D. Butler Dr. W. D. Sink Dr. A. M. Beekler	District Physician and Surgeon
Santa Maria	Dr. A. M. Beekler.	Asst. Dist. Physician and Surgeon
Santa Maria	Dr. M. E. Mesirow	Oculist and Aurist
Guadalupe	Dr. R. C. Randall	District Physician and Surgeon
Santa Barbara	Dr. M. V. Duncan Dr. C. S. Stevens. Dr. A. B. Steele.	District Physician and Surgeon District Physician and Surgeon
Santa Barbara	Dr. A. B. Steele.	District Physician and Surgeon District Physician and Surgeon
Santa Barbara		District Physician and Surgeon
Santa Barbara	Dr. A. B. Wileox	District Physician and Surgeon
Santa Barbara	Dr. A. B. Wilcox Dr. W. J. Mellinger. Dr. William H. Johnston.	Aurist Oculist
Santa Barbara	Dr. W. B. Gibbs	Oculist
2000		(A. S.

Note.—Emergency Surgeons should only be summoned for temporary treatment when prompt attention is required and when patients cannot be sent to or await arrival of Division or District Surgeon.

	AND AN pidarents				arr I			162		1966 Support
	BRUITATE					, ,				
	paratitivities : '1									
1.0	Professional Control									
EN L								DE 01 4		
								d).011		
-11										
MAL.										
							with =	30.11		100
		5200								
									e Mile	
				de ex	12.77					
								1023		
	attent diamen									
	Total Chemistra				83.02	Page 1				1.00
									MAGEL	i esta i luc Luciali
	ment mariles									a constraint
	and the second		Term	100						

The first and the control of the con

and and the minimum of a policy of the property of the propert

and uniform, every brains handing permises extinuous unity mine of the fraint of the form of two of the form of th

2	Terminal Investment				SAN	FRA	NCISC	O SUE	BDIVIS	NOI					1
				EA	STWA	RD					3 7				
					FII	RST CLA	SS	12 14				Time	table No. 154		8 8
1	Capacity of sidings in car lengths	116 Passenger	162 Passenger	114 Passenger	72 Passenger	98 Morning Daylight	250 Passenger	112 Passenger	110 Passenger	106 Passenger	Mile Post Location	J	une 2, 1946		Distance from San Francisco
		Leave Daily Ex. Sunday and Holidays	Leave Sunday and Holidays only	Leave Daily	Leave Daily	Leave Daily	Leave Daily	Leave Daily	Leave Daily Ex. Sunday	Leave Daily		s	TATIONS		
	вкмогтур	11.10	AM 10.30	AM 8.25	AM 8.20	AM 8.15		AM 7.00	AM 6.00	12.30	0.0	TO-R SAN	FRANCISCO		0.0
	DAUGILI	11	10.00	f	0.20			s	s	s	1.9	23	1.9 Ird STREET		1.9
p											4.1	P/	AUL AVE.		4.1
San Francisco yard	BKWOITP	s11.19	s 10.40	s 8.35	8.29			s 7.10	s 6.10	s 12.40	5.2		AYSHORE		5.2
rane	KIP					8.26					6.9	R V	ISITACION		6.9
Sank				f				s	f	f	8.6	BU	TLER ROAD		8.6
		s11.26	s 10.46	s 8.41				s 7.17	s 6.17	s 12.46	9.3		N FRANCISCO		9.3
(P	Commission State of the	s 10.50	A STATE OF THE PARTY OF THE PAR				s 7.21	s 6.21	s 12.49	11.0	Si	AN BRUNO		11.0
		f	f						f	f	12.1	LO	MITA PARK		12.1
м	48 P	s	f	f		8.33		s	s	f	13.7		MILLBRAE		13.7
	P	s 11.39	s 10.58	s 8.52				s 7.29	s 6.29	s 12.57	15.2	В	ROADWAY		15.2
	P		s 11.02	A CONTRACTOR OF THE PARTY OF TH	s 8.45			s 7.33	s 6.32	s 1.00	16.3	g BU	RLINGAME		16.3
	84 WP	AM	s 11.06					s 7.37	s 6.37	s 1.04	17.9	System	AN MATEO		17.9
M	84 WP			f				14	f	f	18.9	НАҮ В	WARD PARK	Doubl	18.9
		f	f	s 9.03		8.41		f	f	s	20.3		IILLSDALE	- 6	20.3
	P		s 11.12	s 9.05				s	s	f	21.9	Automatic	BELMONT	ack	21.9
M	47 P	PM s 12.01	s11.16	s 9.08				s 7.46	8 6.46	s 1.13	23.2	SA	N CARLOS	_	23.2
1		s 12.07	s 11.21	s 9.12	s 8.56			s 7.51	s 6.50	s 1.17	25.4		WOOD CITY	-	25.4
	WIYP					8.47					26.2	R REI	DWOOD JCT.	_	26.2
		f	s 11.25	f				f	f	f	27.8	A	THERTON	-	27.8
	P	s	s	s		-		s	В	s	28.9	MI	ENLO PARK	_	28.9
м	48 P	s 12.17	s11.31	s 9.22	s 9.05			s 8.02	8 7.00	в 1.26	30.1	P	ALO ALTO	_	30.1
м	48 WYP	s 12.22	s 11.35	s 9.26				s 8.07	s 7.03	в 1.29	31.8		FORNIA AVE.	_	31.8
м	46 P	s 12.30	s11.42	s 9.33				s 8.14	8 7.10	s 1.36	36.1	MOL	INTAIN VIEW		36.1
	P		s11.46			8.59	Via Newark	s 8.20	8 7.15	A STORY	38.8	S	UNNYVALE		38.8
, [KIP	s 12.44	s 11.53	s 9.45	9.24	75 10,50	8.40	f 8.28	s 7.23	f 1.49	44.3		NTA CLARA	_	44.3
oc yar	BKWP										45.2	SAN	JOSE YARD		45.2
ban sose yard	IP		f	PACEARIE			1	f			45.7	COI	LLEGE PARK		45.7
ě [BKWOITYP		AM	s 9.50	s 9.30	s 9.08	8 8.45	s 8.35	s 7.30	" 1.55	46.9	TO-R	SAN JOSE	J	46.9
	2	Arrive Daily Ex. Sunday and Holidays	Arrive Sunday and Holidays only	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily Ex. Sunday	Arrive Daily			(46.9)	·verye.	
		(1.40) 28.14	(1.29) 31.62	(1.25) 33.11	(1.10) 40.20	(0.53) 53.09	(0.05) 31.20	(1.35) 29.62	(1.30) 31.27	(1.25) 33.11		Time	over District e Speed per Hou		

7.15

s 6.59

6.35

6.30 AM

Leave Daily Ex. Sunday

and Holidays

(1.13)

s 6.55 s 7.09

7.29

7.26

7.22

7.12

s 6.55

6.49

6.44

6.36

6.30 AM

Leave

Sunday and

Holidays only

7.23

7.15

s 6.59 s 6.59 s 7.05

s 6.50

s 6.40

6.35 AM

Ex. Sunday

7.19 s 7.30

s 7.23

s 7.16

s 7.12

s 6.53

6.40 AM

Leave Daily Leave Daily
Ev. Sunday Ex. Sunday
Ex. Sunday

Ex. Sunday

and Holidays and Holidays and Holidays and Holidays

s 7.41 s 7.48

7.35

s 7.26

7.16

s 7.07

7.44

s 7.28

s 7.22

s 7.12

6.55 AM

Leave Daily

(1.14) 38.03

6.55 s 7.00

s 7.10

s 7.05

s 7.01

s 6.54 s 6.57 s 7.09

s 6.51

s 6.43

s 6.37

s 6.30

s 6.20

6.15 AM

Leave Daily Ex. Sunday

and Holidays

(1.20)

6.45

6.41

6.35

6.33

6.22

6.15

6.10 AM

Leave Daily Ex. Sunday

and Holidays

(1.20)

RULE 5. Schedule time and train-order time apply at the location of station sign at stations between San Francisco and San Jose and on Santa Clara-Newark line will apply at junction switch, Santa Clara.

Timetable No. 154

June 2, 1946

STATIONS

23rd STREET

PAUL AVE.

BAYSHORE

VISITACION

BUTLER ROAD

SO. SAN FRANCISCO

SAN BRUNO

LOMITA PARK

MILLBRAE

BROADWAY

BURLINGAME

SAN MATEO

HAYWARD PARK HILLSDALE

BELMONT

SAN CARLOS

REDWOOD CITY

REDWOOD JCT.

ATHERTON

MENLO PARK

PALO ALTO

MOUNTAIN VIEW

SUNNYVALE

SANTA CLARA

SAN JOSE YARD

COLLEGE PARK

SAN JOSE

(46.9)

.....Time over District...... Average Speed per Hour.

TO-R

R CALIFORNIA AVE.

34.8

33.2

31.7

30.6

29.0

28.0

26.6

25.0

23.7

21.5

20.7

19.1

18.0

16.8

15.1

10.8

8.1

2.6

1.7

1.2

0.0

5.44

5.41

5.38

5.28

5.24

5.15

5.07

5.00

4.56

4.50

4.45 AM

Leave Daily

Ex. Sunday

(1.30)

6.09

6.06

6.02

5.51

5.47

5.40

5.33

5.22

5.10 AM

Leave Daily

Ex. Holidays

(1.30) 31.27

s 5.27

s 5.15

6.43

6.40

6.36

6.25

s 6.21 s

6.08

5.57

5.45 AM

Leave Daily

Ex. Sunday

(1.30) 31.27

s 6.02

s 5.50

5.37 s 6.12 s

TO-R SAN FRANCISCO

Mile Post Location

0.0

1.9

4.1

5.2

6.9

8.6

9.3

11.0

12.1

13.7

15.2

16.3

17.9

18.9

20.3

21.9

23.2

25.4

26.2

27.8

28.9

30.1

31.8

36.1

38.8

44.3

45.2

45.7

46.9

RULES 86 and 93. Second and third-class trains, extra trains and engines, except trains handling passenger equipment only, must clear the time of Nos. 96, 97, 98 and 99 not less than 10 minutes, except between limits of Fourth St. and Potrero interlockings, San Francisco, and must be clear of main track and insulated joints at passing points for Nos. 96, 97, 98 and 99.

E I I I		Receive To	Discharge From	THE RESERVE
Train	At	(or Beyond)	(or Beyond)	Frequency
107 105 }		Any Station	CONTROL SE	

Nos. 105 and 109 stop daily at Newcomb Ave.

_				E	ASTWA	PD	Media -					
-				101		RST CLA	66					Theorem Section
	Capacity of sidings in car lengths	120 Passenger	174 Passenger	118 Passenger	172 Passenger	170 Passenger	168 Passenger	166 Passenger	96 Noon Daylight	164 Passenger	Mile Post Location	Timetable No. 154 June 2, 1946
		Leave Daily	Leave Saturday only	Leave Daily	Leave Saturday only	Leave Saturday only	Leave Saturday only	Leave Saturday only	Leave Daily	Leave Sunday and Holidays only		STATIONS
7	BKWOITYP	PM 3.05	PM 2.15	PM 1.35	PM 1.15	PM 1.00	PM 12.35	PM 12.18	PM 12.15	11.30	0.0	TO-R SAN FRANCISCO
ľ	BRWOITTI	5.05	2.15	f 1.55	1.13	1.00	8	12.10			1.9	1.9 23rd STREET
2							f				4.1	PAUL AVE.
	вкжогтр	f 3 15	f 2 25	s 1.45	1.24	1.09	f 12.46	12.27	12.24	11.39	5.2	BAYSHORE
	KIP	. 5.15	1 2.1.2.5	0 1.15	1	1.02		2,2,3,2,3,			6.9	R VISITACION
1											8.6	BUTLER ROAD
4	Dex	s 3.23	8 2 30	s 1.51	s 1.29		s 12.52	s 12.32		26.5.19	9.3	SO. SAN FRANCISCO
1	P		S EST SOUTH	s 1.55	The state of		s 12.56	1910	BY 19 3	HE RES	11.0	SAN BRUNO
-		f	f	2.00	1.00	DOT:	f	416			12.1	LOMITA PARK
M	48 P	f	f	g	s		s 1.02		12.32		13.7	1.6 MILLBRAE
	P	s 3.36	8 2.43	8 2.03	s 1.41	s 1.21	7	s 12.40	BC.O.	s11.52	15.2	BROADWAY
H	P				A CONTRACTOR OF THE PARTY OF TH	s 1.24	N-F- 05 10 10 10 10 10 10 10 10 10 10 10 10 10	And the second	36,0	s 11.55	16.3	BURLINGAME
	THE SECTION		Commence of the Commence of th	The state of the s		s 1.28	1011027-1		EGIA N	s 11.59	17.9	SAN MATEO
М	84 WP <	f	f	f			f				18.9	HAYWARD PARK
		f	s	f			f		12.39	s	20.3	HILLSDALE
	P	s	s	s	s	140 1	f			s	21.9	BELMONT
м	47 P	s 3.56	s 3.01	s 2.20	s 1.57		s 1.24	s12.54	LEC. II IV	s 12.08	23.2	SAN CARLOS
1				CERTAIN DESCRIPTION &	100000000000000000000000000000000000000	s 1.38	7.00		10000	s12.12	25.4	REDWOOD CITY
{-	WIYP		17-3-						12.45		26.2	R REDWOOD JCT.
171	OR THE STATE OF	f	s	f		8	f	s 1.02		f	27.8	ATHERTON :
M	P	s	s	S	s 2.06	s	s	s	OP S	s	28.9	MENLO PARK
м	48 P	s 4.12	s 3.14			s 1.48	s 1.38	s 1.08	16-19	s12.21	30.1	PALO ALTO
M	G6 810085	4 4 16	s 3.17	s 2.37	s 2.13	s 1.52	s 1.41	s 1.12	The state of	LINE	31.8	R CALIFORNIA AVE.
M	46 P	s 4.24	s 3.24	s 2.44	s 2.19	Via Los Altos	s 1.48	s 1.19		812.30	36.1	MOUNTAIN VIEW
	P		s 3.29		s 2.24		s 1.53	News 1	12.57	s 12.35	38.8	SUNNYVALE
1	KIP		s 3.36	40 CO TO	2.30		s 2.00	1.29	4.44	12.45	44.3	R SANTA CLARA
_	BKWP										45.2	SAN JOSE YARD
- - -	IP	f	f								45.7	COLLEGE PARK
[вкиогтур	s 4.45 PM	s 3.43	s 3.05	s 2.35	I STATE	s 2.05	s 1.34	8 1 Ne	* 12.50	46.9	TO-R SAN JOSE
		Arriva Daily	8 2 5	Lautes Della	Arrive	Arrive Saturday only	Arrive Saturday only	Arrive Saturday only	Arrive Daily	Arrive Sunday and Holidays only		(46.9)
	21.0 4 (67.00)	(1.40) 28.14	(1.28) 31.98	(1.30) 31.27	(1.20) 35.18	(0.52) 36.69	(1.30) 31.27	(1.16) 37.03	(0.51) 55.17	(1.20) 35.18		Time over District

AD	DITIONAL FLAG ST	OPS TO RECEIVE OR D	ISCHARGE REVENUE	PASSENGERS
Train	At	Receive To (or Beyond)	Discharge From (or Beyond)	Frequency
75	Burlingame		Santa Barbara	Daily

			The second second	E/	ASTWA	RD							
		1		11	16- x 1000	ST CLAS	s					Timetable No. 154	ER
	Capacity of sidings in car lengths	134 Passenger	132 Passenger	176 Passenger	130 Passenger	128 Passenger	126 Passenger	124 Passenger	122 Passenger	78 Del Monte	Mile Post Location	June 2, 1946	Distance from San Francisco
	A SHIP OF STREET	Leave Daily Ex. Sat., Sun. and Holidays	Ex. Sat., Sun.	Catuaday only	Leave Daily Ex. Sat., Sun. and Holidays	Leave Daily Ex. Sat., Sun. and Holidays	Leave Daily Ex. Sunday and Holidays	Leave Daily	Leave Daily Ex. Sunday and Holidays	Leave Daily		STATIONS	
7	BKWOITYP	PM 5.20	PM	PM	PM 5.00	PM 4.50	PM 4.40	PM 4.20	PM 4.05	PM 4.00	0.0	TO-R SAN FRANCISCO	0.0
1	BRWOILL	5.20	3.1.	9.00	9.00	9	g	8	g		1.9	23rd STREET	1.9
				5	5	5	8	5	G		4.1	PAUL AVE.	4.1
	BKWOITP		5.26	s 5.11	5.09	s 5.01	4.50	s 4.30	4.16	4.09	5.2	BAYSHORE	5.2
1	KIP		3.23	5 012	3.02	5 5.5					6.9	R VISITACION	6.9
1	- Alan			f			g	g			8.6	BUTLER ROAD	8.6
1				f 5.17		s 5.07	5	s 4.37			9.3	SO. SAN FRANCISCO	9.3
1	P	250b (NB)	AL DITT	s 5.21		s 5.11	1 1	s 4.41	s 4.24		11.0	SAN BRUNO	11.0
_		10-61-6-1		f	g	8 9,1	s 4.58				12.1	LOMITA PARK	12.
7	M 48 P			f	g		g	8			13.7	MILLBRAE	13.
Ava	M 48 P			s 5.30	s 5.22	13:00	s 5.05	8 4.49	s 4.30		15.2	BROADWAY	15.
1	P	EP-IH			s 5.26	0.011,011.01		s 4.52		4/31	16.3	BURLINGAME	16.
7			5.39		s 5.30						17.9	SAN MATEO	17.
M	M 84 WP			f				g		#2Ale	18.9	HAYWARD PARK	. 18.
			7	f	1	g		8			20.3	HILLSDALE	20.
	P			f	Joseph Joseph	g		g		4.26	21.9	BELMONT SE	21.
~	M 47 P		5.45	s 5.48	THE STATE OF	s 5.33		s 5.06	s 4.45		23.2	SAN CARLOS	23.
1	47	s 5.53	No. of London	s 5.52			s 5.21	s 5.11			25.4	REDWOOD CITY	25.
{-	WIYP	8 3.5	5.50		5.41					4.32	26.2	R REDWOOD JCT.	26
		s 5.57		f	g			g	g		27.8	ATHERTON	27
	P	5 3.3.			s 5.46		8	g			28.9	MENLO PARK	28
v	1 48 P	RHEID	s 5.56	Williams St.		. 5.44	s 5.29	s 5.21	8 4.57	4.37	30.1	PALO ALTO	30
-	48 WYP		0 600	s 6.05	Service of	8 5.47	5	s 5.24	s 5.00		31.8	R CALIFORNIA AVE.	31
	1 46 P	BITTO IN	Via	s 6.12			s 5.38	s 5.31		4.45	36.1	MOUNTAIN VIEW	36
IVA	1 46 P	s 6.12		s 6.17	6.04		s 5.43		THE REAL PROPERTY.		38.8	SUNNYVALE	38
1	KIP	6.20	ATRIVING NO	s 6.24	And the second	6.00		s 5.44	5.20	4.53	44.3	R SANTA CLARA	44
-	BKWP	0.20		8 0.2.	5 0	0.00	J. 12	8 3.11			45.2	SAN JOSE YARD	45
Dani ause yan	IP										45.7	COLLEGE PARK	45
11/2	BKWOITYP	s 6.25		s 6.30	s 6.20	8 6.05	s 5.55	s 5.50	8 5.25	8 4.59	46.9	TO-R SAN JOSE	46
L	Limber Diss	Arrive Daily Ex. Sat., Sun.	Was Class Class	Arrive	Arrive Daily Ex. Sat., Sun.	Arrive Dally Ex. Sat., Sun. and Holidays	Arrive Daily Ex. Sunday	Arrive Daily	Arrive Daily	Arrive Daily	1	(46.9)	
T		(1.05) 43.29	(0.43) 44.37	(1.30) 31.27	(1.20) 35.18	(1.15)	(1.15) 37.52	(1.30) 31.27	(1.20) 35.18	(0.59) 47.69		Time over District	

Train	At At a state	Receive To (or Beyond)	Or Beyond)	Frequency	
78 78 122 122	Burlingame Pale Alto Paul Ave Newcomb Ave [Lomita Park Castro	Gilroy. Watsonville Jet Any Station Any Station	Any Station Any Station Any Station	Daily Daily Saturday Only Daily Sun. and Hol.	

RULES 86 and 93. Second and third-class trains, extra trains and engines, except trains handling passenger equipment only, must clear the time of Nos. 96, 97, 98 and 99 not less than 10 minutes, except between limits of Fourth St. and Potrero interlockings, San Francisco, and must be clear of main track and insulated joints at passing points for Nos. 96, 97, 98 and 99.

No. 77 reduce speed at Mountain View, San Mateo and So. San Francisco to exchange U. S. Mail.

8					SAN	FRAI	VCISCO	SUB	DIVIS	ION					
M				EA	STWAI	RD								1	
	A STATE OF THE STA			100	FIR	ST CLAS	35				3		Timetable No. 154		E 8
c	Capacity of sidings in car lengths	70 Coaster	150 Passenger	148 Passenger	146 Passenger	144 Passenger	142 Passenger	140 Passenger	138 Passenger	136 Passenger	Mile Post Location	-	June 2, 1946		Distance from San Francisco
		Leave Daily	Leave Daily	Leave Daily Ex. Sunday and Holidays	Leave Daily Ex. Sunday and Holidays	Leave Daily	Leave Daily Ex. Sat., Sun. and Holidays			STATIONS -					
ſ	BKWOITYP	PM 7.00	PM 6.30	PM 6.00	PM 5.45	PM 5.35	PM 5.32	PM 5.29	PM 5.26	PM 5.23	0.0	2	O-R SAN FRANCISCO		0.0
	Division	1.00	0.00	14	s		4				1.9		23rd STREET		1.9
				The same							4.1		PAUL AVE.		4.1
1	BKWOITP	7.09	die a	CL - In his	s 5.55	18,47	Special Property	3 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -		25-10-1	5.2		BAYSHORE		5.2
1	KIP	1.02									6.9		R VISITACION		6.9
			1								8.6		BUTLER ROAD		8.6
	10000	(F.K8)	s 6.44	AD CH	s 6.01	s 5.48	11.42				9.3		SO. SAN FRANCISCO		9.3
Ť	P	10.0	s 6.47	s 6.16	7	s 5.51	1 - 1	DE-West		1000	11.0		SAN BRUNO		11.0
			0.11	0.10	1 1 1 1	8				2	12.1		LOMITA PARK		12.
-	148 P		g	s	The state of	g	7-1				13.7		MILLBRAE		13.
14	Р	(E. B. 4)	s 6.55	s 6.24	s 6.11	TEIDIA	s 5.53	WINE I	MEDIC N		15.2		BROADWAY		15.
-	P	s 7.21	132.20			s 6.01		s 5.51		10-0-0	16.3		BURLINGAME		16.
	THE P. P.	8 1.21	s 7.02		s 6.19		s 5.59		s 5.49	16 B	17.9	System	SAN MATEO		17.
M	1 84 WP<					g			s 5.52		18.9	ock Sy	HAYWARD PARK	Doub	18.
111			s	s	s			s 5.58		s 5.47	20.3	Blo A	HILLSDALE	Double Track	20.
7	P	7	f	g		s 6.12			s 5.58		21.9	Automatic Bl	BELMONT	ack	21.
7.	1 47 P	31-E-4	s 7.12	s 6.41	s 6.29		s 6.08		The same	8 5.53	23.2	Aut	SAN CARLOS		23.
	1 N. L. M. 17	F. N. 19	The Event	s 6.45		s 6.18		s 6.06			25.4		REDWOOD CITY	生	25.
1	WIYP		3 1.10	5 0.13	0.00	5 0.10				TATE	26.2		R REDWOOD JCT.		26.
			g		g		s 6.16			Lange L	27.8		ATHERTON		27.
Ť	P		g	s 6.51	-	s 6.25	3 3.10			8 6.01	28.9		MENLO PARK		28.
7/	1 48 P	s 7.39	s 7 25	s 6.54	s 6.43	5.25	s 6.21	13 74 11	8 6.10		30.1		PALO ALTO		30.
	1 48 WYP	8 1.39	s 7.28		5 0.15	s 6.31	0.22	s 6.17			31.8		R CALIFORNIA AVE.		31.
	146 P	7.46	s 7.34	8 0.51	s 6.54	8 0.01	8 6.30	s 6.25	18.9	8 6.13	36.1		MOUNTAIN VIEW		36.
IVI	P	7.40	The second second	s 7.07	3 0.51	s 6.42	0.00	3 01410	s 6.23	A DESCRIPTION OF THE PARTY OF T	38.8		SUNNYVALE		38
ſ	KIP	8.00		s 7.14	7.05	6.50	8 6.41	6.35	6.30	The State of World	44.3		R SANTA CLARA		44
1	BKWP	8.00	7.75	11	1,100	0.00	3.11	3,03			45.2		SAN JOSE YARD		45
1	IP										45.7		COLLEGE PARK		45
	вкмогтур	s 8.05	s 7.50	s 7.20	s 7.10	8 6.55 PM	s 6.46	s 6.40	8 6.35	8 6.30 PM	46.9		TO-R SAN JOSE]	46
	BRUOTITE Language	Arrive Daily		Arrive Daily	Arrive Daily Ex. Sunday	40.00	Arrive Daily Ex. Sat., Sun.	Arrive Daily Ex. Sat., Sun.	Arrive Daily Ex. Sat., Sun	Arrive Daily Ex. Sat., Sun. and Holidays			(46.9)		
	NAT I	(1.05) 43.29	(1.20) 35.18	(1.20) 35.18	(1.25) 33.11	(1.20) 35.18	(1.14) 38.03	(1.11) 39.63	(1.09) 40.78	(1.07) 42.00			Time over District Average Speed per Hour		

AD	DITIONAL FLAG ST	OPS TO RECEIVE OR D	ISCHARGE REVENU	E PASSENGERS		
Train	At At	Receive To (or Beyond)	Discharge From (or Beyond)	Frequency		
140 144	Castro	Any Station	Any Station	Daily Sun. & Holidays		

SAN FRANCISCO SUBDIVISION

									WE	STWA	RD	-			
		Timetable No. 154						94	Are TFI	RST CLA	ss				
Location		June 2, 1946		Distance from San Jose	147 Passenger	99 Morning Daylight	255 Passenger	149 Passenger	151 Passenger	153 Passenger	71 Passenger	97 Noon Daylight	155 Passenger	157 Passenger	1
		STATIONS			Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily Ex. Sunday and Holidays	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily	
0.0	-	TO-R SAN FRANCISCO		46.9	PM s 5.20	PM s 6.00		PM s 6.45	PM s 7.30	PM s 7.35	PM 8 9.30	PM s 9.55	PM s 10.40	PM s 11.45	, u
1.9		23rd STREET		45.0	S									s	
4.1		PAUL AVE.		42.8	f										
5.2		BAYSHORE		41.7	s 5.07	5.50		6.35	7.20	s 7.25	9.19	9.45	f 10.30	s 11.36	
6.9		R VISITACION		40.0										Alle III	
8.6		BUTLER ROAD		38.3	S								f	f	
9.3		SO. SAN FRANCISCO		37.6	s 5.01			s 6.29	s 7.15	s 7.21	allite		s 10.22	s 11.29	
11.0		SAN BRUNO		35.9	s 4.57	5.43		s 6.24	s 7.05	s 7.17	9.09	9.38	s 10.18	s 11.25	
12.1		LOMITA PARK		34.8	f				f					f	
13.7		MILLBRAE 1.5		33.2	f			s	s	f .			f	s	
15.2		BROADWAY		31.7	s 4.49			The state of the	f 6.44		REAL B		A CANADA SA DA TRADA	s 11.15	
16.3		BURLINGAME 1.6		30.6	s 4.46			s 6.13	s 6.39	s 7.07	s 9.01			s11.11	
17.9	tem	SAN MATEO		29.0	s 4.42	5.34		s 6.08	s 6.34	s 7.03	s 8.56	9.29	s 10.03	s11.07	
18.9	sk Sys	HAYWARD PARK	Double	28.0	f									f	
20.3	Block	HILLSDALE	ble T	26.6	f			f	f				f	f	
21.9	matic	BELMONT 1.3	Track	25.0	s			f	s	s			f	f	
23.2	Autor	SAN CARLOS		23.7	s 4.32		ELL.	s 5.58	100	s 6.53			SAL MANAGER	s 10.57	
25.4		REDWOOD CITY		21.5	s 4.28			s 5.54	s 6.16	s 6.49	s 8.47		s 9.49	s 10.53	
26.2		R REDWOOD JCT.		20.7		5.25			10.0			9.20			
27.8		ATHERTON 1.1		19.1	f			f	f				f	f	
28.9		MENLO PARK		18.0	S			S	S	s			f	s	
30.1		PALO ALTO		16.8	s 4.18	VIEW VALUE OF		s 5.44	s 6.02	s 6.41	s 8.37		100 10 20 20 20 20 20 20 20 20 20 20 20 20 20	s 10.44	
31.8		R CALIFORNIA AVE.		15.1	s 4.14			s 5.39	f 5.51	s 6.37	Itali			f 10.39	
36.1		MOUNTAIN VIEW		10.8	s 4.07	5.15			1777	s 6.31	A LOUIS OF	9.10		s 10.32	
38.8		SUNNYVALE 5.5		8.1	s 4.03	56.0	Via Newark	8 5.27		s 6.27	I N. No. In J. C.			s 10.27	
44.3		R SANTA CLARA		2.6	s 3.55	Back	PM 5.10	s 5.20	s 5.25	s 6.20	8.15		s 9.15	s 10.20	
45.2		SAN JOSE YARD		1.7		AU E								177.15	
45.7		COLLEGE PARK		1.2	f								FLET	10	
46.9		TO-R SAN JOSE		0.0	3.50 PM	5.03 PM	5.05 PM	5.15 PM		6.15 PM	BNO	8.58 PM 8	9.10 PM	10.15 PM	all
		(46.9)			Leave Daily	Leave Daily			Leave Daily Ex. Sunday and Holidays	Leave Daily	Leave Daily	Leave Daily	Leave Daily	Leave Daily	
		Time over District Average Speed per Hou			(1.30) 31.27	(0.57) 49.37	(0.05) 31.20	(1.30) 31.27	(2.10) 21.65	(1.20) 35.18	(1.20) 35.18	(0.57) 49.37	(1.30) 31.27	(1.30) 31.27	1

RULE 5. Schedule time and train-order time apply at the location of station sign at stations between San Francisco and San Jose and on Santa Clara-Newark line will apply at junction switch, Santa Clara.

RULES 86 and 93. Second and third-class trains, extra trains and engines, except trains handling passenger equipment only, must clear the time of Nos. 96, 97, 98 and 99 not less than 10 minutes, except between limits of Fourth St. and Potrero interlockings, San Francisco, and must be clear of main track and insulated joints at passing points for Nos. 96, 97, 98 and 99.

AD	DITIONAL FLAG ST	OPS TO RECEIVE OR D	ISCHARGE REVENU	E PASSENGERS
Train	At	Receive To (or Beyond)	Discharge From (or Beyond)	Frequency
153	HillsdaleBayshore	Any Station	Any Station	Sun. & Hol.

No. 71 reduce speed, stopping if necessary, at Santa Clara and South San Francisco to exchange U. S. Mail.

=	.0			TEA	COTTA	DD		-							24/17/1-
			18	EA	STWA					-			m		
					FI	RST CLAS	55				#		Timetable No. 154		Hori See
	Capacity of sidings in car lengths	991	100 111	158 Passenger	156 Passenger	76 Lark	154 Passenger	74 Oakland Lark	374 с. м. е.	152 Passenger	Mile Post Location		June 2, 1946		Distance from San Francisco
	and some	i popili		Leave Daily	Leave Daily	Leave Daily	Leave Daily	Leave Daily	Leave Daily Ex. Saturday and Sunday	Leave Daily			STATIONS		
1	BKWOITYP	L. Millian		PM 11.10	PM 9.45	PM 9.00	PM 8.30		PM 7.40	PM 7.20	0.0	r	O-R SAN FRANCISCO		0.0
1	BRWOILI			f	7.10	3,00					1.9		23rd STREET		1.9
				-							4.1		PAUL AVE.		4.1
sco y	BKWOITP	BE.011	EDVAL.	f11.20	f 9.54	9.09	f 8.39		7.50	7.29	5.2		BAYSHORE		5.1
Ban Francisco yard	KIP										6.9	F			6.9
Dans				1111							8.6	1	BUTLER ROAD		8.0
	THE LIE	EE,011		s 11.26	s 10.00	8100-1	s 8.45			s 7.34	9.3		SO. SAN FRANCISCO		9.3
	P	61.01	DER	s 11.29	A STATE OF THE PARTY OF THE PAR	9.15	s 8.49		7.57	s 7.37	11.0		SAN BRUNO	-	11.
				f	s		f			s	12.1		LOMITA PARK		12.
,	(48 P			f	s		f			s	13.7		MILLBRAE	_	13.
-	P	MARCH		s 11.38	s 10.12	7.0	s 8.56		77	s 7.46	15.2		BROADWAY		15.
	P	KONT		s 11.41		s 9.23	s 8.59			s 7.49	16.3	He II	BURLINGAME	-	16.
200	REITS	10,01	THE WAT	s 11.45			s 9.03		8.08	s 7.53	17.9	Syst	SAN MATEO	_	17.
N	84 WP				f		f			f	18.9	Block	HAYWARD PARK	Double	18.
		-		f	f		f			f	20.3	natic	HILLSDALE	le Track	20.
	Р			f	s		f			S	21.9	Auton	BELMONT	- Cr	21.
N	47 P	Mayle, 9		s 11.54	s 10.28		s 9.12		8.14	s 8.02	23.2		SAN CARLOS	_	23.
-	7.02	E- 0.1		PM s 11.58	White Sour Lawrence		s 9.16	W. L.		8 8.06	25.4		REDWOOD CITY	-	25
{	WIYP.		WEST T			9.35	DATE:		8.20		26.2	1	R REDWOOD JCT.	_	26.
				f	f		f			ſ	27.8		ATHERTON	_	27
1	P			s	s 10.37		s 9.22	STATE OF		8	28.9		MENLO PARK	-	28
M	48 P	ME AND		AM		s 9.42	1000000			8 8.16	30.1	1	PALO ALTO	-	30
	48 WYP	MED OF		s 12.11			s 9.29			8 8.19	31.8]	R CALIFORNIA AVE.	_	31
-	46 P	RET F	en de la constante	s12.17		9.50	s 9.36		KIE	8 8.27	36.1		MOUNTAIN VIEW	-	36
917	P	EL G		s 12.22			s 9.41	Via Newark	8.40	s 8.33	38.8		SUNNYVALE	-	38
, [KIP	El Ensi		s 12.29		9.58	s 9.49	PM 9.40	8.48	1 8.40	44.3	1	R SANTA CLARA	-	44
-	BKWP								8:38	1 8.40	45.2		SAN JOSE YARD	_	45
Dan suse yard	IP			f	f		f				45.7		COLLEGE PARK	-	45
Da	BKWOITYP	0 32	WW.E.	s 12.35	811.10	8 10.03 M	8 9.55 PM	s 9.50	PM35	# 8.45	46.9		TO-R SAN JOSE)	46
	Thinne.		1/6/14			Arrive Daily		Arrive Daily	Arrive Daily Ex. Saturday and . Sunday	Arrive Daily			(46.9)	,	
_	The state of the s	1000	The state of the s	(1.25) 33.11	(1.25) 33.11	(1.03) 44.67	(1.25) 33.11	(0.10) 15.60	(1.55)	(1.25) 33.11	S. III STEELS		Time over District Average Speed per Hou	r	

RULES 86 and 93. Second and third-class trains, extra trains and engines, except trains handling passenger equipment only, must clear the time of Nos. 96, 97, 98 and 99 not less than 10 minutes, except between limits of Fourth St. and Potrero interlockings, San Francisco, and must be clear of main track and insulated joints at passing points for Nos. 96, 97, 98 and 99.

Train	At	Receive To (or Beyond)	Discharge From (or Beyond)	Frequency
152	Bayshore	Any Station	Any Station	Sun. & Hol. Daily

No. 76 reduce speed at San Mateo to 25 MPH to exchange U. S. Mail.

4							WE	STWAR	D		100000000000000000000000000000000000000	CROCERON
	Timetable No. 154							IRD CLAS			- We restate the M	TO REAL PROPERTY.
Mile Post Location	June 2, 1946		Distance from	401 Freight	409 Freight	413 Freight	300	2006	285		196	
	STATIONS		,	Arrive Daily	Arrive Daily	Arrive Daily	TINT HAT	Pataina	du maren			
0.0	TO-R SAN FRANCISCO	7	46.9		T HATE							
1.9	1.9 23rd STREET 2.2	-	45.0									-
4.1	PAUL AVE.		42.8									
5.2	BAYSHORE 1.7		41.7	4.10	AM 11.55	PM 7.55		TWO I				
6.9	R VISITACION		40.0	1	11.00							
8.6	BUTLER ROAD		38.3			A THE STATE OF THE						
9.3	SO. SAN FRANCISCO		37.6									
11.0	SAN BRUNO		35.9									
12.1	LOMITA PARK		34.8									1
13.7	MILLBRAE 1.5		33.2									
15.2	BROADWAY		31.7				-					
16.3	BURLINGAME 1.6		30.6	WALL CO.								
17.9	SAN MATEO 1.0 HAYWARD PARK		29.0	Mile .								
18.9	정 1.4	Double	28.0									
20.3	HILLSDALE 1.6 BELMONT	le Track	26.6									
21.9	1.3	- Ck	25.0			Line State Land						
23.2	SAN CARLOS 2.2 REDWOOD CITY	-	21.5	Mr. Cal								
25.4	R REDWOOD JCT.	_	20.7	310	10.55	6.55		-				
27.8	1.6 ATHERTON	-	19.1	3.10 AM Via	10.55 Via	6.55 Via		100				
28.9	1.1 MENLO PARK	-	18.0	Dumbarton	Dumbarton	Dumbarton				1		-
30.1	PALO ALTO	-	16.8	-								-
31.8	R CALIFORNIA AVE.	-	15.1				_					
36.1	MOUNTAIN VIEW	-	10.8	- 1 St. 1								-
38.8	SUNNYVALE	-	8.1	80.0								
44.3	R SANTA CLARA	-	2.6	The state of			_					-
45.2	0.9 SAN JOSE YARD	-	1.7	-				-			1224	-
45.7	0.5 COLLEGE PARK	-	1.2		_	-						-
46.9	TO-R SAN JOSE	-	0.0	CST.					1000			
	(46.9))		Leave Daily	Leave Daily	Leave Daily						
	Time over District	_		(1.00) 21.00	(1.00) 21.00	(1.00) 21.00						

NAME	Mile Post	Capac-
Newcomb Ave. Tanforan Wye. Aqua. (Spur) Howest (Spur) Romac (Spur) Bay Meadows (Spur) Stauffer (Spur) Redwood Harbor (Spur) Castro. (Spur)	3.1 10.4 12.9 16.8 19.7 20.0 27.3 28.7 34.8 40.8	11 12 14 11 29

1	.2		SAN	FRA	NCISC	co sub	DIVIS	ON		1			
Ī		EA	ASTWA	RD								7.	
		THIRD CLA	ss a mil		Value of	SECOND	CLASS				Timetable No. 154		
	Capacity of sidings in car lengths	766 Freight	408 Freight	472 Freight		402 B, M.	444 с. с. м.	108 Express	Mile Post Location		June 2, 1946		Distance from San Francisco
		Leave Daily	Leave Daily	Leave Daily		Leave Daily Ex. Sunday	Leave Daily Ex. Sunday	Leave Daily			STATIONS		14
	BKWOITYP				-	PM 7.50	PM 7.10	AM 1.30	0.0	1	TO-R SAN FRANCISCO	1	0.0
Ī	BRWOITI								1.9		23rd STREET		1.9
									4.1		PAUL AVE.		4.1
o yar	DAMMONIA	PM 9.15	8.30	12.20	0.1	100	LET'S	1.39	5.2		BAYSHORE		5.2
VIDCISC V	BKWOITP	9.15	8.30	12.20					6.9		R VISITACION		6.9
San Francisco yard	KIP					77			8.6		BUTLER ROAD		8.6
ã				9 1111		-		s 1.55	9.3		SO. SAN FRANCISCO		9.3
	P		10 00					s 2.15	11.0		SAN BRUNO		11.0
	P								12.1		LOMITA PARK		12.1
_	M 48 P							s	13.7		MILLBRAE		13.7
1	M 48 P								15.2		BROADWAY		15.2
	P			THE STATE				s 2.35	16.3		BURLINGAME		16.3
-								s 2.55	17.9	men	SAN MATEO		17.9
V	1 84 WP				11000				18.9	k System	HAYWARD PARK	Do	18.9
-					-				20.3	Block	HILLSDALE	Double Track	20.3
	P							s	21.9	Automatic	BELMONT	rack	21.9
*	1 47 P	THE VALUE						s 3.15	23.2	Auto	SAN CARLOS		23.2
_	***							s 3.40	25.4		REDWOOD CITY	_	25.4
10.1	WIYP	10.05	9.30 AM	1.20 AM		8.40 PM	BINO	PRE	26.2		R REDWOOD JCT.		26.2
- '	,,,,,,		Via Dumbarton	Via Dumbarton		Via Dumbarton	Via Dumbarton	THE PROPERTY.	27.8		ATHERTON		27.8
	Р.				-			8	28.9		MENLO PARK		28.9
,	4 48 P		FELL					s 3.58	30.1		PALO ALTO		30.1
10	1 48 WYP			100				8 4.03	31.8		R CALIFORNIA AVE.		31.8
THE	1 46 P				Acres - Section			s 4.28	36.1		MOUNTAIN VIEW		36.1
A.	P P							s 4.43	38.8		SUNNYVALE		38.8
- [KIP							s 4.54	44.3		R SANTA CLARA		44.3
yarr	BKWP	PM 10.45							45.2		SAN JOSE YARD	_	45.2
San Jose yard	IP								45.7		COLLEGE PARK	_	45.7
Sai	BKWOITYP	12,01						s 5.00	46.9		TO-R SAN JOSE)	46.9
		Arrive Daily	Arrive Daily	Arrive Daily		Arrive Daily Ex. Sunday	Arrive Daily Ex. Sunday	Arrive Daily			(46.9)		
		(2.46) 15.07	(1.00) 21.00	(1.00)		(0.50)	(0.50)	(3.30) 13.40			Time over District Average Speed per Hou	ır	

the state of the s

RULE 5. Schedule time and train-order time apply at the location of station sign at stations between San Francisco and San Jose and on Santa Clara-Newark line will apply at junction switch, Santa Clara.

0.0

Leave Daily Ex. Sunday and Holidays

LOS GATOS

(8.9)

.....Time over District...... Average Speed per Hour.

54.3

Arrive Daily

Ex. Sunday and Holidays

(0.35) 15.26

Arrive Saturday only

TO-R

E	ASTWAR	D		Petro Prolitar Land	WEST	WARD
	FIRST	CLASS		Timetable No. 154		FIRST
Capacity of sidings	132	170	Mile Post Location	June 2, 1946	Distance from Vasona Jct.	129
in car lengths	Passenger	Passenger	Local	Los Altos Branch	İstar	Passenger
	Leave Daily Ex. Sat., Sun. and Holidays	Leave Saturday only		STATIONS	А	Arrive Daily Ex. Sunday and Holidays
28 WYP	PM 6.03	PM 1.55	31.8	R CALIFORNIA AVE.	16.3	s 7.26
P	s 6.13	s 2.05	35.7	LOS ALTOS	12.4	s 7.17
	s	s	37.5	SPRINGER ROAD	10.6	f
	s 6.18	s 2.10	38.2	LOYOLA	9.9	f
65 W	f	f	39.7	1.5 SIMLA	8.4	f
	s 6.24	s 2.16	41.0	MONTA VISTA	7.1	f 7.04
	f	f	43.8	AZULE	4.3	f
	s 6.32	f 2.24	45.2	CONGRESS JCT.	2.9	f 6.55
	f	f	46.1	SAN TOMAS	2.0	f
	f	f	46.9	POLLARD ROAD	1.2	· a tres o
	f	f	47.8	QUITO	0.3	4 .
YP	f 6.43	f 2.35 PM	48.1 51.8	R VASONA JCT.	0.0	6.51 AM
	Arrive Daily Ex. Sat., Sun. and Holidays	Arrive Saturday only		(16.3)		Leave Daily Ex. Sunday and Holidays
	(0.40) 24.45	(0.40) 24.45		Time over District		(0.35) 27.95

EASTWARD

Capacity of sidings

in car lengths

Yard Limits

San.

45

BKWOITYP

WP

YP

132

Arrive Daily Ex. Sat., Sun. and Holidays

(0.10)

	AST-	Timetable No. 154	WEST- WARD
	ti e	June 2, 1946	from
	Mile Post	San Bruno Branch	Distance from
	MJ	STATIONS	Dist
0	4.0	BERNAL	9.6
	5.2	ELKTON	8.4
	6.3	OCEAN VIEW	7.3
ard	7.4	DALY CITY	6.2
isco	8.1	UNION PARK	5.5
San Francisco yard	8.5	COLMA	5.1
San	9.7	EMANUEL	3.9
	11.4	1.7 BADEN	2.2
	13.0	TANFORAN	0.6
	13.6 11.0	SAN BRUNO	0.0

Leave Saturday only

(0.35) 15.26

Leave Daily Ex. Sat., Sun. and Holidays

RULE S-72. Exceptions: No. 192 superior to No. 129. No. 170 superior to No. 185. No. 132 superior to No. 193.

ADDITIONAL STAT	IONS	CASTLEONIA
NAME	Mile Post	Capacity
Los Gatos Branch Vasona	52.9	6
Los Altos Branch Neal Alta Mesa Permanente (On spur 2.42 miles from Simla)	33.0 34.0 42.1	::

Train	At	Receive To (or Beyond)	Discharge From (or Beyond)	Frequency	
129-132-170 129-132-170	Road Crossing 1.4 mile west of Azule Alta Mesa	Any Station	Any Station	Daily	

14.			GILR	OY SU	BDIVI	SION	188			
TO GRAWIE	EA	STWA	RD						AWTEAT	
er ay tar		FI	RST CLA	88	Man I		4)	2019	Timetable No. 154	8
Capacity of sidings in car lengths	76	374 c. m. e.	70 Coaster	78 Del Monte	96 Noon Daylight	72 Passenger	98 Morning Daylight	Mile Post Location	June 2, 1946	Distance from
	Leave Daily	Leave Daily Ex. Sat., Sun.	Leave Daily	Leave Daily	Leave Daily	Leave Daily	Leave Daily		STATIONS	
BKWOITYP I	PM 10.12	PM 9.35	PM 8.15	PM 5.06	PM 1.08	AM 9.45	AM 9.12	46.9	TO-R SAN JOSE	0.0
				M				49.1	WPRR Crossing	2.2
sof usg	10.19	9.42	8.22	5.12		9.52		51.4 55.3	LICK)	4.5
M94 WP	10.28	9.51	8.31	5.20	1.20	10.00	9.26	63.1	TO COYOTE	12.3
129 P	10.33		8.38				PER	66.3	PERRY	15.5
P			June	in the second				69.2	MADRONE	18.4
125 P	10.38	10.01	8.48	5.28	1.28	s 10.11	9.34	70.8	TO MORGANHILL	20.0
130 P	10.42					19:11		74.6	SAN MARTIN	23.8
129 P	10.45							77.0	RUČKER	26.2
Yard Limits M98 WTP	10.49	10.13	s 9.01	8 5.40	1.38	810.25	9.44	80.7	TO-R GILROY	29.9
P	HOW SHARE	HC .	3.690			X T		83.2	CARNADERO 3.9	32.4
128 WP	10.56	10.23	9.07	5.47	1.44	10.34	9.50	87.1	SARGENT	36.3
127 P	11.04		10.31					91.9	CHITTENDEN	41.1
P	11.07	10.34	9.18	5.58	1.55	10.45	10.01	93.2	LOGAN	42.4
P						f		94.6	AROMAS	43.8
bord by BKWOTYP	ate Carl			- 600		11.00	10.10	98.6	TO-R PAJARO	47.8
BKWOTYP	s 1 1 17	s 10.46	8 2.28	8 6.08	s 2.04	* 1 1.00	10.10 AM	100.4	TO-R WATSONVILLE JCT.	49.6
TVID (HOLD)	Arrive Daily	Arrive Daily Ex. Sat., Sun.	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily		(49.6)	
	(1.05) 45.79	(1.11)	(1.13)	(1.02) 48.00	(0.56) 53.14	(1.15)	(0.58) 51.31		Time over District	

RULE 5. Schedule time and train-order time apply at the end of double track at Lick, Coyote, Gilroy, Sargent and Logan, except that of eastward trains at Gilroy will apply at train-order signal.

RULE S-72. Exception: No. 98 is superior to Nos. 71, 69, 75, 373 and 77.

RULES 86 and 93. Third-class trains, extra trains and engines, except trains handling passenger equipment only, must clear the time of Nos. 96, 97, 98 and 99 not less than 10 minutes and must be clear of main track and insulated joints at meeting and passing points for Nos. 96, 97, 98 and 99.

AD	DITIONAL FLAG ST	OPS TO RECEIVE OR	DISCHARGE REVENU	E PASSENGERS
Train	At	Receive To (or Beyond)	Discharge From (or Beyond)	Frequency
72	Any Station	Los Angeles,		Daily

	EAST- WARD	Timetable No. 154	WEST- WARD
Capacity of sidings in car lengths	N S	June 2, 1946	from
	Mile Post Location	Lick Branch	Distance from
		STATIONS	A
Se P	51.4 55.3	LICK	3.6
10 P	58.9	ALAMITOS	0.0
		(3.6)	1

S and SE class engines only, permitted to operate on Lick Branch.

(1.05)

(1.02)

RULE 5. Schedule time and train-order time apply at the end of double track at Lick, Coyote, Gilroy, Sargent and Logan, except that of eastward trains at Gilroy will apply at train-order signal.

.....Time over District...... Average Speed per Hour...

RULE S-72. Exception: No. 98 is superior to Nos. 71, 69, 75, 373 and 77

RULES 86 and 93. Third-class trains, extra trains and engines, except trains handling passenger equipment only, must clear the time of Nos. 96, 97, 98 and 99 not less than 10 minutes and must be clear of main track and insulated joints at meeting and passing points for Nos. 96, 97, 98 and 99.

		EAST- WARD	Timetable No. 154	WEST- WARD
Capacity of sic	APPLACE AND A	t g	June 2, 1946	from
		Mile Post Location	Hollister Branch	Distance from Hollister
100		AL .	STATIONS	ä
	P	83.2	CARNADERO	11.7
16	WP	94.9	HOLLISTER	0.0
	mar and		(11.7)	1

AE	DITIONAL FLAG ST	OPS TO RECEIVE OR D	ISCHARGE REVENU	E PASSENGERS
Train	At	Receive To (or Beyond)	Discharge From (or Beyond)	Frequency
71	Any Station		Los Angeles	Daily

(0.58) 51.31

(1.15) 39.68

(0.58)

ADDITIONAL STAT	TIONS	
NAME	Mile Post	Capac- ity
Edenvale (Spur) Lonoke (Spur) Miller (Spur) Eaton (Spur)	57.4 79.1 84.4 97.1	20 P 7 18 13 P
Hollister Branch Hudner(Spur)	90.3	10

16		GILROY SI	UBDIV	ISION				
	EASTW	ARD						
Capacity of sidings in car lengths	78 11	772	770 Freight	768 Freight	766 Freight	Mile Post Location	Timetable No. 154 June 2, 1946	Distance from San Jose
		Leave Daily	Leave Daily	Leave Daily	Leave Daily		STATIONS	4
BKWOITYP E		PM 5.10	PM 1.45	AM 7.45	AM 12.01	46.9	TO-R SAN JOSE	0.
BKWOITYP Interior				11.13	12.0	49.1	WPRR Crossing	2.
P		5.20	2.00	8.00	12.15	51.4 55.3	LICK D	4.
M 94 WP		5.45	2.25	8.30	12.35	63.1	TO COYOTE	12.
129 P		5.53	2.33	8.38	12.43	66.3	PERRY	15.
P					n-	69.2	MADRONE	18.
125 P		6.13	2.53	9.35	1.03	70.8	TO MORGANHILL	20.
130 P		6.19	2.59	9.42	1.09	74.6	SAN MARTIN	23.
129 P		6.24	3.05	9.46	1.14	77.0	SAN MARTIN 2.4 RUCKER	26.
Yard Limits M 98 WTP		6.30	3.11	9.52	1.21	80.7	TO-R GILROY	29.
P						83.2	CARNADERO 3.9	32.
128 WP	77.8 B.CZ	7.02	3.21	10.02	1.30	87.1	SARGENT	36.
127 P		7.13	3.30	10.13	1.45	91.9	CHITTENDEN 1.3	41.
P	NUM TASK	7.16	3.34	10.16	1.50	93.2	LOGAN 1.4	42.
P						94.6	AROMAS	43.
F BKP BKWOTYP		7.30	3.50	10.30	2.05	98.6	TO-R PAJARO	47.
F L BKWOTYP	845 493	7.30 PM	, 3.50 PM	10.30 AM	2.05 AM	100.4	TO-R WATSONVILLE JCT.	49.
		Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily		(49.6)	
		(2.20) 21.26	(2.05) 23.81	(2.45) 18.04	(2.04) 24.00		Average Speed per Hour	
EASTWARD				WEST	WADD			

	EAST	WARD				WEST	WARD
	a deline	SECOND CLASS	n.	Timetable No. 154	1	THIRD	CLASS
		774	Mile Post Location	June 2, 1946	Distance from Olympia	773	in the Late
	city of sidings car lengths	Freight	Log	Santa Cruz Branch	Dista 01	Freight	
		Leave Daily Ex. Sunday		STATIONS		Arrive Daily Ex. Sunday	DATE OF THE SECOND
Watson- ville Jet.	вкуотур	AM 8.30	100.4 100.5	TO-R WATSONVILLE JCT.	28.9	PM 5.00	
Wat			102.0	WATSONVILLE	27.4	A GROW TO	
33	P	THE PARTY NAMED IN	104.0	NUGA	25.4		
12	P		107.3	ELLICOTT	22.1		
9	P	9.05	112.8	APTOS	16.6	4.20	
15	Spur P		115.9	CAPITOLA	13.5		
its.	вкмотур	9.45 AM	120.6	TO-R SANTA CRUZ	8.8	3.45 PM	
Xd.Lmts.	6	1	121.8	▼ EBLIS	7.6		diam'r.
23	P	•	124.4	RINCON	5.0		
31 X	ard Limits WP		127.4	TO FELTON	2.0		
13	P		129.4	OLYMPIA	0.0		
		Arrive Daily Ex. Sunday		(28.9)		Leave Daily Ex. Sunday	12.0
100000		, (1.15) 16.08		Average Speed per Hour		(1.15) 16.08	

RULE 5. Schedule time and train-order time apply at the end of double track at Lick, Coyote, Gilroy, Sargent and Logan, except that of eastward trains at Gilroy will apply at train-order signal.

RULES 86 and 93. Third-class trains, extra trains and engines, except trains handling passenger equipment only, must clear the time of Nos. 96, 97, 98 and 99 not less than ten minutes and must be clear of main track and insulated joints at meeting and passing points for Nos. 96, 97, 98 and 99.

ADDITIONAL STAT	rions	
NAME	Mile Post	Capac-
Santa Cruz Branch Cristo(Spur)	109.0	3
New Brighton (Spur) Cliffside (Spur) Twin Lakes	114.7 118.1 118.9	6
Seabright(Spur) Casino Park St	119.4 120.1 121.4	
Big Trees	126.5 127.7	

						GILR	OY SU	BDIVI	SION	Trate of the				17
									WE	STWA	RD			
		Timetable No. 154		e ti				RAI	IO TH	IRD CLAS	s			
Mile Post Location		June 2, 1946		Distance from Watsonville Jct.	761 Freight	763 Freight	765 Freight	767 Freight	0%	155 2.4.0	85			Applicate (control)
		STATIONS	7	•	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily	4- 19/1				A CONTRACTOR	
46.9		TO-R SAN JOSE		49.6	AM 2.30	AM 8.30	PM 2.50	PM 7.45		105/17	2271			
49.1		WPRR Crossing		47.4	miran.			C. I	EDIT	Commi		ii ii		N. PER
51.4 55.3		LICK 7.8) =	45.1	2.19	8.19	2.35	7.34	2100	10.1.1				AKW AL
63.1		TO COYOTE]:	37.3	2.09	8.07	2.23	7.22		OSCILLO	Ebet	The state of the s		3 - 37
66.3		PERRY 2,9		34.1	2.00	8.01	2.17	7.16	socdt i	100 7	Zeo I I de			Crompa eso.
69.2		MADRONE 1.6		31.2	ar m	1000	SE WEST		30.01	0.00, 1-7	ne de			dir lan
70.8	System	TO MORGANHILL		29.6	1.51	7.52	2.08	7.07		3.6				1 76
74.6	k Sys	SAN MARTIN		25.8	1.41	7.42	1.58	6.57	61.01		edili			TW Inte
77.0	Block	RUCKER 3.7		23.4	1.31	7.34	1.50	6.49					-	
80.7	matic	TO-R GILROY 2.5		19.7	1.21	7.24	1.40	6.39	1000	02.11	etter			277
83.2	Autom	CARNADERO 3.9	D.T.	17.2					die Gr		10.01			T UA
87.1		SARGENT 4.8		13.3	12.56	7.10	1.20	6.25	. E. L. P	1000	REAL PROPERTY.			
91.9		CHITTENDEN 1.3		8.5	12.40	6.55	1.05	6.10	(A.O)	442				7 000
93.2		LOGAN 1.4	7	7.2	12.35	6.50	1.00	6.05	ALC: NO					1
94.6		AROMAS 4.8	6	5.8	(A) (F) (F)	pulsar!	4		La ser		9.8756			T 7 25
99.4		TO-R PAJARO	D.T.	1.0					7	1				Tay.
100.4		TO-R WATSONVILLE JCT.		0.0	12.10 AM	6.30 AM	12.35 PM	5.45 PM	ne year		- Adapted			SWE SI
		(49.6)			Leave Daily	Leave Daily	Leave Daily	Leave Daily		Web York	district			
		Time over District			(2.20) 21.26	(2.00) 24.80	(2.15) 22.04	(2.00) 24.80	Hend	H1711	THE S			

EAST	WARD		of the players with the	- Jag	WESTWARD
	SECOND CLASS	Tu Di	Timetable No. 154	E +	THIRD CLASS
Capacity of sidings	774	Mile Post Location	June 2, 1946	Distance from Davenport	773
in car lengths	Freight	NE	Davenport Branch	Dist	Freight
	Leave Daily Ex. Sunday		STATIONS	100	Arrive Daily Ex. Sunday
BKWOTYP	11.00	120.6 79.2	TO-R SANTA CRUZ	11.5	PM 2.45
17 44		81.1	orby	9.6	
33		85.9	GORDOLA	4.8	
WYP	12,01	90.7	R DAVENPORT	0.0	1.45
	Arrive Daily Ex. Sunday		(11.5)		Leave Daily Ex. Sunday
	(1.01) 11.31		Time over District		(1.00) 11.50

ADDITIONAL STAT	IONS	
NAME	Mile Post	Capac-
Davenport Branch Wilder(Spur) Majors	83.4 86.7	2

A STATE TO THE STATE OF T

RULE 5. Schedule time and train-order time apply at the end of double track at Lick, Coyote, Gilroy, Sargent and Logan, except that of eastward trains at Gilroy will apply at train-order signal.

RULES 86 and 93. Third-class trains, extra trains and engines, except trains handling passenger equipment only, must clear the time of Nos. 96, 97, 98 and 99 not less than 10 minutes and must be clear of main track and insulated joints at meeting and passing points for Nos. 96, 97, 98 and 99.

18			SALI	NAS SI	JBDIV	ISION				
	E/	ASTWA	RD		Market State of the State of th					
		seeda FI	RST CLA	ss					Timetable No. 154	E ti
Capacity of sidings in car lengths	76 Lark	374 c. m. e.	70 Coaster	78 Del Monte	96 Noon Daylight	72 Passenger	98 Morning Daylight	Mile Fost Location	June 2, 1946	Distance from Watsonville Jct.
	Leave Daily	Leave Daily Ex. Sat., Sun.	Leave Daily	Leave Daily	Leave Daily	Leave Daily	Leave Daily		STATIONS	
Watsonville Jet. yard BKWOTYP	PM 11.25	PM 11.02	PM 9.35	PM 6.10	PM 2.05	AM 11.15	AM 10.10	100.4	TO-R WATSONVILLE JCT.	0.0
110 P	11.33	11.10	9.43	6.17		11.23	10.18	105.8	5.4 ELKHORN	5.4
132 WYP	11.39	11.16	9.49	s 6.23	2.18	s 1 1.31	10.23	110.4	TO-R CASTROVILLE	10.0
112 P	11.43	11.20	9.54		VE GUE	THE	182 C	113.9	COOPER	13.5
228 BKWOTP	s 11.55	11.26	s 10.05		s 2.30	s 11.59	s 10.35	118.2	TO-R SALINAS	17.8
93 YP	PM 11.59	To the second	10.08		2.33	PM 12.03	10.38	120.3	SPRECKELS JCT.	19.9
44 P		11.34		3.51	TIO-Y		77.1	125.3		24.9
101 WP .	12.09	11.39	10.18	VE O	2.40	s 12.17	10.46	129.1	3.8	28.7
44 P					OL.			131.9	CHUALAR 2.8 PENVIR	31.5
119 P	12.15	11.46	10.24		2.45	s 12.24	10.51	135.1	TO GONZALES	34.7
43 P	12.21		10.30					140.6	CAMPHORA	40.2
Yard Limits 156 KWP	12.24	PM 11.56	10.34		2.52	s 12.40	10.58	143.6	TO-R SOLEDAD	43.2
102 P	12.29	12.01	10.39		3.03	12.45	10.00	148.3	4.7 HARLEM	47.9
43 P						f 12.50	11.08	152.3	4.0 METZ	51.9
76 P	12.41	12.14	10.51		3.15	12.57	11.14	158.9	COBURN	58.5
YP						12.0	11.1.1	161.0	2.1 ELSA	7
112 KWP	12.46 AM	12.20	s 10.56	Maria 1	3.19 PM	s 1.02	11.20 AM	163.7	TO-R KING CITY	60.6
	Arriva Daily	Arrive Deller	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily	103.7	(63.3)	63.3
	(1.21) 46.89	(1.18) 48.69	(1.21) 48.69	(0.13) 46.15	(1.14) 51.32	(1.47) 35.50	(1.10) 54.26		Time over District	

RULE 5. At Salinas schedule time and train-order time apply Eastward at crossover west of Signal 1185. At Gonzales Eastward at crossover at station.

RULE S-72. Exception: No. 98 is superior to Nos. 71, 69, 75, 373 and 77.

RULES 86 and 93. Third-class trains, extra trains and engines, except trains handling passenger equipment only, must clear the time of Nos. 96, 97, 98 and 99 not less than 10 minutes and must be clear of main track and insulated joints at meeting and passing points for Nos. 96, 97, 98 and 99.

Train	At	Receive To (or Beyond)	Discharge From (or Beyond)	Frequency
72	Any Station	Los Angeles,		Daily

RULE 5. At Salinas schedule time and train-order time apply Eastward at crossover west of Signal 1185. At Gonzales Eastward at crossover at station.

RULE S-72. Exception: No. 98 is superior to Nos. 71, 69, 75, 373 and 77.

RULES 86 and 93. Third-class trains, extra trains and engines, except trains handling passenger equipment only, must clear the time of Nos. 96, 97, 98 and 99 not less than 10 minutes and must be clear of main track and insulated joints at meeting and passing points for Nos. 96, 97, 98 and 99.

AD	DITIONAL FLAG ST	OPS TO RECEIVE OR D	ISCHARGE REVENU	E PASSENGERS
Train	At	Receive To (or Beyond)	Discharge From (or Beyond)	Frequency
71	Any Station		Los Angeles	Daily

ADDITIONAL STA	TIONS	
NAME	Mile Post	Capac- ity
Graves(Spur)	115.6 138.8	28 26

1.09

1.20

1.38

1.48 AM

Arrive Daily

(2.08)

5.45

5.53

6.10

6.20 PM

Arrive Daily

Arrive Daily Ex. Sunday

Arrive Daily Ex. Sunday

RULE 5. At Salinas schedule time and train-order time apply eastward at crossover west of Signal 1185. At Gonzales eastward at crossover at station. At Del Monte westward at crossover just west of station; eastward at crossover just east of station. At Monterey westward at first crossover just west of scale house; eastward at east end of siding.

43

156

102

43

76

Yard Limits KWP

Yard Limits KWP

P

P

P

YP

RULES 86 and 93. Third-class trains, extra trains and engines, except trains handling passenger equipment only, must clear the time of Nos. 96, 97, 98 and 99 not less than ten minutes and must be clear of main track and insulated joints at meeting and passing points for Nos. 96, 97, 98 and 99.

RULE S-72. Exception: No. 764 is superior to No. 769.

NAME	Mile Post	Capac-
Monterey Branch Lapis (Spur) Bardin Marina (Spur) Retreat (Spur) Asilomar (Spur)	114.8 115.4 117.3 122.1 124.3 129.9	115 13 13 13 27

	EAST	WARD	Talent				WEST	WARD
	THE .	THIRD	FIRST	ti e	Timetable No. 154	rom	FIRST	THIRD
	Capacity of sidings in car lengths		78	Mile Post Location	June 2, 1946	Distance from Lake Majella	77	769
an out at	eng	Freight	Del Monte		Monterey Branch	D	Del Monte	Freight
	Leave Daily Ex. Sunday Leave Daily			STATIONS		Arrive Daily	Arrive Daily Ex. Sunday	
132 Yard I	Limits WYP	AM 7.10	PM 6.24	110.4	TO-R CASTROVILLE	19.6	s 8.21	PM 3.30
77	P	7.12		111.5	I.1 GAY	18.5		3.25
- 77		7.15		112.4	NASHUA	17.6		3.20
	Р	7.21		113.9	NEPONSET	16.1		3.05
101	P	Version 10	f 6.40	119.2	5.3 ORD	10.8	f 8.01	
13	P			119.7	GIGLING	10.3		2.45
12				120.4	WORKFIELD	9.6		
st e				123.3	SEASIDE	6.7		
Yard Limits	P		s 6.54	124.9	DEL MONTE	5.1	s 7.52	
117	P	8.30	s 6.57	125.7	TO MONTEREY	4.3	s 7.50	2.00 PM
Yard I	Limits KWTP	8.45 AM	s 7.05	128.3	TO-R PACIFIC GROVE	1.7	7.40 AM	11.30 AM
~				130.0	LAKE MAJELLA	0.0		
		Arrive Daily Ex. Sunday	Arrive Daily		(19.6)		Leave Daily	Leave Daily Ex. Sunday
		(1.35) 11.30	(0.41) 28.68		Time over District		(0.41) 28.68	(4.00) 4.47

7.36

7.44

8.02

8.10

Arrive Daily

(1.55)

143.6

148.3

152.3

158.9

161.0

163.7

SOLEDAD

HARLEM

METZ

COBURN

ELSA

KING CITY

(63.3).....Time over District...... Average Speed per Hour. 43.2

47.9

51.9

58.5

60.6

63.3

TO-R

TO-R

Nos. 77 and 78 stop on flag at Marina to receive or discharge passengers.

Yd.Lmts.

YP

120.3

122.8

SPRECKELS JCT.

SPRECKELS

(2.5)

2.5

0.0

SANTA MARGARITA SUBDIVISION 22 EASTWARD THIRD CLASS FIRST CLASS Distance from King City Timetable No. 154 Post 768 766 770 70 96 72 98 76 374 Mile J June 2, 1946 Capacity of sidings in car lengths Noon Daylight Morning Daylight C. M. E. Freight Freight Freight Coaster Passenger Lark Leave Daily Ex. Sun., Mon Leave Daily STATIONS Yard Limits KWP PM 6.50 8.10 AM 1.55 PM 10.57 PM 3.19 11.20 AM 12.46 1.06 TO-R KING CITY 163.7 0.0 P 6.55 WELBY 75 8.15 2.00 12.51 167.1 3.4 SAN LUCAS P 7.05 8.25 2.10 11.07 3.27 105 1.16 11.29 12.57 172.4 8.7 12.29 P DOCAS 44 1.03 177.7 14.0 122 WOP 7.20 8.40 2.25 11.17 1.29 11.38 SAN ARDO 19.2 1.08 12.40 182.9 TO GETTY P 44 186.4 22.7 P 7.33 2.39 11.44 AM 11.52 WUNPOST 107 8.54 11.24 1.36 1.15 189.7 26.0 12.48 BRADLEY 109 P 7.45 9.06 2.51 11.33 1.46 3.49 1.24 12.56 195.9 32.2 P 68 7.54 9.15 3.00 NACIMIENTO 1.30 201.4 37.7 CAMP ROBERTS 202.8 39.1 3.10 NOON 12.00 7.59 MCKAY P 9.20 11.41 3.57 2.08 106 1.33 1.04 203.8 40.1 37 KWP 8.06 9.28 3.35 2.15 TO SAN MIGUEL 11.46 1.08 207.0 43.3 PM 11.51 AM 12.01 P WELLSONA 8.14 3.56 4.04 101 9.36 2.20 12.07 1.41 210.9 47.2 1.13 PASO ROBLES P 8.21 58 9.43 4.10 2.32 1.47 1.19 216.3 TO 52.6 100 P 8.30 TEMPLETON 9.54 4.21 12.08 4.16 2.40 12.19 1.54 1.25 221.8 58.1 32 P 2.48 224.9 ASUNCION 61.2 P ATASCADERO 8.37 10.01 4.28 12.13 2.51 1.30 226.7 63.0 P HENRY 118 2.53 12.26 228.0 2.02 64.3 P 8.45 10.09 EAGLET 68 4.36 12.18 2.05 1.35 230.3 66.6 P 125 8.53 10.17 4.44 12.21 3.01 2.09 1.38 233.4 CUSHING 69.7 W-130 E-119 TO-R SANTA MARGARITA 9.15 10.30 5.05 4.32 3.10 s 12.31 12.36 2.16 1.52 235.5 71.8 P CUESTA 131 238.9 75.2 SERRANO 175 WP 243.4 79.7 CHORRO P 105 246.3 82.6 GOLDTREE YP 40 248.0 84.3 P HATHAWAY 103 250.6 86.9 6.30 AM S. L. Obispo yard BKWOTYP 10.30 PM 1,20 5.11 1.17 PM 3.02 AM 2.38 AM TO-R SAN LUIS OBISPO 252.1 88.4 Arrive Daily Ex. Sun., Mon Arrive Daily (88.4)(4.35) 19.29Time over District...... Average Speed per Hour..

Rule 5. Schedule time and train-order time apply at San Miguel westward at crossover west of station building.

RULES 86 and 93. Third-class trains, extra trains and engines, except trains handling passenger equipment only, must clear the time of Nos. 96, 97, 98 and 99 not less than 10 minutes and must be clear of main track and insulated joints at meeting and passing points for Nos. 96, 97, 98 and 99.

RULE S-72. Exception: No. 98 is superior to Nos. 71, 69, 75, 373 and 99.

AD	DITIONAL FLAG ST	OPS TO RECEIVE OR D	ISCHARGE REVENUE	E PASSENGERS
Train	At	Receive To (or Beyond)	Discharge From (or Beyond)	Frequency
72 72	Any Station	Los Angeles	Men and supplies	Daily Mon., Wed., Fri

ADDITIONAL STA	TIONS	
NAME	Mile Post	Capac-
Thyle (Spur)	240.0	8

ADDITIONAL STA	TIONS	38
NAME	Mile Post	Capac-
Lompoc Branch Garus (Spur) La Salle (Spur)	308.1 308.3	14 22

ADDITIONAL STATE	TIONS	
NAME	Mile Post	Capac- ity
Guadalupe Subdivision Edna. (Spur) Tiber (Spur) Pismo (Spur) San Augustine (Spur) Drake. (Spur) Coromar (Spur)	257.9 260.0 262.8 331.0 334.2 360.2	5 P 18 5 19 14 P

SANTA MARGARITA SUBDIVISION

									WE	STWAI	RD				
t e		Timetable No. 154		nom olspo			FIF	ST CLAS	55				THIRD	CLASS	
Mile Post	June 2	June 2, 1946		Distance from San Luis Obispo	373 c. m. w.	69 Coaster	75 Lark	99 Morning Daylight	71 Passenger	97 Noon Daylight	DEV	763 Freight	765 Freight	767 Freight	
		STATIONS			Arrive Daily Ex. Sun., Mon	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily		Arrive Daily	Arrive Dally	Arrive Daily	
63.7 -		TO-R KING CITY		88.4	AM 4.00	s 4.15	AM 4.50	PM 2.48	PM s 4.30	PM 6.48		8.00	PM 3.05	PM 11.59	7
67.1		WELBY 5.3		85.0			4.46					7.50		11.50	
72.4		TO SAN LUCAS 5.3		79.7	3.51	4.05	4.40	2.40	s 4.20	6.40	10.2	7.40	2.50	11.40	
77.7		DOCAS 5.2		74.4											
82.9		TO SAN ARDO		69.2	3.39	3.53	4.29	2.31	s 4.08	6.31		7.25	2,31	11.17	
36.4		GETTY 3.3		65.7											
39.7		WUNPOST 6.2		62.4	3.32	3.45	4.22	2.24	3.59	6.24		7.10		10.35	
95.9		TO BRADLEY 5.5		56.2	3.24	3.37	4.14	2.17	s 3.49	6.17		7.00	1.46	10.25	
01.4		NACIMIENTO		50.7	3.18	3.29	4.08					6.50	1000	10.15	
02.8		CAMP ROBERTS		49.3	Tool Control	f			f	10-	1,700	Chicago			
03.8	П	McKAY 3.2		48.3	3.15	3.26	4.05	2.08	3.22	6.08		6.45	1.29	10.10	
07.0	еш	TO SAN MIGUEL		45.1	3.11	3.22	4.01		s 3.15			6.40	1.24	10.05	miles.
10.9	Syst	WELLSONA 5.4		41.2	3.06	3.17	3.56	2.01	3.11	6.01		6.34	1.18	9.59	
16.3	Block	TO PASO ROBLES		35.8	2.59	s 3.11	3.50		s 3.05	4		6.26	1.09	9.51	
21.8	atic	TEMPLETON 3.1		30.3	2.52	3.03	3.43	1.50	s 2.53	5.49		6.18	1.00	9.43	N-A
24.9	Auton	ASUNCION 1.8		27.2					2.48						-14
26.7		TO ATASCADERO		25.4	2.46				s 2.45		VII 11 a	6.08		9.33	
28.0		HENRY 2.3	,	24.1				1.43		5.42	III				
30.3		EAGLET 3.1		21.8	2.42	2.53	3.33		2.39			6.00	12.45	9.25	
33.4		CUSHING 2.1		18.7	2.38	2.49	3.29	1.37	2.35	5.36		5.55	12.40	9.20	
35.5		TO-R SANTA MARGARITA	Ce	16.6	2.35	s 2.46	3.26	1.34	s 2.32	5.33		5.50	12.36 PM	9.15	
38.9		CUESTA 4.5	Centralized	13.2	2.25	2.32	3.12	1.25	2.21	5.24					
43.4		SERRANO 2.9	ized '	8.7			SOLDAN I						EVET		
46.3		CHORRO	Traffic	5.8					1/21			13.50	99.14		L
18.0		GOLDTREE 2.6	c Cor	4.1			15.80					-			
50.6		HATHAWAY	Control	1.5									L mil		
52.1		TO-R SAN LUIS OBISPO		0.0	1.50 AM	2.00	2.40 AM	12.53 PM	1.50 PM	4.52 PM	va a r	4.20 AM	11.00 AM	7.55 PM	
		(88.4)			Leave Daily Ex.Sun.,Mon	Leave Daily	Leave Daily	Leave Daily	Leave Daily	Leave Daily		Leave Daily	1000		
391	_	Time over District Average Speed per Hour	=	p.doi:	(2.10) 40.80	(2.15) 39.29	(2.10) 40.80	(1.55) 46.12	(2.40) 33.15	(1.56) 45.72	MIN	(3.40)	(4.05) 21.65	(4.04) 21.73	

RULE 5. Schedule time and train-order time apply at San Miguel westward at crossover west of station building.

RULE S-72. Exception: No. 98 is superior to Nos. 71, 69, 75, 373 and 99.

RULES 86 and 93. Third-class trains, extra trains and engines, except trains handling passenger equipment only, must clear the time of Nos. 96, 97, 98 and 99 not less than 10 minutes and must be clear of main track and insulated joints at meeting and passing points for Nos. 96, 97, 98 and 99.

Train	At	Receive To (or Beyond)	Or Beyond)	Frequency
71	Any Station		Los Angeles	Daily
71	Chorro		Men and supplies	Mon., Fri.
71	Serrano		Men and supplies	Tues., Thurs., Sat

GUADALUPE SUBDIVISION

	EAST-	Timetable No. 154	WEST- WARD
Capacity of sidings		June 2, 1946	E SI
in car lengths	Mile Post Location	Lompoc-White Hills Branches	Vistance from
	Mil	STATIONS	Distance from White Hills
Yard Limits 117 WOYP	302.7	TO SURF	14.0
30	303.8	BARODA 3.8	12.9
21	307.6	POST 2.2	9.1
9	309.8	ACORN 2.6	6.9
. ВКЖТР	312.4	TO-R LOMPOC 0.5	4.3
Yd.Lmts.	312.9	WHITE HILLS JCT.	3.8
Yd.	316.7	WHITE HILLS	0.0

24						3UADA	LUPE	SUBD	IVISIO	N		-		-
				EA	ASTWA	RD		HIPTON VC						
	2 MAJO	ABO TH	HIRD CLA	ss	- 11/1/16/		FIRST	CLASS					Timetable No. 154	87
- /17/10/5/6/07/10/5/10	y of sidings r lengths	770 Freight	768 Freight	766 Freight	96 Noon Daylight	72 Passenger	98 Morning Daylight	76 Lark	374 c. m. e.	70 Coaster	Mile Post Location		June 2, 1946	Distance from
	gast sub	Leave Daily	Leave Daily	Leave Daily	Leave Daily	Leave Daily	Leave Daily	Leave Daily	Leave Daily Ex. Sun., Mon	Leave Daily			STATIONS	17, 4
S. L. Ob	bispo yard SKWOTYP	PM 7.45	PM 1.35	AM 3.45	PM 5.14	PM 4.10	PM 1.20	AM 3.11	AM 2.50	AM · 1.30	252.1		TO-R SAN LUIS OBISPO	0.0
	Р						1.32	3.23	3.02	1.43	259.1		TO-R SAN LUIS OBISPO 7.0 HADLEY	7.0
125	P	8.10	10000	4.10			1.39	3.31	3.09	1.51	264.2		GROVER	12.1
36	Р	8.18				s 4.55		3.33	3.12	2.04	265.9		TO OCEANO	13.8
98	P	8.26			5.40		1.46	3.38	3.17	2.09	269.9		4.0 CALLENDER	17.8
42	P	8.31	2.16			5.04			3.20	2.12	272.4		BROMELA	20.3
	Limits BKWP	8.45		The State of the sales	5.46	and the second	1.52	3.45	3.26	8 2.35	276.5		TO-R GUADALUPE	24.
77	P	8.54			William I	5.26	1.57	3.50	3.32	2.41	280.7		WALDORF	28.
46	P	9.05	2.50	In the state of the state of		TOTAL		10.00	3.37		284.8		SCHUMAN	32.
87	YP	9.09	2.54		5.58	5.36	2.04	3.58		2.49	286.5		1.7 DEVON	34.
40	P	9.11	2.56			s 5.39	2017		3.42		287.5		TO CASMALIA	35.
74	P	9.16	3.01	5.11		5.42		4.03	3.45	2.55	290.0		ANTONIO	37.
128	Р	9.22	3.07	5.17		5.46	2.11	4.07	3.49	3.00	293.2		NARLON	41.
75	YP	9.30	3.15	5.25	6.09	6.09		4.12	3.54	3.05	297.2		4.0 TANGAIR	45.
Yard I	AND DESCRIPTION OF THE PARTY OF	9.45	3.46	5.40	6.15	s 6.25	2.21	4.19	4.00	s 3.18	302.7	a l	TO SURF	50.
137	P	10.00	4.02	5.55	6.20	6.33	2.26	4.26	4.08	3.25	307.9	System	HONDA	55.
						•				J	310.5	Block Sy	ARLIGHT	58.
	P				Mile Kind						312.5		ARGUELLO	60.
44	P	10.20	4.22	6.15	6.30	6.47	2.36	4.38	4.20	3.37	317.3	Automatic	SUDDEN	65.
85	• P	10.27	4.29	6.22	6.34	6.53	2.40	4.43	4.25	3.42	320.8	γnγ	JALAMA	68.
125	P	10.34	4.36	6.29	6.39	f 7.02	2.45	4.50	4.25	3.42	325.3		TO CONCEPCION	73.
44	P				0			***		3.1	329.8		GATO	77.
105	P	10.49	4.51	6.44	6.49	7.13	2.55	5.03	4.44	4.02	334.8		SACATE	82.
78	WP	11:38	4.58	6.51	6.54	s 7.21	3.00	5.10	4.44	4.02	339.4		TO GAVIOTA	87
44	Р				0.0		3.03	J.,	4.51	4.05	342.6		3.2 LENTO	90
46	P	PM 11.50	5.08	7.01			3 .55	5.18	4.59		345.7		TAJIGUAS	93.
102	P	AM 12.11	5.15	7.08	7.05	7.33	3.13	5.18	5.04	4.23	349.9		CAPITAN	97
75	P	12.25	5.25	7.18	7.10	7.40	3.18	5.31	5.10	4.23	355.0		5.1 NAPLES	102
47	P	1800	5.31	7.24	THE RES	7.45	Date of	5.36	5.10	4.35	358.9		ELLWOOD	106.
									5	4.55	361.7		LA PATERA	109
117	Р	12.35	5.39	7.32	7.16	r 7.51	3.25	5.41	5.20	4.40	362.8		TO GOLETA	110
39	P	A CONTRACTOR		diam's	7.20		3.2	3.1	5.20	4.40	366.5		HOPE RANCH	114
	Р	12.45	5.49	7.42	118	8.00		5.51	5 28	4.50	368.5		WEST SANTA BARBARA	116
Santa Barba BK		1.00 AM	6.00 PM	7.55	s 7,30	8 8.10	8 3.37	s 5.58	5.28 8 5.35	# 5.00	370.7		TO-R SANTA BARBARA	118
	2012/03/05/2012	Children Co. A. C. San San San		National Association of	Arrive Daily	Arrive Daily	Transfer of the Control		Arrive Daily Ex. Sun., Mon	THE RESIDENCE OF THE PERSON NAMED IN COLUMN 1	370.7		(118.6)	#10
		(5.15) 22.53	(4.25) 26.85	(4.10) 28.46	(2.16) 52.25	THE RESERVE OF THE PARTY OF THE		THE RESERVE OF THE PERSON NAMED IN COLUMN 1	BOOLER HOT STREET STREET	THE RESERVE OF THE PERSON NAMED IN		-	Time over District	=
		22.53	26.85	28.46	52.25	(4.00) 29.65	(2.17) 51.94	(2.47) 42.61	(2.45) 43.13	(3.30)			Average Speed per Hour	

RULES 86 and 93. Third-class trains, extra trains and engines, except trains handling passenger equipment only, must clear the time of Nos. 96, 97, 98 and 99 not less than 10 minutes and must be clear of main track and insulated joints at meeting and passing points for Nos. 96, 97, 98 and 99.

No. 72 stop at Pismo daily.

AC	DITIONAL FLAG STOPS	TO RECEIVE OR DISCH	IARGE REVENUE PA	SSENGERS
Train	AL	Receive To (or Beyond)	Discharge From (or Beyond)	Frequency
72 72		Any Station	Any Station Any Station	Daily Daily Daily

No. 76 reduce speed at Guadalupe and Surf to 25 MPH to exchange U. S. Mail.

				G	UADA	LUPE	SUBD	IVISIO	N				25
				Supel mands				WI	ESTWA	RD	-	an Opposite of	d-or regar
dipp		Timetable No. 154	8.5	fireto di tr	ale to be	FIRST	CLASS	mal rug	di avyru		ТН	IRD CLASS	Lead A.
Mile Post Location		June 2, 1946	Distance from Santa Barbara	71 Passenger	99 Morning Daylight	97 Noon Daylight	373 c. m. w.	69 Coaster	75 Lark	763 Freight	765 Freight	767 Freight	
		STATIONS		Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily Ex. Sun., Mon	Arrive Daily	D prywind				
252.1	-	TO-R SAN LUIS OBISPO	118.6	PM s 1.35	PM s 12.50	PM s 4.47	8 1.20	8 1.50	8 2.28	AM 10.15	PM 2.50	AM 1.05	
259.1		7.0 HADLEY 5.1	111.6	1.23	12.38	4.35	1.07	1.36	2.16	10.00	2.35	12.50	
264.2		GROVER	106.5	1.11	12.31	4.28	12.59	1.29	2.07	9.48	2.24	12.38	
265.9	W.	TO OCEANO	104.8	s 1.09	arana 76		12.57	1.26	2.04	9.45	2.21	12.35	M. Date
269.9		CALLENDER 2.5	100.8	1.01	12.25	4.22	12.52	1.21	1.59	9.36	2.11	12.27	
272.4		BROMELA 4.1	98.3	12.58	Testing.		12.49	1.17	1.55	9.30	1.59	12.21	
276.5		TO-R GUADALUPE	94.2	s 12.53	12.19	4.16	12.43	s 1.12	1.50	9.20	1.52	12-11	Inda yetan
280.7		WALDORF 4.1	90.0	12.36	12.14	4.11	12.37	1.03	1.42	8.58	1.25	12.01 AM	SALES IN SEC.
284.8	10	SCHUMAN 1.7	85.9	12.31			12.31	12.57	1.37	8.49	1.17	11.51 PM	TO SERVICE STATE OF THE PERSON
286.5		DEVON 1.0	84.2	12.28	12.07	4.04	12.28	12.54	1.34	8.44	1.14	11.46	
287.5		TO CASMALIA	83.2	s 12.26		11348	12.26	and the		8.42	1.11	11.42	
290.0		ANTONIO 3.2	80.7	12.21	12.03 PM	4.00	12.22	12.49	1.29	8.38	1.07	11.38	
293.2		NARLON 4.0	77.5	12.17	11.59 AM	3.56	12.19	12.45	1.25	8.32	1.02	11.32	
97.2		TANGAIR 5.5	73.5	12.12	11.55	3.52	12.13	12.40	1.20	8.25	12.56	11.25	
302.7		TO SURF 5.2	68.0	s 12.05	11.49	3.46	12.04 AM	s 12.31	1.11	8.10	12.47	11.10	aven de la la
307.9	yster	HONDA 2.6	62.8	11.43 AM	11.43	3.40	11.57	12.18	1.04	7.53	12.34	10.55	Tre pupils we
310.5	lock S	ARLIGHT 2.0	60.2	f		Urbo	4.6				oller but	-610-6	e store
312.5	Automatic Block	ARGUELLO	58.2		0 0 70			17/10				alaya obio	
317.3	toma	SUDDEN 3.5	53.4	11.17	11.34	x init	11.45	12.07	12.53	7.35	12.19	10.35	SULE DUY 9
320.8	Au	JALAMA 4.5	49.9	11.12	11.30	3.27	11.40	12.02 AM	12.48	7.27	12.13	10.27	d web it is
325.3		TO CONCEPCION	45.4	f 11.06	11.25	3.22	11.34	11.56 PM	12.42	7.17	12.05 PM	9.57	
329.8		GATO 5.0	40.9	To both				1.46		and the second			
334.8		SACATE 4.6	35.9	10.54	11.15	3.12	11.22	11.44	12.30	7.01	11.50 AM	9.41	entre de la contract
339.4	F	TO GAVIOTA	31.3	s 10.48	11.10	3.07	11.17	11.38	12.24	6.51	11.42	9.30	
342.6		LENTO 3.1	28.1			3.03		September 15		GTAL S			
345.7		TAJIGUAS	25.0	put itg a	11.04	CARNE .	11.09	11.30	12.17	6.31	11.32	9.20	
349.9		CAPITAN 5.1	20.8	10.31	10.59	2.55	11.04	11.25	12.11	6.24	11.25	9.13	
355.0	H.	NAPLES 3.9	15.7	10.25	10.54		10.58	11.19	12.06	6.15	11.17	9.04	
358.9	11	ELLWOOD 2.8	11.8	10.20	eritana pi	January 1	10.53		12.01 AM	6.08	11.10	8.57	
361.7		LA PATERA	9.0	and of	The contra								
362.8		TO GOLETA	7.9	f 10.16	10.47	2.44	10.49	11.09	11.57 PM	6.01	11.04	8.50	
366.5		HOPE RANCH	4.2		THE WINDS			Marineau		de la la			
368.5		WEST SANTA BARBARA	2.2	10.07	10.41	2.38	10.42	11.02	11.51	5.51	10.55	8.40	OW IN CASE
370.7		TO-R SANTA BARBARA	0.0	10.00 AM	10.35 AM	2.32 PM	10.35 PM	10.55 PM	11.44 PM	5.30 AM	10.45 AM	8.30 PM	
		(118.6)		Leave Daily	Leave Daily		Leave Daily Ex. Sat., Sun.	Leave Daily					
		Time over District		(3.35) 33.10	(2.15) 52.71	(2.15) 52.71	(2.45) 43.13	(2.55) 40.66	(2.44) 43.39	(4.45) 24.97	(4.05) 29.04	(4.35) 25.88	

RULES 86 and 93. Third-class trains, extra trains and engines, except trains handling passenger equipment only, must clear the time of Nos. 96, 97, 98 and 99 not less than 10 minutes and must be clear of main track and insulated joints at meeting and passing points for Nos. 96, 97, 98 and 99.

No. 71 stop at Pismo daily.

AD	DITIONAL FLAG STOPS	TO RECEIVE OR DISCH	HARGE REVENUE PAS	SENGERS
Train	At	Receive To (or Beyond)	Discharge From (or Beyond)	Frequency
71 71	Any Station		Any Station	Daily

No. 75 reduce speed at Guadalupe and Surf to 25 MPH to exchange U. S. Mail. $\,$

RULE 2. Watch Inspectors: S. A. Pope, Manager of Time Service, 65 Market St., San Francisco. San Francisco E. J. Land, 745 Third St.
San Francisco J. J. Ashton, 2939 16th St.
San Francisco I. S. Preston, 357 Phelan Bldg.
Bayshore L. E. Brown, 2442 Bayshore Ave.
San Mateo A. E. Benoit, 224 B St.
Redwood City Kessington Levelors, 2916, Proceder San Mateo A. E. Benoit, 224 B St.
Redwood City Kessingers Jewelers, 2316 Broadway.
San Jose Kochers, 169 So. 1st St.
Watsonville C. Vernon Jolley
Santa Cruz C. M. Pennell
Salinas Goodfriend & Traub
Pacific Grove G. H. Ehmann
King City W. V. Bolton
San Luis Obispo V. C. Jerram
Santa Barbara Howard V. Weirum
Lompoc Walter Ziesche
Los Gatos J. B. Streepey

RULE 2 (A). Watches subject to inspection must be presented monthly, between first and fifteenth, instead of semi-monthly, to a designated inspector.

Los Gatos J. B. Streepey

RULE 4. Designated Holidays: New Year's Day, January 1st.
Washington's Birthday, February 22nd.
Decoration Day, May 30th.
Independence Day, July 4th. Labor Day, first Monday in September. Thanksgiving Day, fourth Thursday in November. Christmas Day, December 25th.

RULE 10 (H). Where yellow signals are displayed within limits of a length of track over which a maximum speed is designated in train order or timetable bulletin and no maximum speed is otherwise specified for the particular section of track protected by these yellow signals, trains must not exceed 15 MPH thereover.

RULE 10 (J). Round yellow slow boards indicate by black figures the speed restriction applying to trains which consist of streamlined cars only (other than Lark equipment) with GS, P-7-10-12, or P-8 (except eng. 2470) class engines.

Certain slow boards have the word "SIGNAL" above the figures.

Such slow boards in approach to a distant signal indicate the speed that must not be exceeded while engine is passing the distant signal three-fourths mile beyond the slow board, unless distant signal can plainly be seen to be displaying proceed indication; and such slow boards in approach to a home signal indicate the speed that must not be exceeded while approaching home signal three-fourths mile beyond the slow board, until indication of home signal can plainly be seen.

Following slow boards have lamp attached which displays yellow light at night. This light is to call attention to slow board, and is not a yellow signal referred to in Rule 10 (H):

Eastward MP	Westward MP
103.04	105.45
103.95	106.67
167.85	169.56
	263.05
	292.08
346.70	348.88

RULE 12 (H). Display of lighted fusee from interlocking or crossing watchman's tower requires train to stop, expecting to find crossing blocked.

RULE 14 (m). That portion requiring whistle to be sounded one mile before reaching stations will not apply between San Francisco and San Jose.

RULE 15. Second paragraph is changed to read as follows: "The explosion of two torpedoes is a signal to proceed with caution for not less than one mile."

RULE 17. Mars signal light on engines shall be used when engine is moving at night, and in foggy or stormy weather. It must be dimmed or extinguished approaching passenger stations, and at other points as prescribed by rules.

RULE 26 is revised to read as follows:

"A blue signal or sign reading 'Men at Work' displayed on engineer's side of cab of an engine or at one or both ends of a car, cut of cars, or at the rear of a train, indicates that workmen are under or about same and the engine, car, cut of cars, or train must not be coupled to nor moved by any method, nor other equipment placed so as to obstruct the view of the blue signal or sign.

"Blue signal or sign must not be removed by any person except the one placing the signal or sign, or someone authorized by him to

"On designated tracks (repair, cleaning, servicing, etc.) where employes work, a sign reading 'Stop-Men at Work' must be placed on the track and switches leading to such track locked; and from sunset to sunrise a blue light must be displayed. Employes placing

such sign and locking switches, only are authorized to change same.
"When repair work is to be done under or about an engine or cars in a train, where movement of same would endanger employes engaged in such work, and a blue signal or sign is not available, the enginemen of engine handling train must be notified by employe engaged in such work and a complete understanding had to prevent movement. After work is completed the same employe must notify enginemen."

RULE 28. In double track territory, signals will be placed to right of track according to direction of movement of train to be flagged. Trains in opposite direction will not be required to observe signals so placed.

RULE S-72. Westward trains are superior to trains of the same class in opposite direction, except as noted on pages 13, 14, 15, 18, 19, 20, 22 and 23.

RULE 99. Third, fourth and sixth paragraphs are changed to read as follows:

"If recalled from a point less than one-half mile from rear of his train, he must, if safety to train requires, leave lighted fusee at proper intervals and, if conditions warrant, also place two torpedoes

on the rail three rail-lengths apart."

"If not recalled, one-half mile from rear of train he must place one torpedo on the rail; one mile from rear of train, or when recalled, if one-half mile or more from rear of train, he must place two torpedoes on the rail three rail-lengths apart. If conditions, such as curves, foggy or stormy weather or descending grade require, he must continue back a greater distance, placing two additional torpedoes."

"When flagman has reached the required flagging distance and has placed torpedoes as required, he may then return to the single torpedo where he must remain until relieved by another flagman or recalled. When recalled, he may remove the single torpedo and return, leaving lighted fusee at such intervals as conditions war-

RULE 102. Should a passenger train break in two, or an emergency application of brakes occur while in motion on the grade between Santa Margarita and San Luis Obispo, or between Santa Cruz and Felton, forward brakeman will immediately go toward rear, close angle cock at opening if train has parted, set hand brakes and turn up retainers on detached portion. After train is coupled air must be applied from engine before hand brakes and retainers are released.

If necessary to leave detached portion on main track, rear truck of detached portion ascending grade, or leading truck of detached portion descending grade, must be chained to rail in such manner as to derail car should they start.

RULE 107. Freight trains must avoid passing between stations and loading tracks when passenger trains are closely approaching from opposite direction on double track, and care must be exercised by non-stopping passenger trains when approaching stations at about the same time that local passenger trains are approaching from opposite direction. When practicable non-stopping trains are to be given preference, but each train must be operated in a manner to avoid confusion and possibility of hazard or personal injury.

In the morning all eastward passenger trains will favor west-ward commute trains, except that No. 98 should be given preference

over No. 133 at Lomita Park.

In the evening all westward passenger trains will favor east-

ward commute trains.

Particular care must be exercised at such stations as Bayshore, Millbrae, Hillsdale, Belmont and Santa Clara where view of station is limited in both directions, also at 23rd St., Newcomb Ave., and Paul Ave., where passengers may attempt to cross tracks closely behind westward trains. Under such circumstances yard drags and engines on eastward track must stop and take necessary precautions to avoid injury to patrons.

RULE 210 is modified to provide that when using revised train-order form CS-2600 which has the words "Repeated and Complete" printed at bottom of the form, operator will write or typewrite the time and his or her last name in the space provided on the order, after it has been made complete by train dispatcher.

RULE 221. First sentence of third paragraph is amended as follows:

"When a train order is to be delivered to an approaching train, or orders are held for any other train in the same direction, except those originating, the operator must not clear the signal."

RULE 271 is revised to read as follows:

Automatic block signals will bear number plates attached to signal masts. Automatic semaphore home signal arms will be painted red and will be distinguished by white stripe near end of semaphore arm. The number plate on a distant light signal will bear the prefix 'D'

"Interlocking signals will not bear number plates.
"Absolute signals will not bear number plates, but will have plates bearing the letter 'A'

"Interlocking and absolute semaphore home signal arms will

be painted red.

Aspects as illustrated or referred to in these rules are shown by the position of semaphore arms or color of lights, or both, as seen from an approaching train. Other combinations may be used."

RULE 295 is revised to read as follows:

"Interlocking or absolute signals may be made part of the automatic block system adjoining interlocking or centralized traffic control limits. When so arranged they will be designated 'Semi-automatic', and distinguished by a plate bearing the letters 'SA'. Trains stopped by such signals must observe interlocking or centralized traffic control rules within the interlocking or centralized traffic control limits, and Rule 509, 509 (F), or 509 (J), as the case may be, within the automatic portion of the block beyond interlocking or centralized traffic control limits."

RULE 297. Following paragraph is added:
"A train, if delayed in the block, must proceed with caution to
the next signal."

RULE 505. AUTOMATIC BLOCK SYSTEM

PUSH BUTTONS

Where signal protection is provided for movements from an adjacent track to main track, push buttons and pilot lights are installed in box near each of the two signals, with time-release feature, to clear signals on one track when the control circuit on the other track is occupied.

Train on main track to let train on siding pass may clear signal on siding by pressing button bearing number of signal on siding. Train on siding to let train on main track pass should not pass Approach Circuit sign, but when necessary to do so, may clear signal on main track by pressing button bearing number of signal on main track.

Pilot light will appear after time-release has operated and signal has cleared.

Further instructions posted inside push-button box.

ELECTRIC SWITCH LOCKS

Where electric switch locks are installed, lock box door must not be opened if movement is to be made into a track leading from main track until engine or car is standing within 150 feet of the switch; or if movement is to be made from such track, or through a crossover to a main track until switch indicator indicates block clear on opposite track. Within C.T.C. limits dispatcher's permission must also be obtained before lock box door is opened.

After lock box door is opened lock lever cannot be moved to opposite position to release switch for hand throwing until indicator

in lock box indicates "unlocked"

Lock lever must not be returned to locked position until all movements over the switch are completed, switch returned to normal position and locked. Within C.T.C. limits dispatcher must also be notified by telephone when completed.

When switch indicators indicate "block occupied", instructions posted inside lock box for operation of push button to start timerelease must be complied with if movement is to be made to main track while approach circuit is occupied by another train, in addition

to providing flag protection when necessary.

Emergency lock release to be used only in case of electrical or mechanical failure, as indicated by failure of time-release to function after several minutes. When necessary to break seal on emergency lock release, dispatcher must be notified immediately, and movement made only after flag protection provided on both tracks.

RULE 535. SPRING SWITCHES

A spring switch with facing point lock must not be trailed through unless switch target displays letters "SS" in normal posi-

tion, or switch has been lined for the movement.

When a signal with triangular number plate protecting a spring switch with facing point lock displays stop indication, member of crew must open and close spring switch by hand, removing any obstruction. If signal does not then display proceed indication, switch must be hand thrown for the movement.

When a spring switch or spring derail is hand thrown, trainman so setting same must again set it for normal position after movement has been completed, unless he has arranged for another train-

man to do so.

RULE 536. Wheels of tenders must not be considered as engine wheels.

RULES 705 and 707 are revised to read as follows:

"LETTER TYPE INDICATORS

"705. Within block system limits, at locations specified in timetable, letter type indicators may be used. These indicators will be attached to an automatic block signal, and will display indications by illuminated letters, which will supersede the superiority of trains within defined limits.

S—Take siding (Fig. 1).

M—Proceed on main track (Fig. 2).

Other letters, or combination of letters may be used. "S-707. When the letter 'M' is displayed, train is thereby given superiority over all trains to the fouling point of the switch at which an opposing train may enter siding or receiving track, and will hold main track at the station, but must observe any restriction that may

be imposed by automatic block or other signals.

"D-707. When the letter 'M' is displayed approaching a siding, or at the initial switch of a siding, train will hold main track; when displayed on a siding near the leaving end of siding, train will enter main track, and in either case train is thereby given superiority over all following trains to the point designated in timetable, but must observe any restriction that may be imposed by automatic block or other signals."

GENERAL REGULATIONS

RULE 825. When cars are left on grade not protected by derails they must be chained to rail.

Fifth paragraph applies to wooden outfit cars the same as to other cars, except that diner should not be separated from kitchen car.

RULE 827. TRAIN INSPECTION

Cars bearing placards denoting contents are explosive, inflammable, poisonous, or otherwise dangerous, must be given careful inspection at all points where train inspection is made.

Maximum distance freight trains may run without stopping for inspection is 55 miles, except as shown in special instructions for Salinas, Santa Margarita and Guadalupe Subdivisions.

RULE 837. Fifth paragraph is revised to read as follows: "Cars standing on grade must not be coupled onto, in descending direction, without knowing sufficient hand brakes are set to prevent uncontrolled movement of any such cars should coupling fail or cars not be securely coupled together."

RULE 848 applies to deadhead diners handled on rear of trains. Doors must be locked before cars are set out.

RULE 849. Steam valve on Pullman troop sleepers cannot be opened while train is in motion, and when such car is on rear of train steam line must not be cut, in any portion of train, until valve is closed on the car on each side of coupling to be opened, to avoid burning by steam.

AIR BRAKE RULES

RULE 25. Rear end test must be made on yard drags before being moved on main track at designated stations where air brakes must be used, except within San Francisco yard limits will be required only for movements between San Francisco and San Bruno, and between San Bruno and Bernal.

PASSENGER TRAINS

RULE 39. Where rails may be slippery from oil or water from columns, or engines standing, running test must not be made until rear of train has passed such point.

MISCELLANEOUS

1. When freight trains are double-headed engines must be detached to take water.

Helper service:

No helper engine will be placed behind wooden underframe cars or cabooses.

Engines weighing more than 235,000 pounds on drivers will not be placed behind steel underframe cabooses.

In no case will more than one helper engine be placed behind

steel underframe cabooses.

One helper may be placed on head end, but not more than two engines will be used on head end of any freight train. When additional helpers are required, they will be placed back in train, and cut in ahead of any cars of wooden frame construction.

Air will be cut in on all helper engines, and engine must not be

cut off when train is in motion.

When used as helpers in rear of train, AC, AM or MM class engines must not be coupled together, nor may more than two F, Mt, or heavier class, nor more than three smaller classes be coupled together. When coupled, larger engines must be placed ahead of smaller engines. If tonnage requires more power, additional helpers of not to exceed two coupled in each case, must be separated by at least four cars.

Helpers must not be operated backing except in emergency, and in such case engines should not push through a backing engine if it

can be avoided.

Helper engines coupled in middle or rear of train must be cut off from forward portion before taking water. On grades road engine and helper must not be cut off from train at the same time without hand brakes being securely set.

4 (a). Pushing trains out of yard:

No engine will be placed behind wooden underframe cabooses or other wooden frame equipment.

Engines weighing more than 235,000 pounds on the drivers will

not be placed behind steel underframe cabooses.

Air will not be coupled through the pusher engine.
Yard engines regularly so used will be equipped with RussellJordan device to hold the coupler pin from dropping, thus making it unnecessary for employes to uncouple the pusher engine when cutting off.

In no case shall the knuckle be removed or closed, or cutting lever temporarily fastened in release position on a pusher engine.
Unless local conditions require, it will not be necessary to stop

trains to detach pusher engines.
7. Capacity of sidings between clearance points is based on an average car length of 49 feet not including engines and caboose.

10. When a sign reading "Occupied Outfit Cars" is attached to switch lock, the outfit cars must not be coupled to, nor moved, until occupants have been notified, and permission given by foreman or his representative.

20. Handling of freight cars in trains behind passenger cars is prohibited, except that passenger equipment may be placed in head end of mixed trains when carrying military personnel and equipment. This does not refer to a baggage, express, or mail car, or a

Baggage, express, mail, refrigerator or other head end cars must not be handled on rear of passenger trains unless trainmen can pass through, except between San Francisco and San Jose, provided re-

tainer is on head end of car.

21. Employes are warned that it is dangerous to ride on top or

sides of cars where impaired side clearance exists.

There are numerous structures with impaired clearance on yard and station tracks on the division, and employes must be familiar with their locations and avoid personal injury.

23. Not more than two light engines will be coupled for any

road movement.

29. Employes operating over Government tracks listed below will be governed by SP Book of Rules, Air Brake Rules, Timetable **Bulletins and Special Instructions:**

Camp Cooke at Tangair. Camp San Luis Obispo at Goldtree.

Camp Roberts at McKay.

Fort Ord at Ord.

Balloon track and spurs to unloading ramps at Gigling.

SPEED RESTRICTIONS

*List of CCB (cross counter-balanced) engines:

All P-8 class, except eng. 2470:
F-1 class: 3611, 3612, 3615, 3616, 3617, 3619, 3620, 3625, 3629, 3634, 3636, 3638, 3643, 3647, 3652;
F-3 class: 3653, 3654, 3655, 3656, 3657, 3658, 3660, 3661, 3662, 3664, 3664, 3665, 3666

3663, 3664, 3665, 3666, 3667;

F-4 class: 3668, 3670, 3671, 3672, 3674, 3675, 3676, 3677, 3678, 3679, 3681, 3682, 3683, 3684, 3685, 3686, 3687, 3688, 3689, 3690, 3692, 3693, 3695, 3696, 3697, 3698, 3699, 3701, 3702, 3703, 3704, 3705, 3706,

3707, 3709, 3711, 3715, 3716, 3717; F-5 class: 3718, 3720, 3721, 3722, 3723, 3727, 3728, 3732, 3734, 3737, 3742, 3752, 3753, 3755, 3760, 3762, 3763, 3764, 3765, 3766, 3767,

3768, 3769

AC-6 class: 4126, 4127, 4128, 4130, 4131, 4132, 4133, 4135, 4136, 4137, 4138, 4139, 4140, 4141, 4142, 4143, 4144, 4146, 4147, 4148, 4149, 4150.

MAXIMUM SPEED PERMITTED CERTAIN ENGINES:

Maximum speed for C-15-17-32, Mk-10-11 and MM-3 class engines, 35 MPH when handling freight and mixed trains.

Maximum speed for S and SE class engines 20 MPH, but must not exceed speed permitted freight and mixed trains and light engines.

Maximum speed for gas-electric cars running light forward, 50 MPH, but must not exceed speed permitted when handling passenger trains.

Engines backing must not exceed 20 MPH on all curves, and when approaching road crossings at grade.

Engines coupled tender to tender must not exceed speed per-

mitted same engines running light backward.

Engines with tenders having water capacity of 7,000 gallons or less, except classes 70-R-1 and 70-SC-1, must not exceed 50 MPH.

Diesel-electric switch engines running forward, with train or light, may make maximum speed as shown below, except must not exceed speed permitted freight and mixed trains. These engines when backing may make speed shown below, except must not exceed speed permitted E class engines backing where such permitted speed is less than 30 MPH:

Class	Running Fo With train		Running Backward With train or Light
DES-200	30	30	30
DES 1 to 7, 100 to 107	40	40	40

Maximum speed of engines under following conditions, running under own steam, or hauled in train:

When all weight has been removed from any one pair 20 MPH When all weight has been removed from only one wheel of any pair of drivers..... When engine truck is removed..... 20 MPH 30 MPH

When main rod only is removed.
When side rod only is removed.
When both main and side rods are removed. **30 MPH** 20 MPH When hauled in train with all rods on..... 30 MPH

MAXIMUM SPEED PERMITTED WITH CERTAIN EQUIPMENT	MPE
Trains handling wooden pile-drivers; locomotive cranes with boom disconnected and heavy end forward; steam shovels and ditchers transported on their own wheels; and car-top ditchers when blocking and tie-down cables are removed: On tangent main tracks, except	35 25
On tangent branch tracks	25
Trains handling locomotive cranes with boom discon- nected and light end forward (must not be handled in this manner except in emergency):	
On tangent main tracks	20 15
Trains handling locomotive cranes with boom in place, either end forward (to be handled in work train when practicable):	
On tangent main tracks	25
On curves and on branch tracks Trains handling steel pile-drivers may make maximum freight train speed.	15
Trains handling relief outfit with steam derrick:	
On tangent main tracks	35 25
On all curves, 5 MPH less than speed authorized. Where slow boards in place, 5 MPH less than shown on slow boards, except where speed indicated is 15 MPH or less be governed by slow boards.	

Maximum speed provided for passenger trains, other than streamlined trains, will apply to Nos. 373 and 374 when those trains consist entirely of passenger equipment, or cars with steel wheels, including box cars with steel wheels, or caboose with steel wheels, except that maximum speed of 60 MPH must not be exceeded.

When train known as "MM" (Monterey Mdse.) operating between Watsonville Jct., Salinas, Pacific Grove and Santa Cruz is entirely made up of steel wheel box cars and caboose, passenger train speed may be made, observing other restrictions as to class of engine.

of engine.

No. 444 (CCM), and No. 402 (BM) may make maximum speed of 50 MPH San Francisco to Redwood Jct. using ordinary box cars in territory where maximum freight and mixed train speed is shown as 40 MPH.

Passenger trains handling steel wheel box cars in series 5810 to 5874, and foreign line steel wheel box cars equipped for movement in passenger trains, but not equipped with high speed trucks, must not exceed 60 MPH.

Wooden equipment must not be handled in regular passenger trains.

Extra passenger trains handling wooden coaches or chair cars must not exceed 40 MPH.

Maximum speed of deadhead equipment or passenger trains with standard caboose is 50 MPH.

Trains consisting of engine and caboose only restricted to freight train speed.

RULE 14 (d). As specified below, — — — o will be indication that flagman may return from west as prescribed by Rule 99: Redwood Jct..... Trains on Western Division.

Santa Clara......Trains on Western Division. Vasona Jct...... Trains on Los Altos Branch.

RULE 14 (e). As specified below, — — — indication that flagman may return from east as prescribed by Rule 99:

Redwood Jct..... Trains on Western Division. California Ave...... Trains on Los Altos Branch. Santa Clara..... Trains on Western Division. San Jose Trains on Los Gatos Branch.

RULE 21 (C). Engines of passenger trains may display indicators between Mission Bay roundhouse and Third St. station, San Francisco; and from San Jose passenger station to roundhouse. They must be removed on arrival delivery track at roundhouse.

Gilroy Subdivision trains may display indicators and signals between San Jose and San Jose Yard.

RULE 82 (A). Crew ordered for No. 193 may assume the schedule without clearance at Los Gatos.

Nos. 250 and 74 from Western Division may assume correspond-

ing schedules at Santa Clara without clearance.

First-class trains to Western Division at Santa Clara must obtain two clearances at San Jose, one endorsed "Coast Division" and one endorsed "Western Division", and receive train orders applying to Western Division at San Jose, and need not obtain clearance at Santa

Westward extra trains originating San Jose Yard will obtain clearance at Santa Clara.

RULE 83 (A). At the following stations only the trains indicated will register:

Visitacion.....Trains originating or terminating at Bayshore. Redwood Jct.... Trains originating or terminating.

California Ave.. Regular trains via Los Altos Branch, and trains

originating or terminating.

Santa Clara.... Trains to or from Western Division and Coast
Division second and third class and extra trains, except trains consisting entirely of passenger equipment.

Los Gatos..... Trains originating or terminating.

RULE 83 (B). At open train-order offices, trains may register by ticket as follows:

Visitacion.....Trains originating or terminating at Bayshore.

Redwood Jct....Trains to or from Western Division.
Santa Clara....Trains to or from Western Division, and eastward Coast Division second and third class and extra trains, except trains consisting entirely of passenger equipment.

San Jose.....Nos. 70, 72, 76, 78, 96, 98, 374, 69, 71, 75, 77, 97,

99 and 373.

RULES 86 (b) and (c). Trains other than first class handling passenger equipment only may run ahead of first-class trains, except Nos. 96, 97, 98 and 99, between San Francisco and San Jose.

RULE 93. Yard limits in which the provisions of Rule 93 will apply are established at the following stations:

	East MP
San Francisco	11.5
" (San Bruno Branch)	13.6
Redwood Jct	27.2
" (Western Division)	28.2
San Jose	56.0
" (Milnitas line)	51.5
" (Agnew line)	
	" (Milpitas line)

When freight cars are moved from one point to another on main track within San Francisco yard limits at night, a red light must be displayed on rear of rear car.

Yard engine movements between Bayshore and Union stock

yards must be made as follows:

Flag protection must be provided on westward track until clear of main track. All members of crew must accompany engine to stock corrals. Electric lock lever and time-release knob must be operated before switch to spur can be thrown, and lock lever must be returned to normal position after movement is clear of main track and switch lined to normal position.

Movement out of spur must be made as follows: First, flagman must go to east end of Tunnel 3 and notify crew by telephone that flag protection has been provided on westward track. Meanwhile

foreman must obtain line-up of trains from signal operator at Bay-

Second, If switch indicators at derail both indicate "block clear"

derail may be lined;

Third, Unlock electric lock box and open door, and if "unlocked" is displayed, move lock lever from right to left;

Fourth, Line crossover switch in eastward track; Fifth, Line crossover switch in westward track; Sixth, Line switch from spur to westward track.

After crossover movement completed, return all switches and derail to normal position, recall flagman, and throw lock lever in electric lock box from left to right, close and lock the door, and proceed.

None of these switches are to be changed from normal position if switch indicators indicate "block occupied" for either track, except as outlined in instructions posted inside of electric lock box for emergency operation.

Double indicator at derail of stock spur; easterly indicator for

westward track; westerly indicator for eastward track.

When Union stock yards tracks are operated by AT&SFRy, SP crews must make movements between main track and stock yards under flag protection.

RULE 95. Train orders issued under Form F by Western Division reading to or from Santa Clara will apply on Coast Division

into or out of San Jose or San Jose Yard.

Nos. 401, 409, and 413 and sections of those schedules will be cleared at Redwood Jct., according to identification arriving at that point, and are authorized to display this identification to Bayshore without train-order authority; clearance for sections to show: "No Signals", or "Green Signals", following train number.

RULE 97. Extra trains must not run via Los Gatos or Los Altos Branches unless train order so specifies.

RULE D-97 (A). Will apply between San Francisco and San Jose.

RULE 99. Permanente Corp. will do switching at Permanente-SP crews will protect. Navy Dept. will do switching at Moffatt Field-SP crews will protect.

First-class trains move with caution between Signal Bridge 466 and Signal 473, San Jose. Trains or engines stopped between these signals need not protect against first-class trains, but must comply with Rule 99 (A).

RULE 99 (C). Will apply on Los Altos and Los Gatos Branches.

RULE 103 (A). Between Seventh St. and 17th and Harrison Sts., San Francisco, member of crew of yard engines must protect street crossings when no watchman on duty.

Speed of 10 MPH must not be exceeded entering Bayshore Highway crossing on Redwood Harbor spur, and crossing must be cleared

as quickly as possible.

Western Division trains of over 39 cars with no set-out must not pass Middlefield Road crossing east of Redwood Jct. unless Signal D-269 displays proceed indication. When necessary to cut Middlefield Road crossing, do not leave cars between white marks on rail, each

side of crossing.

Member of crew must protect street crossings on spurs over Lincoln St., Race St., Moorpark Ave., San Jose; and on drill track

over Eighth and Taylor Sts., San Jose.

Westward freight trains on Los Altos Branch must not leave cars between approach circuit sign and El Camino Real crossing while switching at California Ave.

RULE 104. The normal position of rigid switches at junctions is as follows:

San Bruno San Bruno Branch, for eastward track. California Ave.. Los Altos Branch, for eastward track. San Jose..... Los Gatos Branch, for freight lead. San Jose Yard. Milpitas line, for freight lead.

Vasona Jet..... Los Gatos Branch for Los Gatos-Los Altos line. Permanente.. . Permanente Corp., for track No. 1.

At Redwood City, Hayes derail on west end of drill track at Jefferson St., has no target or light; but sign reading "DERAIL 100 FEET" will be illuminated when approaching on drill track.

RULE 107. Station train indicators in approach to following stations will be illuminated with word "Train" if train at platform on opposite track:

Broadway; Burlingame; San Mateo; Hayward Park; Hillsdale; Redwood City. Eastward:

Westward: San Bruno.

RULE D-152. Crossovers between San Francisco and San Jose are located as follows:

Just west of Tunnel 3 San Francisco; just west of Tunnel 4 San Francisco; So. San Francisco; San Bruno; Millbrae; Burlingame; Belmont; San Carlos; Redwood Jct.; Menlo Park; Palo Alto; California Ave.; Mountain View; Sunnyvale and Lawrence.

San Mateo. When making eastward movement from middle siding to westward track switches must be lined in following order: Inside switch; derail, and westward main track switch. When movement completed line switches back in reverse order.

RULE 221. Trains from Western Division must obtain clearance before leaving Redwood Jct.

Trains must obtain clearance at Los Gatos only when operator

on duty.

Trains originating Bayshore obtain clearance at Visitacion in-

stead of Bayshore.

Westward trains except those having received clearance at San Jose, must obtain clearance at Santa Clara. Train-order office is in Santa Clara tower.

RULE D-251. Applies to both tracks between San Francisco and San Bruno; and between Santa Clara and College Park interlockings.

RULE 281-D. Exception: When dwarf signals for entrance to station tracks 1 to 14 inc., San Francisco, display indication as shown in Figs. 6 or 7, movement must be made with caution.

RULE 505. AUTOMATIC BLOCK SYSTEM

California Ave.: Junction switch No. 2 and crossover switch No. 3 are equipped with electric locks. If switch indicator indicates "block clear", lock box door may be opened and lock lever thrown from right to left, after which switch may be thrown for movement. After movement completed return switches to normal position, throw lock lever from left to right, close lock box door and lock it. Further instructions are posted in lock box.

Eastward trains should not pass Approach Circuit sign 2000 feet west of Signal 312; and westward trains should not pass Approach Circuit sign, 3500 feet east of Signal 339, when first-class trains from Los Altos Branch are due and normally should move to

westward track first to maintain schedule.

San Jose: Track from Signal 50 feet west of spring switch on wye to Signal 467 on Milpitas line, not protected by block signals. When Signal 467 on Milpitas line displays stop indication, train must stop clear of San Pedro St. until flagman has preceded train from Signal 467 as required by Rule 509 (J), to avoid blocking street crossings.

When signals 463A, 463B, 464, 465, 466 or 467 display stop indication, train, after stopping, may proceed with caution, provided proceed signal received from yardman at The Alameda, green flag

by day, green light by night.

Signal 464 on Signal Bridge 466 is a diverging route signal only, and governs entrance into station tracks 1, 2 and 3 from westward track, and when displaying yellow aspect movements must be made with caution. Lower unit on Signal 466 governs entrance to these tracks through crossover from eastward track. No signal protection beyond fouling point on these tracks.

When signals 468.5, 470 or 473 display stop indication, train, after stopping, may proceed with caution, provided proceed signal received from yardman at Park Avenue, green flag by day, green

light by night.

Eastward main track between Signal 466 and crossover at Signal 473 at Park Ave. is protected by automatic signals for movements in both directions; and signal indication will supersede the superiority of trains between these two signals.

Signal 463B governs all movements from coach tracks 6 to 11

inclusive.

Starting indicators for westward trains on tracks 1, 2 and 3 are controlled by yardman at The Alameda, and when displaying red aspect must not be passed; and when displaying yellow permit movement with caution to Signal 465.

RULE 510. The following block signals equipped with triangular number plate displaying the letter "P" have included in their control limits some special protective device:

Eastward Signal Protection Westward Signal P-274 Spring switch, end double track, Redwood Jct.... P-275

RULE 535. SPRING SWITCHES

Spring switches equipped with facing point locks are located as follows, and speed indicated must not be exceeded while trailing through them:

Location Normal Position MPH
Redwood Jct.....End double track.....Westward track..... 25

Spring switches not equipped with facing point locks are located as follows, and speed indicated must not be exceeded while passing over them in facing movement, or in trailing through them:

LocationNormal PositionMPHSan Jose.....East end freight lead......Trailing eastward on main track30San Jose.....Milpitaswye switch...Westward track...15

Spring derails on spur to Permanente 200 feet west of interchange yard, and on west end No. 1 interchange track, and may be trailed through on eastward or ascending grade movement. They must be lined for westward movement.

RULE 605. INTERLOCKING

o — — sounds of whistle is signal for Coast Division main track. Movements governed by diverging route or dwarf signals must be made with caution and position of switches observed, as such signals govern movements for various routes.

When interlocking signal has been cleared for train or engine and to use the route is not desired sound whistle signal o o — o o,

for information of signal operator.

Fourth Street—San Francisco: Limits extend from point where main tracks intersect King Street to terminal station and include main tracks, leads and certain switches adjacent.

Trains or engines from train sheds may proceed to first signal

eastward.

One sound of siren or air whistle requires that trains and engines within limits of interlocking must stop.

As detector circuits control switches, cars or engines must not

be left standing on them.

Tracks and switches within this plant are numbered. Yardmen and signal operator when arranging movements will use track, or switch numbers to avoid misunderstanding. Telephone instructions must be carefully given and repeated.

Leaving signals on station tracks 1, 2, 3, 13 and 14 San Francisco, are so arranged that signal operator may clear the signals temporarily, even though portion of train is beyond the signal. Before starting, call for signal. The signals on tracks 1, 3, 13 and 14 are searchlight type, and necessary that trainman or yardman relay signal indication to enginemen when it is cleared.

Potrero—San Francisco: Limits extend from signal 650 feet east of east portal of Tunnel 1, on westward main track to signal 600

feet west of tower on eastward main track.

Telephone located at interlocking Signal 22L on westward main track between Tunnels 1 and 2 at 23rd Street. Trains and engines being delayed by "stop" indication will communicate with signal operator Potrero Tower.

Whistle signals governing routes as follows:

For Mission Bay yard, — o —. For Roundhouse, o o o — o. For Track No. 2, o — o o o. For Track No. 3 o — o o.

For track adjacent and parallel to eastward main track......

To facilitate movement, engines and drags when ready to leave San Francisco for Bayshore, will use following whistle signals for route desired at Bayshore.

For outbound yard, — o — o.

For inbound yard, o o — o.

For movement into yard, Bayshore, through either 5 or 7 switch just east of westward crossover which is 300 feet east of Bayshore sta-

 One long blast of air whistle on tower requires that trains and

engines within limits of interlocking must stop.
Signal operator Potrero Tower will notify signal operator Bayshore Tower where engines and drags desire to go on their arrival at Bayshore.

When there is a possibility of delaying passenger trains by engines or yard drags, signal operator will consult yardmaster and be governed by his instructions, making memorandum of verbal instructions which will be filed for future reference.

Bayshore: Limits extend from signal 150 feet west of west portal Tunnel 4, on eastward main track to signal 1850 feet east of east portal Tunnel 4 on westward main track.

Whistle signals governing routes as follows: For outbound yard, — o — o.

For inbound yard, o o — o.

For inbound yard, o o — o.

For movement into yard through either 5 or 7 switch located just east of westward crossover 300 o — o. feet east of Bayshore station....

For car repair yard, o o — — o o. For drill Track No. 1, o o o — o. For drill Track No. 2, 0 — 0 0 0. For lead No. 3 — — 0 — —.

For Garbage spur o — o. For Government Hold yard o — o —. Telephones located as follows:

Interlocking Signal No. 1 on westward main track 1850 feet east of east portal Tunnel 4. Interlocking Signal No. 24 on east of east portal Tunner 4. Interferking Signal No. 24 on eastward main track 150 feet west of west portal Tunnel 4. Trains and engines delayed by "stop" indication by these signals will communicate with signal operator Bayshore Tower, and be governed by Rule 663 (b).

One long blast of siren on tower requires that trains and engines within limits of interlocking must stop.

To facilitate movement, engines and drags when ready to leave

for San Francisco, will use following whistle signals:

For Mission Bay yard, — o —.

For Track No. 2, o — o o o.

For Track No. 3, o — o o.

Signal operator Bayshore Tower will notify signal operator Potrero Tower where engines and drags leaving Bayshore desire to go on their arrival at San Francisco.

When there is a possibility of delaying passenger trains by engines or yard drags, signal operator will consult yardmaster and be governed by his instructions, making memorandum of verbal instructions which will be filed for future reference.

Visitacion: The limits extend from signal 935 feet east of tower on eastward main track to signal bridge 780 feet west of tower.

Whistle signals governing routes as follows: For inbound track — o —.

For Tunnel 5, spur o o o — o. For outbound track, o - o o.

Ninth and Division Streets-San Francisco: Limits of Coast Division tracks extend from signal 250 feet west of tower to signal 600 feet east of tower

feet east of tower
Whistle signals governing routes as follows:
For Track 813 Chemical Works, o o o — o.
For Track 819 Gunn-Carle steel, o — o o.

Portland Cement Co.'s track o — — o. Portland Cement Co.'s track o — — o. For Dunham, Carrigan and Hayden spur, — o — o. For old eastward track, — o -

Redwood Jct.: Limits extend from Signal Bridge 740 feet west of tower to signal bridge 870 feet east of tower on Coast Division, and to signal 950 feet east of tower on Western Division.

Whistle signals governing routes as follows:
To Western Division eastward, — o —. To Western Division westward, - o - o. Movement against current of traffic, o - o o o. For siding, o o — — o o. For drill track westward, o o - o. For Harbor spur, o — o o. For S&W spur, o — — o.

Santa Clara: Limits extend from signal 2150 feet east of tower on Coast Division westward main track to signal 1675 feet west of tower on Coast Division eastward main track, and on Newark line to signal 1650 feet west of tower.

One sound of siren on tower requires that all trains and engines

within the limits of the interlocking must stop.

Whistle signals govern routes as follows: For Newark line, o o — — o o.

For Yard, - o -

Yard to roundhouse, - o - o.

Yard to San Jose passenger station, o o o — o. Yard to Santa Clara drill track, o — — o.

Yard to drill track, o o — o.

Yard to old team track, o - o o o.

College Park: Limits extend from Signal Bridge 455 to 466 inclusive on eastward and westward main tracks; from Signal Bridge 466 to signal located just west of spring switch at junction of Milpitas line and roundhouse lead; and from dwarf signal located 800 feet east of Newhall Street to Signal Bridge 465 on freight lead.

Tracks between San Jose passenger station and College Park facing San Francisco will be designated as follows:

Track on extreme left......Freight Lead.

Track next adjacent......Eastward Main Track.

Track next adjacent.......Westward Main Track.

Trains may operate in either direction on any of these tracks on proper signal indication. Speed against current of traffic on eastward and westward main tracks and both directions on freight lead re-

stricted to 20 MPH.

Derails on tracks Nos. 404, 411, 412, 416, 515 and E. B. Pray Co. spur, within these limits are equipped with electric locks under control of signal operator at College Park tower. Permission of signal operator must be obtained to unlock derails. Release of lock will be authority to proceed. When entering main track, derail must be thrown first, then main track switch. Restore derail and electric lock to normal position when not in use. Instructions on operation of electric lock are posted inside door of lock box.

Switches on spur tracks Nos. 405, 406 and 409 leading off freight lead are manually operated. Engines must not foul freight lead with-

out permission from signal operator.

The main track switch and derail leading to round house oppo-site roundhouse office and all cross-over switches are power operated. Interlocking signals govern the movement only to the derail and not to the fouling point of track 51. The switch at west end of wye is a spring switch, normally lined for Milpitas line main track.

Trains stopped by signals call signal operator on the telephone. If authority obtained to move against "stop" indication, a careful examination of switches must be made before passing over them. Telephones located in boxes on signal bridges or in close proximity of interlocking signals or locked derails, and direct communication may be had with signal operator at College Park. Button on ear phone should be pressed while in use.

For San Jose freight yard, — o o —. For Freight Lead, — o — o. For Santa Clara, drill track, o o o — o —.

For roundhouse, o — — o o. For Milpitas line, o o — o o.

Bell cord communicating signal between San Jose roundhouse and signal operator to be used in lieu of telephone when requesting authority to make movements from roundhouse to main track.

Roundhouse to passenger station: one pull of cord.
Roundhouse to College Park: two pulls of cord.
For movements in roundhouse yard when necessary to foul westward main track: three pulls of cord.

San Jose-Los Gatos Line — (Western Pacific R. R. Crossing): Limits extend from signal 486 feet west of crossing to signal 604 feet east of tower.

No signal operators on duty. Signals, switches and derails in position for Southern Pacific main track movements and against Western Pacific movements.

Speed on main track must not exceed 20 MPH through limits of plant.

When signals indicate "stop", Rule 663 (c) will govern.
Derail switches on drill tracks are manually operated and movements over Western Pacific tracks on these tracks must be made under provisions of Rule 663 (c).

Instructions for handling electric lock and time release posted

at crossing.

San Jose-Lick: See instructions for Gilroy Subdivision.

GENERAL REGULATIONS

RULE 825. Engines may operate over the live rail of track scale at Simla, not exceeding 5 MPH.

AIR BRAKE RULES

FREIGHT TRAINS

RULE 17. One retainer must be turned up for each 120 Ms in train Permanente (from interchange tracks) to Simla.

RULE 24. Road test must be made before leaving Permanente as prescribed by this rule.

RULE 33. The maximum tonnage per operative brake between Permanente interchange tracks and Simla is 120 Ms.

PASSENGER TRAINS

RULE 36. Car inspectors at San Francisco will furnish passenger conductors and engineers a written check of the number, type, percentage of graduated release, and condition of air brake equipment in their trains. Conductors will give this information to road and helper engines coupled to their trains enroute, delivering a written check to relieving conductors.

Car inspectors at San Jose will furnish same information for trains to and from Western Division and Western Pacific.

RULE 39. Running test must be made on eastward trains at San Francisco after rear of train has passed Fourth St., except that trains of over 8 cars must straighten out on Seventh St. before test is made.

Running test must be made on eastward trains at San Jose after rear of train has passed over spring switch at east end freight lead.

MISCELLANEOUS

10. Freight trains or engines with freight cars must not operate over tracks 2, 3, 4 or 5 in San Jose passenger yard. Engines listed must not operate on tracks shown below:

Class of Engine Restricted Tracks

Mk-F-AC-AM-MM-Mt-G8-SP T-40, P, A	Millbrae Dairy and pottery spurs. Broadway. Oil spur. Burlingame. Cahalan spur. Howest. San Mateo Feed & Fuel, and H. E. Casey spurs. San Mateo Wisnom spur, PG&E spur. Hayward Park. Salt spur.
	RomacSpur.
	San Carlos Industry spur on bay side of main track; house track
	Pedwood City West of freight shed.
	Redwood City Team tracks, Pratt-Lowe
	spur; Cullen spur; Red- wood Harbor track spurs; all spurs off Dumbarton line.
	Menlo Park Peninsular Bldg. Matl. Co. spur; wood spur; house track west of freight speed
	Palo Alto All spurs leading off drill track.
	Mountain View. Minton spur; Shell Oil spur; beet spur; Moffatt Field spur.
	SunnyvaleAll spurs off both drill tracks except Schuckl and Berry Growers spurs.

GS class engines entering stub-end tracks San Francisco passenger station must stop at least fifty feet from bulkhead or bumping post.

Engines equipped with pilot plow, except Mt and GS class, are prohibited over tracks adjacent to station platforms at San Fran-

cisco and San Jose.

Load limit (car and contents):

SPEED RESTRICTIONS

Maximum speed between Redwood Jct. and end of Coast Di-

vision at MP 27.59 on Newark line, 35 MPH.

Maximum speed between junction switch westward track at MP 47.39 and end of Coast Division at MP 45.17 on Milpitas line,

15 MPH.

Maximum speed between Santa Clara and end of Coast Division at MP 43.75 on Newark line, Passenger 50 MPH; Freight 35 MPH.
Maximum speed of yard drags between San Francisco and San
Bruno with S or SE class engines 20 MPH, with other classes 35 MPH.

SPEED RI	ESTRI AN M	CTIONS FOR OTHER AIN TRACKS	With Caution Not Exceeding MPH
except San Jo	racks, se. on	yard, and other side-tracks, wyes, crossovers, turnouts and slip-switch freight lead.	nes, 10
LOCATIO	ON OI	spur F OVERHEAD AND SIDE STRUCT	TIRES NOT
STANDA MP Locatio	RD C	LEARANCE ON MAIN TRACK AN Description	D SIDINGS
0.0 San	Franci	sco. Station umbrella sheds—Side	
0.2	**	4th St. interlocking tower—Side	
0.0-1.3	"	Dwarf signals—Side	
1.3	**	Mariposa St. bridge—Overhead	
1.3	44	AT&SFRy bridge—Overhead	11 7
1.5	44	Tunnel 1—Overhead and Side	
	**	The state of the s	

. .22nd Street bridge—Overhead . .23rd Street bridge—Overhead 1.9 2.0 ...Tunnel 2—Overhead and Side 3.1 ..Oakdale Avenue bridge—Overhead and Side ..Tunnel 3—Overhead and Side ** 3.4 . . Paul Ave. bridge-Overhead and Side 4.2 Bayshore Tunnel 4—Overhead and Side Visitacion Tunnel 5—Overhead and Side 4.6 7.7 Palo Alto San Francisquito Creek bridge — Overhead 29.7

and Side San Jose.....Station umbrella sheds—Side 46.9

San Bruno Branch Elkton 5.3 Ocean Ave trolley wires—Overhead

Los Gatos Branch Campbell When cars on siding-Side

44

SPEED RESTRICTIONS: Maximum speed of Passenger trains must not exceed 50 MPH and Freight and Mixed trains 35 MPH except as otherwise provided for herein, or by bulletin, train order or fixed signal.

Maximum speed of any train with an engine not shown in Speed Restriction table, 35 MPH, and is further restricted to maximum speed shown for Freight and Mixed trains if less than 35 MPH.

	_	SF	ECIAL INSTRUC
BACKING	RAIN OR	M AC AM-2 AMM-3 Gas- elec.	22222222222
NGINE	MITH T	TO PTAR TO SPS	828888888888888888888888888888888888888
WARDIE		C-15- 17-32 17-32 MK-2-4-FE 10-11-17 AM-2 17-11-17 MM-3	828888888
LIGHT ENGINE RUNNING FORWARDIENGINE		M T-1-8-9-23-28-C 31-36-57-58 C-2-45-9-9- 10-18-19-26- MK-5-6-7-8-9 A MK-5-6-7-8-9 MK-5-6-7-8-9 MK-5-6-7-8-9 MK-5-6-7-8-9 MK-5-6-7-8-9 MK-5-8-7-8-8-9 MK-5-8-7-8-9 MK-5-8-7-8-9 MK-5-8-7-8-9 MK-5-8-7-8-9 MK-5-8-7-8-8-9 MK-5-8-7-8-9 MK-5-8-7-8-8-8-8 MK-5-8-7-8-8-8-8 MK-5-8-7-8-8-8-8 MK-5-8-7-8-8-8-8 MK-5-8-7-8-8-8-8 MK-5-8-7-8-8-8-8 MK-5-8-7-8-8-8-8 MK-5-8-7-8-8-8-8 MK-5-8-7-8-8-8-8 MK-5-8-7-8-8-8-8 MK-5-8-7-8-8-8-8 MK-5-8-7-8-8-8-8 MK-5-8-8-8-8-8-8-8-8-8-8-8-8-8-8-8-8-8-8-	8288888888
ENGINE		7-26- 17-28- 14-0-17-0-17-0-17-0-17-0-17-0-17-0-17-0-	2444444828
LIGHT	T	Me 4 Mg	84444444828
A 18		FREIGHT	8844444888
		C-15-17- 32 MK-10- 11 MM-3	8788888888888
ORWARD		C-2-4-5-9-10-18-19-26-27-28-29 MK-2-4 (if not CGB*)	233333333333333333333333333333333333333
NING F		M AM-2	8233333338
WITH TRAIN - ENGINE RUNNING FORWARD	GER	7-1-8-9- 23-28-31- 38-57-58 Mk-5-6-7- 8-9 8-9 SP Cars	222222
IN - EN	PASSENGER	AC-4-5- 7-8-9- 10-11- 12- AC-6 (if	222222222
H	4	_\$959	222222222
×		P-8 (if cc8*)	22888488418
		P-8 (if CCB*) P-7- 16-12 GS Mt	22858458418
		GS P (if CCB*) with stream- lined cars only (other than Lark equipment)	22858458458 22858458458
		TERRITORY	2 to 12 San Francisco-East Portal Tunnel 1 East Portal Tunnel 1-Bayshore Bayshore-MP 19.0 MP 19.0-MP 24.6 MP 24.6-MP 32.0, except *Redwood City, MP 24.6 to MP 26.4 MP 32.0-MP 44.0 MP 32.0-MP 44.0 MP 44.0-College Park College Park-Signal Bridge 464, except *Over Stockton Ave. and Emery 8t. 10 PM-6 AM Signal Bridge 464-End of double track
		82	to 12

24	TERRITORY	PASSENGER	FREIGHT	LIGHT ENGINE RUNNING FORWARD	ENGINE	SWITCH ENGINE S-SE GLASS
13	San Bruno Branch		15	15	12	155
	California AveVasona Jct., except.	35	30	30	200	06
	With Mt, F-1, Mk engine.	15	15	12	15	3
	With P-1-3-45 engine, except.	32	30	30	303	:
	MP 47.61-MP 48.06.	25	25	22	8	:
	Vasons JctLos Gatos, except	30	18	25	15	30
	Vasona JctMP 52.67.	25	18	:	1	-
	With Mt, F-1, Mk engine.	15	15	15	15	-
	San Jose-Vasona Jct., except	30	30	30	20	30
	With Mt, F-1, Mk engine, except.	15	15	15	15	:
	San Jose-MP 47.38	10	10	10	10	
	With P-1-3-4-5 engine, except	30	30	30	20	
	San Jose-MP 47.38.	10	10	10	10	
	MP 53.28 to Vasona Jet.	25	18	18	18	

RATING OF ENGINES-In Ms of 1000 lbs. Back of Tender.

NOMINAL CLASS	ENGINE NUMBERS	San Francisco and San Jose	California Ava. to Los Gatos San Jose and Vasona Jet	Los Gatos to California Ave.	Simia to Permanente
ES-1, 2, 3, 4, 5, 6, 7 ES-100 to 107 23 4 6, 8 9, 11	1000 to 1022. 1300 to 1395. 1500 and 1502. 1617 to 1713. 1721 to 1803, 1823 to 1825. 1804 to 1822, 1826 to 1831 and 1836. 1832 to 1835.	1550 2450 2300 2950 3650 3850 3950	1850 2200 2300 2500	2400 2850 3000 3250	630 720 820 900
9 , 31 , 40	2242 to 2271. 2161, 2174 and 2178. 2301 to 2310. 2283 to 2299. 2311 to 2362. 2363 to 2384. 2103. 2105 and 2106. 2385 and 2386.	2600 1850 3750 3300 4200 4300 2800 3750 3400	1650 1150 2350 2050 2600 2650 1750 2350 2150	2150 1500 3100 2700 3400 3450 2300 3100 2800	560 370 830 700 930 950 630 840 760
1, 3, 5 1 4 6 6 7 8, 10 8, 10 11 12	{2408, 2411 to 2413, 2416 to 2418, 2423, 2425 to 2435, 2437 to 2452, 2459 and 2460 2400, 2403 to 2407 and 2415. 2401, 2402, 2409, 2410, 2414, 2419, 2420, 2422, 2424 and 2436 2453, 2454 and 2458. 2476 and 2477. 2461 to 2474, 2478 to 2483. 2475, 2484 to 2491 3100 to 3109. 3120 to 3129.	3500 3550 4000 4300 4350 4600 4800 3700 5050	1950 2200 2150	2600 2900 2850	690 720 760
5, 8, 9, 10, 26 to 29 -15, 32 -17 -18 -19 W-1 W-2, 3 W-4, 6 W-8	2513 to 2599, 2624 to 2860, 3440 to 3469 2500, 2505 to 2507 2510 and 2511 3400 to 3409. 3410 to 3426. 2900 to 2913. 2932 to 2952. 2926 to 2931 and 2957. 2914 to 2923.	4600 2900 3600 4200 4350 3500 2800 2650 3900	2900 1850 2300 2650 2750 2200 1750 1650 2450	3750 2400 2950 3450 3600 2900 2300 2150 3200	1040 660 850 980 1000 800 620 570 890
3 3 6 k-2, 4 k-5, 6 k-7, 8, 9 k-10 k-11	3029. 3025, 3036, 3052 and 3057. 3000 to 3003. 3201 to 3240. 3241 to 3277. 3300 to 3324. 3295. 3297 and 3298.	2800 2900 3250 5400 5850 6350 4900 4700	3200 3550 3900 3100 3000	4250 4650 5150 4050 3900	1110 1260 1450 1150 1100
1 3 4, 5 M-2 M-3 C-1, 2, 3 C-4, 5 C-6 to 12	3600 to 3652. 3653 to 3667. 3668 to 3769. 3900 to 3911. 3930 and 3931. 4000 to 4048. 4100 to 4125. 3800 to 3811, 4126 to 4294.	6700 7600 8000 7550 8750 9150 11900 12500	4050	5400	1500
It-1, 3, 4, 5 It-2 IS-1, 2 IS-3, 4, 5, 6 P-1, 2, 3	4300 to 4376. 4385 to 4390. 4400 to 4415. 4416 to 4469. 5000 to 5048.	6600 6650 7000 7200 8000			
Empty and	Less than 45 Ms 45 Ms to 55 Ms More than 55 Ms	6 3 0		dffe (a	

RULE 10 (J). Slow board to left of track westward at MP 86.7 reads 60-40.

RULE 14 (e). As specified below, — — — — will be indication that flagman may return from east as prescribed by Rule 99:

Carnadero...... Trains on Hollister Branch.
Watsonville Jct.... Trains on Santa Cruz Branch.
Santa Cruz..... Trains on Davenport Branch.

RULE 82 (A). Westward third-class and extra trains originating Watsonville Jct. may obtain clearance at Pajaro instead of Watsonville Jct.

Crew ordered for No. 773 may assume schedule without clearance at Davenport.

RULE 83. Identification may be made at San Jose, or between Lick and Coyote; Gilroy and Sargent; and westward between Watsonville Jct. and Logan, to be applied at end of double track. Trains approaching each other between these stations must reduce speed sufficiently to permit identification, and Rule 14 (k) will apply.

RULE 83 (A). At the following stations, only trains indicated will register:

Gilroy..... Trains originating or terminating.
Pajaro..... Third class and extra trains originating or terminating in freight yard.

Watsonville Jct..... Trains originating or terminating that

do not register at Pajaro.

Operators Watsonville Jct. and Pajaro will report registration to each other of trains via Logan, and enter on registers and verify by repeating registration. Operator Pajaro will enter on his register the time train passes his office, and only after observing it.

RULE 83 (B). At open train-order offices, trains may register by ticket as follows:

San Jose......Nos. 70, 72, 76, 78, 96, 98, 374, 69, 71, 75, 77, 97, 99 and 373 and trains to or from San Jose Yard.

Watsonville Jct.... Nos. 77, 78, 96, 97, 98 and 99.

RULE 93. Yard limits in which the provisions of Rule 93 will apply are established at the following stations:

West MP	the state of the s	East MP
43.5	San Jose	56.0
	" (Lick Branch)	58.9
	" (Los Gatos Branch)	515
44.8	" - (Milpitas line)	
43.7	" (Agnew line)	
79.3	Giroy	22 4
96.1	Watsonville Jct	101.3
	" (Santa Cruz Branch)	103.6
119.27	Santa Cruz	122.7
	" (Davenport Branch)	81.7

RULE 98. Railroad crossings at grade not interlocked: WPRR, at Valbrick (in San Jose yard). After stopping, if no movement approaching on intersecting line, may proceed over crossing.

RULE 99. Logan: Granite Rock Co. will do switching on other than main track. SP crews will protect.

First-class trains move with caution between Signal Bridge 466 and Signal 473 San Jose. Trains or engines stopped between these signals need not protect against first-class trains, but must comply with Rule 99 (A).

RULE 99 (C). Will apply on Hollister, Santa Cruz and Davenport Branches.

RULE 103 (A). First St. crossing, Watsonville protected by crossing watchman only from Sept. 1st to Dec. 15th each year. At other times switching movements must be protected by member of crew at the crossing. Cars to be spotted must be left as far as practicable from crossing.

ticable from crossing.

Movements on other than main track over Walnut, Lincoln and Laurel Sts. Santa Cruz must be protected by member of crew.

RULE 104. The normal position of rigid switches at junctions is as follows:

San Jose..... Los Gatos Branch, for freight lead.
Lick..... Lick Branch, for eastward track.
Carnadero..... Hollister Branch, for westward track.
Watsonville Jct... Santa Cruz Branch, for west leg of wye.
Santa Cruz... Davenport Branch, for Santa Cruz Branch.

RULE 221. Trains destined to San Jose Yard need not obtain clearance at San Jose.

Pajaro is train order office only for westward third class and extra trains. Such trains having received clearance at Watsonville Jct. need not obtain clearance at Pajaro.

Trains may leave Santa Cruz without clearance if no operator

Light will not be displayed in train-order signal at Felton except when train-order operator is on duty.

RULE 505. AUTOMATIC BLOCK SYSTEM

San Jose: See instructions for San Francisco Subdivision.
Gilroy: End of double track: Westward trains leaving end of
double track from eastward main track will be governed by Signal
P-805.

Carnadero: In moving from eastward main track to Hollister Branch, first throw crossover switch in eastward main track; then other switches as most convenient. From Hollister Branch to westward main track, first throw derail, then junction switch.

Watsonville Jct.: Following will govern freight trains entering Watsonville Jct. yard:

West end: If Signal 984 is in proceed position for diverging route which governs entrance to yard at crossovers Nos. 1 or 2, trains must receive signal from yardman, green flag by day, green light by night before entering yard. If Signal 984 is in stop position, must remain at the signal until given a proceed signal by yardman, green flag by day, green light by night.

Santa Cruz: Track from station building to Signal 791 not protected by block signals.

RULE 510. The following block signals equipped with triangular number plate displaying the letter "P" have included in their control limits some special protective device:

Eastw: Signal	Protection	Westward Signal
P-514	Spring switch, end double track, Lick	2010001000000000
P-634	Spring switch, end double track, Coyote	P-635
P-660	Spring switch, west end siding, Perry	
	Spring switch, east end siding, Perry	P-673
P-708	Spring switch, west end siding, Morganhill	
	Spring switch, east end siding, Morganhill	P-719
P-740	Spring switch, west end siding. San Martin.	
	Spring switch, east end siding. San Martin	P-753
P-770	Spring switch, west end siding, Rucker	
	Spring switch, east end siding, Rucker	P-783
P-804	Spring switch, end double track. Gilrov.	P-805
P-866	Spring switch, end double track. Sargent	P-867
D 000	Spring switch, east end siding, Sargent	P-870
P-908	Spring switch, west end siding. Chittenden	
	Spring switch, east end siding, Chittenden	P-925
P-924	Earthquake detector, Pajaro River Bridge, Ch	ittenden]
P-930	Slide detector fence, Logan Spring switch, end double track, Logan	P-031

RULE 516. Overlap post: Chittenden — Affecting eastward trains.

RULE 535. SPRING SWITCHES

Spring switches equipped with facing point locks are located as follows, and speed indicated must not be exceeded while trailing through them:

Location	Normal Position	MPH			
Lick End doub	le track Eastward track	35			
Covote. End doub	le track Westward track	00			
Porry West and	siding Main track	25			
Powers Took and	siding	25			
Perry	siding Main track	25			
Morganniii west end	siding Main track	15			
Morganniii East end	siding	15			
San Martin West end	siding Main track	25			
San Martin East end	siding Main track	25			
Rucker West end	siding Main track	20			
Rucker East end	olding	25			
	siding Main track				
Giroy	le track Eastward track	25			
Sargent End doub	le track Westward track	25			
Sargent East end	siding Main track	25			
Chittenden West end	siding Main track	25			
Chittenden East end	sidingMain track	25			
Logan End doub	le track Eastward track	25			
-ogomining doub	Facing costward				
	Facing eastward	25			

When signal governing westward movement through spring switch at Lick displays stop indication, permission must be obtained from signal operator at San Jose to pass signal, and switch must be hand thrown before and after movement made, in addition to complying with block signal rules.

INTERLOCKING **RULE 605.**

San Jose-Lick: Limits extend from dwarf signals on eastward and westward main tracks 1500 feet west of end of double track San Jose to light signal 700 feet east of end of double track Lick on westward track, and to light signal 500 feet east of end of double track Lick on eastward track.

On Lick Branch, to dwarf signal at clearance point.

On freight lead from signal bridge 464 to junction with eastward main track 1250 feet west of end of double track.

On Los Gatos Branch, from junction with freight lead to west-

ward signal opposite signal 474.

Movements within these limits are governed by interlocking signals under control of signal operator, except some of the intermediate signals are automatic, or semi-automatic.

Switch at end of double track is power operated over which speed is restricted to 30 MPH in either direction for trains operating

through turnout.

When automatic block signals indicate "stop" Rule 509, 509 (F) or 509 (J) as the case may be, as applied to single track will govern.

When for any reason, proceed indication of an interlocking signal cannot be acted upon at once, signal operator must immediately

be notified.

From Los Gatos Branch, movement governed by westward interlocking Signal 11-W located 30 feet east of crossover between freight lead and Los Gatos Branch. Upper unit governs to westward main track and station tracks. Lower unit governs to freight lead. When both units indicate "stop" and it is desired to use connecting link to spur track No. 829, California Packing Corporation, after stopping and if crossover switches are lined normally, and the track is seen to be clear to westward automatic Signal 474.5 located at clearance point 250 feet west of Signal 11-W, proceed without authority from signal operator at San Jose station.

A westward dwarf interlocking signal located opposite Signal

471 at Park Avenue Subway. Signal will be normally dark until lineup is made. Westward movement from Los Gatos Branch to freight lead must first be authorized by signal operator. Crossover switches must not be lined for such movement without first obtaining permission from signal operator by telephone. After permission is received, crossover switches lined, and if interlocking signal indi-

cates "proceed," movement may be made.

Movement to Los Gatos Branch from eastward main track governed by lower unit Signal 470 located east of station, and from freight lead governed by lower unit of signal located 400 feet west of junction switch.

Eastward dwarf Signal 474.5 on seven-foot mast will display RED or GREEN aspect.

RED—Stop. To enter block comply with Rule 509 (F).

GREEN—Proceed to next Signal 474.

Signal on San Jose Canning Co. spur at MP 48.5 governs movement to main track. Derail or main track switch must not be thrown until permission received from signal operator, and in addition switch indicator for both directions must indicate "block clear."

Movements from Valbrick (San Jose yard) connection to main track must first be authorized by signal operator. Derail and main track switches must not be lined for such movement without first obtaining permission from signal operator by telephone. After permission is received, switch lined, and if signal indicates "proceed," movement may be made.

Telephones located closely adjacent to signals involved. If de-

layed, consult signal operator.

San Jose-Lick Line - (Western Pacific R. R. Crossing): Limits extend from signal located 700 feet west of crossing to signal 700 feet east of crossing.

No signal operators on duty. Signals, switches and derails in position for Southern Pacific movements and against Western Pacific movements.

When signals indicate "stop", Rule 663 (c) will govern. Instructions for handling electric lock and time release posted at crossing.

RULE 705 LETTER TYPE INDICATORS

Indicato	rs located a	as follows:	
Illuminated Letter	On Signal	Approaching	Authorizes and requires movement as follows:
М	. 621	West end siding Coyote	.Enter westward track and proceed to Lick.
M S	. 643	Coyote	.Proceed to Lick. .Enter middle siding.

GENERAL REGULATIONS

RULE 825. Cars must not be stored within 150 feet of crossings of Monterey Road at Watsonville Jct.

When freight trains are tied up in Watsonville Jct. yard trainmen will set sufficient hand brakes on the rear of westward trains, and on the head end of eastward trains.

AIR BRAKE RULES

RULE 17. One retainer must be turned up for each 120 Ms in freight trains Olympia to MP 127.6, and Rincon to MP 121.8.

On passenger trains between the above points, three retainers for six cars; four retainers for eight cars; five retainers for 10 cars, and seven retainers for 12 cars must be turned up on head end of the train.

FREIGHT TRAINS

RULE 33. The maximum tonnage per operative brake between Olympia and Santa Cruz is 120 Ms.

PASSENGER TRAINS

RULE 39. Running test must be made on eastward trains at San Jose after rear of train has passed over spring switch at east end freight lead.

MISCELLANEOUS

10. Freight trains or engines with freight cars must not operate over tracks 2, 3, 4 or 5 in San Jose passenger yard. Engines listed must not operate on tracks shown below:

Class of Engine Restricted Tracks

Mk-F-AC-AM-MM-Mt-GS-SP T-40, P, A	Morganhill	Standard Oil spur; Dried fruit spur.
AND EXPERIMENT PRINCIPAL	Lonoke	Spur.

Engines must not go more than 110 feet beyond derail at west end of No. 1 track at Logan.

Engines equipped with pilot plow, except Mt and GS class, are prohibited over tracks adjacent to station platform at San Jose.

Load limit (car and contents): Lick Branch ... 169,000 pounds

With Couties

SPEED RESTRICTION FOR OTHER THAN MAIN TRACKS		Exceeding MPH
Through sidings, yard and other side-tracks, wyes,	bal-	

ex	on tracks, c					 	 			 			. 1
Sa	n Jose, on	freig	ht 1	lea	d.		 			 			 . 2
W	atsonville J	ct.,	wye				 						
Sa	nta Cruz, w	vye.	-				 						
Da	venport, w	ye .					 						

LOCATION OF OVERHEAD AND SIDE STRUCTURES NOT STANDARD CLEARANCE ON MAIN TRACK AND SIDINGS MP Location Description

	Santa Cruz Branch
119.7	Santa Cruz San Lorenzo River bridge—Side
121.5	EblisTunnel 6—Overhead and Side
125.6	RinconTunnel 5—Overhead and Side
126.3	Big Trees San Lorenzo River bridge—Side
126.0	Big TreesRedwood tree—Side

38

Maximum speed of Passenger trains must not exceed 50 MPH and Freight and Mixed trains 35 MPH except as otherwise provided for herein, or by

SPEED RESTRICTIONS:

bulletin, train order or fixed signal.

Maximum speed of any train with an engine not shown in Speed Restriction table, 35 MPH, and is further restricted to maximum speed shown for Freight and Mixed

WITH TRAIN - ENGINE RUNNING FORWARD

PASSENGER

ENGINE BACKING WITH TRAIN OR LIGHT

LIGHT ENGINE RUNNING FORWARD

¥™#SS

FREIGHT AND MIXED

MK-10--12-12

7-1-8-4 32-28-31-36-57-58 MK-5-6-7-8-8

TERRITORY

200

SPECIAL INSTRUCTIONS

-GILROY AND SALINAS SUBDIVISIONS

		/ -			11	Ī
į				91	н	
2	75	7.5	75	45	Ħ	

and the second	ı		
200			

MACHENI	I	n	
388	H	1	

12	DAL
7	II K

_	_	_			_
			ш	M	
	-		н	н	
S.	10	10		11	

4 64		
य द्य		

RR

88			
----	--	--	--

	AND DESCRIPTION
8888888	8888

នន្តន្តន្តន្តន្តន្តន្ត

 11	K	
 . II	Н	

112	OFL
chinaries	11 15

	П	1	
20.00	П		

0.000	1		
25	1	1	
0			

-1	П		
- 1	11		
5	П		

888888888888888

84448448484848

844484484844448

84448448484448

84428328232548

8348888888888

823588888885538

2222222222

End double track Sargent-MP 87.9
MP 87.9-MP 88.9
MP 88.9-MP 92.1
MP 92.1-MP 93.0
MP 93.0-MP 94.5
MP 94.5-MP 94.6
MP 96.0-Watsonville Jct. Yard OfficeWatsonville Jct. Yard Office-End double track

Signal Bridge 464-End of double track End of double track-MP 49 Over WPRR Crossing MP 49

14 to 17

MP 49-MP 86.0, except.
*Gilroy, MP 79.5 to MP 81
MP 86.0-End of double track Sargent

8444%4484%448%

84448448484488

8444448844444

88888888888888

888844884444

2222222222222

2444442244444

844448844444

824238888888

834385885885

| Watsonville Jet. Yard Office-End double track Watsonville Jet. end double track-MP 103.8 |
| MP 103.8-MP 105.5 |
| MP 105.5-MP 109.0 |
| MP 105.5-MP 112.5 |
| MP 112.5-MP 117.5 |
| MP 117.5-MP 119.7 |
| *Salinas, MP 118.4 to MP 119.7 |
| MP 119.7-MP 147.0 |
| MP 147.0-MP 154.5 |

18 to 21

MP 154.5-MP 158.0 MP 158.0-MP 163.5 MP 163.5-MP 164.0

83333333333

ENGINE RUNNING FORWARD

PASSENGER

TERRITORY

ź

Maximum speed of passenger, freight and mixed trains is as shown below:

SPEED RESTRICTIONS—BRANCHES

BACKING

15

8 8

555855555

88888888888888

8888228888

Watsonville Jct.-Santa Cruz, except

16

Watsonville City limits ... Santa Cruz City limits... Santa Cruz-MP 122.5.

Carnadero-Hollister, except.

Lick-Alamitos

517

1010

555

Speed may be resumed at Gilroy and Salinas after engine has passed last crossing within these limits in direction train is moving.

- MP 127.3-Asilomar..... Spreckels Jct.-Spreckels

21

*Regulated by city ordinance.

MP 122.5.MP 126.5
MP 126.5-Olympia
Davenport-Santa Cruz
Castroville-Monterey, except
With F-1, Mk, P, Mt, GS engines on curves.
Monterey-MP 127.3, except.
With P-1-3-5-6 engines where slow boards reading

84228

RATING OF ENGINES-In Ms of 1000 lbs. Back of Tender.

NOMINAL CLASS	ENGINE, NUMBERS	San Jose to Morganhill Watsonville Jct. to Morganhill	Morganhiil to Wetsonville Jct. Morganhiil to San Joee	Watsonville Jcf. and Santa Gruz	Santa Cruz to Davenport	Devenport to Santa Gruz	Santa Gruz and Olympia	Gilroy and Hollister
DES-1, 2, 3, 4, 5, 6, 7 DES-100 to 107 E-23 M-4 M-6, 8 M-9, 11 M-11	1000 to 1022 1300 to 1395 1500 and 1502 1617 to 1713 1721 to 1803, 1823 to 1825 1804 to 1822, 1826 to 1831 and 1836 1832 to 1835	1550 2450 2300 2950 3650 3850 3950	4400 5500 5100 6500 7500 8000 8600	1200 1450 1550 1650	1400 1650 1750 1900	2550 3000 3150 3350	610 740 790 860	3450 4050 4250 4550
T-1 T-8, 9 T-23 T-26 T-28, 31 T-32, 40 T-36 T-37 T-57, 58	2242 to 2271. 2161, 2174 and 2178. 2301 to 2310. 2283 to 2299. 2311 to 2362. 2263 to 2384. 2103. 2105 and 2106. 2385 and 2386.	2600 1850 3750 3300 4200 4300 2800 3750 3400	5700 4100 8200 7200 9000 9000 6100 8200 7400	1100 760 1550 1350 1750 *1800 1200 1600 1400	1200 860 1800 1550 1950 *2000 1350 1800 1600	2200 1550 3200 2800 3500 *3600 2350 3200 2900	540 350 800 650 890 *910 610 800 730	3000 2150 4300 3800 4750 *4850 3200 4350 3900
P-1, 3, 5 P-1 P-4 P-6 P-7 P-8, 10 P-8, 10 P-11 P-12	(2408, 2411 to 2413, 2416 to 2418, 2423, 2425 to 2435,) 2437 to 2452, 2459 and 2460 2400, 2403 to 2407 and 2415. 2401, 2402, 2409, 2410, 2414, 2419, 2420, 2422, 2424 and 2436 2453, 2454 and 2458. 2476 and 2477, 2461 to 2474, 2478 to 2483. 2475, 2484 to 2491 3100 to 3109.	3500 3550 4000 4300 4350 4600 4800 3700 5050	7000 7800 8000 9000 9000 10000 10000 7000 10000	1350 1450 1500	1550 1650 1700	2850 3000 3150	660 690 730	
C-5, 8, 9, 10, 26 to 29 C-15, 32 C-17 C-18 C-19 FW-1 FW-2, 3 FW-4, 6 FW-8	2513 to 2599, 2624 to 2860, 3440 to 3469 2500, 2505 to 2507. 2510 and 2511. 3400 to 3409. 3410 to 3426. 2900 to 2913. 2932 to 2952. 2926 to 2931 and 2957. 2914 to 2923.	4600 2900 3600 4200 4350 3500 2800 2650 3900	10000 6300 7800 9100 9500 7500 6100 5800 9000	1950 1250 1550 1800 1850 1350 1150 1100 1650	2200 1400 1750 2000 2100 1700 1300 1250 1900	3900 2500 3050 3550 3700 3000 2350 2250 3350	1000 640 820 940 970 760 590 550 850	5250 3350 4150 4800 5000 4000 3200 3050 4450
A-3 A-3 Mk-2, 4 Mk-5, 6 Mk-7, 8, 9 Mk-10 Mk-11	3029. 3025, 3036, 3052 and 3057. 3000 to 3003. 3201 to 3240. 3241 to 3277. 3300 to 3324. 3295.	2800 2900 3250 5400 5850 6350 4900 4700	5500 6000 7200 10000 12000 12000 10600 10200					
F-1 F-3, 5 C-4, 5 C-4, 2 MM-3 CC-1, 2, 3 CC-4, 5 CC-6 to 12	3600 to 3652. 3653 to 3667. 3668 to 3769. 3900 to 3911. 3930 and 3931. 4000 to 4048. 4100 to 4125. 3800 to 3811, 4126 to 4294.	6700 7600 8000 7550 8750 9150 11900 12500	12000 12000 12000 14000 16000 16000 16000 17000					
At-1, 3, 4, 5 At-2 SS-1, 2 SS-3, 4, 5, 6 P-1, 2, 3	4300 to 4376. 4385 to 4390. 4400 to 4415. 4416 to 4469. 5000 to 5048.	6600 6650 7000 7200 8000	12000 12000 12000 12000 12000					
Empty and	Less than 45 Ms 45 Ms to 55 Ms More than 55 Ms	6 3 0	6 3 0	Louis and				10 10 W

*Exception: Eng. 2371 not permitted on these branches.

RULE 10 (J). Westward slow board at MP 116.90 reading "75"; and eastward slow board on Monterey Branch at MP 124.96 reading "25-20" are located to left of track.

Eastward slow boards to right of track but with one track intervening at MP 117.74, reading "25", and at MP 119.74, reading "75".

RULE 14 (e). As specified below. indication that flagman may return from east as prescribed by Rule 99:

Castroville..... Trains on Monterey Branch.

RULE 82 (A). Crew ordered for No. 77 at Pacific Grove on Sunday and Holidays only, may assume schedule without clearance.

RULE 83 (A). At the following stations, only the trains indicated will register:

Castroville..... Trains to or from Monterey Branch, and trains originating or terminating.

Salinas..... Trains originating or terminating. Soledad..... Trains originating or terminating.

RULE 83 (B). At open train-order offices, trains may register by ticket as follows:

Watsonville Jct....... Nos. 77, 78, 96, 97, 98, 99. King City....... All trains.

RULE 93. Yard limits in which the provisions of Rule 93 will apply are established at the following stations:

West MP		East MP
96.1	Watsonville Jct	101.3
109.6	Castroville	111.7
1100	" (Monterey Branch)	112.1
113.2	Salinas	121.5
	" (Spreckels Branch)	122.8
142.4	Soledad	144.7
162.2	King City	164.7
123.3	Monterey	127.6
127.7	Pacific Grove	129.9

RULE 99. Lapis: Pacific Coast Aggregates Co. will do switching at Lapis. SP crews will protect.

RULE 99 (C). Will apply on Monterey Branch.

RULE 103(A). Trains and engines must stop before reaching State Highway crossings of tracks 2, 3 and 4 at MP 118.8, 118.9 and 119.5 at Ord and after crossing signals have been in operation 20 seconds or more, may then move over highway.

Spring derail on each of these tracks may be trailed through on movement into Fort Ord; but reverse movement must not be made while engine or cars are on the derail; and derails must be hand thrown for movement out of Fort Ord.

Movements over county road crossing on spur and siding at Chualar must be protected by member of crew.

RULE 104. The normal position of rigid switches at junctions is as follows:

Castroville...... Monterey Branch, for Salinas line.

Spreckels Jct......Spreckels Branch, for Salinas line. Crossover on No. 2 track at Fort Ord must be left lined for stub end.

RULE 221. Trains must obtain clearance before leaving Monterey and Pacific Grove only when operator is on duty.

RULE 505. AUTOMATIC BLOCK SYSTEM

Watsonville Jct.: Eastward trains leaving end of double track from westward track will be governed by Signal P-1008.

East end: If Signal 1001 is in stop position, train after stopping may proceed to highway crossing at yard office, but will not pass that point nor make crossover movement until proceed signal received from yardman, green flag by day, green light by night. If Signal 1001 is in proceed position for diverging route train may proceed to highway crossing at yard office, but will not pass that point nor make crossover movement until proceed signal received from yardman, green flag by day, green light by night.

THE OF PERMITTER WALLEY WITH A REPLY TO SEE

RULE 510. The following block signals equipped with tr lar number plate displaying the letter "P" have included in control limits some special protective device:	n their
---	---------

Eastward Westward Signal Protection Signal P-1008 Spring switch, end double track, Watsonville Jct... P-1009

RULE 516. Overlap posts:

RULE 535. SPRING SWITCHES

Spring switch equipped with facing point lock is located as follows, and speed indicated must not be exceeded while trailing through it: Location **Normal Position**

Watsonville Jct. End double track....Westward track

RULE 705. LETTER TYPE INDICATORS

Indicators located as follows:

Illuminated On Approaching Authorizes and requires Letter Signal King City....movement as follows: M......1612.....King City.....Proceed to train-order office. S 1612.... King City.... Enter siding.

GENERAL REGULATIONS

RULE 825. When freight trains are tied up in Watsonville Jct. yard, trainmen will set sufficient hand brakes on the rear cars on westward trains.

Cars must not be left on storage track between Spreckels Jct. and Spreckels within 100 feet of Hunter Lane crossing at MP 121.8; and Harkins Road crossing at MP 122.2.

RULE 827. TRAIN INSPECTION

Load limit (car and contents):

113.5

When conditions are favorable and in judgment of conductor and engineer it is safe to do so, may run in either direction between King City and Watsonville Jct.

AIR BRAKE RULES

RULE 25. Westward movements off tracks 2 or 3 at Ord must have air cut in on all cars.

MISCELLANEOUS

1. Engines take water at Salinas, Chualar or Soledad in preference to King City.

10. Engines listed must not operate on tracks shown below:

Class of Engine Restricted Tracks (Mk-F-AC-AM-MM-Mt-GS-SP. ...)
Castroville. All industry and spur tracks.
Salinas. . . . Leads 4, 35, 55, 57, 200, 210, and
250; and all industry spurs; Lead
133 east of girder-rail crossing. Nashua...Spur. Lapis...Spur. Seaside...Siding. Seaside....Soung.
Retreat...Spur.
Del Monte. Hotel spur.
Monterey.. House track; team track; corral
track and all industry tracks.

210,000 pounds With Caution SPEED RESTRICTIONS FOR OTHER THAN MAIN TRACKS Not Exceeding MPH

Through sidings, yard and other side-tracks, wyes, balloon tracks, crossovers, turnouts and slip-switches, except 10 Castroville wye Spreckels Jct. wye 5 Elsa wye Gigling balloon track....

LOCATION OF OVERHEAD AND SIDE STRUCTURES NOT STANDARD CLEARANCE ON MAIN TRACK AND SIDINGS

Neponset......Salinas River bridge—Side

MP Location DescriptionTunnel 5½-Side 155.1 Metz Monterey Branch

RATING OF ENGINES-In Ms of 1000 lbs. Back of Tender.

NOMINAL CLASS	ENGINE NUMBERS	Watsonville Jct. to King City	King City to Watsonville Jet.	Monterey and Pacific Grove	Ord to Castroville Ord to Monterey	Castroville to Ord Monterey to Ord	
DES-1,2,3,4,5,6,7 DES-100 to 107 E-23 A-4 A-6, 8 A-9, 11 A-11	1000 to 1022. 1300 to 1395. 1500 and 1502. 1617 to 1713. 1721 to 1803, 1823 to 1825. 1804 to 1822, 1826 to 1831 and 1836. 1832 to 1835.	1350 2200 2000 2550 3150 3350 3450	1550 2450 2300 2950 3650 3850 3950	1150 1550 1850 1950 2100	2650 3450 4050 4250 4550	1150 1550 1850 1950 2100	I has side another display W (3) 64 to and 21 y 25 fillers
Γ-1 Γ-8, 9 Γ-23 Γ-26, 31 Γ-32, 40 Γ-36 Γ-37 Γ-57, 58	2242 to 2271 2161, 2174 and 2178 2301 to 2310 2283 to 2299 2311 to 2362 2363 to 2384 2103 2105 and 2106 2385 and 2386	2250 1600 3250 2850 3650 3750 2400 3250 2950	2600 1850 3750 3300 4200 4300 2800 3750 3400	1350 970 2000 1700 2200 2250 1500 2000 1800	3000 2150 4300 3800 4750 4850 3200 4350 3900	1700 2200	ST (C) IS Sen Line C Sen Line C Sen Sen Sen St Sen Sen Sen Sen Sen Sen Sen Sen Sen Sen
P-1, 3, 5 P-1 P-4 P-6 P-7 P-8, 10 P-8, 10 P-11 P-12	[2408, 2411 to 2413, 2416 to 2418, 2423, 2425 to 2435,] 2437 to 2452, 2459 and 2460 2400, 2403 to 2407 and 2415. 2401, 2402, 2409, 2410, 2414, 2419, 2420, 2422, 2424 and 2436 2453, 2454 and 2458. 2476 and 2477 2461 to 2474, 2478 to 2483 2475, 2484 to 2491 3100 to 3109 3120 to 3129.	3050 3100 3450 3750 3800 4000 4150 3200 4400	3500 3550 4000 4300 4350 4600 4800 3700 5050	1700 1850 1900 2200	3700 4100 4250 4850 5150 5350 5650 4200 5650	1700 1850 1900 2200 2350 2400 2550 1900 2550	
C-5, 8, 9, 10, 26 to 29 C-15, 32 C-17 C-18 C-19 FW-1 FW-2, 3 FW-4, 6 FW-8	2513 to 2599, 2624 to 2860, 3440 to 3469. 2500, 2505 to 2507. 2510 and 2511. 3400 to 3409. 3410 to 3426. 2900 to 2913. 2932 to 2952. 2926 to 2931 and 2957. 2914 to 2923.	3950 2550 3150 3650 3800 3050 2400 2300 3200	4600 2900 3600 4200 4350 3500 2800 2650 3900	2450 1550 1950 2250 2350 1850 1450 1400 2050	5250 3350 4150 4800 5000 4000 3200 3050 4450	2450 1550 1950 2250 2350 1850 1450 1400 2050	
A-3 A-3 A-6 Mk-2, 4 Mk-5, 6 Mk-7, 8, 9 Mk-10 Mk-11	3029 3025, 3036, 3052 and 3057 3000 to 3003. 3201 to 3240. 3241 to 3277. 3300 to 3324. 3295. 3297 and 3298.	2400 2500 2800 4650 5150 5550 4250 4100	2800 2900 3250 5400 5850 6350 4900 4700	(2) (1) (2) (3) (4) (4) (4) (4) (4) (4) (4) (4) (4) (4		2700	I stangill on the entropy of force the not off Ark ottoe sector ros alterni for
7-1 7-3 14, 5 1M-2 4M-3 1C-1, 2, 3 1C-4, 5 1C-6 to 12	3600 to 3652. 3653 to 3667. 3668 to 3769. 3900 to 3911. 3930 and 3931. 4000 to 4048. 4100 to 4125. 3800 to 3811, 4126 to 4294.	5800 6600 7000 6600 7650 8000 10400 11000	6700 7600 8000 7550 8750 9150 11900 12500	indenta indi.idi indi.idi indi.idi indi.idi indi.idi indi.idi indi.idi indi.idi indi.idi indi.idi idi idi idi idi idi idi idi idi i	7500 8650 9000	4100	Epring with Fire detects The detects plk. Orne
ft-1, 3, 4, 5 ft-2 iS-1, 2 iS-3, 4, 5, 6 P-1, 2, 3	4300 to 4376. 4385 to 4390. 4400 to 4415. 4416 to 4469. 5000 to 5048.	5750 5800 6100 6300 7900	6600 6650 7000 7200 8000	ool 1 Story when the prpr(3250 3550 3450 3600	
Allowance for Empty and iderloaded Cars	Less than 45 Ms 45 Ms to 55 Ms More than 55 Ms	6 3 0	6 3 0	RECTU			TAN AUT

RULE 10 (J). Slow boards to left of track:

Eastward MP	Reading	Westward MP	Reading
211.15 228.37	50-35 40-35	195.36 230.09	40-20 40-35
		233.52	55-40

Westward slow board at MP 188.87 is located one-half mile from point of restriction.

Oval slow boards with the words "APPROACH CIRCUIT" above the figures "40-20" indicate the speed that must not be exceeded passing Approach Circuit sign on signal case 1500 feet in approach to Signals 1932 and 1943. Trains must approach these signals in accordance with automatic signal indications received.

RULE 14 (k). Will apply in C.T.C. limits.

RULE 17. Eastward passenger trains at Santa Margarita will extinguish headlight when helper engines are being coupled to train.

RULE 21. Will apply in C.T.C. limits.

RULE 21 (C). Engines of passenger trains may display indicators from San Luis Obispo passenger station to roundhouse. They must be removed on arrival delivery track at roundhouse.

RULE 83 (A). Only trains originating or terminating will register at Santa Margarita.

RULE 83 (B). All trains may register by ticket at King City.

RULE 93. Yard limits in which the provisions of Rule 93 will apply, except within C.T.C. limits are established at the following stations:

West MP	2000 - 2000 - 0000	East MP
162.2 233.9 249.6	King City Santa Margarita San Luis Obispo	236.8

RULE 103 (A). Trains and engines must stop and member of crew must protect traffic while crossing Highway 101 over spur to Camp Roberts near McKay.

RULE 105. Santa Margarita: Eastward siding extends from MP 234.1 to crossover just west of station building, and is assigned for use of eastward trains. The portion of this track east of this crossover must be left clear for use of helper engines. Westward siding is on opposite side of main track from station building, and is assigned for use of westward trains.

RULE 505. AUTOMATIC BLOCK SYSTEM

Cushing: Signals P-2329 and P-2331 at west end of siding have push button device for clearing signals on adjoining track. See instructions for all subdivisions.

RULE 510. The following block signals equipped with tri-angular number plate displaying the letter "P" have included in their control limits some special protective device:

Eastward Signal	Protection	Westward Signal
P-2328	Spring switch, west end siding, Cushing Fire detector, Tunnel 6, Cuesta	D.9401
	Fire detector, Steiner Creek bridge, Goldtree	P-2493

RULE 51				
Eaglet .	 	 Affecting	westward	trains.
Cushing	 	 Affecting	eastward	trains.

RULE 535. SPRING SWITCHES

Spring switch equipped with facing point lock located as follows, and speed indicated must not be exceeded while trailing through it:

Location	Normal Position	MPH
Cushing, West end siding	Main track	25

RULE 705. LETTER TYPE INDICATORS

Indicators located as follows:

Illuminated Letter		Approaching	Authorizes and requires movement as follows:
M S	1657	King City	Proceed to train-order officeEnter siding.

RULE 760. CENTRALIZED TRAFFIC CONTROL SYSTEM

Limits extend from west end westward siding Santa Margarita,

to end of double track San Luis Obispo.

Lower unit of eastward signal at end double track San Luis Obispo governs only to C.T.C. limit at fouling point on westward track, and trains and engines must not accept proceed indication for diverging route until verbal understanding has been had with yardmaster or his representative that protection has been provided on westward track, except that proceed signal from yardman, green flag by day or green light by night, may be accepted as authority to move from C.T.C. limit to the first switch leading to yard tracks

only.

Westward siding Santa Margarita has a dual control switch at east end, but this is not a controlled siding, and has no signal control east end, but this is not a controlled siding, and has no signal control east end, but this is not a controlled siding, and has no signal control beyond fouling point. Before fouling westward siding at west end, or at either crossover, dispatcher's permission and time limit must be

obtained.

Absolute signals at east and west switches of westward siding and at east switch of engine track at Santa Margarita; and at end of double track at San Luis Obispo have call-on unit, and when engine stands within 50 feet of signal and call-on unit flashes yellow, authorizes engine to pass signal to couple to train without securing dispatcher's permission by telephone, providing train has stopped, and hand or lamp signal is received from a member of the train

Eastward and westward signals on siding at middle crossovers at Serrano have call-on unit which, when flashing yellow authorizes a train on siding, after stopping, to proceed on siding beyond crossover switches without securing telephone permission from dispatcher, but must expect to find a train at any point on siding.

RULE 763. Revised to read as follows:

"Train indicators, signals and markers must be displayed through C.T.C. limits. Rule S-17, Fig. 7 of Rule 19, and Rule 19 (A) will not apply on controlled sidings.

RULE 776 (a). When necessary to send flagman through Tunnel 6 at Cuesta, train must wait until flagman calls on telephone from opposite end of tunnel.

GENERAL REGULATIONS

RULE 825. When freight trains are tied up in San Luis Obispo yard trainmen will set sufficient hand brakes on the head end of eastward trains.

Portable rail skids are hung on posts at lower end of sidings at: Cushing Cuesta Serrano Chorro

When necessary to leave cars on any of these sidings permission must first be obtained from chief train dispatcher, after which rail skid must be placed on rail and leading wheel of first car in descending direction run onto the rail skid, and hand brakes set if brakes are operative, before engine is detached. Trains picking up cars from these sidings must remove rail skid and return it to proper post and lock it in place with switch lock.

RULE 827. TRAIN INSPECTION

Eastward freight trains must stop between switches Serrano 10 minutes to permit heat of wheels to equalize, and for train inspec-

When conditions are favorable, and in judgment of conductor and engineer it is safe to do so, may run in either direction between Santa Margarita and King City.

AIR BRAKE RULES

RULE 17. Retainers will be used on passenger trains as follows:

Eastward, all retainers from summit in Tunnel 6 to west switch Hathaway, if accessible; but if more than four head-end cars on which retainers are not accessible, stop must be made at Serrano to turn such retainers up. If operating stop is not made at Hathaway inaccessible retainers on head end cars may be left turned up until train stops at San Luis Obispo. On any train having as many inaccessible as accessible retainers, stop must be made at Serrano to turn up all retainers; and when over one-third of the total equipment in train consists of head-end cars on which retainers are not accessible, stop will be made after running test has been made leaving Santa Margarita, and before reaching summit, where such retainers must be turned up.
Westward, all accessible retainers from summit in Tunnel 6 to

Santa Margarita.

On spur between Goldtree and Camp San Luis Obispo with over 5 cars, one retainer for each two cars must be turned up on head end.

When streamlined trains are controlled on descending grade with electro-pneumatic brakes, retaining valves will not be used.

Retainers will be used on freight trains as follows:

One retainer for each 120 Ms in train, eastward from summit in Tunnel 6 to west switch Hathaway; westward from summit in Tunnel 6 to Santa Margarita; and on spur in both directions between Goldtree and Camp San Luis Obispo.

Eastward trains must not exceed 10 MPH from one-half mile west of west switch to east switch Hathaway to enable trainmen

to turn down retainers.

When eastward trains have over 45 cars, retainers on head 15 cars will be left up until train stops at San Luis Obispo, where they must be turned down.

When helper engines remain cut in train in either direction, three additional retainers must be turned up for each helper engine in above territories.

FREIGHT TRAINS

RULE 25. Rear end test must be made on eastward freight trains immediately prior to leaving Santa Margarita in accordance with paragraph (b).

RULE 33. The maximum tonnage per operative brake between Santa Margarita and San Luis Obispo and on spur between Goldtree and Camp San Luis Obispo is 120 Ms.

PASSENGER TRAINS

RULE 38. Will apply at San Luis Obispo when car men not on duty.

RULE 39. Running test must be made immediately after passing summit in Tunnel 6 in both directions.

MISCELLANEOUS

Engines with tenders of less than 9,000 gallons capacity must have full tank of water leaving San Luis Obispo westward, and leaving Santa Margarita eastward. Engines take water at Soledad, Chualar or Salinas in prefer-

ence to King City.

4. Helper engines must not be placed behind caboose of eastward freight trains from Santa Margarita.

10. Engines listed must not operate on tracks shown below: Class of Engine

Load limit (car and contents): Lompoc-White Hills Branches...... 210,000 pounds

With Caution SPEED RESTRICTIONS FOR OTHER Not Exceeding THAN MAIN TRACKS MPH

Through sidings, yard and other side-tracks, wyes, balloon tracks, crossovers, turnouts and slip-switches, 10 Entering, leaving and passing through sidings in C.T.C. limits with engine running forward.....

LOCATION OF OVERHEAD AND SIDE STRUCTURES NOT STANDARD CLEARANCE ON MAIN TRACK AND SIDINGS

ML Toca	tion Description
182.9	San ArdoEast water tank spout on siding-Side
200.6	NacimientoSalinas River bridge—Side
207.0	San Miguel Water tank spout, main track and siding—Side
222.0	TempletonOvergrade crossing—Side
223.4	Asuncion Graves Creek bridge—Side
239.6	CuestaTunnel 6—Overhead and Side
240.2	Thyle " 7— " "
240.6	" " <u>8</u> "
240.9	" " 9— "
241.7	" " 10— " "
245.8	Chorro " 11—Side
251.1	Hathaway Overgrade crossing—Side
251.2	" —Side
251.8	San Luis Ohisno " " Side

SPEED RESTRICTIONS: Maximum speed of Passenger trains must not exceed 50 MPH and Freight and Mixed trains 35 MPH except as otherwise provided for herein, or by bulletin, train order or fixed signal.

Maximum speed of any train with an engine not shown in Speed Restriction table, 35 MPH, and is further restricted to maximum speed shown for Freight and Mixed

44

1					WITH	H TRAIN	1 4	ENGINE RUNNING FORWARD SENGER	NING F	ORWARD			LIGHT	ENGIN	ENGINE RUNNING FORWARD	ORWARI	WITH	WITH TRAIN OR
ERRITORY	у в с		GS CCB*) with stream- lined cars only (other than Lark equipment)	P-8 (If CCB*) P-7- 10-12 GS	P-1-3- 11 P-8 (If not CCB*)	_ \$4.44 4.44	AC-4-5- 7-8-9- 10-11- 12 AC-6 (if S	T-1-8-9- 23-28-31- 36-57-58 Mk-5-6-7- 8-9 F (if CCB*) SP Gas-elec. cars	M AM-2	C-2-4-5-8-9- 10-18-19-26- 27-28-29 TW Mk-2-4 F (if not CCB+) AC-1-2-3-6 (if not GCB+)	G-15-17- 32 MK-10- 11 MM-3	FREIGHT AND MIXED	GS A PE	T-26- 32-37- 40 F (if CCB*)	M T-1-8-9-23-28-0 31-38-57-8 7- C-2-4-5-8-9 10-18-19-26-0 27-28-9 A 8-0 (in not CCB) A	-C-15- TV-32 TW-2-4 TV-11 TW-2-4 AM-2	TA MK	AM-2 AM-3 Gas- elec.
			455558	453538	888888	4888888	2002000	333333	333333	044044 04004	333333	948844	333333	333333	55 55 55 55 55 55 55 55 55 55 55 55 55	888888	888888	888888
MP 193.7-MP 194.2 MP 194.2-MP 235.1 MP 235.1-MP 236.6 MP 236.6-MP 248.3 MP 241.3-MP 251.5 MP 251.5-MP 252.8			588885	ខឧឧឧឧឧ	មឧមមន	888884	15 35 25 25 25 25 25 25 25 25 25 25 25 25 25	848888	848885	848883	88888	898882	848885	848888	2888882	88888	888255	888855
MF 251.3-MF 252.8 MP 252.8-MP 259.0 MP 259.0-MP 261.2 MP 261.2-MP 262.3			30 60	3888	15 50 30 30	3265	2222	15 45 30	15 45 30	15 40 40 30	35 35 30	2988	3338	2348	35 35 25 25	2882	2888	ន្ទនេង
262.3-MP 267.9 267.9-MP 269.0 269.0-MP 275.6 277.0-MP 280.0 280.0-MP 283.0 280.0-MP 283.0 283.0-MP 291.3 283.0-MP 291.3 291.3-MP 295.8			232332222	545885858	3488888888	999999999999999999999999999999999999999	222222222	2222233333	464444444	33333333	55 55 55 55 55 55 55 55	9%999999	393333333	99999999	**********	88888888	88888888	888888888
MP 300.2-MP 309.0 MP 309.0-MP 312.0 MP 312.0-MP 318.0 MP 318.0-MP 318.0 MP 323.0-MP 338.6 MP 338.6-MP 338.6 MP 343.5-MP 350.0 MP 360.0-MP 368.0 MP 368.0-Santa Barbara, except *Santa Barbara, MP 368.7-MP 370.7	ept		88558858888888888888888888888888888888	90000000000000000000000000000000000000	22555555	220000000000000000000000000000000000000	222222222	22224444468	444444444 8	333333333	288888888888	3%3%33338X	244444444 8	999999998	**************	88888888	88888888	ន្តម្ភង្គម្ភង្គម្ភង្គម្ភ
		Maxii	Maximum speed	SPEED RESTRICT of passenger, freight		STRI	RESTRICTIONS	BR	-BRANCHES	cd	n below	The second second		Man To		3	3	7
	Page No.0	TO SE	TERI	RITORY	*	M-1ch-G	Salt Trees Markets in Markets	PAS	PASSENGER	FREIGHT AND MIXED	Winds	LIGHT ENGINE RUNNING FORWARD	ENGINE					
0.5	83	Surf-Lompoc	te Hills					ovad ne no ne e	20	15	12	10	15	einder St. sed				

	SPEED RESTRICTIONS—BRANCHES Maximum speed of passenger, freight and mixed trains is as shown below:	RANCHE ed trains is	as shown	below:	
Page No.	TERRITORY	PASSENGER	FREIGHT	LIGHT ENGINE RUNNING FORWARD	ENGIN
23	Surf-Lompoe Lompoe-White Hills	20	15	100	15

*Regulated by city ordinance.

RATING OF ENGINES—In Ms of 1000 lbs. Back of Tender.

NOMINAL CLASS	ENGINE NUMBERS	King City to Senta Mergarita	Senta Margarita to King City	Santa Margarita to San Luis Obispo	San Luis Obispo to Santa Margarita
DES-1,2,3,4,5,6,7 DES-100 to 107 E-23 M-4 M-6,8 M-9,11 M-11	1300 to 1395. 1500 and 1502. 1617 to 1713. 1721 to 1803, 1823 to 1825. 1804 to 1822, 1826 to 1831 and 1836. 1832 to 1835.	OFFI	1550 2450 2300 2950 3650 3850 3950	400 700 560 780 990 1050 1050	400 700 490 700 890 950 970
T-1 T-8, 9 T-23 T-26 T-28, 31 T-32, 40 T-36 T-37 T-57, 58	2242 to 2271 2161, 2174 and 2178. 2301 to 2310. 2283 to 2299 2311 to 2362. 2363 to 2384. 2103. 2105 and 2106. 2385 and 2386.	2250 1600 3250 2850 3650 3750 2400 3250 2950	2600 1850 3750 3300 4200 4300 2800 3750 3400	680 460 1000 850 1150 1150 760 1000 910	610 410 900 760 1050 1050 680 910 820
P-1, 3, 5 P-1 P-4 P-6 P-7 P-8, 10 P-8, 10 P-11 P-12	{2408, 2411 to 2413, 2416 to 2418, 2423, 2425 to 2435,} 2437 to 2452, 2459 and 2460 2400, 2403 to 2407 and 2415 2401, 2402, 2409, 2410, 2414, 2419, 2420, 2422, 2424 and 2436 2453, 2454 and 2458 2476 and 2477 2461 to 2474, 2478 to 2483 2475, 2484 to 2491 3100 to 3109 3120 to 3129	3050 3100 3450 3750 3800 4000 4150 3200 4400	3500 3550 4000 4300 4350 4600 4800 3700 5050	860 890 1000 1100 1150 1200 1250 900 1250	770 790 860 970 1050 1050 1150 800
C-5,8,9,10,26 to 29 C-15, 32 C-17 C-18 C-19 TW-1 TW-2, 3 TW-4, 6 TW-8	2513 to 2599, 2624 to 2860, 3440 to 3469. 2500, 2505 to 2507. 2510 and 2511 3400 to 3409. 3410 to 3426. 2900 to 2913. 2932 to 2952. 2926 to 2931 and 2957. 2914 to 2923.	3950 2550 3150 3650 3800 3050 2400 2300 3200	4600 2900 3600 4200 4350 3500 2800 2650 3900	1300 800 1000 1150 1200 950 740 690 1050	1150 720 920 1050 1050 850 670 620 950
Mk-11	3029. 3025, 3036, 3052 and 3057. 3000 to 3003. 3201 to 3240. 3241 to 3277. 3300 to 3324. 3295. 3297 and 3298.	2400 2500 2800 4650 5150 5550 4250 4100	2800 2900 3250 5400 5850 6350 4900 4700	630 630 800 1500 1600 1750 1350 1300	550 550 710 1350 1450 1600 1300 1200
F-4, 5 AM-2 MM-3 AC-1, 2, 3 AC-4, 5	3600 to 3652 3653 to 3667 3668 to 3769 3900 to 3911 3930 and 3931 4000 to 4048 4100 to 4125 3800 to 3811, 4126 to 4294	5800 6600 7000 6600 7650 8000 10400 11000	6700 7600 8000 7550 8750 9150 11900 12500	1900 2100 2350 2050 2400 2550 3150 3300	1700 1900 1900 1850 2200 2300 2950 3100
GS-1, 2 GS-3, 4, 5, 6	4300 to 4376. 4385 to 4390. 4400 to 4415. 4416 to 4469. 5000 to 5048.	5750 5800 6100 6300 7900	6600 6650 7000 7200 8000	1700 1800 1750 1800 2600	1500 1600 1550 1600 2100
Empty and	Less than 45 Ms. 45 Ms to 55 Ms More than 55 Ms	6 3 0	6 3 0	3 3 0	3 3 0

RULE 10 (J). Slow boards to left of track:

 Westward MP	Reading
264.70	60-40
286.42	40-30
312.50	50-35

Oval slow boards with the words "APPROACH CIRCUIT" above the figures "40-20" indicate the speed that must not be exceeded passing Approach Circuit sign on signal case 1500 feet in approach to Signals P-2608, 2676 and 2693. Trains must approach these signals in accordance with automatic signal indications received.

RULE 14 (e). As specified below, — — — — will be indication that flagman may return from east as prescribed by Rule 99:

Surf...... Trains on Lompoc Branch.

RULE 21 (C). Engines of passenger trains may display indicators from San Luis Obispo passenger station to roundhouse. They must be removed on arrival delivery track at roundhouse.

RULE 83. Identification may be made eastward between San Luis Obispo and Hadley, and westward between Santa Barbara and West Santa Barbara, to be applied at the end of double track. Trains approaching each other between these points must reduce speed sufficiently to permit identification, and Rule 14 (k) will apply.

RULE 83 (A). Only trains originating or terminating will register at Guadalupe.

RULE 93. Yard limits in which the provisions of Rule 93 will apply are established at the following stations:

West MP		East MP
249.6	San Luis Obispo	254.0
275.2	Guadalupe	277.3
301.8	Suri	303 5
	" (Lompoc Branch)	303.8
369.2	Santa Barbara	373.3
310.6	Lompoc	316.7

RULE 99. Army will do switching at Camp Cooke. SP crews will protect.

RULE 99 (C), Will apply on Lompoc-White Hills Branches.

RULE 103 (A). Movements over H St. crossing, Lompoc, must be protected by member of crew.

RULE 104. The normal position of rigid switches at junctions is as follows:

SurfMiddle track, for Lompoc-White Hills Branch. White Hills Jct....White Hills Branch, for Lompoc-Surf line.

RULE 221. Trains must obtain clearance before leaving Lompoc only when operator is on duty.

Train-order office Santa Barbara is located at freight station. Crews of westward passenger trains will receive orders at train-order office and deliver them to relieving crews at passenger station.

RULE 282. Exceptions: Signal without number plate, located at MP 262.18 displaying indication as illustrated by Rule 282, Fig. 1, governing the approach to 10 degree curve three-fourths mile in advance of this signal requires speed to be restricted to 30 MPH for passenger trains, and 25 MPH for all other trains on the 10 degree curve. Signal does not govern movement for balance of the block.

RULE 510. The following block signals equipped with triangular number plate displaying the letter "P" have included in their control limits some special protective device:

Eastward Signal	Protection	Westward Signal
P-2588 P-2608	Spring switch, end double track, Hadley	P-2589
	Flood detector, second Villa Creek bridge, Tiber MP 261.37.	P-2623
P-2736	Collision detector, Oso Flaco underpass, MP 274.06	P-2747
P-2846	Mud slide detector fence, MP 284.6	P-2851
P-2940	Fire detector, Los Alamos bridge, Narlon	P-2953
P-3082	Fire detector, Honda Canon bridge, Honda	P-3097
P-3188	Fire detector, Jalama Canon bridge, Jalama	P-3207
P-3252) P-3254	Spring switch, east end siding, Concepcion	P-3253
P-3356	Fire detector, Alegria Canon bridge, Sacate	P-3373
P-3368 P-3686	Fire detector, Gaviota Canon bridge, Gaviota Spring switch, end double track, West Santa	P-3389
MANAGE STATE	Barbara	P-3687

	RULE 516. Overlap posts:
	Grover
1	Callender Affecting eastward trains.
	Devon Affecting eastward and westward trains.

RULE 535. SPRING SWITCHES

Spring switches equipped with facing point locks are located as follows, and speed indicated must not be exceeded while trailing through them:

Location .	Normal Positio	n MPH
West Santa BarbaraEnd	double track. Westward track. end siding. Main track. double track. Eastward track.	25

Spring switch not equipped with facing point lock is located as follows, and speed indicated must not be exceeded while passing over it in facing movement, or in trailing through it:

Location Normal Position MPH San Luis Obispo....On west leg of wye.....Engine lead.... 5

Spring derail on west end of turntable lead at San Luis Obispo may be trailed through on westward movement.

RULE 705. LETTER TYPE INDICATORS

Indicators located as follows:

Illuminated Letter		Approaching	Authorizes and requires movement as follows:
M	3010.	Surf	. Proceed on main track to east
S	3010.	Surf	end of siding.
М	3041.	Surf	Proceed on main track to west
S	3041	Surf	.Enter siding.

GENERAL REGULATIONS

RULE 825. When freight trains are tied up in San Luis Obispo yard trainmen will set sufficient hand brakes on the rear of westward trains.

RULE 827. TRAIN INSPECTION

Maximum distance freight trains may run without stopping for inspection is 55 miles, except when conditions are favorable, and in the judgment of conductor and engineer it is safe to do so, may run in either direction between Surf and Santa Barbara, and between San Luis Obispo and Concepcion.

AIR BRAKE RULES

RULE 17. All retainers must be turned up White Hills to

Eastward freight trains of 30 to 50 cars turn up 10 retainers; 51 to 75 cars 15 retainers; and over 75 cars twenty retainers solid just behind engine from end double track West Santa Barbara until train has stopped in Santa Barbara yard, where they must be turned down. Trains reduce speed to 20 MPH approaching West Santa Barbara to enable trainmen to turn up retainers.

RULE 24. Road test must be made before leaving White Hills as prescribed by this rule.

PASSENGER TRAINS

RULE 38. Will apply at San Luis Obispo and Santa Barbara when car men not on duty. At Santa Barbara engineers will use hand, instead of steam whistle signals. Trainmen will place themselves in position to relay signals to the best advantage.

MISCELLANEOUS

1. Water supply at Gaviota and Lompoc for emergency use only. Engines take only sufficient water at Guadalupe to make San Luis Obispo or Surf.

10. Engines listed must not operate on tracks shown below:
Class of Engine Restricted Tracks

Mk-F-AC-AM-MM-Mt-GS-SP.	San Luis ObispoVegetable spur.
1-10, 1, A	San Luis Obispo. Vegetable spur. Surf Short leg of wye. Goleta

REGINES FOR WHICH NO SATING IS SHOWN IN THE PATING OF BUGINES SARIL WOLLD PROPERTY TO OFFICE AND THE PATING AND AUTHORITY OF SUPERINTENDENT.

GUADALUPE SUBDIVISION

RATING OF ENGINES-In Ms of 1000 lbs. Back of Tender.

NOMINAL CLASS	ENGINE NUMBERS	San Luis Obispo and Santa Barbara Surf to MP 304	MP 304 and Lompoc	poe to Wh	The Court Mark of the Court of
DES-1, 2, 3, 4, 5, 6, 7 DES-100 to 107 E-23 M-4 M-6, 8 M-9, 11 M-11	1000 to 1022. 1300 to 1395. 1500 and 1502. 1617 to 1713. 1721 to 1803, 1823 to 1825. 1804 to 1822, 1826 to 1831 and 1836. 1832 to 1835.	1000 1600 1300 1750 2150 2250 2300	2000 2350 2500 2600	490 600 650 680	CHANDARY CHANGE ON VALUE OF THE CONTROL OF THE CONT
T-1 T-8, 9 T-23 T-26 T-28, 31 T-32, 40 T-36 T-37 T-57, 58	2242 to 2271. 2161, 2174 and 2178. 2301 to 2310. 2283 to 2299. 2311 to 2362. 2363 to 2384. 2103. 2105 and 2106. 2385 and 2386.	1500 1050 2200 1900 2500 2550 1650 2200 2000	1700 1200 2450 2150 2750 2800 1850 2450 2250	420 260 620 520 700 *720 480 630 570	THE STATE OF THE S
P-1, 3, 5 P-1 P-4 P-6 P-7 P-8, 10 P-11 P-12	(2408, 2411 to 2413, 2416 to 2418, 2423, 2425 to 2435,) 2437 to 2452, 2459 and 2460 2400, 2403 to 2407 and 2415	2000 2050 2400 2500 2550 2650 2900 2100 2900			
C-5, 8, 9, 10, 26 to 29 C-15, 32 C-17 C-18 C-19 FW-1 FW-2, 3 FW-4, 6 FW-8	2513 to 2599, 2624 to 2860, 3440 to 3469. 2500, 2505 to 2507. 2510 and 2511. 3400 to 3409. 3410 to 3426. 2900 to 2913. 2932 to 2952. 2926 to 2931 and 2957. 2914 to 2923.	2700 1700 2150 2500 2600 2050 1650 1550 2250	3000 1900 2400 2800 2900 2300 1850 1750 2550	780 510 660 750 770 600 460 430 660	
A-3 A-3 Mk-2, 4 Mk-5, 6 Mk-7, 8, 9 Mk-10 Mk-11	3029 3025, 3036, 3052 and 3057 3000 to 3003 3201 to 3240 3241 to 3277 3300 to 3324 3295 3297 and 3298	1550 1700 . 1850 3200 3500 3750 2900 2800			
F-1 F-3, 5 F-4, 5 AM-2 MM-3 AC-1, 2, 3 AC-4, 5 AC-6 to 12	3600 to 3652. 3653 to 3667. 3668 to 3769. 3900 to 3911. 3930 and 3931. 4000 to 4048. 4100 to 4125. 3800 to 3811, 4126 to 4294.	3900 4500 4750 4450 5200 5450 6900 7300			Chronell Type and a cold years deather the cold and a c
Mt-1, 3, 4, 5 Mt-2 SS-1, 2 SS-3, 4, 5, 6 SP-1, 2, 3	4300 to 4376. 4385 to 4390. 4400 to 4415. 4416 to 4469. 5000 to 5048.	4000 3900 4200 4350 5300			
Allowance for Empty and Inderloaded Cars	(Less than 45 Ms	6 3 0			

*Exception: Eng. 2371 not permitted on this branch.

DIVISION MILEAGE

DIVISION I	MILEAGE		
First Main San Francisco 3rd St. to Santa Barbara		365.07	
End Western Division to San Jose	C. P. Ry 1.51 S. P. R. R. Co. 0.71	2.22	
End Western Division to Santa Clara	(S. P. Co 1.24 (S. P. R. R. Co 04	1.28	
End Western Division to Redwood Junction. College Park to San Jose	C. P. RyS. P. Co	1.37 1.31	
Total First Main Track	*************	371.25	
Second Mai			
Nan Francisco to Santa Barbara	S. P. R. R. Co. 66.86 S. P. Co. 10.37	77.23	
Redwood Jet. to Sweeney	.C. P. Ry	1.32	
Total Second Main Track Total 1st and 2nd Main Track		78.55	449.80

Branches	
San Bruno to Bernal	9.81
$\begin{array}{ll} \text{Baden to San Bruno via South San Francisco} \left\{ \begin{matrix} \text{S. P. R. R. Co.} & 1.60 \\ \text{S. P. Co.} & 1.29 \end{matrix} \right. \\ \end{array}$	2.89
California Ave. to Vasona Junction S. P. R. R. Co. 0.01 S. P. Co. 16.25	16.27
San Jose to Los Gatos S. P. Co.	8.85
Mympia to Santa Cruz S. P. Co S. P. Co	9.14
Lick to Alamitos S. P. R. R. Co.	3.83
Hanta Cruz to Davenport S. P. R. R. Co.	11.91
Watsonville Junction to Santa Cruz S. P. R. R. Co	20.19 19.60
	2.82
Surf to White Hills. S. P. R. R. Co. 10.35 S. P. R. R. Co. 3.96	14.31

Total Branches	130.51
Total All Tracks Coast Division	580.31

SPEED TABLE

		TEED TABLE	
	TIME		MILES
	MILE		HOUR
	36" 37"		97.3
	38" 39"		94.7 92.3
	40"		90
	41"	*********	87.8
	42" 43"		85.7 83.7
	44" 45"		81.8 80
	46"	***********	78.3
	47"		76.6
	48" 49"		75 73.5
	50"		72
	51" 52"		70.6 69.2
	53"		67.9
١	54" 55"		66.6
	56"		64.2
	57" 58"		63.1 62
	59"		61
	1′ 00″		60
	1' 01" 1' 02"		59 58
	1' 03" 1' 04"		57.1
	1' 05"		56.2 55.3
	1' 06"		54.5
	1' 07" 1' 08"		53.7 52.9
	1' 09" 1' 10"		52.1 51.4
	1' 11"		50.7
	1' 12"		50
	1' 13" 1' 14"	 	49.3 48.6
	1' 15"		48
	1' 16" 1' 17"		47.3 46.7
	1' 18"		46
	1' 19" 1' 20"		45.5 45
	1' 25"		42.3
	1' 30" 1' 35"		40 37.9
	1' 40"		36
1	1' 45" 1' 50"		34.3
	1' 55"		31.3
1	2' 00" 2' 15"		30 26.6
1	2' 30"		24
1	2' 45" 3' 00"		21.8 20
1	3' 30"		17.1
1	4' 00" 5' 00"		15 12
1	6' 00"		10
	7' 00" 7' 30"		8.6
	8' 00"		7.5
L	10' 00"		6

