

# SOUTHERN PACIFIC COMPANY

(PACIFIC LINES).

## TIME TABLE

FOR THE

## SAN JOAQUIN DIVISION

# 158

*Effective February 20, 1938, San Joaquin Division assumed jurisdiction of operation and maintenance of narrow gauge line between Keeler and Benton, formerly Salt Lake Division territory. Ballance of narrow gauge between Benton and Mina abandoned.*



To Take Effect Sunday, February 13, 1938, at 12:01 A. M.

To January 15, 1939

PACIFIC STANDARD TIME (120th MERIDIAN)

SEE PAGE N°5

For the government and information of employees only.

A. T. MERCIER, Appointed Vice President  
L. B. McDONALD, General Manager. April 1, 1938  
April 1, 1938

W. B. KIRKLAND,  
Superintendent of Transportation.

L. U. MORRIS,  
Assistant General Manager.

J. D. BRENNAN,  
Superintendent.



FRESNO SUBDIVISION

EASTWARD										Time Table No. 158	WESTWARD									
SECOND CLASS		FIRST CLASS								Distance from San Francisco	February 13, 1938	Distance from Bakersfield	FIRST CLASS							THIRD CLASS
782	400	56	346	52	12	58	60	26	25		59		55	345	5	51	57	783		
Freight	Freight	Tehachapi	Motor	San Joaquin	Santa Fe Motor	Sequoia	West Coast	Owl	Owl	West Coast	Tehachapi	Motor	Santa Fe Motor	San Joaquin	Sequoia	Freight				
Leave Daily	Leave Daily	Leave Daily	Leave Daily	Leave Daily	Leave Daily	Leave Daily	Leave Daily	Leave Daily	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily				
WOTYP Yard									201.8	FRESNO YARD 1.4	111.1									
									203.2	F. T. Co. Crossing 2.3	109.7									
BKWOTYP Yard	1.55 PM	4.20 AM	8.00 PM		1.50 PM		6.50 AM	12.30 AM	205.5	TO-R FRESNO 3.6	107.4	s 2.40 AM	s 4.00 AM	s 7.30 AM		s 3.55 PM s 10.00 PM 1.20 PM				
I P	2.05	4.30	8.10		1.59		7.00	12.40	209.1	TO CALWA TOWER A. T. & S. F. Crossing 1.3	103.8	2.30	3.50	7.20		3.45 9.48 1.10				
No Siding P			f				s		210.4	MALAGA 4.7	102.5			f						
118 P	2.15	4.40	f 8.20				s 7.08		215.1	TO FOWLER 5.6	97.8			s 7.08		3.36 f 9.39 12.57				
125 Yard WP	2.25	4.50	s 8.30		f 2.12		s 7.20	12.53	220.7	TO SELMA 4.9	92.2	f 2.14	3.34	s 6.58		f 3.27 s 9.31 12.47				
100 Yard WP	2.35	5.00	s 8.40		f 2.18		s 7.30	12.59	225.6	TO KINGSBURG 5.7	87.3	2.05	3.27	s 6.48		f 3.17 s 9.22 12.37				
106 P	2.44	5.09	f 8.48		2.24		7.37	1.06	231.3	TRAVER 2.4	81.6	1.58	3.21	f 6.38		3.09 9.13 12.28				
60 P			8.51				7.40	1.09	233.7	CROSS 5.4	79.2	1.55	3.18	6.35		3.06 9.10				
94 KWOTYP Yard	2.56	5.21	s 9.00		s 2.41		s 7.47 AM	1.16	239.1	TO-R GOSHEN JCT. 6.5	73.8	1.48	3.12	s 6.25		s 2.56 9.00 PM 12.16				
59 P	3.06	5.31	f 9.13		2.48			1.24	245.6	TAGUS 4.1	67.3	1.40	3.05	6.02		2.48 12.06 PM				
									249.7	TO TULARE TOWER A. T. & S. F. Crossing 0.3	63.2									
89 Yard WP	3.15	5.40	s 9.20		s 3.00			1.30	250.0	TULARE 5.8	62.9	s 1.30	2.58	s 5.40		s 2.43 11.57 AM				
59 P	3.25	5.58	9.40		3.07			1.39	255.8	OCTOL 4.6	57.1	1.16	2.51	5.22		2.33 11.47				
83 WP	3.42	6.05	s 9.55		f 3.13			1.45	260.4	TO TIPTON 6.4	52.5	1.11	2.46	s 5.12		2.28 11.40				
94 P	3.52	6.15	s 10.05		3.20			1.52	266.8	TO PIXLEY 5.6	46.1	1.04	2.39	s 5.02		2.21 11.22				
83 P			f 10.15		3.26			1.59	272.4	TO EARLIMART 4.1	40.5	12.57	2.33	s 4.52		2.15				
59 P	4.07	6.30	10.21		3.31			2.04	276.5	RADNOR 4.2	36.4	12.52	2.28	4.42		2.11 11.07				
82 Yard WP	4.14	6.37	s 10.30		s 3.39			2.09	280.7	TO DELANO 6.3	32.2	f 12.47	2.23	s 4.37		s 2.06 11.00				
59 P	4.24	6.47	s 10.40		3.47			2.16	287.0	TO Mc FARLAND 5.6	25.9	12.40	2.16	s 4.26		1.58 10.50				
79 KWTP	4.35	7.00	f 10.49	10.32 PM	3.54	9.12 AM		2.26	292.6	TO-R FAMOSO 3.3	20.3	12.34	2.09	f 4.15	s 7.00 AM s 12.51 PM	1.52 10.40				
59 P	4.40	7.05	10.53	f 10.38	3.58	9.16		2.30	295.9	SLATER 4.6	17.0	12.30	2.05	4.10		12.47 1.48 10.35				
82 P	4.47	7.12	10.59	f 10.44	4.05	9.22		2.35	300.5	LERDO 2.5	12.4	12.25	2.00	4.05	f 6.51	12.42 1.43 10.28				
90 P	4.51	7.16	11.02	10.47	4.08	9.26		2.38	303.0	PROSPERO 2.8	9.9	12.22	1.57	4.02	6.48	12.39 1.40 10.24				
59 P	4.56	7.21	11.06	f 10.51	4.11	9.30		2.41	305.8	SACO 2.8	7.1			3.58	6.44	12.36 1.37 10.19				
80 P	5.01	7.26	11.10	10.55	4.15	s 9.36 AM		2.45	308.6	R OIL JCT. 2.5	4.3	12.15	1.50	3.55	f 6.40	12.32 PM 1.33 10.14				
No Siding P									311.1	NOME 1.8	1.8									
Yard BKWOTYP	5.15 PM	7.40 AM	s 11.20 PM	s 11.05 PM	s 4.25 PM			s 2.55 AM	312.9	TO-R BAKERSFIELD 1.1	0.0	12.05 AM	1.40 AM	3.45 AM	6.30 AM	1.23 PM 10.00 AM				
	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily				Leave Daily	Leave Daily	Leave Daily	Leave Daily	Leave Daily				
	(3.20) 32.22	(3.20) 32.22	(3.20) 32.22	(0.33) 36.90	(2.35) 41.57	(0.24) 35.83	(0.57) 35.36	(2.25) 44.44	(2.35) 41.57	.....Time over District.....		(2.35) 41.57	(2.20) 46.02	(3.45) 28.64	(0.30) 40.60	(0.19) 50.52	(2.32) 42.38	(1.00) 33.60	(3.20) 32.22	

Schedule time and train orders for eastward trains at Calwa Tower apply at end of double track, 360 feet west of the tower. Rule S-72 Exception; No. 56 is superior to No. 57.  
 Schedule time and train orders for eastward trains at Famoso apply at junction switch of Porterville Line.  
 Schedule time and train orders for trains at Oil Jct. apply at crossover switch just west of Signal 3086.

ADDITIONAL STATIONS:

Muscatel.....	200.2
Calwa.....	208.3
Winedale (Spur).....	222.8
Midvalley (Spur).....	232.4
Affac (Spur).....	232.3
Quail (Spur).....	233.7
Vinland (Spur).....	284.5
Dow (Spur).....	299.6

ADDITIONAL FLAG STOPS TO RECEIVE OR DISCHARGE REVENUE PASSENGERS

Train	At	Receive or Discharge	To (or beyond)	From (or beyond)	Frequency
60	Selma	Discharge		Stockton	Daily
60	Tulare	Discharge		Stockton	Daily
60	Delano	Discharge		Stockton	Daily
56	Any Station	Discharge		Delano	Daily
55	Any Station	Discharge		Los Angeles	Daily
52	Any Station	Discharge		Ogden	Daily
26	Delano	Receive & Discharge	Los Angeles	Tracy	Daily
59	Delano	Receive	Stockton		Daily
59	Tulare	Receive	Stockton		Daily

**EASTWARD**

**FRESNO SUBDIVISION**

**WESTWARD**

Capacity of Sidings in Car Lengths	FIRST CLASS				Distance from San Francisco	Time Table No. 158 February 13, 1938	Distance from Famoso	FIRST CLASS			
	346	348	12	58				345	5	347	57
	Motor	Motor	Santa Fe Motor	Sequoia				Motor	Santa Fe Motor	Motor	Sequoia
	Leave Daily	Leave Daily	Leave Daily	Leave Daily				Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily
BKWOTYP Yard	7.15 PM				205.5	TO-R FRESNO	104.3	s 10.20 AM			
I					207.0	1.5 TO SUNMAID TOWER	102.8				
	7.26				208.5	A. T. & S. F. Crossing 1.5 BLOSSOMA	101.3	f 10.08			
15 P	7.30				211.8	3.3 BUTLER	98.0	f 10.03			
PY					213.0	1.2 LOCANS	96.8	f			
58	7.34				214.5	1.5 IVESTA	95.3	f 9.59			
77 P	f 7.36				215.9	1.4 CLOTHO	93.9	f 9.56			
90 Yard WP	s 7.44				219.8	3.9 TO SANGER	90.0	s 9.50			
8 P	f 7.48				222.8	3.0 TARN	87.0	f 9.42			
P	f 7.52				225.3	2.5 FARGO	84.5	f 9.38			
	f 7.56				227.9	2.6 LACJAO	81.9	f 9.34			
					228.0	0.1 A. T. & S. F. Crossing (Stop)	81.8				
85 Yard P	s 8.02				229.9	1.9 TO REEDLEY	79.9	s 9.28			
63 Yard WP	s 8.11				235.0	5.1 TO DINUBA	74.8	s 9.18			
P	f				237.2	2.2 SMYRNA	72.6	f			
17 P	f 8.18				239.6	2.4 MONSON	70.2	f 9.08			
					243.6	4.0 A. T. & S. F. Crossing (Stop)	66.2				
18 P	8.30				246.4	2.8 TAURUSA	63.4	f 8.56			
14	s 8.37				249.4	3.0 TO IVANHOE	60.4	s 8.51			
P	f 8.41				252.2	2.8 ROOHE	57.6	f 8.46			
18 P	8.43				253.1	0.9 CAPLIN	56.7	f 8.44			
74 KWYP Yard	s 8.55	3.45 PM		8.35 AM	257.4	4.3 TO-R EXETER	52.4	s 8.35	s 1.45 PM	s 7.50 PM	
8	f 9.00	3.50		8.45	260.5	3.1 BURR	49.3	8.25	1.39	7.44	
124 P Yard	s 9.08	s 3.58		s 8.53	264.3	3.8 TO LINDSAY	45.5	s 8.20	s 1.33	s 7.38	
32 P	s 9.15	f 4.05		s 9.00	268.6	4.3 TO STRATHMORE	41.2	s 8.10	f 1.23	f 7.28	
7	f				270.9	2.3 ZANTE	38.9				
14 P	s 9.30	s 4.15		s 9.10	274.4	3.5 PORTERVILLE	35.4	s 8.00	s 1.15	s 7.20	
42 BKWYP Yard	9.33	4.30 PM		9.25 AM	274.8	0.4 TO-R PORTERVILLE-OLIVE ST.	35.0	7.57	1.05 PM	7.10 PM	
13	9.36				276.5	1.7 PONOA	33.3	7.54			
25	f				278.0	1.5 LOIS	31.8	f			
17 P	s 9.46				282.6	4.6 TO TERRA BELLA	27.2	f 7.45			
69 KP	s 9.55		8.38 AM		287.1	4.5 TO-R DUOOR	22.7	f 7.38	s 1.27 PM		
17 P	f 10.00		8.43		290.0	2.9 ORRIS	19.8	f 7.32	1.22		
Spur	f		f		291.5	1.5 VESTAL	18.3	f	f		
67 YP	f 10.07		f 8.50		294.9	3.4 RICHGROVE	14.9	f 7.25	f 1.15		
18 P	f 10.13		f 8.56		299.0	4.1 JASMIN	10.8	f 7.19	f 1.09		
4 KWTP	s 10.30 PM		s 9.11 AM		309.8	10.8 TO-R FAMOSO	0.0	7.03 AM	12.54 PM		
	Arrive Daily	Arrive Daily	Arrive Daily	Arrive Daily		(194.3)		Leave Daily	Leave Daily	Leave Daily	Leave Daily

(3.15) 32.09 (0.45) 23.20 (0.33) 41.27 (0.50) 20.88

.....Time over District..... (3.17) (0.33) (0.40) (0.40)  
.....Average Speed per Hour..... 31.76 41.27 26.10 26.10

**ADDITIONAL STATIONS:**

Goldleaf.....	209.8	Efoo (Spur).....	227.6
Eshel (Spur).....	210.6	Dorsey (Spur).....	250.8
Roka.....	221.0	Lort (Spur).....	254.0
Rusconi (Spur).....	221.8	Vance.....	262.8
Uva (Spur).....	227.1	Stout (Spur).....	265.8
		Lisko (Spur).....	272.2
		Quality.....	295.8

No. 347 and No. 57 head in at east end of siding at Exeter and use siding to junction of Visalia Branch

**FRESNO SUBDIVISION**

Capacity of Sidings in Car Lengths	EASTWARD		Distance from San Francisco	Time Table No. 158 February 13, 1938	Distance from Clavicle	WESTWARD	
	Success Branch					STATIONS	
	STATIONS						
Yard 42 BKWYP			274.8	TO-R PORTERVILLE-OLIVE ST.	13.3		
			275.6	0.8 A. T. & S. F. CROSSING (Stop)	12.5		
			278.6	3.0 PERNU JOT.	9.5		
15			280.0	1.4 WORTH	8.1		
26			282.4	2.4 SUCCESS	5.7		
			288.1	5.7 OLAVIOLE	0.0		
				(13.3)			

.....Time over District.....  
.....Average speed per hour.....

Capacity of Sidings in Car Lengths	EASTWARD		Distance from San Francisco	Time Table No. 158 February 13, 1938	Distance from Pernu	WESTWARD	
	Pernu Branch					STATIONS	
	STATIONS						
Spur			278.6	PERNU JOT.	1.3		
Spur			279.3	0.7 TANDY	0.6		
			279.9	0.6 PERNU	0.0		
				(1.3)			

.....Time over District.....  
.....Average speed per hour.....

Capacity of Sidings in Car Lengths	EASTWARD		Distance from San Francisco	Time Table No. 158 February 13, 1938	Distance from Jovista	WESTWARD	
	Richgrove Branch					STATIONS	
	STATIONS						
72			294.9	RICHGROVE	4.1		
50			297.6	2.7 TROCHA	1.4		
18			299.0	1.4 JOVISTA	0.0		
				(4.1)			

.....Time over District.....  
.....Average speed per hour.....







# MOJAVE SUBDIVISION

EASTWARD									Distance from San Francisco	WESTWARD								
SECOND CLASS				FIRST CLASS				Distance from Burbank Jct.		FIRST CLASS				THIRD CLASS				
Capacity of Sidings in Car Lengths	816 Freight Leave Daily	814 Freight Leave Daily	810 Freight Leave Daily	52 San Joaquin Leave Daily	60 West Coast Leave Daily	26 Owl Leave Daily	56 Tehachapi Leave Daily			51 San Joaquin Arrive Daily	25 Owl Arrive Daily	59 West Coast Arrive Daily	55 Tehachapi Arrive Daily	811 Freight Arrive Daily	813 Freight Arrive Daily	815 Freight Arrive Daily		
BKWOTYP Yard	11.25 PM	4.50 PM	4.40 AM	6.48 PM	5.25 AM	5.05 AM	2.30 AM	380.7	TO-R MOJAVE	90.9	s 11.03 AM	s 9.25 PM	s 11.06 PM	s 12.40 AM	5.05 AM	1.40 PM	10.30 PM	
84 P	11.35	5.00	4.50	6.54	5.31	5.11	2.36	384.8	FLETA	86.8	10.57	9.19	11.00	12.34	4.50	1.25	10.16	
85 P	11.40	5.05	5.00	6.57	5.35	5.15	2.40	387.3	GLOSTER	84.3	10.54	9.15	10.56	12.30	4.46	1.15	10.11	
81 P	11.46	5.11	5.06	7.01	5.40	5.20	2.45	390.4	ANSEL	81.2	10.50	9.10	10.51	12.25	4.41	1.06	10.03	
80 P	11.53 PM	5.18	5.13	7.06	5.46	5.26	f 2.52	394.3	ROSAMOND	77.3	10.45	9.04	10.45	f 12.19	4.35	12.58	9.56	
50 P	12.10 AM	5.28	5.23	7.12	5.54	5.34	3.00	399.9	OBAN	71.7	10.38	8.56	10.37	12.10	4.26	12.48	9.46	
70 KWP Yard	12.30	5.45	5.42	s 7.20	6.02	5.42	s 3.11	405.5	TO-R LANCASTER	66.1	s 10.31	f 8.48	10.28	s 12.01 AM	4.17	12.38	9.36	
50 P	12.43	6.00	6.08	7.25	6.08	5.48	3.18	409.8	DENIS	61.8	10.25	8.40	10.18	11.47 PM	4.10	12.29	9.28	
68 P	12.51	6.08	6.28	f 7.30	6.13	5.53	s 3.27	413.8	TO PALMDALE	57.8	f 10.20	8.35	10.13	s 11.42	4.04	12.21	9.20	
WOY P	12.58	6.15	6.35	7.33	6.17	5.57	3.32	416.3	HAROLD	55.3	10.16	8.31	10.09	11.36	3.57	12.14 PM	9.13	
90 P	1.20	6.45	7.00	7.43	6.29	6.09	3.45	420.5	TO VINCENT	51.1	10.07	8.22	10.00	11.27	3.45	11.59 AM	9.00	
East 75 Yard	1.34	6.59	7.19	7.53	6.39	6.19	3.56	425.0	PARIS	46.6	9.57	8.11	9.49	11.17	3.22	11.32	8.35	
West 81 YP									ACTON	45.5				f 11.14				
84 P							f 4.00	426.1	RAVENNA	42.6	9.48	8.02	9.40	f 11.06	3.09	11.19	8.02	
32 P	1.50	7.21	7.41	8.02	6.48	6.28	f 4.09	429.0	RUSS	37.0	9.36	7.47	9.26	10.54	2.52	11.02	7.36	
95 WP	2.15	7.36	7.58	8.14	7.00	6.40	4.22	434.6	TO LANG	32.8	9.27	7.38	9.17	f 10.45	2.39	10.49	7.19	
82 P	2.39	8.05	8.11	8.23	7.09	6.49	f 4.33	438.8	HUMPHREYS	28.5	9.18	7.28	9.08	f 10.36	2.27	10.37	7.07	
101 WP	2.53	8.18	8.24	8.32	7.18	6.58	4.44	443.1	HONBY	24.7	9.10	7.19	8.59	10.27	2.16	10.26	6.56	
85 P	3.05	8.30	8.36	8.41	7.27	7.07	4.54	446.9	TO-R SAUGUS	21.0	f 9.02	s 7.10	8.50	s 10.18	2.05	10.15	6.45	
81 P	3.20	8.50	9.02	s 8.50	7.35	f 7.15	s 5.05	450.6	NEWHALL	18.6				f				
W 78 Yard									ELAYON	17.9	8.56	7.04	8.44	10.06				
E71BKWOYP									WALTZ JCT.	17.2								
63 P									TUNNEL	15.0	8.47	6.57	8.38	10.00	1.37	9.49	6.20	
80				8.58	7.40	7.20	5.10	453.7	SYLMAR	12.4	8.42	6.52	8.34	9.55	1.27	9.40	6.12	
									TO SAN FERNANDO	9.8	s 8.38	6.48	8.30	s 9.50	1.14	9.30	6.05	
58 P	3.48	9.26	9.30	9.05	7.49	7.31	5.21	456.6	PACOIMA	8.2	8.35	6.45	8.27	9.44	12.59	9.20	5.50	
83 P	3.58	9.36	9.40	9.09	7.53	7.35	5.26	459.2	WAHOO	6.0								
Yard 105	4.10	9.50	9.55	s 9.14	7.58	7.41	s 5.33	461.8	ROSCOE	3.7	8.29	6.39	8.21	9.37	12.47	9.10	5.40	
WOTP	4.15	9.54	10.01	9.17	8.01	7.45	f 5.38	463.4	TO BURBANK JCT.	0.0	8.23 AM	6.33 PM	8.16 PM	9.31 PM	12.35 AM	9.00 AM	5.25 PM	
85 P									90.9		Leave Daily	Leave Daily	Leave Daily	Leave Daily	Leave Daily	Leave Daily	Leave Daily	
39 P									Time over District.....		(2.40)	(2.52)	(2.50)	(3.09)	(4.30)	(4.40)	(5.05)	
96 P	4.26	10.05	10.16	9.25	8.07	7.52	f 5.46	467.9	Average Speed per Hour.....		34.80	31.70	32.08	28.85	20.20	19.46	17.88	
52 PI	4.38 AM	10.17 PM	10.30 AM	9.31 PM	8.13 AM	7.59 AM	5.54 AM	471.6										

Schedule time and train orders for first class trains at Saugus apply at initial switch Middle Siding at which opposing trains enter Siding. See special rule 105.  
 Schedule time and train orders at Burbank Jct. apply at End of double track.  
 Intermediate Spur: Consolidated Rock Co. M.P. 465.1. Capacity 10 cars.

*Effective with this Timetable - Mojave Subdivision  
 Extended from Saugus to Burbank Junction.*

ADDITIONAL FLAG STOPS TO RECEIVE OR DISCHARGE REVENUE PASSENGERS					
Train	At	Receive or Discharge	To (or beyond)	From (or beyond)	Frequency
25	Lancaster	Receive	Glendale		Daily
26	Palmdale	Receive	Glendale		Daily
59	Lancaster	Receive	Stockton		Daily
60	Lancaster	Discharge		Stockton	Daily
25	San Fernando	Receive	Mojave		Daily
59	San Fernando	Receive	Stockton		Daily
59	Saugus	Receive	Stockton		Daily
26	San Fernando	Receive & Discharge	Colton	Fresno	Daily
60	Saugus	Discharge		Stockton	Daily
60	San Fernando	Discharge		Stockton	Daily



FRESNO SUBDIVISION

Capacity of Sidings in Car Lengths	EASTWARD				Distance from San Francisco	Time Table No. 158 February 13, 1938 Kerman and Visalia Branches				Distance from Exeter	WESTWARD			
	FIRST CLASS					FIRST CLASS								
	348 Motor	58 Sequoia	341 Motor	347 Motor		57 Sequoia								
	Leave Daily	Leave Daily	Arrive Daily	Arrive Daily		Arrive Daily	Arrive Daily	Arrive Daily						
48 WYP Yard					193.0	TO-R KERMAN 6.7				70.2				
No Siding					199.7	MC MULLIN 5.4				63.5				
24					205.1	RAISIN CITY 5.6				58.1				
48					210.7	CARUTHERS 6.1				52.5				
21					216.8	CANDO 3.5				46.4				
					220.3	LATON & WESTERN RY. CROSSING (Stop) 2.7				42.9				
47					223.0	HARDWICK 6.1				40.2				
East 40 WYP West 35 Yard		2.00 PM			229.1	TO-R ARMONA 3.1			s 1.50 PM	34.1				
I					232.2	A. T. & S. F. CROSSING 0.3				31.0				
66 BKP Yard		s 2.10			232.5	TO-R HANFORD 1.4			1.40 PM s 3.25 PM	30.7				
Spur					233.9	SHELL 3.7				29.3				
54					237.6	REMNOY 7.7				25.6				
94 WOYP Yard		s 2.35 2.58	7.50 AM		245.3	TO-R GOSHEN JOT. 7.8			s 2.58 2.30	17.9		s 8.45 PM		
41 P Yard		s 3.20	s 8.10		253.1	A.B.S. VISALIA 0.1			s 2.15	10.1		s 8.20		
					253.2	A. T. & S. F. CROSSING Stop 2.0				10.0				
P		3.30	8.20		255.2	AMBLER 2.1			2.02	8.0		8.07		
Spur					257.3	RECTOR 1.7				5.9				
7 P		3.36	8.26		259.0	FARMERSVILLE 1.2			1.56	4.2		8.01		
P		3.38	8.28		260.2	GIANT OAK 3.0			1.53	3.0		7.58		
74 KWYP Yard		s 3.43 PM	s 8.35 AM		263.2	TO-R EXETER 0.0			1.48 PM	0.0		7.53 PM		
		Arrive Daily	Arrive Daily			(70.2)			Leave Daily	Leave Daily	Leave Daily			
		(1.43) 19.86	(0.45) 23.86			Time over District..... Average Speed per Hour.....			(0.10) 20.40	(1.37) 18.98	(0.52) 20.65			

Capacity of Sidings in Car Lengths	EASTWARD				Distance from San Francisco	Time Table No. 158 February 13, 1938 Riverdale Branch				Distance from Hardwick	WESTWARD			
	FIRST CLASS					FIRST CLASS								
	341 Motor	347 Motor	57 Sequoia			341 Motor	347 Motor	57 Sequoia						
	Arrive Daily	Arrive Daily	Arrive Daily			Arrive Daily	Arrive Daily	Arrive Daily			Arrive Daily	Arrive Daily	Arrive Daily	
Y					181.9	INGLE 5.3				42.3				
39					187.2	TRANQUILITY 4.5				37.0				
56					191.7	SAN JOAQUIN 3.3				32.5				
					194.9	CALDWELL 4.1				29.3				
25					199.0	TO HELM 7.2				25.2				
20					206.2	BURRELL 3.2				18.0				
					209.4	BENDER 5.2				14.8				
7					214.6	TO RIVERDALE 2.6				9.6				
Spur 4					217.2	ROBINSON 2.0				7.0				
Spur 3					219.2	HUB 1.8				5.0				
					221.0	LATON & WESTERN RY. CROSSING (Stop) 3.2				3.2				
52 Yard					224.2	HARDWICK (42.3)				0.0				
						Time over District..... Average Speed per Hour.....								

Capacity of Sidings in Car Lengths	EASTWARD				Distance from San Francisco	Time Table No. 158 February 13, 1938 Oil City Branch				Distance from Oil City	WESTWARD			
	FIRST CLASS					FIRST CLASS								
	341 Motor	347 Motor	57 Sequoia			341 Motor	347 Motor	57 Sequoia						
	Arrive Daily	Arrive Daily	Arrive Daily			Arrive Daily	Arrive Daily	Arrive Daily			Arrive Daily	Arrive Daily	Arrive Daily	
					308.6	R OIL JOT. 1.9			5.1					
					310.5	SEGURO 1.1			3.2					
					311.6	MALPHA 2.1			2.1					
					313.7	OIL CITY 0.0			0.0					
						5.1								
						Time over District..... Average speed per hour.....								

Capacity of Sidings in Car Lengths	EASTWARD				Distance from San Francisco	Time Table No. 158 February 13, 1938 Coalinga Branch				Distance from Armona	WESTWARD			
	FIRST CLASS					FIRST CLASS								
	341 Motor	347 Motor	57 Sequoia			341 Motor	347 Motor	57 Sequoia						
	Arrive Daily	Arrive Daily	Arrive Daily			Arrive Daily	Arrive Daily	Arrive Daily			Arrive Daily	Arrive Daily	Arrive Daily	
16 Spur					269.9	ORUMP 1.5				40.8				
71 YP Yard					268.4	TO-R COALINGA 1.7				39.3				
38 P					266.7	ORA 6.7				37.6				
14 P					260.0	TURK 7.3				30.9				
39 P					252.7	TO HURON 6.6				23.6				
48 P					246.1	WESTHAVEN 6.7				17.0				
5 P					239.4	LETHENT 2.9				10.3				
65 YP					236.5	ROSSI 1.1				7.4				
14 Spur					235.4	HEINLEN 1.5				6.3				
57 P					233.9	TO LEMOORE 2.7				4.8				
Spur					231.2	ORION 2.1				2.1				
East 40 WYP West 35 Yard					229.1	TO-R ARMONA 0.0				0.0				
						(40.8)								
						Time over District..... Average Speed per Hour.....								

Note.—Oil Jct. to Oil City operated as part of Bakersfield yard.



FRESNO SUBDIVISION

Capacity of Sidings in Car Lengths	EASTWARD			WESTWARD		
	Time Table No. 158 February 13, 1938			Distance from Friant		
	Clovis Branch			STATIONS		
Yard BKWOTYP		205.5	TO-R FRESNO 1.6	24.4		
I		207.1	FRESNO TOWER A. T. & S. F. CROSSING 2.3	22.8		
Spur		209.4	BARTON 2.2	20.5		
Spur 18		211.6	GRANZ 0.2	18.3		
Spur 44		211.8	MALTERMORO 0.3	18.1		
		212.1	NAVIN 0.8	17.8		
10		212.9	LAS PALMAS 0.3	17.0		
		213.2	FRESNO INTERURBAN RY. CROSSING 0.7	16.7		
No Siding		213.9	VANRIS 1.0	16.0		
27		214.9	TARPEY 1.2	15.0		
17		216.1	MELVIN 1.3	13.8		
37 W		217.4	TO OLOVIS 1.1	12.5		
7		218.5	GLORIETTA 2.4	11.4		
67		220.9	PINEDALE JCT. 2.0	9.0		
38		222.9	GORDON 2.8	7.0		
		225.7	ROCKFIELD 0.3	4.2		
		226.0	GAND 3.9	3.9		
63 WT Yard		229.9	FRIANT	0.0		
				(24.4)		

.....Time over District.....  
.....Average speed per hour.....

FRESNO SUBDIVISION

Capacity of Sidings in Car Lengths	EASTWARD			WESTWARD		
	Time Table No. 158 February 13, 1938			Distance from Olig		
	McKittrick Branch			STATIONS		
KI		313.6	TO-R KERN JOT. 1.7	49.1		
P		315.3	BAKERSFIELD CORRALS 1.4	47.4		
15		316.7	STRADER 2.1	46.0		
43 P		318.8	WIBLE ORCHARD 1.7	43.9		
		320.5	VENOLA 2.1	42.2		
54 YP		322.6	GOSFORD 5.8	40.1		
46		328.4	STEVENS 2.3	34.3		
Spur 3		330.7	STRAND 5.4	32.0		
		336.1	RIO BRAVO 9.3	26.6		
		345.4	KILOWATT 0.9	17.3		
91		346.3	TO BUTTONWILLOW 4.2	16.4		
64		350.5	LOKERN 10.1	12.2		
30 Y		360.6	McKITTRICK 2.1	2.1		
		362.7	OLIG	0.0		
				(49.1)		

.....Time over District.....  
.....Average speed per hour.....

TEHACHAPI SUBDIVISION

Capacity of Sidings in Car Lengths	EASTWARD			WESTWARD		
	Time Table No. 158 February 13, 1938			Distance from Stratford		
	Stratford Branch			STATIONS		
41		244.1	TO STRATFORD 4.2	0.0		
Spur 20		239.9	OUNEO 3.4	4.2		
65 YP		236.5	ROSSI	7.6		
				(7.6)		

.....Time over District.....  
.....Average speed per hour.....

Capacity of Sidings in Car Lengths	EASTWARD			WESTWARD		
	Time Table No. 158 February 13, 1938			Distance from Arvin		
	Arvin Branch			STATIONS		
		316.6	MAGUNDEN 0.3	16.5		
		316.9	ALGOSO 4.2	16.2		
		321.1	HARPERTOWN 3.5	12.0		
		324.6	LAMONT 2.2	8.5		
		326.8	RIBIER 2.0	6.3		
		328.8	DI GIORGIO 1.9	4.3		
		330.7	GIFFIN JCT. 2.4	2.4		
		333.1	ARVIN	0.0		
				(16.5)		

.....Times over District.....  
.....Average speed per hour.....

Additional Stations (PATCH....325.9  
GIFFIN....332.1 (on Spur 1.4 miles from Giffin Jct.)  
VACCARO...334.4 (on spur 1.3 miles from Arvin)



MOJAVE SUBDIVISION

EASTWARD				WESTWARD				
Capacity of Sidings in Car Lengths	SECOND CLASS	FIRST CLASS	Distance from San Francisco	Time Table No. 158 February 13, 1938		Distance from Owenyo	SECOND CLASS	THIRD CLASS
	802	788		789	803			
	Freight	Mixed		Owenyo Branch			Mixed	Freight
	Leave Daily	Leave Daily Ex. Sunday		STATIONS			Arrive Daily Ex. Monday	Arrive Daily
BKWOTYP Yard	4.00PM	1.25AM	380.7	TO-R	MOJAVE 1.3	143.5	s 12.30AM	11.05PM
45	4.04	f 1.29	380.8		CHAFFEE 3.2	142.2	f 12.20	10.55
48	4.11	f 1.36	384.0		OAMBIO 8.9	139.0	f 12.05AM	10.40
48	4.30	f 1.55	392.9		NEURALIA 4.4	130.1	f 11.45PM	10.20
48	4.40	f 2.04	397.3		CINCO 5.2	125.7	f 11.30	10.05
East 48 W West 48	5.00	s 2.19	402.5		OANTIL 2.8	120.5	s 11.15	9.50
Spur 15		f	405.3		GYPSITE 2.2	117.7	f	
39	5.15	f 2.30	407.5		OENEDA 1.0	115.5	f 10.50	9.20
2	5.18	f 2.32	408.5		SALTDAL 3.7	114.5	f 10.45	9.15
East 48 Y West 70	5.30	f 2.40	412.2		GARLOOK 4.2	110.8	f 10.35	9.00
48	5.40	f 2.49	416.4		GOLER 4.1	106.6	f 10.25	8.45
48	5.55	f 3.00	420.5		RAND 7.9	102.5	f 10.15	8.30
48 Yard	6.15PM	s 3.45	428.4	TO-R	SEARLES 4.4	94.6	s 9.55	8.00PM
48		f 3.55	432.8		RADEMA 5.5	90.2	f 9.10	
52		f 4.06	438.3		CODE 8.9	84.7	f 8.55	
48		s 4.28	447.2		INYOKER 4.5	75.8	s 8.35	
Spur 27 W		f 4.38	451.7		LELITER 4.6	71.3	f 8.20	
48		s 4.48	456.3		BROWN 4.4	66.7	s 8.10	
48		f 4.57	460.7		LINNIE 7.6	62.3	f 7.53	
47		s 5.15	468.3		LITTLE LAKE 3.2	54.7	s 7.35	
48 Y		f 5.25	471.5		COSO 4.1	51.5	f 7.25	
48		f 5.35	475.6		SYKES 8.5	47.4	f 7.15	
47 W		f 5.57	484.1		HAIWEE 4.4	38.9	f 6.55	
52		f 6.06	488.5		LOCO 4.8	34.5	f 6.45	
48		f 6.16	493.3		OLANCHA 4.4	29.7	f 6.35	
52		s 6.27	497.7		CARTAGO 4.6	25.3	s 6.25	
52		f 6.37	502.3		MONACHEE 4.0	20.7	f 6.01	
52		f 6.46	506.3		BRIER 2.9	16.7	f 5.54	
		f	509.2		BARTLETT 5.1	13.8	f	
52 W		f 7.04	514.3		DIAZ 4.5	8.7	f 5.40	
East 28 West 52		s 7.40	518.8		LONE PINE 4.2	4.2	s 5.30	
37 KOY Yard		s 7.55AM	523.0	TO-R	OWENYO	0.0		5.15PM
	Arrive Daily	Arrive Daily Ex. Sunday			(143.5)		Leave Daily Ex. Sunday	Leave Daily
	(2.15) 21.73	(6.30) 22.07					(7.15) 19.79	(3.05) 15.85

.....Time over District..... (7.15) (3.05)  
 .....Average speed per hour..... 19.79 15.85

SUNSET RAILWAY COMPANY

Capacity of Sidings in Car Lengths	EASTWARD	Distance from Gosford	Time Table No. 158 February 13, 1938		Distance from Maricopa	WESTWARD
			STATIONS			
50 YP		0.0	R	GOSFORD 3.0	31.9	
14 SP		3.0		BANNISTER 6.5	28.9	
40		9.5		CONNER 4.7	22.4	
41 W		14.2		MILLUX 6.7	17.7	
48		21.9		KYAN 6.5	11.0	
Yard 55 Y		27.4	R	PENTLAND 2.7	4.5	
22 Y		30.1		HAZELTON 1.8	1.8	
Yard 11		31.9	R	MARICOPA	0.0	
				(31.9)		
				.....Time over District.....		
				.....Average speed per hour.....		

Capacity of Sidings in Car Lengths	EASTWARD	Distance from Pentland	Time Table No. 158 February 13, 1938		Distance from Shale	WESTWARD
			STATIONS			
Yard 55 Y		0.0	R	PENTLAND 2.2	17.0	
47		2.2		KERTO 6.5	14.8	
Yard 39		8.7	TO	TAFT 3.8	8.3	
20		12.5		MIDOIL 2.0	4.5	
15		14.5		FELLOWS 2.5	2.5	
12 Y		17.0	R	SHALE	0.0	
				(17.0)		
				.....Time over District.....		
				.....Average speed per hour.....		

ADDITIONAL STATIONS

Levee.....	Distance from Gosford	16.5
Winoil.....	Distance from Pentland	3.4
Lowry.....		7.1
Chanslor.....		11.2

SPECIAL INSTRUCTIONS

Southern Pacific Company Rules and Regulations of the Transportation Department, Air Brake Rules and Special Instructions in San Joaquin Division Time Table govern on Sunset Ry.

Train will not exceed the speed in miles per hour shown below.

BETWEEN	Pass.	Freight	Backing
Gosford and Pentland.....	30	25	15
Except M.P. 26 and Pentland.....	12	12	12
Pentland and Maricopa.....	12	12	12
Pentland and Kerto.....	12	12	12
Kerto and Shale.....	20	20	15
East Switch Long Siding at Taft and derailer in main track west of Taft	10	10	10

Exercise caution in going over sags in track between M. P. 26 and Maricopa and between Pentland and Kerto and do not exceed 6 miles per hour over sag in track 500 feet east of opening 11A, east of Taft.

At Pentland, normal position of junction switch will be for Taft line.

There is a spring derailer on main track 900 feet west of west switch at Taft.

RULE 93: Yard limits are established at:

- Pentland
- Taft
- Maricopa.

Dr. A. R. Moodie, District Physician and Surgeon, Taft, California.



**RULE 2.** Authorized watch inspectors:  
 S. A. Pope, Manager of Time Service, 65 Market St., San Francisco.  
 Fresno. Bert Fuller, 1335 Fulton St. Visalia... A. G. Hooper.  
 Fresno. A. L. Colvin, 1211 Fulton St. 111 W. Main St.  
 Porterville... Frank Haener Exeter... W. B. Adams  
 Hanford... Hanford Jewelry Co. Bakersfield. J. N. Cheney,  
 Lancaster... C. E. Miller 1425 19th St.—901 Baker St.  
 San Fernando... F. G. Marshall Mojave... A. Ogulnick  
 Los Angeles... { Wm. B. Baehr, 103 Pacific Electric Bldg.  
 Geo. D. Davidson Co., 445 S. Spring St.  
 O. H. Patzer, 2708 North Broadway  
 Ralph Laraway, 1222 San Fernando Rd.

**RULE 3.** Conductors on eastward Santa Fe trains originating at Bakersfield will show on reverse side of Kern Jct. register ticket watch comparison made at Santa Fe station Bakersfield, also comparison with enginemen.

**RULE 14 (d).** As specified below, four long and one short sounds will be indication that flagman may return from west as prescribed by Rule 99.

Famoso.....Trains on Exeter main track.  
 Ducor.....Trains on Minkler-Southern Branch.  
 Exeter.....Trains on Visalia Branch.  
 Hardwick.....Trains on Riverdale Branch.  
 Goshen Jct.....Trains on Kerman Branch.

**RULE 14 (e).** As specified below, six long sounds will be indication that flagman may return from east as prescribed by Rule 99.

Fresno.....Trains on Exeter main track and Clovis Branch.  
 Porterville.....Trains on Success Branch.  
 Rossi.....Trains on Stratford Branch.  
 Goshen Junction...Trains on Visalia Branch.  
 Ingle.....Trains on Riverdale Branch.  
 Richgrove.....Trains on Richgrove Branch.  
 Magunden.....Trains on Arvin Branch.  
 Mojave.....Trains on Owenyo Branch.

**RULES 17 and 19.** Night signals will be displayed through tunnels.

**RULE 21.** In Bakersfield and Fresno indicators on engines must be displayed to relief track.

**RULE D-71.** Trains and engines may move between Calwa Tower and Clinton Ave., Fresno, with current of traffic irrespective of time table superiority but must avoid delaying first class trains.

**RULE S-72.** Westward trains are superior to trains of the same class in the opposite direction.

**RULE 83.** Train registers are not maintained at Calwa Tower or Bena. When an observation check be made between Fresno and Calwa Tower, and between Bakersfield and Bena, it will apply at end of double track.

Trains approaching each other between these stations will reduce speed sufficiently to permit identification.

When first class trains on opposite track between Mojave and Tehachapi are identified, it will not be necessary to obtain check of such trains before making movements in the same direction between Summit Switch and Mojave.

Rule 14-K must be applied when approaching trains on opposite track.

**RULE 83 (A).** At the following stations, only the trains indicated will register.

Oil Jct.....  
 Lancaster.....  
 Saugus.....  
 Famoso.....Trains to and from Exeter main track.  
 Tehachapi.....First and second class trains, and trains originating and terminating.  
 Goshen Jct.....No. 55, No. 56, No. 57, No. 58 and trains to and from Visalia and Kerman Branches, and extras originating and terminating.

Extra trains register at Porterville Olive St., Exeter, Armona and Coalinga.

When directed to register at an intermediate station, an extra train must show in column captioned "signals," the number and date of train order authorizing its movement; also the restricting order if such an order is in effect.

**RULE 83 (B).** At open train order offices trains may register by ticket as follows:

Kern Jct.....Santa Fe trains, S. P. first class trains and Westward light engines.  
 Tehachapi.....First and second class trains.  
 Porterville Olive St. First class trains.  
 Famoso.....Trains to and from Exeter main track.

Operator Kern Jct. will report arrival and departure Santa Fe first-class trains to Operator Bakersfield, who will enter same on register.

Operator Kern Jct. will report arrival and departure of all scheduled trains to operator Santa Fe station Bakersfield, who will enter same on Southern Pacific register located at Santa Fe station Bakersfield.

**RULE 83 (D).** Westward Santa Fe trains via Southern Pacific will get clearance and train orders from operator Santa Fe station Bakersfield authorizing movement from Oil Junction westward.

Eastward Clovis-Branch trains destined to Fresno Interurban secure train orders or clearance from operator at Fresno Tower, authorizing movement over Fresno Interurban.

Conductors and Engineers from Riverdale Branch to Western Division, in addition to orders and clearance signed by Chief Dispatcher of Western Division, authorizing movement from Ingle to Kerman on Los Banos subdivision of Western Division, will also procure from operator at the same point where such orders and clearances are issued, clearance signed by Chief Dispatcher of the San Joaquin Division.

Trains via Visalia and Kerman branches must obtain clearance before leaving Goshen Jct. when operator on duty. Trains to and from Santa Paula Branch must obtain a clearance before leaving Saugus.

Scheduled trains originating Hanford and Armona are not required to obtain a clearance when no operator on duty.

San Joaquin Division routed trains must obtain San Joaquin Division clearance authorizing movement west of Burbank Jct., in addition to Los Angeles Division clearance, at initial station on Los Angeles Division. Each clearance must be properly designated.

Eastward trains from San Joaquin Division are authorized to assume corresponding schedule on Los Angeles Division from Burbank Jct. to terminal station of schedule. Trains to and from San Joaquin Division are not required to obtain clearance at Burbank Jct. provided train is properly cleared by train-order signal.

**RULE 83 (E).** A train, when authorized by train order, may check the register against an extra train and proceed if such extra train appears on the register with the number and date of its restricting order registered in column captioned "Signals".

When a train is so authorized to check the register, it must register and place the restricting order number and date in column captioned "Signals".

**RULE 86 (B) and (C).** Inferior trains and engines may run ahead of first-class trains Bakersfield to Bena and Bena to Bakersfield, but will take necessary precautions to avoid delay to passenger trains.

**RULE 93.** Yard limits are established at:

Fresno	Bakersfield	Summit Switch
Goshen Jct.	Visalia	Eric
Coalinga	Exeter	Mojave
Armona	Lindsay	Searles
Kerman	Porterville Olive St.	Owenyo
Hanford	Saugus	Dinuba
Sanger	Kingsburg	Selma
Reedley	Friant	Lancaster
Delano	Tehachapi	Vincent
Tulare		San Fernando

**Fresno:** Limits are defined by yard limit signs at the following points:

Kerman Line.....	Mile Post 206.32.
Merced Line.....	Mile Post 199.08.
Bakersfield Line....	Mile Post 210.81.
Exeter Main Track...	Mile Post 208.15.
Clovis Branch.....	Mile Post 209.6.

Trains or engines will not move against current of traffic on double track between Divisadero Street and Clinton Avenue and between Cherry Avenue and Calwa Tower, Fresno, except on authority of Yardmaster. When making movements against current of traffic, trains or engines must be preceded by flagman over railway and street crossings at grade where wigwags are installed, protecting these crossings during movements.

Trains arriving and departing via Los Banos line at Fresno will receive proceed signal from herder at Divisadero Street, green flag by day and green light by night.

Westward trains or engines must receive proceed signal from yardman at Kern Street; and eastward trains or engines must receive proceed signal from yardman at Merced Street.

Trains may use No. 1 running track between Clinton Ave. and Biola Jct.

**Mojave:** First class trains may pass through Mojave without hand signals, providing switches are properly lined for such movement, and will move with caution irrespective of timetable superiority between Signals 3802 and 3811. Inferior trains entering or leaving Mojave must receive green signal unless yardmaster or his subordinate notifies train that they may enter or leave without green signal.

Trains leaving east end of yard may proceed without signal from herder provided they are notified switches are properly lined.

Trains from Owenyo Branch stop before fouling main track or blocking highway crossing regardless of position of derailer or signals received.

Unless yardmaster or his subordinate instruct otherwise, crossover movement from Owenyo Branch to Mojave will be made as follows: First

throw derailer on Owenyo Branch, second throw trailing point switch on eastward main track, third crossover switch on westward main track, fourth Owenyo Branch switch—then wait three minutes before proceeding. Be governed by Rule 93.

Following code of signals will govern eastward trains entering yard: Southern Pacific:

Passenger trains.....One long.  
 Freight trains.....One short, one long, one short.

Santa Fe:

Passenger trains.....One long, one short.  
 Freight trains.....One long, one short, one long.

**RULE 95.** Eastward trains from San Joaquin Division holding train order authority to display signals for following section to Burbank Jct. are authorized to display signals to terminal station of schedule on Los Angeles Division.

**RULE D-97 (A).** Will apply between Tehachapi and Summit Switch.

Eastward extra trains with running orders terminating at Burbank Junction may proceed beyond that station without a clearance, being governed by train order signal.

**RULE 98. RAILROAD CROSSINGS AT GRADE NOT INTERLOCKED**

A. T. & S. F. Railway, 744 feet east of Lacjac, STOP.  
 A. T. & S. F. Railway, 14718 feet west of Taurusa, STOP.  
 A. T. & S. F. Railway, 602 feet east of Visalia, STOP, and not pass over crossing without receiving proceed signal from flagman, who must precede train.

Laton & Western Railway, 2.7 miles west of Hardwick, STOP.  
 Laton & Western Railway, 1.8 miles east of Hub, STOP.

A. T. & S. F. Railway (on Success Branch), 4515 feet east of Porterville, STOP.

Fresno Interurban Railway, 1771 feet east of Las Palmas.  
 Fresno—Trains from Clovis Branch and Exeter main track stop at "stop" board at junction of these lines.

Goshen Jct.—Trains from Visalia Branch stop at "stop" board east end of yard.

End of the Visalia Branch will be at first switch east of the station where it enters Bakersfield-Fresno main track.

**RULE 103 (A).** At Selma no switching movements will be made over West Front Street while switching industrial tracks east of station and opposite Libby, McNeill and Libby Plant unless crossing is protected by member of crew.

No train, engine, car or motor shall be stored within 100 feet of either property line of County Road Crossing or Western Dairy Products track at Tipton, unless crossing is protected by flagman.

At Armona no switching movements will be made over Lake Street crossing unless protected by member of crew.

Trains switching Knudsen Laboratories, Inc. (Creamery) Spur, Visalia, must stop before making reverse movement across Goshen Avenue crossing.

When using spur track leading to freight station, Bakersfield, member of crew will see that highway traffic on U. S. Highway 99 is protected. After having entered upon crossing, it should be cleared as quickly as practicable.

In general, highway crossing signals are so designed that they will not operate for trains or engines making a reverse movement after having passed over the crossing. Trains or engines making such reverse movements must protect the crossing unless it is known signals are operating.

**RULE 104.** The normal position of switches at junctions will be for main tracks.

Exceptions:

Fresno Yard, Clinton Avenue (end of double track) for eastward track. This is an oil buffer spring switch.

Fresno, junction Los Banos line, for eastward track. This is an oil buffer spring switch.

Bena (end of double track) for westward track. This is an oil buffer spring switch.

Tehachapi (end of double track) for eastward track.

Mojave (end of double track) for westward track.

Hardwick.....for Kerman Branch

Armona.....for Coalinga Branch

Rossi.....for Coalinga Branch

Pernu Jct.....for Success Branch

Gosford.....for Sunset Railway

Switch at stem of wye McKittrick must be set for direct movement along the east leg of wye to serve as derail for cars spotted on stem of wye.

Deraillers in main track.

McKittrick. East wye switch is spring switch and serves as derail.

Porterville. 310 feet east of junction switch on Success Branch.

Mojave. 230 feet east of junction switch on Owenyo Branch.

Famoso. 168 feet west of junction switch, on Exeter main track.

**RULE 104 (D).** Use of heavier than C class engines in making running switches is prohibited unless engine is routed over other than diverging track.



**SPECIAL INSTRUCTIONS**

**RULE 105.** Track next to and north of main track at Ducor will be used as siding No. 1. Second track north of main track, will be used as Minkler Southern Ry. main or No. 2 track. Trains will use extreme east switch to enter or leave Southern Pacific main track. Inside switches will be left lined for Siding No. 2.

At Caliente, Bealville and Marcel the siding next to main track will be used as eastward siding, adjoining track will be used as westward siding. Inside siding switches are oil spring switches and normal position is for train entering siding. Trains entering siding passing an inoperative signal must assure themselves this switch is properly lined.

At Rowen the siding east of the crossovers will be used as the westward siding, the one west of the crossovers as the eastward siding.

Track (No. 1) next to main track west of station at Tehachapi will be used as westward siding.

At Vincent siding next to main track will be used as eastward siding, adjoining track will be used as westward siding.

Trains using other than the designated siding, unless authorized by the dispatcher, must be preceded by a flagman.

In the territory between Caliente and Tehachapi trains entering designated sidings against current of traffic must do so with caution expecting to find sidings occupied.

When pulling out of sidings they must be sure that signals in advance are for their movements and not for other trains on parallel sidings, stopping if necessary before reaching fouling point to determine their right to the route.

At Saugus the siding east of the station is the westward siding and the siding west of the station is the eastward siding. Track opposite station extending from westerly connection 863 feet east of station to connection with main track 722 feet west of station shall be known as middle siding. First-class trains meeting at Saugus use middle siding unless otherwise instructed.

**RULE 221.** Light will not be displayed in train order signals on McKittrick, Clovis, Coalinga, Kerman, Richgrove, Riverdale, Success, Stratford and Visalia branches, except when train orders are to be delivered.

Trains will not be required to obtain clearance at Kern Jct. and Bakersfield except when such trains originate or receive orders at these stations.

**RULE 221 (A).** It is unnecessary for dispatchers to O. K. a clearance and operators to transmit the address and order numbers from clearance to the train dispatcher, unless requested to do so by train dispatcher, nor will they complete that portion of clearance (Form CS-2643) reading:

"OK at.....M.....Chief Train Dispatcher," all provided that said orders affect movement of a train wholly within block system or signal dispatching limits.

If the orders affect movement, either wholly or in part, outside of the block system or signal dispatching limits, operators must repeat address and order numbers and obtain dispatcher's OK before the orders are delivered.

**RULE 824.** Instructions for setting brakes.

**MOJAVE**

**PASSENGER TRAINS**—Two brakes on east end and two brakes on west end on trains of 16 cars or less. When train is set out to tie up, at least half of the brakes on the train will be set but in case train consists of 2 or 3 cars, 2 brakes will be set.

**FREIGHT TRAINS**—Ten brakes on east end, 5 in middle and 5 on west end on trains of 72 cars, or less; 73 to 102 cars, 15 brakes on east end, 10 in middle and 5 on west end.

**WOODFORD (When taking water)**

**FREIGHT TRAINS (Eastward)**—First helper will spot for water, 5 brakes will be set ahead of this helper, 5 behind road engine and 5 ahead of second helper. First helper will keep engine brake applied until ready to proceed.

**RAVENNA (When taking water)**

**FREIGHT TRAINS (Westward)**—Road engine will spot for water, engine brake will be left applied on road engine and 8 brakes set ahead of helper that cuts off and takes water.

**CALIENTE (When taking water)**

**FREIGHT TRAINS (Eastward)**—Road engine will spot for water, and 8 hand brakes will be set just ahead of first helper that cuts off and takes water.

In complying with the above, hand brakes on freight trains must be set with assistance of brake club after train has stopped. When for any reason hand brakes are released under these conditions, the same number must be set to replace them. Where the use of hand brake is required, air brakes must not be relied upon as a substitute.

In event it should happen that the road engine and first helper are spotted at same time to take water at Woodford, Ravenna, and Caliente, automatic brakes will be released and it will not be necessary to apply hand brakes as long as road engine remains on the train.

When going to eat, or at any time that either train or engine crew leave train, sufficient hand brakes will be applied to hold the train.

In the application of Rule 825 in non-grade territory, conductors will take into consideration conditions such as heavy winds which arise from time to time on the Division.

**RULE 825.** Outfit cars must not be left in front of warehouses, storehouses, lumber yards, or other buildings.

House track at Woodford must not be used for setting out or storing of cars.

When necessary to cut crossing and a distance of 100 feet on each side cannot be provided, a human flagman must protect. Cars must not be left in any position that would obstruct the view of an autoist or pedestrian of an approaching train, unless crossing is protected as stated above.

In cutting crossing Roscoe or Sheldon Ave., Wahoo, openings must be made so that cars or engines will not be left within 100 feet of either property line unless crossing is protected by a member of train crew or other competent employe acting as flagman.

**RULE 833.** Whenever practicable locomotive cranes, or cranes of similar type must be handled in trains with heavy end forward.

Except those of Southern Pacific ownership, cranes or machines of similar type, with rotating body, loaded on open cars, must not be moved until inspected and released by mechanical department. Conductors must not move Jordan Spreaders, except when in use, unless wings are protected against spreading by chain or tie bar extending from wing to wing and wing arm to wing arm.

**RULE 834**—addition—must not be placed next to cab of Mallet or AC engines.

**RULE 836.** Cars moved from one station to another ahead of engine on descending grade must be chained to the engine. Switching movement on descending grades must be protected by a derail. When practicable engine must be kept on down hill end of cars.

When necessary to move cars ahead of engine do not exceed 20 miles per hour.

**RULE 843.** When a train is split at two sidings for the purpose of meeting or passing trains, conductor must accompany both portions of the train.

**RULE 869.** Trainmen will ride on top of trains through yards, entering and leaving terminals, through interlocking plants, also Vincent to Saugus, Vincent to Palmdale, Summit Switch to Mojave, Summit Switch to Ilmon, Tunnel to Burbank excepting rear brakeman, Searles to Cantil, McKittrick to Lokern and at other places as instructed by Conductor. Additional swing men must ride near the middle portion of train assigned to them. Trainmen must not ride on top of their train while passing through Tunnel 25.

**RULE 883.** Engines under steam must not be stored or left unattended on tracks that are not protected by derails against entry to main track.

**AUTOMATIC BLOCK SYSTEM**

**RULE 509.** A train or engine, when backing out of a siding or other track in block system limits, will, unless backed to clear block signal, proceed as if signal be in stop position.

Eastward freight trains having more cars than can be placed between San Fernando Road and home interlocking signal at Burbank Junction; if automatic home signal 4706 indicates stop, must stop west of crossing and communicate with signal operator by telephone located on post opposite isgnal 4706.

**RULE 509 (E).** That portion reading: "And the intervening track is seen to be clear," is interpreted as referring to the track being clear of engines and/or cars.

**RULE 511.** Within block signal limits after switches of a crossover are thrown, wait three minutes before crossing over, unless block signals protecting the movement can be seen to be in stop position not less than one-half mile distant.

**RULE 516.** Overlap post is located at:  
Newhall—Eastward trains—2000 feet east of west switch.

That section of track in Fresno between Tuolumne Street and Ventura Avenue is not protected by block signals. Be governed by third paragraph Rule 93.

Dwarf light signals governing movements to main track located as follows: Signals 2020 and 2022 Clinton Ave., Fresno, Signals 2565 and 2625 at Exeter, Signal 2870 Ducor, Signal 3627 Summit Switch, and Signal 3679 Eric. The first switch or derail lined, dwarf signal will indicate red. When all switches and derail are lined dwarf signal will indicate proceed. If signal indicates stop after proper line up has been made, a train will not move to main track except as provided by Rules 509 and 99.

Fresno.—West switch and derail of running track, Fresno Yard near Biola Jct., the Biola main track junction switch and derail, and switch No. 2 track west of Ashland Ave. are hand operated by using the switch levers on side of electric switch machines.

Signals governing movements from Biola Branch and from the west end of No. 1 track will indicate stop until derails and switches have been properly lined for route desired, when signals will indicate proceed.

Exeter.—Signal 2628 at junction Visalia Branch and Exeter main track normally indicates stop until crossover lined for movement to main track.

Bena.—Eastward trains leaving siding will be governed by dwarf light Signal 3282 which will indicate proceed after siding switch has been thrown to reverse position for two minutes.

Tehachapi.—Trains on No. 1 track at Tehachapi ready to leave, finding dwarf light Signal 3595 at stop, will push button located in box on post two feet east of Signal 3593. After pushing this button signal will clear in two minutes if no trains in block.

Warren.—When dwarf light signals located at either end of siding indicate stop, trains entering will be preceded by a flagman.

Searles.—Automatic block signals 4277 and 4268, located at east and west end of Tunnel 29 at Searles.

Knife switches have been installed in relay boxes located at these signals for use of operators of motor cars passing through tunnel.

Motor cars should stop and if signal indicates proceed, switch in box should be thrown to reverse position which will place signals at stop before entering tunnel. After passing through tunnel, stop must be made at signal and knife switch thrown to reverse position, which will clear signals.

The following block signals, equipped with a triangular number plate, have included in their control limits some special protective device. When indicating "STOP" careful inspection must be made of the track and structure as indicated below and it must be known that they are safe for passage of trains before proceeding.

Signals	Location
2016	Clinton Ave., Fresno..Spring switch, end of double track.
3281	Bena.....Spring switch, end of double track.
3308	Ilmon.....Spring switch, west end.
3450	Rowen.....Spring switch, west end.
3512	Walong.....Spring switch, west end.
3564	Cable.....Spring switch, west end.
3592	Tehachapi.....Spring switch, west end.
4574	.....Culvert 457 D.
4579	.....Culvert 457 D.

Block signals 4500 to 4513 Saugus govern movement of trains entering yard. If signals indicate stop, after stopping train may proceed with caution, not exceeding 12 miles per hour.

**OIL BUFFER SPRING SWITCHES**

When a block signal in advance of a facing point oil buffer spring switch indicates "STOP", careful examination of switch must be made before passing over it.

When making trailing point movement and train is stopped on switches, a reverse movement must not be made, nor the slack taken until the switch has been thrown by hand. When movement has been completed through switch, reverse movement must not be made until point closes.

Running switches are prohibited and sand, blow-off cocks, and injectors must not be used nor boosters started while passing over these switches.

Oil buffer spring switches are located as follows, and speed indicated must not be exceeded when passing over such switches.

	M.P.H.
Fresno, Clinton Ave., end double track.....	Trailing westward 35
	Facing eastward 20
Fresno, junction Los Banos line.....	Trailing eastward 15
	Facing westward 10
Bena, end double track.....	Trailing eastward 35
	Facing westward 20
Bena, west end siding.....	Trailing westward 50
Ilmon, west end.....	Trailing westward 30
	Facing eastward 30
Caliente, west end siding No. 2.....	Trailing westward 10
	Facing eastward 10
Caliente, east end siding No. 1.....	Trailing eastward 10
	Facing westward 10
Allard, west end.....	Trailing westward 30
	Facing eastward 30
Bealville, west end siding No. 2.....	Trailing westward 10
	Facing eastward 10
Bealville, east end siding No. 1.....	Trailing eastward 10
	Facing westward 10
Rowen, west end.....	Trailing westward 30
	Facing eastward 30
Walong, west end.....	Trailing westward 30
	Facing eastward 30
Marcel, west end siding No. 2.....	Trailing westward 10
	Facing eastward 10
Marcel, east end siding No. 1.....	Trailing eastward 10
	Facing westward 10
Cable, west end.....	Trailing westward 30
	Facing eastward 30
Tehachapi, west end.....	Trailing westward 30
	Facing eastward 30
Summit Switch, east end.....	Trailing eastward 50



## INTERLOCKING

At all interlocking plants, when route lined is not to be used, following signal will be sounded by Engineers, two short, one long and two short (00 — 00).

**FRESNO TOWER—A. T. & S. F. Crossing 1.6 miles east of Fresno on Clovis Branch**  
For main track, one long whistle (—).

To or from spur track, one short and two long whistles (o —).

**SUN MAID TOWER—A. T. & S. F. Crossing 1.5 miles east of Fresno on Exeter main track**  
One long whistle (—).

**CALWA TOWER—A. T. & S. F. Crossing and double track 3.5 miles east of Fresno**  
Eastward trains approaching end of double track will call for switch and derailer by one long, one short and one long whistle (— o —).

Westward trains, one long whistle for crossing and for double track (—).

**HANFORD TOWER—A. T. & S. F. Crossing 0.3 miles west of Hanford**  
One long whistle (—).

**TULARE TOWER—A. T. & S. F. Crossing 0.3 miles west of Tulare**  
One long whistle (—).

**KERN JCT. TOWER—A. T. & S. F. Crossing, double track and McKittrick Branch 0.7 mile east of Bakersfield**

For main track, one long whistle (—).

For movement over crossing on siding, one long, one short and one long whistle (— o —).

From S. P. to A. T. & S. F. main track, one short and two long whistles (o —).

Between main track and transfer track, one short, one long and one short whistle (o — o).

No. 1 track, two short, one long and one short whistles (o o — o).

Dwarf light signals opposite end of double track governing westward movement are as follows:

Green.....Westward track to S. P. single track.

Yellow.....To Santa Fe westward double track or S. P. No. 1 track.

Dwarf light signal for eastward movement is located at west limits of interlocking plant. Light signals as follows:

Green.....Eastward main track.

Yellow.....Against current of traffic.

Transfer tracks have pipe connected derails to main track (transfer switch).

At Kern Jct. only, Rule 628 is modified to permit movement, without stopping, of helper cuts only, past interlocking signals in stop position, provided yellow signal is received from the towerman in tower or on ground, and helper engineer sees that track is properly lined for movement to be made.

## TEHACHAPI

Main track movements (to or from double track) one long whistle (—).

No. 1 siding, one short, one long and one short whistle (o — o).

Trains or engines entering interlocking limits, except where fixed signals govern movements must receive authority from signal operator when may proceed with caution, not exceeding twelve miles per hour to next signal.

## CALIENTE, ALLARD, BEALVILLE, CLIFF, WOODFORD, MARCEL

The east and west switches of sidings at Caliente, Bealville, Cliff, Woodford, Marcel and the east switch of siding at Allard are interlocked and controlled from Telegraph office. All other switches are hand throw. The switches and signals at Allard and Cliff are controlled by the plant at Bealville.

Interlocking limits extend on main track from the eastward signal, located fifty (50) feet west of the west switch, to the westward signal, located fifty (50) feet east of the east switch at Caliente, Woodford and Marcel, and on both main track and siding at Woodford, and at Bealville from the eastward signal, located fifty (50) feet west of the west switch Allard to westward signal, located fifty (50) feet east of the east switch Cliff. All signals within these limits are interlocking, except Signals 3412 and 3417, which are automatic.

When the eastbound interlocking signals east end Bealville or the westbound interlocking signals west end Cliff are inoperative, trains must be preceded by flagman to the next signal.

Trains stopped by signals must communicate with signal operator by telephone located in telephone booths at east and west switches and be governed by his instructions. Additional telephones are provided at derail west end house track Woodford, and at derail of house track extension at Caliente. If instructed by signal operator to throw interlocking switch by hand, follow instructions posted in telephone booth.

The member of crew cranking switch over, after receiving permission from signal operator, must notify rear member of his crew in order that switch will be returned to normal position, or remain at switch and return it to normal position, unless instructed by signal operator to leave switch open.

When for any reason, proceed indication of an interlocking signal cannot be acted upon at once signal operator must immediately be notified.

Trains or engines entering main track, except where fixed signals govern movement, must receive authority from signal operator then may proceed with caution, not exceeding 12 miles per hour to next signal.

At Cliff, Spur switch west end siding will be hand operated and trains must not enter or leave spur except on telephone authority from signal operator at Bealville.

At Woodford "Take Siding Indicator" mounted on mast of westward interlocking signal will govern westward trains that are to use house track.

When westward third class and extra trains are given main track Allard, and unable to proceed farther ahead of superior trains in same direction, they will immediately advise the signal operator at Bealville.

Trains entering sidings at Caliente, Bealville and Marcel will stop clear of adjacent siding unless a proceed signal is indicated in light signal governing the movement to main track.

## FRESNO, OLIVE AVE. CROSSING, AUTOMATIC INTERLOCKER

Interlocking limits extend from eastward Light Type Signal SA-2032, located 750 feet west of Fresno Traction Company crossing to westward Light Type Signal SA-2032 located 750 feet east of this crossing.

When these signals display stop, trains will be governed by interlocking rules within the interlocking limits and Rule 509 within the automatic portion of the block beyond the interlocking limits and will be preceded by crossing by flagman.

Dwarf light type signals installed between main tracks and located 80 feet east and west of this crossing govern moving against current of traffic. These signals indicate stop only and trains must be preceded by flagman who will give proceed signal from center of crossing.

LOS ANGELES YARD  
BURBANK JUNCTION TOWER

To Roscoe or Los Angeles, one long. To siding, five short.

To Hewitt, one long, four short.

To industrial lead, one short, one long, one short.

## TRAIN AND AIR INSPECTION

At the following stations freight trains descending grade between Caliente and Lang will stop 10 minutes to allow heat to equalize in wheels and make inspection:

Ravenna.

Marcel Rowen.—Or in making other stops, inspection may be made provided initial run is not to exceed 8 miles, succeeding runs not to exceed 10 miles.

A continuous run of 10 miles will not be made where the run from the last inspection point was less than 7 miles.

Warren.

Owenyo Branch.—Rand. If retainers are not used, need not stop if in opinion of conductor it is safe to do so.

Freight trains must not run more than 40 miles without a stop for inspection: Except run may be made by westward freight trains, Saugus to Lancaster, Ravenna to Mojave, also from Bakersfield to Tipton and Tipton to Fresno or vice versa without stopping for train inspection when in the judgment of the conductor it is safe to do so. Inspection will be made at any intermediate stops.

## AIR BRAKE RULE 11.

Air brake inspection at points where no car inspectors are on duty, and motive power and/or engine crew or train crew is changed on a freight train, shall be made as follows:

After the train is made up and the engine attached, the engineer will apply the brakes with a 20 pound service reduction and leave them applied. The trainmen will then pass along the train to determine that the brake is applied on each car. The numbers of any cars found with inoperative air brakes must be reported on Form 2809 and such cars assembled and switched to the rear of the train, next ahead of the caboose, before leaving that station. After this inspection has been made, brakes have been released, and trainmen have noted that normal brake pipe pressure has been restored as indicated on caboose gauge, and have given signal to engineer, the latter must comply with last part of Rule 11 to avoid brakes sticking from an overcharge of the brake system, etc.

If it is necessary to switch any cars to the rear account brakes being inoperative, Rule 17 must be complied with before departure.

Rule 34 must be observed to determine by rolling inspection that each brake releases properly.

Attention is directed to the Safety Appliance Act which requires that whenever any train is operated with power or train brakes, not less than 85 per cent. of the cars of such train shall have their brakes used and operated by the engineer of the locomotive drawing such train; and all power-brake cars in every such train which are associated together with the 85 per cent., shall have their brakes sq used and operated.

## AIR BRAKE RULE 13.

At lay-over points for passenger equipment, where there are no car inspectors, crews must make air brake test before starting on initial trip, as follows: Brake pipe must be fully charged, engineer then apply air brake; trainmen must examine each car to see whether all brakes are applied. If all brakes apply, trainmen must give signal 16-E from rear car, examine each car in train to see that all brakes release, and report condition to the engineer.

## AIR BRAKE RULE 16.

Passenger Trains: Make running air brake test at Summit Switch and between initial and crossover switch at Vincent. Not necessary to make running test on passenger trains leaving Mojave that have not had the continuity of the brake pipe broken. Eastward Santa Fe passenger trains leaving Kern Jct. will not make running test. Within yard limits of Fresno, running air brake test will be made on eastward trains only when leaving Fresno.

When running air brake test is made trainmen will use communicating Signal 16-H instead of hand or lantern signals.

On westward passenger trains leaving Bakersfield, running test shall not be made until rear car has cleared Baker Street.

Freight Trains: Freight trains not stopping at Summit Switch will make running air brake test between wye switches as follows: While working steam, engineer will make a reduction of approximately 7 pounds, waiting for slack to adjust itself and then add about 3 pounds, making total reduction of 10 pounds before releasing.

Conductor will note reduction on caboose gauge and following build up in pressure when brakes are released, then give proceed signal which will be relayed by other trainmen from their portion of the train, providing they note retainers releasing in their vicinity.

If conductor is on the head end, the rear brakeman is held responsible for such observance of the gauge as will insure against danger from closed angle cock or low pressure.

When such observance indicates danger, take every needed precaution as the circumstances warrant.

If releasing of brakes cannot be made at a greater speed than 15 miles per hour, stop and make rear end test.

Whenever plug tests or running tests, whichever are required under the rules, have been made on eastward trains at Tehachapi, it will not be necessary to make running tests on such trains not stopping at Summit Switch.

Westward freight trains that do not have helpers to cut out at Vincent and do not stop there for other operating reasons, will turn up the retaining valves on the first ten cars behind the engine at the east distant signal approaching Vincent, and will make air brake running test between siding switches as follows:

While working steam and not allowing driver brakes to apply, follow the same procedure as outlined in instructions relative to making the freight train running test at Summit Switch, with the exception that a release may be made at a speed not slower than 8 miles per hour. If train has to stop for any reason, or if speed of at least 8 miles per hour cannot be made at time release is desired, standing air brake test as per Rule 17 of the air brake rules will be made.

On Eastward freight trains not having helpers to cut out or required to stop at Vincent for operating reasons, they will follow the same procedure as outlined in next paragraph above, except that one retaining valve for each 115 M's contained in train will be used. These retaining valves must be turned up at or near west distant signal, the retaining valves on head portion of train to be turned up first.

## AIR BRAKE RULE 17.

Rear end test will be made in accordance with Rules 17 and 17-A of the Air Brake Rules, and this test will also be made at the following places under the conditions hereinafter stated:

Vincent.....Freight trains stopping.

Summit Switch.....All trains stopping.

Mojave.....Freight trains not originating.

Leading engineer will not signal for rear end test on trains having helpers until such helpers indicate by one blast of the whistle that the train is ready for the test.

Before a train which has stopped on grade is signalled to proceed, air gauge in caboose must be observed. If gauge indicates brake pipe unobstructed and registers a pressure of not less than 65 pounds, proceed signal may be given.

## AIR BRAKE RULE 54.

Emergency hose must be used on all freight trains between Los Angeles and Bakersfield.

Trains of 50 cars or less 2 emergency plugs will be used located approximately 20th and 40th cars from engine.

Trains of 50 to 71 cars 3 plugs located approximately between 20th, 40th and 60th cars from engine.

Trains of 71 to 100 cars 4 plugs located approximately on the 20th, 40th, 60th and 80th cars from engine.

Trains of 100 to 124 cars 4 plugs located on the 20th, 40th, 60th and 100th cars from engine.

On westward freight trains plugs will be fastened on east end of car and on eastward freight trains on west end of car.

Emergency hose will be handled by carmen at Los Angeles and Bakersfield, but must be applied and removed when necessary by trainmen at intermediate stations and placed in caboose.

In applying these hose efforts should be made to apply them between through loads so as to avoid having to change them enroute where emergency is encountered.

Handle of emergency hose must be sealed by carmen and full report made by trainmen when seal broken.







**SPEED RESTRICTIONS**  
 Maximum speed of any passenger train must not exceed 60 miles an hour except as otherwise provided for:  
 Maximum speed of any freight or mixed train must not exceed 35 miles an hour except as otherwise provided for:  
 Speed Restrictions in Miles Per Hour, Will Apply as Follows:

Page No.	TERRITORY	PASSENGER					FREIGHT	Engines Backing With or Without Cars	Yard Engines S-SE Type	LIGHT ENGINES RUNNING FORWARD			
		Maximum	With E T-28, 32, 37, 40 P Motors	With M T 1, 2, 8, 9, 23, 28, 31, 36, 57, 58 MK 5, 6, 7, 8, 9	With Mt. GS Sta. Fe Mt. type	With C 2 to 10 incl C 18 to 29 incl. AC 4, 5, 6, MM, AM SP				Freight and Mixed Maximum	E T 26, 32, 37, 40 P A Mt. 1, 2, 3, 4, 5 Santa Fe Mt. type	M T 1, 2, 8, 9, 23, 28, 31, 36, 57, 58 C 2 to 10 incl. C 18 to 29 incl. MK 5, 6, 7, 8, 9	F SP GS Santa Fe 3800 type
2	Biola Jct.-Calwa Tower, except	50	50	50	50	45	40	30	20	40	35	35	30
2, 3, 7	F. T. Co., Crossing, Olive Ave., Fresno	20	20	20	20	20	20	20	20	20	20	20	20
	Within City Limits Fresno along or on across street crossings	20	20	20	20	20	20	12	12	12	12	12	12
2	Calwa Tower - Goshen Jct.	60	60	50	60	40	40	30	20	40	35	35	30
2	Goshen Jct.-East Switch Oil Jct., except	60	60	50	60	40	40	30	20	40	35	35	30
2	A. T. & S. F. Ry., crossing at Tulare Tower.	40	40	40	40	40	40	30	20	40	35	35	30
2, 4	East switch Oil Jct.-One mile east Kern Jct., except over street crossings in Bakersfield	35	35	35	35	35	20	20	20	20	20	20	20
3	Fresno-Famoso, except	45	45	45			30	20	20	30	30	30	30
3	On curves at Mile Post 218.54 and 218.74	35	35	35			20	20	20	20	20	20	20
3	On curve west of Orris	35	35	35			20	20	20	20	20	20	20
4	One mile east Kern Jct. - one mile west Ilmon	50	50	50	50	45	40	30	20	40	35	35	30
4	One mile west Ilmon - West Switch Tehachapi	30	30	28	30	28	20	15	20	25	25	20	20
4	West Switch Tehachapi-One Mile east of Cameron	50	50	50	50	45	35	30	20	35	35	35	30
4	One mile east of Cameron-Mojave, except Westward freight trains Mojave to one mile east of Cameron	45	45	45	45	45	20	20	20	25	25	25	25
4, 5	Mojave Yard, between Standard Oil switch and extreme east switch	15	15	15	15	15	10	10	15	15	15	15	15
5	Mojave - Palmdale	55	55	50	55	45	40	30	20	40	35	35	30
5	Palmdale - Mile Post 417, except Westward freight trains M. P. 417 to Palmdale	50	50	50	50	45	40	30	20	40	35	35	30
5	Mile Post 417-Lang	30	30	28	30	28	20	15	15	25	25	20	20
5	Lang-Saugus	30	30	28	30	28	22	15	15	25	25	22	22
5	Saugus - Burbank Jct., except	50	50	50	50	45	35	30	20	35	35	35	30
5	East switch Saugus and West Portal tunnel 25	40	40	40	40	40	25	25	20	25	25	25	25
5	West Portal tunnel 25 and M.P. 458.14	30	30	30	30	30	20	20	20	20	20	20	20
5	M.P. 458.80 - 458.94	40	40	40	40	40	25	25	20	25	25	25	25
5	M.P. 458.14 - 471.60 (eastward freight trains only)						25						
5	Burbank Jct. (Crossover west of tower)	30	30	30	30	30	20	20	30	30	30	30	30
	(Crossover east of tower)	35	35	35	35	35	20	20	20	20	20	20	20
6	Armona-Crump, except	25					25	15	20	25	25		
6	Over trestle at M.P. 267.3	15					15	15	15	15	15		
6	Kerman-Goshen Jct.	25					25	15	20	25	25		
6	Goshen Jct.-Exeter, except	40					30	15	20	30	30		
6	On curve at Goshen Jct. and curve at Ambler	30					20	15	20	20	20		
6	Ingle - Hardwick, except	25					25	15	20	25	25		
6	Mile Post 219 - Kings River Bridge	25					25	15	15	15	15		
7	Fresno-Gordon, except	25					25	15	20	25	25		
7	On curves at Barton and Maltermoro	20					20	15	15	20	20		
7	Over Fresno Interurban tracks, Las Palmas	15					15	15	15	15	15		
7	Gordon-Friant	20					20	15	15	20	20		
7	Rossi-Stratford	12					12	12	12	12	12		
3	Porterville-Clavicle-Pernu, except	15					15	15	15	15	15		
3	On curves, Success and Pernu branches	12					12	12	12	12	12		
3	Richgrove-Jovista, except	25					25	15	20	25	25		
3	On curves, Richgrove branch	15					15	15	15	15	15		
7	Kern Jct.-M.P. 354 1/2	25					25	15	20	25	25		
7	Mile Post 354 1/2-Olig, except	20					20	15	15	20	20		
7	Mile Post 354-Olig, with large loaded oil cars						15	15	15	15	15		
7	Magunden-Arvin, except	25					25	15	20	25	25		
	On curves, Arvin branch	15					15	15	15	15	15		
8	Mojave-Owenyo, except	30					30	20	20	30	30		
	F-4&F-5 engines-Mojave-Searles						25	20	20	20	25		
8	Over west siding switch, Owenyo	10					10	10	10	10	10		

Speed of 60 miles per hour is permitted gas-electric motor car trains on main track between Fresno and Goshen Jct.

**SPEED OF TRAINS REGULATED BY ORDINANCE THROUGH CITY LIMITS**

Page	STATION	Passenger	Freight	Running Backward	Page	STATION	Passenger	Freight	Running Backward
2-3-7	Fresno, along or across street crossings	20	20	12	3	Exeter, between 5 A. M. and 11 P. M.	20	20	20
2	Fowler, between 6 A. M. and 9 P. M.	30	30	30	3	Lindsay, between 5 A. M. and 11 P. M.	20	20	20
2	Selma, between 5 A. M. and 11 P. M.	30	30	30	5	San Fernando over street crossings east and west of station	25	25	25
2	Kingsburg, between 6 A. M. and 9 P. M.	30	30	30	6	Armona, Lake Street Crossing	20	20	20
2	Tulare, between 5 A. M. and 11 P. M.	20	20	20	6	Visalia	15	15	15
3	Reedley, between 5 A. M. and 11 P. M.	20	20	20					

At Fowler, Selma and Kingsburg it is lawful to increase speed to 40 M.P.H. after locomotive has passed last crossing within city limits in direction train is moving.

**SPEED RESTRICTIONS**

Speed restrictions for engines are shown in speed table; however, attention is called to the following maximum speeds at which tenders may be operated subject to restrictions imposed locally:

Tenders having water capacity, 7,000 gallons or less, except classes 70-R-1 and 70-SC-1, maximum speed 50 miles an hour.

Engines operated coupled tender to tender must not exceed speed permitted for light engines of that class running backwards.

Maximum speed of disabled engines hauled in train, or running under own steam, must not exceed:

- When pilot removed..... 20 M.P.H.
- When main rod only removed..... 30 M.P.H.
- When side rod only removed..... 30 M.P.H.
- When both main and side rods removed..... 20 M.P.H.
- When hauled in train and all rods are on..... 30 M.P.H.
- GS engines..... 15 M.P.H.
- SP 1, 2 and when inside main rod removed..... 30 M.P.H.
- S and SE engines and all other classes of engines when not equipped with engine trucks..... 20 M.P.H.
- When all weight has been removed from any one pair of drivers on an engine, speed must not exceed..... 20 M.P.H.
- When all weight has been removed from one wheel of any pair drivers on an engine, speed must not exceed..... 30 M.P.H.

West of Saugus F-1, 3, 4, 5, SP-1, 2, 3, Santa Fe-3800 and AC type engine must not exceed 8 M.P.H. backward movement over switch turnout.

When engines 3625, 3665, 3681, 3711, 3727, 3737, 3742, 4111, 4114, 4115, 4116, 4117, 4123, and 4124 are used in passenger service they are permitted maximum passenger speed between Bakersfield and Burbank Jct.

When Santa Fe 3800 type engines are used in passenger service they are permitted maximum speed of 45 miles per hour between one mile east of Kern Jct. and one mile west of Ilmon: also between west switch Tehachapi and one mile east of Cameron.

When used in passenger service, AC 4 and 5 engines and Santa Fe 3700 and 3800 type engines are permitted maximum speed of 30 miles per hour between one mile west of Ilmon and west switch Tehachapi, also between Mile Post 417 and Saugus.

Engines not shown in speed table must not exceed freight speed except MC engines must not exceed 20 miles per hour between Lang and Saugus.

F and SP Class engines must not exceed 8 miles per hour on No. 7 turn outs and all slip switches.

When interlocking signals at Caliente, Allard, Bealville, Woodford and Marcel indicate proceed trains may run at speed and through other interlocking plants with caution. At Locans do not exceed six miles per hour over wye and packing house tracks.

Trains must not exceed 30 miles per hour through limits of interlocking plant at Calwa Tower.

For speed over Oil Buffer Spring Switches, see list of such switches on Page 10 and be governed by speed given therein.

Through other cross-overs and turnouts trains must not exceed 10 miles per hour.

On sidings in territory between Bakersfield and Burbank Jct. trains will run with caution, not exceeding 10 miles per hour.

Trains handling relief outfit must not exceed 25 miles per hour between Fresno and Bakersfield, Fresno and Famoso via Sanger, Kerman and Exeter, Bakersfield and one mile west of Ilmon, one mile west of Tehachapi and one mile east of Cameron, Mojave and Mile Post 417, Saugus and Burbank Jct., and 20 miles per hour between one mile east of Cameron and Mojave, and must not exceed 15 miles per hour over other track. Where freight speed is less be governed thereby.

When locomotive Cranes, of the type SPMW 3636, are placed in trains, they must be handled with the heavy end forward, except where it is impossible to turn them, in which case they may be turned at the first available point.

In isolated cases, where it becomes absolutely necessary to handle these cranes with the light end forward, extreme care must be exercised and speed of 25 miles per hour not exceeded.

All cars moved in passenger trains must be equipped with steel-tired or all-steel wheels. When cars not so equipped are offered for movement, they will be handled in freight trains—passengers, if any, to move on passenger train.

Trains consisting of engine and caboose only should be considered freight trains and speed restricted accordingly.

Trains carrying cabooses equipped with cast iron wheels must not exceed 40 miles per hour.

Wooden passenger-carrying cars, wooden baggage, express and other head-end cars, unless equipped with steel center sills and steel platforms, must not be used in passenger service except upon authority.

Speed of trains handling such cars must be restricted as follows: When consist includes not more than three wooden passenger-carrying cars, maximum speed must not exceed 50 miles per hour.

When consist includes more than three wooden passenger-carrying cars, maximum speed must not exceed 40 miles per hour.

If consist of train includes wooden and steel passenger-carrying cars, wooden cars must be kept together and handled on the rear.



SPECIAL INSTRUCTIONS

SPEED TABLE

Speed per Hour	1 Mile in Min. Sec.	Speed per Hour	1 Mile in Min. Sec.	Speed per Hour	1 Mile in Min. Sec.	Speed per Hour	1 Mile in Min. Sec.
6	10.00	25	2.24	39	1.33	53	1.08
8	7.30	26	2.18	40	1.30	54	1.06
10	6.00	27	2.13	41	1.27	55	1.05
12	5.00	28	2.08	42	1.25	56	1.04
15	4.00	29	2.04	43	1.23	57	1.03
16	3.45	30	2.00	44	1.21	58	1.02
17	3.31	31	1.96	45	1.20	59	1.01
18	3.20	32	1.92	46	1.18	60	1.00
19	3.09	33	1.89	47	1.16	61	0.99
20	3.00	34	1.86	48	1.15	62	0.98
21	2.91	35	1.83	49	1.13	63	0.97
22	2.83	36	1.81	50	1.12	64	0.96
23	2.76	37	1.79	51	1.10	65	0.95
24	2.70	38	1.77	52	1.09		

STRUCTURES LESS THAN STANDARD CLEARANCE

Mile Post	Location	Description
<b>Fresno-Saugus—Main Track</b>		
205.5	Fresno Shop Yard	Water tank spout.....Side
205.5	Fresno	Pullman shed.....Side
220.7	Selma	Libby-McNeill & Libby.....Side
313.2	Bakersfield, east end Round House lead	Water column.....Side
313.2	Bakersfield Emergency Column No. 4	Water column.....Side
313.2	Bakersfield, roundhouse turnout tracks	Sandhouse.....Side and Overhead
313.2	Bakersfield	P. F. E. ice dock.....Side
313.2	Bakersfield	Pullman shed.....Side
313.2	Bakersfield	Wheel unloading crane.....Overhead
313.2	Bakersfield	Coal house at store.....Side
313.2	Bakersfield	Air pump house.....Side
313.2	Bakersfield	Gravel Bunkers, Gravel Pit.....Side and Overhead
340.5	Bealville	Water tank spout.....Side
354.2	Marcel	Water tank spout.....Side
434.8	East of Russ	Tunnel 17 1/2.....Overhead
437.0	East of Russ	Tunnel 18.....Overhead
439.5	East of Lang	Tunnel 20.....Overhead
440.1	East of Lang	Tunnel 21.....Overhead
441.5	East of Lang	Tunnel 22.....Overhead
445.3	East of Humphreys	Tunnel 23.....Overhead
449.7	East of Honby	Tunnel 24.....Overhead
<b>Fresno-Famoso via Porterville</b>		
205.5	Fresno	S. J. L. & P. Corp. plant.....Side and Overhead
225.8	Fargo	Southern Pacific Freight Shed.....Side
257.4	Exeter	Water tank spout.....Side
<b>Goshen Jct.—Coalinga-Kerman</b>		
229.1	Armons	Water tank spout.....Side
268.4	Coalinga	Water tank spout.....Side
272.0	Leroy	Guy wire and Warehouse.....Side and Overhead
<b>Fresno-Friant</b>		
205.5	Fresno	Alley Drill Track, Fulton.....Side
217.4	Clovis	Water tank spout.....Side
<b>Bakersfield-Olig</b>		
345.4	Kilowatt	Power House.....Overhead and Side
<b>Mojave-Owenyo</b>		
402.5	Cantij	Water tank spout.....Side
426.8	West of Searles	Tunnel 29.....Overhead
484.1	Haiwee	Water tank spout.....Side
523.0	Owenyo	Highline trestle on Calif. Alkali Co. Spur.....Overhead and Side
<b>Saugus-Burbank Junction</b>		
453.7	Elayon	Standard Oil Co. filling racks.....Side
465.6	Wahoo	Consolidated Rock Co. rock crusher.....Side and Overhead
465.6	Wahoo	Consolidated Rock Co. piles of rock.....Side
467.9	Roscoe	Consolidated Rock Co. bunkers.....Both Sides
467.9	Roscoe	Consolidated Rock Co. sand piles and switch stands.....Side

Employees are warned that it is dangerous to ride on top or sides of cars at above-mentioned points. Employees must guard against coming in contact with overhead wires or their connections.

AVERAGE TARE WEIGHTS OF PASSENGER TRAIN CARS

CLASS	NOT AIR-CONDITIONED		AIR-CONDITIONED	
	All-Steel	Steel Underframe	All-Steel Cooling Season	All-Steel Heating Season
Baggage—60 ft.	93,070			
“ —66 ft.	127,610			
“ —70 ft.	122,620			
“ —70 ft. (With Auto. End Door)	125,800			
“ —(Dynamo)	98,730			
“ —Passenger		87,120		
Baggage & Mail—60 ft.	103,620			
“ —69 ft.	124,760			
“ —70 ft.	129,140			
“ —Passenger	108,675	103,590		
Express Refr.—N. P. Ry.		112,640		
“ —A. R. E. No. 40-154		74,000		
“ —“ “ 153-224		78,000		
“ —“ “ 500-506		89,000		
“ —“ “ 1101-1175		110,000		
“ —P. F. E. 500-799		85,000		
Express, Horse	133,050			
Postal	112,120			
Postal Storage—40 ft.	74,530			
“ —60 ft.	105,120			
Assembly (ACW)		168,950	168,950	
Club (ACI)	146,210	122,300	172,200	164,700
Official (NAC)	170,700	155,370		
“ —Cars 107-128 (ACW)			182,800	182,800
“ —Cars 140-141 (ACW)			195,040	195,040
Chair—60 ft. (ACI)	100,620		138,000	132,000
“ —72 ft. (ACI)			165,000	157,800
“ —72 ft. (ACW)			158,700	158,700
“ —Streamline—Single (ACS)			120,500	104,500
“ —Art. (ACS)			205,400	172,600
“ —74 ft. (ACI)			180,915	173,125
“ —74 ft. (ACS)			197,944	181,600
Coaches—60 ft. (ACI)	98,130		136,100	130,100
“ —70 ft. (ACI)	137,640		157,800	151,000
“ —70 ft. (ACW)	137,640		151,000	151,000
“ —72 ft. (ACI)			164,500	157,400
“ —72 ft. (ACW)			155,500	153,500
“ —73 ft. 6 in. (ACW)			163,000	163,000
“ —73 ft. 6 in. (ACI)			168,500	161,200
“ —72 ft. (Interurban)	120,000			
All-Day Lunch—Chair	105,970			
“ —Coach	103,875			
Cafe-Coach (ACI)		138,600	155,700	149,000*
Cafe-Lounge (ACI)	148,950	161,200	173,500	166,000
“ (ACW)			156,000	156,000
Daylight—(12-car train) (ACS)			1,344,080	1,147,280
“ —Comb. Baggage & Coach (ACS)			118,940	102,540
“ —Art. Chair (ACS)			203,640	170,840
“ —Tavern (ACS)			130,850	114,450
“ —Diner (ACS)			129,860	113,460
“ —Parlor (ACS)			115,880	99,480
“ —Parlor-Observation (ACS)			118,690	102,290
Diner—70 ft.		135,930		
“ —72 ft.	155,330	146,930		
“ —77 ft. (Arch Roof) (ACI)	156,000		170,100	162,700
“ —77 ft. ( ) (ACW)			162,950	162,950
“ —77 ft. (Clere Story Roof) (ACW)		165,530	169,450	169,450
“ —77 ft. ( ) (ACM)			189,581	173,836
“ —79 ft. (NAC)	169,100			
“ —80 ft. (Clere Story Roof) (ACM)			301,323	184,700
Lounge ( ) (ACI)			189,800	181,630
“ (Arch Roof) (ACI)			167,500	160,300
“ ( ) (ACW)			164,980	157,780
Observation—75 ft. (ACI)	154,400		169,185	161,900
“ —77 ft. (ACI)			194,543	186,166
Pullman—Observation (ACI)	160,800	141,870		
“ (ACM)	153,000	177,314	169,200	
“ —Lounge (ACM)	171,200	192,300	176,300	
“ (ACI)	171,200	194,900	178,900	
“ —Bedroom (ACI)	167,600	187,682	179,600	
“ (ACM)	167,600	183,920	176,000	
“ —Sleeper (ACM)	165,100	195,800	179,800	
“ (ACI)	165,100	191,100	175,100	
“ —Tourist (ACM)	153,000	180,075	171,500	
“ (ACI)	153,000	185,200	169,200	
Rail, Gas-Electric—400 H.P.	158,400		168,663	161,400
“ —600 H.P.	167,200			

\*Steel underframe.  
CODE:—NAC—Non-Air Conditioned.  
—ACI—Air-Conditioned—Ice System.  
—ACM—Air-Conditioned—Mechanical System.  
—ACW—Air-Conditioned—Waukesha System.  
—ACS—Air-Conditioned—Steam Ejector System.

LIST OF SURGEONS

NAME	TITLE	LOCATION
Dr. W. B. Coffey	Manager and Chief Surgeon	San Francisco, Cal.
Dr. J. D. Morgan	District Surgeon	Fresno, Cal.
Dr. Chas. A. James	District Surgeon	Fresno, Cal.
Dr. D. H. Trowbridge, Jr.	Oculist	Fresno, Cal.
Dr. Wayne Hunt	Aurist	Fresno, Cal.
Dr. O. B. Doyle	Asst. District Surgeon	Fresno, Cal.
Dr. J. D. Wagner	District Surgeon	Selma, Cal.
Dr. W. H. Nielson	District Surgeon	Fowler, Cal.
Dr. E. C. Halley	District Surgeon	Sanger, Cal.
Dr. G. A. Hawkins	District Surgeon	Reedley, Cal.
Dr. R. E. Cronemiller	District Surgeon	Exeter, Cal.
Dr. Edgar Brigham	District Surgeon	Dinuba, Cal.
Dr. O. A. Olson	District Surgeon	Kingsburg, Cal.
Dr. M. S. McMurtry	Emergency Surgeon	Clovis, Cal.
Dr. R. N. Fuller	District Surgeon	Tulare, Cal.
Dr. J. Seiberth	District Surgeon	Pixley, Cal.
Dr. Henry A. Rivin	District Surgeon	Delano, Cal.
Dr. W. B. Smith	District Surgeon	Delano, Cal.
Dr. F. R. Guido	District Surgeon	Visalia, Cal.
Dr. C. T. Rosson	District Surgeon	Hanford, Cal.
Dr. C. T. Rosson, Jr.	Asso. Dist. Physician & Surgeon	Hanford, Cal.
Dr. J. C. Drake	District Surgeon	Kerman, Cal.
Dr. Geo. A. Meracle	Emergency Surgeon	Caruthers, Cal.
Dr. Wm. P. Byron	District Surgeon	Lemoore, Cal.
Dr. Bryson E. Cox	District Surgeon	Coalinga, Cal.
Dr. P. S. Barber	District Surgeon	Porterville, Cal.
Dr. W. W. Tourtillott	District Surgeon	Porterville, Cal.
Dr. J. R. Fillmore	Emergency Surgeon	Strathmore, Cal.
Dr. H. D. R. Shoemaker	District Surgeon	Lindsay, Cal.
Dr. H. W. Bell	Division Surgeon	Bakersfield, Cal.
Dr. C. L. Moore	District Surgeon	Bakersfield, Cal.
Dr. J. M. Kirby	Consulting Physician & Surgeon	Bakersfield, Cal.
Dr. R. M. Jones	Oculist and Aurist	Bakersfield, Cal.
Dr. Harold L. Schlotthauer	District Surgeon	Tehachapi, Cal.
Dr. Phil J. Vogel	District Surgeon	Mojave, Cal.
Dr. M. A. Williamson	District Surgeon	Lone Pine, Cal.
Dr. Howard W. Ducker	Acting Dist. Phys. & Surgeon	Lone Pine, Cal.
Dr. Harvey Crook	District Surgeon	Bishop, Cal.
Dr. George D. Shultz	District Surgeon	Independence, Cal.
Dr. Thomas A. Drummond	Emergency Surgeon	Randsburg, Cal.
Dr. S. H. Savage	District Surgeon	Lancaster, Cal.
Dr. W. R. Senseman	District Surgeon	Palmdale, Cal.
Dr. E. C. Innis	District Surgeon	Saugus-Newhall, Cal.
Dr. R. W. Johnson	District Surgeon	San Fernando, Cal.

Note.—Emergency Surgeons should be summoned only for temporary treatment when prompt attention is required and when patients cannot be sent to or await arrival of Division or District Surgeon.

LOCATION OF HOSPITAL STRETCHERS

FRESNO	BAGGAGE ROOM	MOJAVE	BAGGAGE ROOM
	STORE ROOM		CAR SHOPS
	RELIEF TRAIN		
GOSHEN JUNCTION		SAUGUS	
BAKERSFIELD	BAGGAGE ROOM	EXETER	PORTERVILLE
	EMERGENCY HOSPITAL		COALINGA
	RELIEF TRAIN		HANFORD
	CAR SHOPS		OWENYO
TEHACHAPI			

LOCATION OF HOSPITALS

GENERAL HOSPITAL	SAN FRANCISCO
EMERGENCY HOSPITAL	BAKERSFIELD
WHITE MEMORIAL HOSPITAL	LOS ANGELES



RATING OF LOCOMOTIVES—SAN JOAQUIN DIVISION

In M's of 1000 Lbs. Back of Tender.

Nominal Class	Official Class	Engine Numbers	Boiler Pressure	Bakersfield and Fresno via Goshen Jct., Bakersfield and Kerman via Armona	Famoso and Fresno, via Exeter	Rosamond and Lancaster	Bakersfield to Rosamond	Lancaster to Saugus	Saugus to Lancaster	Rosamond to Bakersfield	Los Angeles to Saugus	Saugus to Los Angeles
M-4	M-63 20/28 135-S	1617 to 1713	190	4150	3300	4150	580	750	680	680	730	820
M-4	M-63 20/28 126	1617 to 1713	190	3950	3150	3950	580	740	670	670	730	820
M-8	M-63 21/28 159-S	1721 to 1803	200	4850	3800	4850	700	900	820	820	930	000
M-6	M-63 21/28 150-S											
M-9	M-63 21/28 150-S	1806 to 1822	210	5100	4050	5100	760	970	890	890	990	1100
M-11	M-63 21/28 153-S	1831	210	5100	4050	5100	780	1000	910	910	990	1100
M-11	M-63 22/28 153-S & 162-SF	1832 to 1835	200	5300	4200	5300	780	1000	910	910	990	1100
T-23	T-63 21/28 156-S	2301 to 2310	210	5050	4000	5050	730	940	850	850	930	1030
T-23	T-63 21/28 163-SF											
T-28, 31	T-63 22/28 162-S	2311 to 2362	210	5550	4400	5550	820	1050	950	950	1050	1200
T-32	T-69 23/28 174-S	2363 to 2370, 2372 to 2384	210	5700	4500	5700	860	1050	990	990	1050	1200
P-1, 3, 5	P-77 22/28 141-S	2400 to 2452, 2459, 2460	210	4600	3600	4600	630	800	740	740	800	890
P-4	P-77 23/28-155/B 58-SF	2400 to 2437	210	5000	3950	5000	690	870	800	800	900	1100
P-6	P-77 25/28 172-S	2453 to 2458	200	5650	4450	5650	810	1000	940	940	1000	1150
P-10	P-73 25/30 181-SF	2478 to 2483	200	6250	4950	6250	830	1100	980	980	1100	1250
P-10	P-73 25/30-183/B-63-SF	2484 to 2491										
C-9, 10	C-57 22/30 200-SF	2513 to 2599, 2698 to 2860	210	6100	4800	6100	900	1150	1050	1050	1200	1300
C-9, 10	C-57 22/30 194-S											
C-8	C-57 22/30 192-S											
C-5	C-57 22/30 187-S											
C-5	C-57 22/30 185-S	2680 to 2693										
A-6	A-81 22/28-127/B-64-SF	3000 to 3003	210	4400	3450	4400	600	750	690	690	700	800
A-3	A-81 20/28 112-S	3025 to 3040, 3043 to 3071	210	3600	2850	3600	450	580	530	530	550	630
A-3	A-81 20/28-116/B-59-S	3025 to 3040, 3043 to 3071										
Mk-5, 6	Mk-63 26/28 210-S	3241 to 3277	210	7800	6200	7800	1200	1500	1350	1350	1450	1600
Mk-5, 6	Mk-63 26/28 231-SF	3300 to 3324	176	8550	6750	8550	1300	1650	1500	1500	1650	1850
Mk-7, 8, 9	Mk-63 29/30 247-S & 257-SF											
F-4, 5	F-63 29 1/2/32-306/B-61-SF	3668 to 3768	200	10,200	8050	10,200	1500	1950	1750	1750	2100	2300
F-5	F-63 29 1/2/32-306/B-62-SF											
AC-1, 2, 3	AC-57 23 1/2/30 441-SF	4000 to 4048	210	12,300	9750	12,300	1900	2450	2200	2200	2250	2450
AC-4	AC-63 24 1/2/30 475-SF	4100 to 4125	235	16,000	12,700	16,000	2500	3200	2900	2900	3200	3500
AC-5	AC-63 24 1/2/30 483-SF											
Mt-1,3,4,5	Mt-73 28/30-246/B-60-SF	4300 to 4376	210	8350	6600	8350	1150	1500	1350	1350	1550	1750
GS-1	GS-73 27/30 262/B-104-SF	4400 to 4415	250	9000	7050	9000	1200	1550	1400	1400	1600	1800
GS-2	GS-73 27/30 266/B-104-SF											
GS-3	GS-80 26/32 267/B-105-SF	4416 to 4429	280	9200	7250	9200	1250	1600	1450	1450	1650	1850
SP-1	SP-63 22 1/2/30 316/B-60-SF	5000 to 5048	225	12,000	9500	12,000	1800	2350	2100	2100	2450	2700
SP-2, 3	SP-63 22 1/2/30 317/B-61-SF											
Allowance for Empty and Underloaded Cars.				Less than 40 Ms.	6	6	6	3	3	3	3	3
				40 Ms. to 50 Ms.	3	3	3	0	0	0	0	0
				More than 50 Ms.	0	0	0	0	0	0	0	0

MAIN LINES		Owned By	
SAN JOAQUIN DIVISION:			
End Western Division to Goshen Jct.	C. P. Ry.	40.10	
Goshen Jct. to Saugus	S. P. R. R.	211.02	
Fresno to Famoso, via Exeter	S. P. R. R.	103.95	
Total main Lines			355.07
BRANCHES		Owned By	
Arvin	S. P. Co.	Magunden to Arvin	16.89
Clovis	S. P. R. R.	Fresno to Friant	24.14
Coalinga	S. P. R. R.	Armona to Crump	41.02
		(Barton to Hammond)	2.29
Fresno Interurban	F. I. Ry. Co.	(Barton to Belmont Ave.)	14.60
Kerman	S. P. R. R.	Kerman to Goshen Jct., via Armona	51.37
McKittrick	S. P. R. R.	Bakersfield to Olig.	50.07
Minkler Southern	A. T. & S. F. Ry.	Porterville to Ducor	12.53
Oil City	S. P. R. R.	Oil Junction to Oil City	6.76
Owenyo	C. P. Ry.	McJave to Owenyo	143.15
Pernu	S. P. Co.	Pernu Jct. to Pernu	1.48
Riebgrove	S. P. R. R.	Riebgrove to Jovista	4.16
Riverdale	S. P. R. R.	Ingle to Hardwick	42.15
Stratford	S. P. R. R.	Rossi to Stratford	8.26
Success	S. P. Co.	Porterville (Olive St.) to Clavicle	13.43
Visalia	S. P. R. R.	Goshen Junction to Exeter	16.76
Total Branches			449.06
Total San Joaquin Division			804.13

These ratings include the total weight of train, exclusive of engine and tender, which the different class of locomotives will haul in each direction between the stations shown.

CLASS "C"—Consolidation engine "M"—Moguls "Mk"—Mikado "E"—Eight-wheeler "T"—Ten-wheelers "TW"—Twelve-wheelers "P"—Pacific Type


Example:—Consolidation engine having 57-inch drivers, Cylinders 22-inch diameter and 30-inch stroke, and weighing 187,000 pounds on Drivers: C-57  $\frac{22}{30}$  187

C. G. TANDY, Trainmaster, Fresno  
 A. H. HOFFMAN, Trainmaster—Road Foreman of Engines, Bakersfield  
 F. E. KALBAUGH, Asst. Trainmaster, Bakersfield, July 1, 1938

E. F. WASEM, Chief Dispatcher,  
 P. E. TURNER, Asst. Chief Dispatcher,  
 J. S. FOCKLER, Asst. Chief Dispatcher.

B. W. MITCHELL, Asst. Superintendent.






# MAP OF THE SAN JOAQUIN DIVISION

SOUTHERN PACIFIC COMPANY

JUNE, 1918.  
J. F. M.

REVISED OCT. 6, 1938  
 JAN. 1, 1930  
 JULY 15, 1920  
 FEB. 15, 1910  
 JAN. 7, 1900  
 JAN. 7, 1893.



TULARE LAKE