SPEED RESTRICTIONS

Location	Passenger Trains M. P. H.	Freight Trains M. P. H.
Maximum SpeedEastward track Westward track	79 79	60 50
Operating against current of traffic Trains making back-up movement on the west- ward track between St. Croix tower and St.	59	49
Poul	20	20
All crossovers, turnouts and sidings unless otherwise specified	10	10
Newport, Westward track to lead tracks of St. Paul Yard, and through crossovers between		
Eastward and Westward tracks at Oakland	25	25
St. Croix Interlocking Eastward track	40	25
Westward track	30	25
Through turnout from Eastward track to CB&Q Eastward track	30	25
CB&Q Westward trackBetween St. Croix Tower and MP 415.25Q	30	25
Westward track	55	40
Between MP 415.25Q and MP 418.25Q Westward track Between MP 406.50 CMStP&P and Daytons	60	40
Bluff Westward track	75	
Through Interlockings at Oakland	75 45	25
Division Street	30	25
Eastward track Between MP 396.62 CMStP&P and MP 395.60	75	
CMStP&P Eastward track Between MP 395.60 CMStP&P and St. Croix	75	
Tower Eastward track	55	35

SPECIAL INSTRUCTIONS

The two main tracks of the C.M.St.P.&P. and CB&Q Railroads between St. Croix Tower and St. Paul are used as joint tracks. The C.M.St.P.&P. operate the eastward track and train orders will be issued over the signatures of the Superintendent at La Crosse. The CB&Q operate the westward track and train orders will be issued over the signature of the Superintendent at Cicero.

These tracks are operated as double track. Unless otherwise provided by train order, trains must keep to the left. ABS is in use between St. Croix Tower and Division Street.

Rules 251, 252, 253 and 254 are in effect—EXCEPT CTC is in use on westward track between M.P. 403.43 and M.P. 406.34 and is controlled

by the train dispatcher at Newport.

6.M.St.P.&P. Automatic Block and Interlocking signal aspects apply between Newport and St. Paul on westward track and between Newport and St. Croix Tower on eastward track.

Burlington Lines Automatic Block and Interlocking signal aspects as contained in the 1967 edition Consolidated Code of Operating Rules apply between St. Croix Tower and Newport on westward track and between St. Paul and Newport on eastward track.

In compliance with Rule D-91, the following will apply:

Where trains are to be moved against the current of traffic, following trains will not be permitted to enter the block until the preceding train

Stop indication must be displayed immediately after rear of a train has passed the signal, and following trains will not be permitted to enter the block until it is clear of the preceding train.

Rules 91 and 91-A do not apply for movements against the current

Protection against following trains on the same track is not required of trains moving against the current of traffic. This provision does not apply to any unit of equipment which does not actuate block or cab signals, or to a work extra.

Extra trains may be operated on eastward and westward tracks with current of traffic without train orders.

Rule 83(B) does not apply at St. Croix Tower, Newport and Oakland if train order signal indicates proceed and only applies to eastward C.B.&Q. passenger trains at St. Paul. Such trains must obtain both a CMStP&P and a CR&Q clearance.

Interlockings are located at St. Croix Tower, Newport, Oakland, Hoffman Avenue and Division Street.

C.R.I.AP, trains will use joint tracks between Newport and St. Paul. Train order signal at Newport does not govern C.R.I.&P. trains leaving C.M. St.P.&P.-C.B.&Q. joint tracks.

At Oakland, the westward train order signal does not govern trains terminating at Oakland or Daytons Bluff.

The Consolidated Code of Operating Rules, Edition of 1967, in addition to the following instructions will govern employes while operating on Minnesota Transfer Railway Co. and The St. Paul Union Depot Com-

(a) All trackage of the Minnesota Transfer Railway Company is defined as a system of tracks within yard limits over which movements must be made at reduced speed and are not authorized by time-table. or train order, but subject to prescribed signals and rules or special

The limits of The Saint Paul Union Depot Company property extend from connection with the Northern Pacific Ry. and Great Northern Ry-track at Third Street and connection with the C.M.St.P.&P.-C.B.&Q. R.R. tracks opposite depot round-house, on the east, to connection with the C.G.W. Ry, and C.M.St.P.&P. R.R. tracks at Robert Street on the west.

(b) The time-table of The Saint Paul Union Depot Company is for information only. Employes of railroads using the tracks of this Com-pany will be governed by current time-table of their respective Com-panies only as to arriving and departing time of trains.

(c) Where in the rules of the Consolidated Code reference is made to trains, such rules will also apply to yard movements and engines.

(e) Under Rule 11, burning fusees must not be used except in case of emergency and then only when held in hand and must be extin-guished before leaving.

(f) There is no superiority of trains within the limits of The Saint Paul Union Depot Company property.

(g) Within the limits of The Saint Paul Union Depot Company property trains and engines must move at restricted speed and must not exceed ten (10) miles per hour through crossovers, turnouts and puzzle

The entrance to and all movements on this property will be made only on authority of hand signals from switch tenders. No train or engine may foul any track or puzzle switch without authority of hand signals from switch tenders in control of such movements, except that short interior switching movements may be made through crossovers connecting shed tracks when authorized by train director.

Any lead or track may be used for the make-up of trains on authority of train director. The movement of trains should be given preference. Switchtenders are equipped with yellow lightbulbs in their lanterns so as to distinguish their signals from other signals.

(h) When indicated by the ringing of the bell, flashing of headlight, hand or light signal that a train or engine is ready to move, the switch-tender in charge of the shed track on which the movement is standing will handle as follows: at west end of station the switchtender will control the movement by hand or light signal; at the east end of station the switchtender will inform the train director, who will route the movement by instructions over the public address system. Switchtenders will be governed by these instructions relaying such instructions between the public address system. will be governed by these instructions, relaying such instructions by hand or light signal to the next switchtender in the direction of the movement, each must receive an acknowledgment before signalling the movement. Signals must not be acknowledged or acted upon unless the signal corresponds with instructions from the train director and is

(i) When backing, the back-up air brake valve on passenger trains must be operated by the conductor, except in the movement of empty equipment, it may be operated by a competent trainman or yardman. When practicable, conductors must see that trainmen are stationed so hand or light signals may be used, in case of any emergency.

When backing a train, the engine brake valve must be in running position; an application of the brakes must be made with back-up air brake valve before starting and it must be known that the brakes are in operative condition. Movement must not be started until the proper signal is given. A running test must be made with the back-up air brake valve before the train has moved 300 feet; if the running test is not made within 300 feet the engineer must stop the train and ascer-tain cause. The speed of train must not exceed eight (8) miles per hour and train must be under such control that it can be stopped short of train, or obstruction, and short of bumping post on stub tracks.

(1) Headlights must be dimmed while on shed tracks

(k) Vestibule doors are to remain closed when trains are pulling or backing into the St. Paul Union Depot until the train comes to a com-

Seconds	Miles	Seconds	Miles
per Mile	per Hour	per Mile	per Hour
40	90	62	58.1
42.4	85	63	57.1
45	80	64	56.3
46	78.3	65	55.4
47	76.6	66	54.5
48	75	67	53.7
49	73.5	68	52.9
50	72	69	52.2
51	70.6	70	51.4
52	69.2	75	48
53	67.9	80	45
54	66.7	85	42.4
55	65.5	90	40
56	64.3	100	36
57	63.2	120	30
58	62.1	144	25
59	61	180	20
60	60	240	15
61	59	360	10

CHICAGO, MILWAUKEE, ST. PAUL AND PACIFIC RAILROAD CO.

CHICAGO, BURLINGTON & QUINCY RAILROAD CO.

JOINT TIME TABLE No. 1

Taking effect at 12:01 A. M. **Central Standard Time**

Sunday, June 9, 1968

For the government and information of employes only

TRACK OPERATED BY CHICAGO, BURLINGTON & QUINCY RAILROAD CO.

ST. CROIX TOWER TO ST. PAUL-WESTWARD

	1	2171	ALC:	FIRST CLASS																					
		Office Hours	57	47	1	55	21	5	421	3	25	23													1
	nee from roix Tow	Hours	C. M. St. P. & P. Passenger	C. B. & Q. Passenger	C. M. St. P. & P. Passenger	C. M. St. P. & P. Passenger	C. B. & Q. Passenger	C. M. St. P. & P. Passenger	C.R.I.& P. Passenger 18	C. M. St. P. & P. Passenger	C. B. & Q Passenger	C. B. & Q. Passenger	٠.			e .									
	Distar		Daily	Daily	Daily	Daily	Daily	Daily	Daily	Daily	Daily	Fri. & Sun. Only													
ST. CROIX TOWER		Continuous	4.12	6.29 AN	6.23	10.01	2.01 PM	5.57 PM		6.48 PM	7.20 PM	10.43PM			1										
CURRY	5.0	No Office																							
ST. PAUL PARK	10.7	No Office																							
NEWPORT	11.9	Continuous							6.16 PM											100					
RED ROCK	13.0	No Office						17.14		971 1											11				
DUNN	14.8	No Office																		F 12					
OAKLAND	16.4	Continuous																		01-01-					
DAYTONS BLUFF	17.7	No Office			- 1																				
HOFFMAN AVENUE	18.6	Continuous																						THE THE	
DIVISION STREET	19.2	No Office													- 1										
ST. PAUL	20.0	6.00 AM to 12.01 AM	A 4.45 M	A 7.20 M	A 7.00 M	A10.40	A 2.40 ₽	A 6.25 PM	A 6.30 PM	A 7.15 PM	A 8.00 PM	A11.25PM							-		- 01				

R. A. MOLITOR, Chief Dispatcher, Cicero, III.

J. A. BEEBE, Superintendent of Terminals, Dayton Bluff, Minn. J. D. LARSON, Assistant Superintendent, North La Crosse, Wis. C. J. MILLER, Superintendent, Cicero, III. Train Dispatchers, Newport.
F. W. WALTON, P. A. MADSEN,
H. E. OTTERNESS, C. MILLER.
J. B. DALEY,

TRACK OPERATED BY CHICAGO, MILWAUKEE, ST. PAUL & PACIFIC RAILROAD CO.

ST. PAUL TO ST. CROIX TOWER-EASTWARD

TIME TABLE No. 1		Capacity in Cars		FIRST CLASS																					
		-	-	6	32	58	420	2	24	56	48	4													
June 9, 1968	nee from			C. M. St. P. & P. Passenger	C. B. & Q. Passenger	C. M. St. P. & P. Passenger	C.R.I.&P. Passenger 17	C. M. St. P. & P. Passenger	C. B. & Q. Passenger	C. M. St. P. & P. Passenger	C. B. & Q. Passenger	C. M. St. P. & P. Passenger								B	-			14	
STATIONS	Distar St. Pa	g 6	track	Daily	Daily	Daily	Daily	Daily	Daily	Daily	Daily	Daily								le s					
ST. CROIX TOWER	18.4	4	_	A 8.23 AM	A 8.30 AM	A10-30 AM		A12-58 PM	A 4.40 PM	A 8.34 PM	▲11.05P	A11.40PM													
CHEMOLITE	14.4	35		190 119	1997		71														Brery				
NEWPORT	8.1		119				A11.25M																		
RED ROCK	7.0																								
OAKLAND	3.6	3	ard																						
DAYTONS BLUFF	2.3	, ,	Yard							*															
HOFFMAN AVENUE	1.4	1																		tarons	D half				
DIVISION STREET	0.8																			100			h = n n		
ST. PAUL			Yard	8.05 AM	8-10 AM	10-10AM	11.15M	12.40PM	4.25 №	8-15P	10.45PM	11.20PM				The Marie of the	Lillian Post							ion rom b	

A. G. BEAUVIAS, G. A. McCOLE, S. C. PULFORD, S. J. BARRY, Trainmasters

D. K. KRIDER, Traveling Engineer-Trainmaster C. D. ANDERSON, Ass't Supt. E. P. SNEE, Ass't. Supt. N. H. McKEGNEY, Superintendent H. M. HARRIS, Chief Dispatcher, La Crosse, Wis. C. Y. DEMPSEY,
Traveling EngineerTrainmaster

W. J. WESTMARK, Trainmaster, La Crosse, Wis. M. T. SEVEDGE, Superintendent, La Crosse, Wis.

T. C. T. St. Paul Between Newport and St. Paul

Between St. Croix Tower and Newport