

E. O. CHADDOCK,
Asst. Superintendent Oklahoma City, Okla.
R. E. CALDWELL, Trainmaster Newton, Kans.
T. H. LINN, Trainmaster Newton, Kans.
B. D. JOHNSTON, Trainmaster Newton, Kans.
A. C. RICKETTS, Road Foreman of Engines Emporia, Kans.
R. G. SHAW, Road Foreman of Engines Newton, Kans.
C. W. SMITH, Road Foreman of Engines Arkansas City, Kans.
R. D. MARTIN, Chief Dispatcher Newton, Kans.
M. C. SEELY, Asst. Chief Dispatcher Newton, Kans.
C. M. GREGORY, Asst. Chief Dispatcher Newton, Kans.
R. F. SHIELDS, Asst. Chief Dispatcher Newton, Kans.
C. A. MATHIES, Asst. Chief Dispatcher Newton, Kans.

TRAIN DISPATCHERS—NEWTON, KANSAS

R. H. WILLIS	W. G. WILLIAMS	E. M. SMITH
M. E. HOWELL	B. L. JOSEPH	C. H. TATE
S. R. BELEW	B. J. ECKERT	R. N. MASON
J. Q. COOPER	W. G. BURTON	S. P. MARK
G. O. THOMAS	D. L. RESER	R. C. COPPOCK
H. E. SHEPHERD	W. P. VAUGHN	J. L. MITCHAM
	D. S. OSBURN	G. H. HARDEY

AVOID DAMAGE—SWITCH CUSTOMERS CARS CAREFULLY

OVERSPEED Couplings are **DAMAGING**—Here's what happens:

Speed	SAFE COUPLING SPEED
4 miles per hour <input type="checkbox"/>	Damage Begins
5 miles per hour <input type="checkbox"/>	2½ times as damaging as 4 MPH
6 miles per hour <input type="checkbox"/>	3 times as damaging as 4 MPH
7 miles per hour <input type="checkbox"/>	4 times as damaging as 4 MPH
8 miles per hour <input type="checkbox"/>	5 times as damaging as 4 MPH
9 miles per hour <input type="checkbox"/>	6 times as damaging as 4 MPH
10 miles per hour <input type="checkbox"/>	

Damage to freight or car can be avoided by always keeping coupling speed within the safe range—**NOT OVER 4 MILES PER HOUR—A BRISK WALK.**

HANDLE FREIGHT CAREFULLY AND KEEP OUR CUSTOMERS

IT'S EVERYBODY'S JOB ON THE SANTA FE

SPEED TABLE

Table of speeds (minutes and seconds per mile, in terms of miles per hour).

Time Per Mile Min. Sec.	Miles Per Hour	Time Per Mile Min. Sec.	Miles Per Hour	Time Per Mile Min. Sec.	Miles Per Hour
36	100	58	62.1	1 40	36.0
37	97.3	59	61.0	1 42	35.3
38	94.7	1	60.0	1 44	34.6
39	92.3	1 02	58.0	1 46	34.0
40	90.0	1 04	56.2	1 48	33.3
41	87.8	1 06	54.5	1 50	32.7
42	85.7	1 08	52.9	1 52	32.1
43	83.7	1 10	51.4	1 54	31.6
44	81.8	1 12	50.0	1 56	31.0
45	80.0	1 14	48.6	1 58	30.5
46	78.3	1 16	47.4	2	30.0
47	76.6	1 18	46.1	2 05	28.8
48	75.0	1 20	45.0	2 10	27.7
49	73.5	1 22	43.9	2 15	26.7
50	72.0	1 24	42.9	2 30	24.0
51	70.6	1 26	41.9	2 45	21.8
52	69.2	1 28	40.9	3	20.0
53	67.9	1 30	40.0	3 30	17.1
54	66.6	1 32	39.1	4	15.0
55	65.5	1 34	38.3	4 30	13.3
56	64.2	1 36	37.5	5	12.0
57	63.2	1 38	36.8	6	10.0

**The Atchison, Topeka and Santa Fe
Railway Co.**

EASTERN LINES

MIDDLE DIVISION

TIME TABLE No.

19

IN EFFECT

Monday, July 12, 1971

At 12:01 A. M.

Central Standard Time

This Time Table is for the exclusive use and guidance of Employees.

L. M. OLSON,
General Manager,
Topeka, Kansas

L. P. HEATH,
Asst. General Manager,
Topeka, Kansas

J. R. FITZGERALD,
Superintendent,
Newton, Kansas

Siding Capacity 50 Ft. Per Car	WESTWARD		Ruling Grade Ascending	TIME TABLE No. 19 July 12, 1971	Ruling Grade Ascending	Mile Post	Communications Turn Tables and Wyes	EASTWARD	
	First Class							First Class	
	17	15						18	16
	Leave Daily	Leave Daily	Feet Per Mile	STATIONS	Feet Per Mile			Arrive Daily	Arrive Daily
	AM 4.00	AM 3.35	6.1	EMPORIA YL 3.2	21.2	112.1	T C R	AM 3.30	PM 11.05
			6.1	MERRICK YL 4.9	0	115.3			
			4.4	PLYMOUTH 3.2	0	120.2			
			6.8	SAFFORDVILLE 2.0	0	123.4			
	4.10	3.45	9.2	ELLINOR 6.3	0	125.4		3.16	10.50
W 103 E 119	4.15	3.50	10.4	STRONG CITY 4.1	0	131.7	Y C	3.11	10.45
	4.18	3.53	0	NEVA 2.5	0	135.8	B	3.07	10.42
			17.4	ELMDALE 7.3	12.8	138.3			
E 81	4.25	4.00	13.0	CLEMENTS 5.1	0	145.6	B	2.59	10.34
W 58 E 54			0	CEDAR POINT 6.2	0	150.7			
W 129 E 185	4.34	4.10	19.3	FLORENCE 11.4	0	156.9	C	2.50	10.25
W 103 E 57	4.43	4.18	14.8	PEABODY 0.3	0	168.3	C	2.41	10.16
			45.4	C.R.I.&P. Crossing 9.7	16.3	168.6			
	4.51	4.26	0	WALTON 6.3	21.1	178.3		2.33	10.08
			0	Mo. Pac. Crossing 0.5	19.1	184.6			
	5.05 AM	4.40 AM		NEWTON YL		185.1	T Y C R	2.25 AM	10.00 PM
	Arrive Daily	Arrive Daily		(73.0)				Leave Daily	Leave Daily
	67.4	67.4		Average speed per hour				67.4	67.4

RULE 251 IN EFFECT:

Emporia to Mo. Pac. crossing Newton except westward Main Track between interlocking Strong City and interlocking Neva, and on Main Track No. 3 between Merrick and Ellinor.

RULES 261 AND T.C.S. IN EFFECT:

Main Track No. 3 between Merrick and Ellinor.

Westward Main Track between interlockings Strong City and Neva.

Trains originating Emporia, Newton and Sand Creek must secure numbered clearance card.

Strong City District and McPherson District trains originating Emporia, Sand Creek or Newton must secure two

clearance cards—one marked "First District" and one marked "Strong City District" or "McPherson District". McPherson District trains also secure Rock Island clearance card.

Between Merrick and Ellinor north track designated Main Track No. 2 upon which the current of traffic is westward; middle track designated Main Track No. 1 upon which the current of traffic is eastward and south track is designated Main Track No. 3 upon which there is no current of traffic.

At Newton between Mo. Pac. crossing and interlocked crossover M.P. 186 Second District, the first six tracks south of passenger station are designated as passenger yard tracks 1, 2, 3, 4, 5 and 6. Trains and engines using these tracks must move at restricted speed.

MAXIMUM AUTHORIZED SPEED FOR TRAINS

	MPH	
	Psg.	Fr.
Emporia to Newton	90	60*

*Freight trains may observe passenger train speed but not to exceed 70 MPH, provided:

- (1) Maximum district speed is 60 MPH for freight trains.
- (2) Train does not exceed 5000 tons.
- (3) Train does not exceed 90 cars.
- (4) Train does not average more than 70 tons per car.
- (5) Locomotive can control speed to 70 MPH without use of air brakes.

EXCEPTIONS:

- (A) Westbound — M.P. 167 to M.P. 168.5
M.P. 181 to Newton
- Eastbound — M.P. 176.5 to M.P. 163.5
M.P. 147.5 to M.P. 139.5
M.P. 117.5 to Emporia

(B) Maximum authorized speed for freight trains when averaging:

- 71 to 84 tons per car 60 MPH
- 85 tons and over per car,
or over 7000 tons total 45 MPH

SPEED RESTRICTIONS - CURVES AND RR CROSSINGS:

	MPH
Curve, M.P. 132.4 to 132.8	75
Curve, M.P. 133.7 to 133.9	60
Curve, M.P. 135.9 to 136.4	75
Curve, M.P. 162.6 to 162.9	75
3 Curves, M.P. 166.4 to 170.5	75
RR Crossing, M.P. 168.6 (Auto. Interlocking)	90
4 Curves, M.P. 173.3 to 175.9	75
RR Crossing, MP 184.6 (Interlocking)	20

SWITCHES AND SIDINGS—MAXIMUM AUTHORIZED SPEED

Maximum authorized speed 10 MPH heading in or out over other than main track switches; 15 MPH over main track switches except those listed herein. Trains or engines trailing through and springing points of spring switches will not exceed speed prescribed for turnout. Trains or engines using siding will not exceed maximum turnout speed for that siding.

"I"—Interlocked Switch
"S"—Spring Switch

STATION	TYPE	SWITCHES AND TURNOUTS	MPH
Merrick	I	West crossover between Main tracks Nos. 3 and 1 and two West crossovers between Main tracks Nos. 2 and 1.	50
		Other crossovers and turnouts from Main track No. 3 to yard track.	30
Ellinor	I	Main track turnouts and crossovers except turnout connecting Fourth District and track No. 3 First Dist.	40
	I	Turnout connecting Fourth District and track No. 3 First District	70
Strong City	I	West end eastward siding	40
	I	East end westward siding	40
	I	Crossover from eastward to westward track	30
	S	West end westward siding	30
	S	East end eastward siding	30
Neva	I	Turnout to Strong City District	20
Florence	I	West end eastward siding	40
	I	East end westward siding	40
	S	East end eastward siding	30
	S	West end westward siding	30
Peabody	S	West end westward siding	30
Newton	S	East end freight yard connection and passenger yard track No. 3.	30
	S	West end crossover between main tracks east of Mo. Pac. crossing	30
	I	East end crossover between main tracks east of Mo. Pac. crossing	30

OVERHEAD OBSTRUCTIONS (Rule 761)

Mile Post	Name
Yard	Newton, cinder pit hoist.

Siding Capacity 50 Ft. Per Car	WEST-WARD		Ruling Grade Ascending	TIME TABLE			Ruling Grade Ascending	Mile Post	Communications Turn Tables and Ways	EAST-WARD	
	First Class	17		No. 19						First Class	18
	Leave Daily			July 12, 1971						Arrive Daily	
	AM		Feet Per Mile	STATIONS	Feet Per Mile					AM	
	5.10	0		NEWTON YL } 2 Tracks					T	AM	
		21.1		1.6 SAND CREEK } 2 Tracks	31.8	185.1	CR		a	2.20	
				7.9	15.8	186.7	YRC				
60				HALSTEAD	0	194.6	C				
120		21.1		9.1 BURRTON		203.7				1.57	
200	5.25			0.4 S.L.-S.F. Crossing	0	204.1					
			9.5	10.8 WAY	0	214.9	YR				
			0	1.6 C.R.I.&P. Crossing	0	216.5					
663	s 5.40		0	1.5 HUTCHINSON	0	218.0	YRC	s		1.43	
			0	0.3 CH JCT.	0	218.3					
			0	0.9 ND JCT.	0	219.2	B			1.39	
	5.42	21.1		4.2 Mo. Pac. Crossing YL	0	219.2					
82	5.46	0		WHITESIDE	0	223.4	B			1.35	
82	5.50	21.1		5.5 PARTRIDGE	0	228.9				1.31	
200	5.55	21.1		6.2 ABBYVILLE	0	235.1	B			1.27	
84	5.59	21.1		5.6 PLEVNA	20.3	240.7	B			1.23	
88		21.1		5.7 SYLVIA	0	246.4	C			1.19	
200	6.06	21.1		4.7 ZENITH	0	251.1	B			1.15	
84	6.10	0		5.9 STAFFORD	0	257.0	C			1.11	
		0		0.2 Mo. Pac. Crossing	0	257.2					
200	6.16	21.1		8.8 ST. JOHN	0	266.0	CR			1.04	
85	6.21	15.8		6.8 DILLWYN	0	272.8	B			12.59	
				4.8	0						
82	6.25	15.8		MACKSVILLE	0	277.6	CR			12.55	
200	6.30	0		7.3 BELPRE	0	284.9	B			12.50	
				8.4	0						
84	6.36	0		LEWIS	0	293.3	C			12.44	
				9.1	0	302.4	Y				
135	6.44	21.1		KINSLEY YL	0	(318.7)	CR			12.37	
99				8.0	0						
101		21.1		OFFERLE	0	324.7	C				
141		21.1		5.6 BELLEFONT	0	330.3					
153		21.1		5.8	0						
105				SPEARVILLE	24.2	336.1	CR				
		24.2		8.6	24.2						
144	7.04	26.5		WRIGHT } 2 Tracks	26.5	344.7				12.17	
	s 7.20			7.8 DODGE CITY YL		352.5	TY			12.08	
	AM						CR			AM	
	Arrive Daily			(153.1)						Leave Daily	
	70.6			Average speed per hour						69.6	

See special rule 6 regarding home signal indications of interlockings at Wright and Dodge City.

RULE 261 IN EFFECT:

On main tracks, M.P. 186 (Newton) to ND Jct.

On main tracks Kinsley to M.P. 352.1 (Dodge City).

On sidings Halstead, Burrton, Hutchinson and Kinsley.

Trains originating Newton, Sand Creek and Dodge City must secure numbered clearance card.

At Newton between Mo. Pac. crossing and interlocked crossover M.P. 186 Second District, the first six tracks south of passenger station are designated as passenger yard tracks 1, 2, 3, 4, 5 and 6. Trains and engines using these tracks must move at restricted speed.

At Hutchinson between C.R.I.&P. crossing and CH Jct. first track north of siding is designated as running yard track No. 3.

At Dodge City between M.P. 352.1 and M.P. 352.8 there is no superiority of trains. Trains and engines within these limits will move at restricted speed; between these points main track may be used not protecting against regular trains, extras or engines.

MIDDLE DIVISION

MAXIMUM AUTHORIZED SPEED FOR TRAINS

	MPH	
	Psgr.	Frts.
Newton to CH Jct.	79	60*
CH Jct. to Dodge City	90	60*

*Speed limit 45 MPH for trains handling in excess of 7000 tons.

SPEED RESTRICTIONS - CURVES AND RR CROSSINGS:

	MPH	
	Psgr.	Frts.
Curve, M.P. 187.3 to 187.8	65	55
RR Crossing, M.P. 204.1 (Interlocking)	79	60
RR Crossing, M.P. 216.5 (Interlocking)	40	40
Curve, M.P. 218.4 to 218.6	40	30
RR Crossing, M.P. 219.2 (Interlocking)	40	40
2 Curves, M.P. 219.4 to 220.2	55	50
Curve, M.P. 228.3 to 228.8	75	60
RR Crossing, M.P. 257.2 (Auto. Interlocking)	85	60
Curve, M.P. 257.2 to 257.5	85	60
Curve, M.P. 266.1 to 266.5	85	60
Curve, M.P. 301.7 to 302.0	55	55
2 Curves, M.P. 348.0 to 349.8 WB	75	60
2 Curves, M.P. 348.0 to 349.8 EB	70	60
Curve, M.P. 352.0 to 352.1	20	20

SWITCHES AND SIDINGS—MAXIMUM AUTHORIZED SPEED

Maximum authorized speed 10 MPH heading in or out over other than main track switches; 15 MPH over main track switches except those listed herein. Trains or engines trailing through and springing points of spring switches will not exceed speed prescribed for turnout. Trains or engines using siding will not exceed maximum turnout speed for that siding.

"I"—Interlocked Switch

"S"—Spring Switch

STATION	TYPE	SWITCHES AND TURNOUTS	MPH
Sand Creek	I	Crossover M.P. 186	40
	I	West end yard. Main track switches	30
	I	Turnout end two tracks M.P. 190	40
Halstead	I	Both ends siding	40
Burrton	I	Both ends siding	40
M.P. 212.6	I	East end siding	40
Way	I	Crossover east end yard	30

SWITCHES AND SIDINGS—MAXIMUM AUTHORIZED SPEED—(Cont'd).

"I"—Interlocked Switch
 "S"—Spring Switch

STATION	TYPE	SWITCHES AND TURNOUTS	MPH
CRI&P Crsg. (M.P. 216.5)	I	First crossover west of CRI&P crossing between main track and siding	40
	I	Second crossover west of CRI &P crossing between siding and main track	15
	I	First crossover west of CRI&P crossing between running yard track No. 3 and siding	15
	I	Second crossover west of CRI &P crossing between siding and running yard track No. 3	30
CH Jct.	I	Crossover between main track and siding	30
	I	Turnout siding to Fifth District	30
	I	Turnout Fifth District main track to running yard track No. 3	15
ND Jct.	I	West end siding M.P. 219.1	40
	I	Turnout to Plains Division	15
Whiteside	S	Both ends siding	30
Partridge	S	Both ends siding	30
Abbyville	S	Both ends siding	30
Plevna	S	Both ends siding	30
Sylvia	S	Both ends siding	15
Zenith	S	Both ends siding	30
Stafford	S	Both ends siding	15
St. John	S	Both ends siding	30
Dillwyn	S	Both ends siding	15
Macksville	S	Both ends siding	15
Belpre	S	Both ends siding	30
Lewis	S	Both ends siding	15
Kinsley	I	Turnouts and crossovers between Depot and Colony Ave.	30
	I	West end siding (M.P. 318.4)	40
Offerle	I	Both ends both sidings	30
Bellefont	I	Both ends siding	30
Spearville	I	Both ends both sidings	30
Wright	I	East end siding	30
	I	Crossover M.P. 344.6	30
	I	Turnout from or to track No. 1 M.P. 344.7	40
Dodge City	I	Turnouts East end Freight leads	30
	I	Double Crossovers M.P. 350.1	30

INDUSTRY AND OTHER TRACKS BETWEEN STATIONS

Name	Location	Capacity
Paxton	M.P. 199.4	6 Cars

6 THIRD DISTRICT

MIDDLE DIVISION

Siding Capacity 50 Ft. Per Car	WEST- WARD	Ruling Grade Ascending	TIME TABLE No. 19 July 12, 1971	Ruling Grade Ascending	Mile Post	Communications Turn Tables and Wyes	EAST- WARD
	First Class						First Class
	15						16
	Leave Daily	Feet Per Mile	STATIONS	Feet Per Mile			Arrive Daily
	AM 4.50		NEWTON		185.1	TY CR	PM 9.50
		0	0.4 A.T.&S.F. Crossing FIRST STREET	27.8	185.5		
		0	2.5 McGRAW	27.8	188.0		
133		0	3.2 PUTNAM	18.0	191.2		9.30
146		0	4.0 SEDGWICK	5.5	195.2	C	
		0	6.6 VALLEY CENTER S.L.-S.F. Crossing	10.4	201.8		
130	5.05	0	7.3 NO. WICHITA YL	7.2	209.1	T CR	9.16
	5.11	0	1.0 Mo. Pac. Crossing	9.5	210.1		
		0	1.6 NORTH JCT. YL	10.8	211.7		9.12
	5.16	21.2	0.6 WICHITA U.S.	0	212.3	C	9.10
	5.30	0	0.9 SOUTH JCT.	28.8	213.2	Y	8.57
	5.32	31.7	4.2 CONNELL	10.9	217.4		
133		16.4	5.6 DERBY	31.7	223.0		
134		21.6	4.9 MULVANE	31.7	227.9	Y CR	8.43
265	5.47	31.7	10.0 UDALL	18.6	237.9	C	
124		0	11.8 WN JCT.	39.6	249.7	YR	8.20
183	6.10	13.5	0.7 S.L.-S.F. Crossing	16.3	250.4		
		0	0.4 WINFIELD	16.3	250.8	CR	
		31.7	5.3 HACKNEY	31.7	256.1	B	
156		31.7	7.3 ARKANSAS CITY	31.7	263.4	TY CR	8.05 PM
483	6.35 AM						Leave Daily
	Arrive Daily		(78.3)				44.7
			Average speed per hour				

Westward Third District trains will not leave passenger station Newton until verbal authority received from train dispatcher.

Westward Third District trains will not leave Sand Creek Yard until white train departure light, located west of McGraw Jct. switch, is displayed or authority received from train dispatcher.

Independent track between No. Wichita and No. Jct. is the first track south (time table direction) of eastward main track and will be used by westward trains and engines only on instructions of Yardmaster. Eastward movements may be authorized by signal indication at North Jct. Speed limit on independent track, 10 MPH between 15th Street and 22nd Street.

Eastward freight trains Englewood or Wichita Districts secure permission to proceed eastward from Wichita Junction before passing that point. Yard crews obtain permission to make through movement West Wichita to South Jct., or to foul Englewood District main track from south yard tail track.

Trains and engines between North Jct. and South Jct. will be governed by The Wichita Union Terminal Railway Company Special Rules and Regulations, which provide:

"Between interlocking North Jct. and interlocking South Jct. the two west tracks are main tracks signalled in both directions. Trains and engines using these main tracks will be governed by interlocking and block signals whose indications supercede the superiority of trains for both opposing and following movements on the same track.

Interlocking signals at North Jct. and South Jct. controlled by Santa Fe train dispatcher located at Newton, Kansas.

Speed limit 30 MPH on main tracks and through interlockings North Jct. and South Jct., except at South Jct. 15 MPH when using turnout to or from tail track, and when using crossover between main tracks to or from AT&SF Englewood District.

Speed limit 15 MPH heading in or out over all hand throw switches, and trailing through and springing points of spring switches.

Trains and engines using other than main tracks must move prepared to stop short of train, engine, obstruction, or switch not properly lined, but not exceeding 15 MPH.

Trains or engines on other than main track between North Jct. and South Jct. must secure permission from Santa Fe dispatcher before departing station.

Freight cars must not be handled on tracks adjacent to train sheds.

Except as provided above, crews on trains and engines operating over tracks of the Wichita Union Terminal Railway Company will be governed by rules and regulations of their respective company."

At Arkansas City between hand throw crossover M.P. 262.9 and interlocked crossover M.P. 264.1 maximum authorized speed on main track 20 MPH.

RULE 251 IN EFFECT:

M.P. 207.9 (No. Wichita) to North Jct.

RULE 261 IN EFFECT:

On main track and sidings.

First Street to M.P. 207.9 (No. Wichita) and North Jct. to Arkansas City.

Trains originating Newton, Sand Creek, North Wichita and Arkansas City secure numbered clearance card, except Plains Division trains originating North Wichita.

At Newton between Mo. Pac. crossing and interlocked crossover M.P. 186 Second District, the first six tracks south of passenger station are designated as passenger yard tracks 1, 2, 3, 4, 5 and 6. Trains and engines using these tracks must move at restricted speed.

MAXIMUM AUTHORIZED SPEED FOR TRAINS

	MPH	
	Psg.	Frt.
Newton to Arkansas City	90	60*

*Speed limit 45 MPH for trains handling in excess of 7000 tons.

Between WN Jct. and Arkansas City, freight trains may observe passenger train speed but not to exceed 70 MPH, provided:

- (1) Maximum district speed is 60 MPH for freight trains.
- (2) Train does not exceed 5000 tons.
- (3) Train does not exceed 90 cars.
- (4) Train does not average more than 70 tons per car.
- (5) Locomotive can control speed to 70 MPH without use of air brakes.

EXCEPTIONS:

Maximum authorized speed for freight trains when averaging:

71 to 84 tons per car	60 MPH
85 tons and over per car, or over 7000 tons total	45 MPH

SPEED RESTRICTIONS - CURVES AND RR CROSSINGS:

	MPH	
	Psg.	Frt.
RR Crossing, M.P. 185.5 (Interlocking)	20	20
2 Curves, M.P. 186.7 to 185.7, eastward	60	45
RR Crossing, M.P. 201.8 (Interlocking)	90	60
RR Crossing, M.P. 210.1 (Auto. Interlocking)	30	30
Curve, M.P. 227.7 to 227.9	65	60
3 Curves, M.P. 228.2 to 229.8	65	60
Curve, M.P. 233.6 to 233.9	75	60
Curve, M.P. 242.4 to 242.6	70	60
Curve, M.P. 243.2 to 243.4	60	50
3 Curves, M.P. 243.6 to 245.1	55	40
3 Curves, M.P. 245.8 to 248.0	50	40
6 Curves, M.P. 248.1 to 249.0	45	45
6 Curves, M.P. 249.7 to 251.9	45	45
RR Crossing, M.P. 250.4 (Interlocking)	45	45
2 Curves, M.P. 252.0 to 253.7	70	70
Curve, M.P. 260.4 to 260.7	70	70
Curve, M.P. 260.9 to 261.2	65	65

JOINT TRACK FACILITIES

WICHITA—A.T. & S.F. trains will use Wichita Union Terminal Ry. Co. tracks between North Jct. and South Jct.

WN JCT.-MULVANE-BELLE PLAINE—Mo. Pac. trains use A.T. & S.F. main track between WN Jct. and Belle Plaine via Mulvane, will be governed by A.T. & S.F. Time Table and Rules.

SWITCHES AND SIDINGS—MAXIMUM AUTHORIZED SPEED

Maximum authorized speed 10 MPH heading in or out over other than main track switches; 15 MPH over main track switches except those listed herein. Trains or engines trailing through and springing points of spring switches will not exceed speed prescribed for turnout. Trains or engines using siding will not exceed maximum turnout speed for that siding.

"I"—Interlocked Switch

"S"—Spring Switch

STATION	TYPE	SWITCHES AND TURNOUTS	MPH
McGraw	I	Turnout from Third District to Sand Creek Yard	30
Putnam	I	Both ends siding	40
Sedgwick	I	Both ends siding	40
Valley Center	I	Both ends siding	40
North Wichita	I	End of two tracks westward	40
	I	East end No. 1 yard track	30
Connell	I	Both ends siding	40
Derby	I	Both ends siding	40
Mulvane	I	East end of siding M.P. 225.3	40
	I	Crossover between Third District and Fourth District at Fourth District M.P. 220	40
	I	Other main track turnouts and crossovers east end of yard	30
	I	Main track turnouts and crossover west of depot	30
	I	West end siding M.P. 228.8	30
Udall	I	Both ends siding	40
WN Jct.	I	Both ends siding	40
	I	Turnouts to Douglass District main track and siding	30
	I	Turnouts to Eastern Division	15
	I	Crossovers between main track and siding	30
Hackney	I	Both ends siding	40
Arkansas City	I	East end siding M.P. 261.2	40
	S	M.P. 262.3	30
	I	Crossover between main track and siding M.P. 262.7	30

INDUSTRY AND OTHER TRACKS BETWEEN STATIONS

Name	Location	Capacity
Standard Oil Company Spurs	M.P. 202.6	57 Cars
Quality Concrete Inc. spurs	M.P. 216.3	16 Cars
Keeler spurs	M.P. 218.1	43 Cars

8 FOURTH DISTRICT

MIDDLE DIVISION

Siding Capacity 50 Ft. Per Car	WEST- WARD	Ruling Grade Ascending	TIME TABLE		Ruling Grade Ascending	Mile Post	Communications Turn Tables and Wyes	EAST- WARD
			No. 19					
			July 12, 1971					
			STATIONS	Feet Per Mile				
229	0	TCS	ELLINOR 4.9	0	125.4			
130	21.2		GLADSTONE 5.8	0	130.3			
200	21.2	TCS	BAZAR 8.3	0	136.1			
159	0		MATFIELD GREEN 9.8	21.2	144.4	C		
295	14.7	AUTO. BLOCK SYS.	CASSODAY 4.2	21.1	154.2	CR		
288	0		AIKMAN 7.7	21.2	158.4			
143	21.1	TCS	CHELSEA 8.2	21.2	166.1			
95	0		EL DORADO YL 3.3	0	174.3	YCR		
	0	AUTO. BLOCK SYS.	VANORA 7.7	0	177.6			
E 129 W 189	0		AG TOWER YL S.L.-S.F. Crossing 0.4	0	185.3	CR		
	0	TCS	AUGUSTA YL 5.7	0	185.7 (199.5)			
133	31.7		TCS	SALTER 6.4	21.1	205.2		
133	21.6	ROSE HILL 9.0		31.7	211.6			
141	0	TCS	MULVANE 5.9	21.4	220.6	CR		
147	0		BELLE PLAINE 0.7	18.8	226.5	C		
	31.7	TCS ABS	Mo. Pac. Crossing 4.5	0	227.2			
	0		CICERO 7.4	21.4	231.7			
			WELLINGTON		238.9	TYCR		
			(99.9)					

MAXIMUM AUTHORIZED SPEED FOR TRAINS

	MPH	
	Psg.	Fr.
Ellinor to Wellington	79	60*

*Freight trains may observe passenger train speed but not to exceed 70 MPH, provided:

- (1) Maximum district speed is 60 MPH for freight trains.
- (2) Train does not exceed 5000 tons.
- (3) Train does not exceed 90 cars.
- (4) Train does not average more than 70 tons per car.
- (5) Locomotive can control speed to 70 MPH without use of air brakes.

EXCEPTIONS.

- (A) Eastbound — MP 227 to MP 224
- (B) Maximum authorized speed for freight trains when averaging:
- | | |
|---|--------|
| 71 to 84 tons per car | 60 MPH |
| 85 tons and over per car, or over 7000 tons total | 45 MPH |

SPEED RESTRICTIONS - CURVES AND RR CROSSINGS:

	MPH
Curve, M.P. 129.5 to 129.8	75
Curve, M.P. 133.5 to 133.8	75
Curve, M.P. 138.5 to 138.8	75
Curve, M.P. 141.0 to 141.3	75
13 Curves, M.P. 142.3 to 149.6	60
Curve, M.P. 152.4 to 152.8	75
Curve, M.P. 159.8 to 160.0	75
Curve, M.P. 172.3 to 172.5	65
Curve, M.P. 173.4 to 173.7	50
Curve at Eldorado Station Sign— Eastward Track	40
Westward Track	30
Curve, M.P. 175.3 to 175.5	70
Curve, M.P. 179.6 to 179.8	65
Curve, M.P. 182.8 to 183.0	70
RR Crossing, M.P. 185.3 (Interlocking)	50
2 Curves, M.P. 200.4 to 200.7	55
2 Curves, M.P. 202.4 to 203.2	65
2 Curves, M.P. 204.3 to 204.7	45
2 Curves, M.P. 205.1 to 205.5	60
Curve, M.P. 209.5 to 209.7	60
Curve, M.P. 210.2 to 210.4	70
Curve, M.P. 215.6 to 215.8	65
3 Curves, M.P. 219.4 to 220.9 Westward Track	30
RR Crossing M.P. 227.2	Electrically locked gate normally across Mo. Pac. Track (MP 227.2). If gate is normal and home signal indicates "proceed" observe maximum speed shown.
Curve, M.P. 228.4 to 228.6	70
Curve, M.P. 233.1 to 233.5	70
2 Curves, M.P. 236.6 to 238.9	50

HOT BOX DETECTORS

Detector Location	Locator Location
M.P. 179.1	Westward M.P. 181.2 (Signal 1811) Eastward M.P. 176.7 (Signal 1762)
Rotating white light on field side at detector and locator location.	

See special rule 6 regarding home signal indications of interlocking at AG Tower.

RULE 251 IN EFFECT:

El Dorado to M.P. 201.8 (west of Augusta) and M.P. 230.6 (East of Cicero) to division board M.P. 237.1.

RULE 261 IN EFFECT:

On main tracks and sidings Ellinor to El Dorado; M.P. 201.8 (west of Augusta) to M.P. 230.6 (east of Cicero), and division board M.P. 237.1 to Wellington.

TWO TRACKS: M.P. 215.8 to M.P. 221.9 (Mulvane).

Trains must secure numbered clearance card at Wellington.

Proceed indication on eastward home signal Douglass District at AG Tower authorizes eastward extras Fourth District.

Mulvane is an open office of communication on westward or No. 2 track only.

At Wellington speed limit 10 MPH on connection track between Middle and Eastern Division Fourth Districts.

SWITCHES AND SIDINGS—MAXIMUM AUTHORIZED SPEED

Maximum authorized speed 10 MPH heading in or out over other than main track switches; 15 MPH over main track switches except those listed herein. Trains or engines trailing through and springing points of spring switches will not exceed speed prescribed for turnout. Trains or engines using siding will not exceed maximum turnout speed for that siding.

"I"—Interlocked Switch

"S"—Spring Switch

STATION	TYPE	SWITCHES AND TURNOUTS	MPH
Ellinor	I	Main track turnouts and cross-overs except turnout connecting Fourth District and track No. 3 First Dist.	40
	I	Turnout connecting Fourth District and track No. 3 First District	70
Gladstone	I	Both ends siding	40
Bazar	I	Both ends siding	40
Matfield Green	I	Both ends siding	40
Cassoday	I	Both ends siding	40
Aikman	I	Both ends siding	40
Chelsea	I	Both ends siding	40
El Dorado	I	Crossovers west end siding and east end siding	40
	I	Turnout to belt track	30
	I	Main track turnout and cross-overs west end	30
AG Tower	I	East end westward siding	30
	S	East end eastward siding	30
	I	Main track turnouts and cross-overs	30
Augusta	I	End of two tracks westward	50
Salter	I	Both ends siding	40
Rose Hill	I	Both ends siding	40
Mulvane	I	Turnout westward track M.P. 215.8	50
	I	Crossover between Fourth District and Third District at M.P. 220	40
	I	Other main track turnouts and crossovers east end yard	30
	I	Main track turnouts and cross-overs west of depot	30
	I	Turnout westward track M.P. 221.9	40
	I	West end siding	30
Belle Plaine	I	Both ends siding	30
Cicero	I	End of two tracks (MP 230.6)	70
Wellington	I	End of two tracks	40
	I	Switches leading to and from freight yard and Eastern Division	30
	I	East end siding	15

JOINT TRACK FACILITIES

WN JCT.-MULVANE-BELLE PLAINE—Mo. Pac. trains use A.T.&S.F. main track between WN Jct. and Belle Plaine via Mulvane, will be governed by A.T.&S.F. Time Table and Rules.

INDUSTRY AND OTHER TRACKS BETWEEN STATIONS

Name	Location	Capacity
FOURTH DISTRICT KG&E Spur	M.P. 209.3	25 Cars

Siding Capacity 50 Ft. Per Car	WESTWARD Ruling Grade Ascending	TIME TABLE No. 19 July 12, 1971			Mile Post	Communications Turn Tables and Wyes	EASTWARD
		Feet Per Mile	STATIONS	Feet Per Mile			
			AG TOWER YL S.L.-S.F. Crossing 0.4		185.3	Y C R	
		0	AUGUSTA YL 6.3	0	185.7		
134		0	GORDON 5.0	0	192.0		
139		10.6	DOUGLASS 5.6	15.8	197.0	C	
131		0	ROCK 6.2	15.8	202.6		
135		10.6	AKRON 7.2	15.8	208.8	B	
117		10.6	WN JCT. YL (30.7)	15.8	216.0	Y R	

See special rule 6 regarding home signal indications of interlocking at AG Tower.

Westward trains secure numbered clearance card at AG Tower.

Eastward trains secure numbered clearance card at Winfield when operator on duty.

MAXIMUM AUTHORIZED SPEED FOR TRAINS

	MPH	
	Psgr.	Frts.
AG Tower to WN Jct.	59	49*

*Speed limit 45 MPH for trains handling in excess of 7000 tons.

SPEED RESTRICTION - CURVES AND RR CROSSINGS

	MPH
RR Crossing, M.P. 185.3 (Interlocking)	50
3 Curves, M.P. 187.2 to 188.7	40
5 Curves, M.P. 198.8 to 200.0	25
Curve, M.P. 211.2 to 211.5	40
2 Curves, M.P. 215.6 to 216.0	30

SWITCHES AND SIDINGS - MAXIMUM AUTHORIZED SPEED

Maximum authorized speed 10 MPH heading in or out over other than main track switches; 15 MPH heading in or out over main track switches except those listed herein.

Trains or engines using siding must not exceed maximum turnout speed for that siding.

"I"—Interlocked Switch.

"S"—Spring Switch.

STATION	TYPE	SWITCHES AND TURNOUTS	MPH
WN Jct.	I	East end siding	30
	I	Turnout to Third District	30
AG Tower	I	Turnout to Fourth District	30

Siding Capacity 50 Ft. Per Car	WEST-WARD		TIME TABLE				EAST-WARD		Siding Capacity 50 Ft. Per Car	WEST-WARD		TIME TABLE				EAST-WARD			
	↓		Ruling Grade Ascending	No. 19 July 12, 1971		Ruling Grade Ascending	Mile Post	Communications Turn Tables and Wyes		↑		↓		Ruling Grade Ascending	No. 19 July 12, 1971		Ruling Grade Ascending	Mile Post	Communications Turn Tables and Wyes
	Feet Per Mile		Feet Per Mile	STATIONS		Feet Per Mile				Feet Per Mile		Feet Per Mile	STATIONS		Feet Per Mile				
				CH JCT. YL		218.3							GREAT BEND YL						
				4.4									8.3						
				YA JCT.		222.7	B						HEIZER	0		8.0			
82				0.5						35			7.1	0		15.1	C		
82		7.4		YAGGY		223.2	B					9.1	0		24.2	C			
				5.4								7.7	0		31.9	C			
				NICKERSON		228.6	C					6.9	0		38.8				
				7.0						85		6.0	0		44.8	C			
				ST JCT.		235.6	B					7.7	0		52.5	C			
				1.1								11.6	0		64.1	C			
85		11.1		STERLING YL		236.7	RC					8.4	31.7		72.5				
				6.2								7.7	31.7		80.2				
82				ALDEN		242.9						6.7	0		86.9				
				6.1								9.0	0		96.9	C			
53				RAYMOND		249.0				82		7.3	0		103.2				
				4.5								6.3	0		109.6				
53		10.5		CLARENDON		253.5	B			78		6.3	31.7		115.8				
				5.9								3.1	0		118.9				
82				ELLINWOOD YL		259.4	YC					1.2	0		120.1	YC			
				4.5															
82				DARTMOUTH		263.9	B												
				5.6															
				GREAT BEND YL		269.5	YRC												
				7.8															
52		13.0		DUNDEE		277.3	B												
				5.7															
82				PAWNEE ROCK		283.0	C												
				8.8															
83				LARNED YL		291.8	YRC												
				5.6															
53				HAMBURG		297.4	B												
				5.1															
84		17.4		GARFIELD		302.5	C												
				6.9															
52				NETTLETON		309.4	B												
				7.3															
				KINSLEY YL		316.7	YRC												
				9.0															
				(98.4)															

Eastward trains must secure numbered clearance card before leaving Kinsley. Westward trains must secure numbered clearance card at Hutchinson before leaving CH Jct.

Train order signal at Kinsley governs Second District trains only.

MAXIMUM AUTHORIZED SPEED FOR TRAINS

	MPH	
	Psg.	Frt.
CH Jct. to Kinsley	59	49*

*Speed limit 45 MPH for trains handling in excess of 7000 tons.

SWITCHES AND SIDINGS—MAXIMUM AUTHORIZED SPEED

Maximum authorized speed 10 MPH heading in or out over other than main track switches; 15 MPH heading in or out over main track switches.

Trains or engines using siding must not exceed maximum turnout speed for that siding.

JUNCTION SWITCHES Rule 98 (C)

LOCATION	NORMAL POSITION
YA Jct.	AT&SF Ry.
ST Jct.	AT&SF Ry.

JOINT TRACK FACILITIES

YA JCT. - ST. JCT. - MO. PAC. trains will use AT&SF tracks between YA Jct. and ST Jct. and will be governed by AT&SF Time Table and Special Instructions.

INDUSTRY AND OTHER TRACKS BETWEEN STATIONS

Name	Location	Capacity
Great Bend Industrial Spur	M.P. 274.6	174 Cars

Rule 99 (D) in effect.

No switch lights on Great Bend District.

MAXIMUM AUTHORIZED SPEED FOR TRAINS

	MPH
Great Bend to Scott City	30

SPEED RESTRICTIONS - CURVES AND RR CROSSINGS

RR	MPH
Interlocking, protected by Crossing M.P. 118.9 derails. Stop and follow instructions posted in box.	15

SWITCHES AND SIDINGS—MAXIMUM AUTHORIZED SPEED

Maximum authorized speed 10 MPH heading in or out over other than main track switches; 15 MPH heading in or out over main track switches.

Trains or engines using siding must not exceed maximum turnout speed for that siding.

JUNCTION SWITCHES Rule 98 (C)

LOCATION	NORMAL POSITION
Great Bend	Fifth District

INDUSTRY AND OTHER TRACKS BETWEEN STATIONS

Name	Location	Capacity
Western Light & Telephone Co.	M.P. 6.5	40 Cars
Shallow Track	M.P. 77.0	4 Cars

LARNED DISTRICT

MIDDLE DIVISION

STILLWATER DISTRICT

11

Siding Capacity 50 Ft. Per Car	WEST- WARD	Ruling Grade Ascending	TIME TABLE No. 19 July 12, 1971		Ruling Grade Ascending	Mile Post	Communications Turn Tables and Wyes	EAST- WARD
	↓		STATIONS	↑				
83							Y CR	
		10.5	LARNED YL	0				
			6.6 FRIZELL	0	6.6			
		10.5	5.6 SANFORD	0	12.2			
			4.8 ROZEL	0	17.0	C		
		24.8	6.9 BURDETT	0	23.9	C		
		0	6.8 GRAY	0	30.7			
		7.0	4.7 HANSTON	0	35.4	C		
		52.8	10.8 JETMORE YL	52.8	46.2		Y C	
			(46.2)					

Siding Capacity 50 Ft. Per Car	WEST- WARD	Ruling Grade Ascending	TIME TABLE No. 19 July 12, 1971		Ruling Grade Ascending	Mile Post	Communications Turn Tables and Wyes	EAST- WARD
	↓		STATIONS	↑				
							Y B	
		31.7	ESAU JCT. YL	31.7				
			6.6 PAWNEE	0	6.6	C		
		0	1.8 S.L.-S.F. Crossing	0	8.4			
		52.8	9.5 GLENCOE	29.0	17.9			
			12.0 STILLWATER YL	31.7	29.9	C		
		22	0.6 END OF TRACK	28.2	30.5			
		0	(30.5)					

Trains secure clearance card before leaving Stillwater when operator on duty.

No switch lights on Stillwater District.

MAXIMUM AUTHORIZED SPEED FOR TRAINS

	MPH
Esau Jct. to Stillwater	30

SPEED RESTRICTIONS - BRIDGES AND RR CROSSINGS:

	MPH
Bridge M.P. 2.7	10
Bridge M.P. 5.7	10
RR Crossing M.P. 8.4 (Auto. Interlocking)	20*

*Speed shown applies only until head end of train is through interlocking limits.

SWITCHES AND SIDINGS - MAXIMUM AUTHORIZED SPEED

Maximum authorized speed 10 MPH heading in or out over other than main track switches; 15 MPH heading in or out over main track switches.

Trains or engines using siding must not exceed maximum turnout speed for that siding.

JUNCTION SWITCHES Rule 98 (C)

LOCATION	NORMAL POSITION
Esau Jct.	Cushing District

INDUSTRY AND OTHER TRACKS BETWEEN STATIONS

Name	Location	Capacity
Swan Rubber	M.P. 26.5	50 Cars
Boomer Spur	M.P. 27.0	55 Cars

Rule 99 (D) in effect.

No switch lights on Larned District.

MAXIMUM AUTHORIZED SPEED FOR TRAINS

	MPH
Larned to Jetmore	25

SWITCHES AND SIDINGS - MAXIMUM AUTHORIZED SPEED

Maximum authorized speed 10 MPH heading in or out over other than main track switches; 15 MPH heading in or out over main track switches.

Trains or engines using siding must not exceed maximum turnout speed for that siding.

JUNCTION SWITCHES Rule 98 (C)

LOCATION	NORMAL POSITION
Larned	Fifth District

INDUSTRY AND OTHER TRACKS BETWEEN STATIONS

Name	Location	Capacity
Bert Wetta Track	M.P. 15.1	7 Cars
Bosse Track	M.P. 42.7	11 Cars

WEST- WARD First Class	Siding Capacity 50 Ft. Per Car	Ruling Grade Ascending	TIME TABLE No. 19 July 12, 1971	Ruling Grade Ascending	Mile Post	Communications Turn Tables and Ways	EAST- WARD First Class
15							16
Leave Daily		Feet Per Mile	STATIONS	Feet Per Mile			Arrive Daily
AM 6.40	483	0	ARKANSAS CITY 0.8	0	263.4	T Y C R	PM 8.05
		31.7	SLSF-MP Crossing 4.4	22.1	264.2		
		40.6	CHILOCCO 7.1	31.7	268.6		
	264	0	NEWKIRK 5.2	52.8	275.8	C	
		0	KILDARE 7.8	34.4	281.0		
s 7.22	576	0	PONCA CITY 1.8	35.8	288.9	Y C R	s 7.28
		45.8	CRI&P Crossing 9.6	40.9	290.7		
	173	22.0	MARLAND 6.5	52.8	300.3	C	
	146	52.8	RED ROCK 5.9	29.9	306.8	C	
	160	0	OTOE 3.6	52.8	312.7		
		52.8	SL SF Crossing 5.3	33.1	316.3		
s 7.58	69 108	52.8	PERRY 6.8	52.8	321.6	R C	s 6.47
	188	25.1	ASP 4.3	52.8	328.4		
	200	0	ORLANDO 6.1	49.3	332.7		
	173	52.8	MULHALL 8.1	52.8	338.8		
		36.2	LAWRIE 5.4	35.3	347.2		
s 8.30	276	38.6	GUTHRIE 7.4	16.2	352.6	Y C R	s 6.10
	190	37.0	SEWARD 10.0	0	360.1		
	125	50.1	EDMOND 6.7	23.9	370.1		
	159	52.8	BRITTON 3.8	52.8	376.8		
9.00		48.8	NOWERS YL 3.4	45.8	380.6		
s 9.15			OKLAHOMA CITY 1.7	17.6	384.0	Y C R	s 5.40
9.25		24.0	BURNETT YL 3.1	0	385.7		s 5.30
	159	46.3		0	385.7		5.20
		33.3	FLYNN 4.4	46.7	388.8		
	163	28.5	MOORE 8.6	48.6	393.2	C R	
s 9.55	128	46.5	NORMAN 6.2	32.5	401.8	C	s 5.00
	186	0	NOBLE 9.2	52.8	408.1		
s 10.25 AM			PURCELL		417.3	T Y C R	4.40 PM
Arrive Daily			(153.2)				Leave Daily
42.7			Average speed per hour				47.1

RULE 251 IN EFFECT:

Nowers to MP 383.6 (Oklahoma City).
MP 384.6 (Oklahoma City) to Burnett.

RULE 261 IN EFFECT:

Main track and sidings:
Arkansas City to Nowers.
Burnett to Purcell.

HOT BOX DETECTOR

Detector Location	Locator Location
M.P. 341.5	Westward, M.P. 343.9 Eastward, M.P. 339.1

SHIFTED LOAD DETECTOR

Detector Location	Indicator Location
M.P. 407.4 (Both sides track)	M.P. 407.6 M.P. 409.5

Detectors will not clear man on side of car.

Trains originating Arkansas City, Nowers and Purcell secure numbered clearance card before leaving.

Within TCS limits, where maximum speed exceeds 20 MPH, a train or engine must not clear the main track through a hand thrown switch, not electrically locked, for the purpose of meeting, passing or being passed by another train or engine.

At Arkansas City, between hand thrown crossover MP 262.9 and interlocked crossover MP 264.1, maximum authorized speed on main track is 20 MPH.

Proceed indication on home signal governing movement from Cushing District to Oklahoma District at Newkirk authorizes movement on Oklahoma District as an Extra East.

Between North 4th Street MP 383.6 and Rock Island underpass MP 384.6 Oklahoma City, all tracks are designated as yard tracks. Trains and engines using these tracks move at restricted speed. Westward trains ordinarily use Track 1. Eastward trains ordinarily use Track 4. Any variation from this procedure will be handled by yardmaster.

At Purcell, trains and engines move at restricted speed between westward interlocking signal east of station and MP 418.

MIDDLE DIVISION

OKLAHOMA DISTRICT 13

MAXIMUM AUTHORIZED SPEED FOR TRAINS

	MPH	
	Psg.	Fr.
Arkansas City to Purcell	90	60*

*Freight trains may observe passenger train speed but not to exceed 70 MPH provided:

- (1) Maximum district speed is 60 MPH for freight trains
- (2) Train does not exceed 5,000 tons.
- (3) Train does not exceed 90 cars.
- (4) Train does not average more than 70 tons per car.
- (5) Locomotive can control speed to 70 MPH without use of air brakes.

EXCEPTIONS

A	Westward	MP 350 to MP 352
	Eastward	MP 364 to MP 362
B	Maximum authorized speed for freight trains when averaging:	
	71 to 84 tons per car	60 MPH
	85 tons and over per car or over 7000 tons total	45 MPH

SPEED RESTRICTIONS - CURVES AND RR CROSSINGS:

	MPH
4 Curves, M.P. 263.0 to 264.1	20
4 Curves, M.P. 264.1 to 265.0	30
RR Crossing, M.P. 264.2 (Interlocking)	30
Curve, M.P. 265.3 to 265.5	65
Curve, M.P. 266.1 to 266.2	65
4 Curves, M.P. 288.7 to 288.9	40
Curve, M.P. 290.4 to 290.5	60
RR Crossing, M.P. 290.7 (Interlocking)	
Main track	65
Siding	40
Storage track.	20
Curve, M.P. 315.7 to 315.8	75
RR Crossing, M.P. 316.3 (Auto. Interlocking)	75
Curve, M.P. 351.2 to 351.3	80
Curve, M.P. 351.8 to 351.9	50
Curve, M.P. 371.8 to 372.3	75
Curve, M.P. 377.1 to 377.3	50
Curve, M.P. 378.5 to 378.6	70
Curve, M.P. 415.9 to 416.0	70
Curve, M.P. 416.2 to 416.6	50

OVERHEAD OBSTRUCTIONS (Rule 761)

Mile Post	Name
266.8	Highway Viaduct.
267.3	Highway Viaduct.
344.9	Skeleton Creek.
380.1	Highway Viaduct
384.0	Oklahoma City Train Sheds.
412.1	South Canadian River.

SWITCHES AND SIDINGS—MAXIMUM AUTHORIZED SPEED

Maximum authorized speed 10 MPH heading in or out over other than main track switches; 15 MPH over main track switches except those listed herein. Trains or engines trailing through and springing points of spring switches will not exceed speed prescribed for turnout. Trains or engines using siding will not exceed maximum turnout speed for that siding.

"I"—Interlocked Switch
"S"—Spring Switch

STATION	TYPE	SWITCHES AND TURNOUTS	MPH
Arkansas City	I	Both ends siding	40
	I	All dual control switches and crossovers between siding and main track	30
	S	East end yard lead, east end of yard	30
Newkirk	I	Both ends siding	40
	I	Switch to yard track 0.3 mile west of station	15
	I	Turnouts Oklahoma to Cushing District	30
Ponca City	I	Both ends siding. All dual controlled switches and crossovers between siding and main track	40
	I	East end yard lead	30
Marland	I	Both ends siding	40
Red Rock	I	Both ends siding	40
Otoe	I	Both ends siding	40
Perry	I	Both ends siding	40
Asp	I	Both ends siding	40
Mulhall	I	Both ends siding	40
Lawrie	I	Both ends siding	40
Guthrie	I	Both ends siding	40
	I	Crossovers between siding and main track	40
	I	Crossover between Enid District and Oklahoma District	30
Seward	I	Both ends siding	40
Edmond	I	Both ends siding	40
Britton	I	Both ends siding	40
Nowers	I	End of two tracks Eastward	40
Burnett	I	End of two tracks Westward	40
	I	Both ends siding	40
Moore	I	Both ends siding	40
Norman	I	Both ends siding	40
Noble	I	Both ends siding	40
	I	Both ends siding	40
Purcell	I	Crossover east end yard	30
	I	West end tail track	30
	S	East end tail track	30

INDUSTRY AND OTHER TRACKS BETWEEN STATIONS

Name	Location	Capacity
Team Track	M.P. 366.7	31 Cars
Central Fixtures Spurs	M.P. 372.5	9 Cars
General Portland Cement Spurs	M.P. 372.9	55 Cars
Murphy Perkins	M.P. 372.9	10 Cars
Ralston Purina	M.P. 373.0	91 Cars
Harper Oil Co. (Dereco)	M.P. 373.5	28 Cars
Dow Chemical Spur	M.P. 373.6	10 Cars
Cain's Coffee	M.P. 373.9	19 Cars
Acme Brick Spur	M.P. 374.3	16 Cars
W. E. Davis	M.P. 374.6	10 Cars
Dolese Spur	M.P. 375.0	22 Cars
Tyler Simpson	M.P. 400.2	13 Cars
IBM Spur	M.P. 405.2	10 Cars
Dolese Spur	M.P. 405.7	22 Cars

WEST- WARD ↓	Siding Capacity 50 Ft. Per Car	Rating Grade Ascending	TIME TABLE No. 19 July 12, 1971		Rating Grade Ascending	Mile Post	Communications Turn Tables and Wyes	EAST- WARD ↑
			Feet Per Mile	STATIONS				
				KIOWA YL			Y CR	
			0	0.8	21.1			
				Mo. Pac. Crossing	31.7	0.6		
	125		0	8.2				
				BURLINGTON	15.8	8.8	C	
			0	10.9				
	95			CHEROKEE YL		19.7	C	
			31.7	12.1	29.6			
	39			JET		31.8	C	
			31.7	8.2	31.7			
	41			NASH		40.0	C	
			31.7	7.8	0			
	35			HILLSDALE		47.8		
			31.7	5.8	0			
	24			ITUNA		53.6		
			22.2	4.6	31.7			
	80			BLANTON YL		58.2	B	
			0	2.8	52.8			
			0	S.L.-S.F. Jct.		61.0		
				0.3	23.8			
				ENID YL		61.3	Y CR	
			19.4	0.6	22.8			
				S.L.-S.F. Jct.		61.9		
			16.4	0.1	0			
			0	C.R.I.&P. Crossing	0	62.0		
				0.1	0			
			0	S.L.-S.F. Jct.	10.6	62.1		
				1.1	10.6			
			29.3	S.L.-S.F. Crossing	52.8	63.2		
				9.6	52.8			
	62		0	FAIRMONT		72.8		
				0.8	0			
			38.1	S.L.-S.F. Crossing	52.8	73.6		
				6.8	52.8			
	26		0	DOUGLAS	38.5	80.4	C	
				8.0		88.4	C	
	125		52.8	MARSHALL	52.8			
				6.7		95.1		
	27		52.8	LOVELL	52.8			
				7.7		102.8	CR	
	39		0	CRESCENT	52.8			
				7.6		110.4		
	29		26.4	MUDGE	0			
				6.3		116.7	Y CR	
				GUTHRIE YL				
				(116.9)				

MAXIMUM AUTHORIZED SPEED FOR TRAINS

	MPH
Kiowa to Guthrie	30

SPEED RESTRICTIONS - BRIDGES, CURVES AND RR CROSSINGS

	MPH
RR Crossing, M.P. 0.6 Gate normally across Mo. Pac. track. Approach prepared to stop. If gate is normal, observe maximum speed shown. If gate is across AT&SF track, stop must be made back of clearance sign.	20
RR Crossing, M.P. 62.0 (Auto. Interlocking)	30
RR Crossing, M.P. 63.2 Stop. Rules 98, 98(A), 98(B) and 98(D).	30
RR Crossing, M.P. 73.6 (Auto. Interlocking)	20*
4 Curves, M.P. 115.4 to Guthrie	15

*Speed shown applies only until head end of train is through interlocking limits.

SWITCHES AND SIDINGS—MAXIMUM AUTHORIZED SPEED

Maximum authorized speed 10 MPH heading in or out over other than main track switches; 15 MPH over main track switches except those listed herein. Train or engines trailing through and springing points of spring switches will not exceed speed prescribed for turnout. Trains or engines using siding will not exceed maximum turnout speed for that siding.

"I"—Interlocked Switch
"S"—Spring Switch

STATION	TYPE	SWITCHES AND TURNOUTS	MPH
Enid	S	Entering and leaving Interlocking Limits MP 61.9 and MP 62.1	15

JUNCTION SWITCHES Rule 98 (C)

LOCATION	NORMAL POSITION
Kiowa	Plains Division
Cherokee	Enid District
Blanton	SL-SF Ry.
Enid, SL-SF Jct.	SL-SF Ry.

JOINT TRACK FACILITIES

BLANTON—S.L.-S.F. JCT. MP 61.0—A.T. & S.F. trains use S.L.-S.F. tracks and are governed by S.L.-S.F. time table, rules and special instructions.

ENID—Within interlocking limits MP 61.9 and MP 62.1, A.T. & S.F. trains use S.L.-S.F. tracks and be governed by S.L.-S.F. time table, rules and special instructions.

OVERHEAD OBSTRUCTIONS (Rule 761)

Mile Post	Name
36.3 Yard	Highway Viaduct. Crescent, overhead pipes, Cimarron Spur.

Eastward trains secure both AT&SF and SL-SF clearance cards before leaving Enid.

Between outlying wye switch and Kiowa, on Plains Division, TCS Rules in effect on Main track and siding.

No switch lights on Enid District.

INDUSTRY AND OTHER TRACKS BETWEEN STATIONS

Name	Location	Capacity
Schoeb Ranch Spur	M.P. 10.9	13 Cars

Siding Capacity 50 Ft. Per Car	WEST- WARD	TIME TABLE	Mile Post	Communications Turn Tables and Wyes	EASTWARD
	↓	No. 19 July 12, 1971			↑
		STATIONS			
		HARTER (Oklahoma City) 36.7		CRI&P	
		SHAWNEE 23			
		OCA JCT. 8.9	38.6		
		HARJO 7.9	47.5		
35		MAUD 8.9	55.4		
		FINN 5.1	64.3		
24		KONAWA 15.1	69.4		
		S.L.-S.F. Crossing 0.6	84.5		
25		ADA YL 3.4	85.1		C
		AHLOSO 9.2	88.5		
		STONEWALL 6.4	97.7		
		TUPELO YL	104.1		
		(104.5)			

Rule 99(D) in effect between OCA Jct. and Tupelo.

Westward trains must secure AT&SF numbered clearance card before leaving Nowers, and CRI&P numbered clearance before leaving Nowers or Harter.

No switch lights on OCAA district.

MAXIMUM AUTHORIZED SPEED FOR TRAINS

	MPH
OCA Jct. to Ada	30
Ada to Tupelo	25
Midwest City Industrial Spur	20

SPEED RESTRICTIONS - BRIDGES AND RR CROSSINGS

	MPH
RR Crossing, Yard Track Shawnee Stop. Rules 98, 98 (A), 98 (B) and 98 (D).	10
Bridge, M.P. 38.3	10
Bridge, M.P. 73.7	15
RR Crossing, M.P. 84.5 (Auto. Interlocking)	20*

*Speed shown applies only until head end of train is through interlocking limits.

SWITCHES AND SIDINGS—MAXIMUM AUTHORIZED SPEED

Maximum authorized speed 10 MPH heading in or out over all switches.

Trains or engines using siding must not exceed maximum turnout speed for that siding.

JUNCTION SWITCHES Rule 98 (C)

LOCATION	NORMAL POSITION
OCA Jct.	CRI&P

JOINT TRACK FACILITIES

OCA JCT.—HARTER (CRI&P)—OCAA District trains and engines will use CRI&P tracks and be governed by CRI&P rules and time table.

INDUSTRY AND OTHER TRACKS BETWEEN STATIONS

Name	Location	Capacity
Midwest City Industrial Spur	CRI&P M.P. 482.6 & M.P. 483.3	1.5 Miles
OG&E Spur	M.P. 67.6	

WEST- WARD ↓	Siding Capacity 60 Ft. Per Car	Ruling Grade Ascending	TIME TABLE		Ruling Grade Ascending	Mile Post	Communications Turn Tables and Wyes	EAST- WARD ↑
			No. 19					
July 12, 1971								
	Feet Per Mile	STATIONS		Feet Per Mile				
	30.1	NEWKIRK	YL	31.7	0.9	C		
	0	10.7			11.6	B		
70		UNCAS		31.7				
		5.8			17.4	C		
	31.7	KAW		0				
		2.1			19.5			
	31.7	SOLDANI		30.7				
		1.6			21.1			
68	0	APPERSON		31.7				
		4.6			25.7	B		
	0	BURBANK		30.2				
		11.9			37.6	C		
	0	FAIRFAX		31.7				
		5.5			43.1	C		
100	25.0	RALSTON	YL	31.7				
		9.2			52.3	B		
	31.7	SKEDEE	YL	31.7				
		1.8			54.1	Y		
	29.9	ESAU JCT.	YL	31.7				
		4.1			58.2	B		
	31.7	SL-SF Crossing		31.7				
		10.3			68.5	B		
	0	QUAY		31.7				
		3.2			71.7	B		
	0	YALE		30.4				
		1.7			73.4			
	31.7	MKT Gantlet		0				
		9.0			82.4	Y		
	31.7	CUSHING	YL	31.7				
		14.4			96.8	B		
91	31.7	KENDRICK		31.7				
		5.6			102.4			
	31.7	DAVENPORT		31.7				
		17.0			119.4			
45	31.7	MEEKER		31.7				
		12.6			132.0	Y		
	0	SHAWNEE	YL	0	132.0	C R		
		2.1			134.1			
		END OF TRACK						
(133.2)								

Trains secure clearance card before leaving Cushing, when operator on duty.

MAXIMUM AUTHORIZED SPEED FOR TRAINS

	MPH	
	Psgr.	Frts.
Newkirk to Burbank	30	30
Burbank to Shawnee	50	40

SPEED RESTRICTIONS - BRIDGES, CURVES AND RR CROSSINGS

	MPH	
	Psgr.	Frts.
Curve, M.P. 30.8 to 30.9	20	20
4 Curves, M.P. 33.5 to 35.9	40	35
2 Curves, M.P. 36.6 to 36.9	45	35
RR Crossing, M.P. 58.2 (Auto. Interlocking)	20*	20*
6 Curves, M.P. 63.2 to 65.3	40	35
2 Curves, M.P. 69.0 to 69.5	40	35
2 Curves, M.P. 72.3 to 72.5	15	15
RR Crossing, M.P. 73.4 Automatic Interlocking. Gantlet track used jointly with MKT over Cimarron River bridge.	20*	20*
Bridge, M.P. 110.5	30	30
M.P. 119.0 to 132.0	30	30

*Speed shown applies only until head end of train is through interlocking limits.

SWITCHES AND SIDINGS - MAXIMUM AUTHORIZED SPEED

Maximum authorized speed 10 MPH heading in or out over other than main track switches; 15 MPH heading in or out over main track switches except those listed herein.

Trains or engines using siding must not exceed maximum turnout speed for that siding.

"I"—Interlocked Switch.

"S"—Spring Switch.

STATION	TYPE	SWITCHES AND TURNOUTS	MPH
Newkirk	I	Turnouts Cushing to Oklahoma District	30

OVERHEAD OBSTRUCTIONS (Rule 761)

Mile Post	Name
50.4	Highway Viaduct.
52.2	Coal Chute.
82.2	Railroad Viaduct.
100.1	Highway Viaduct.
102.6	Railroad Viaduct.
132.6	Railroad Viaduct.
132.7	Railroad Viaduct.

INDUSTRY AND OTHER TRACKS BETWEEN STATIONS

Name	Location	Capacity
Corning Glass Spur	M.P. 127.6	18 Cars

LITTLE RIVER DISTRICT MIDDLE DIVISION MINNEAPOLIS DISTRICT 17

WEST- WARD	TIME TABLE No. 19 July 12, 1971				EAST- WARD
Ruling Grade Ascending	STATIONS	Ruling Grade Ascending	Mile Post	Communications Turn Tables and Wyes	
Feet Per Mile		Feet Per Mile		Y C	
52.8	LITTLE RIVER YL 11.0	0			
45.7	Mo. Pac. Crossing 0.5	0	10.9		
52.2	GENESEO 9.1	45.4	11.4		
37.5	S.L.-S.F. Crossing LORRAINE YL 5.6	51.7	20.5		
52.8	HOLYROOD YL 4.6	0	26.1	C	
52.8	FARHMAN 5.7	44.9	30.7		
0	HITSCHMANN 4.8	37.0	36.4		
47.5	BEAVER 5.8	27.3	41.2		
45.5	SUSANK 2.9	31.7	47.0		
52.8	STICKNEY 2.9	51.5	49.9		
52.8	MILLARD 4.1	52.8	52.8		
	GALATIA YL		56.9	Y	
	(57.0)				

Rule 99(D) in effect.
No switch lights on the Little River District.

MAXIMUM AUTHORIZED SPEED FOR TRAINS

	MPH
Little River to Galatia	30

SPEED RESTRICTIONS - RR CROSSINGS.

	MPH
RR Crossing M.P. 10.9 Electric locked gate normally across AT&SF track. Be governed by instructions in lock box. Stop, open and close gate.	
RR Crossing M.P. 20.5 Gate normally across SL-SF track. Approach prepared to stop. If gate normal, observe maximum speed shown.	15

SWITCHES AND SIDINGS—MAXIMUM AUTHORIZED SPEED

Maximum authorized speed 10 MPH heading in or out over other than main track switches; 15 MPH heading in or out over main track switches.

Trains or engines using siding must not exceed maximum turnout speed for that siding.

JUNCTION SWITCHES Rule 98 (C)

LOCATION	NORMAL POSITION
Little River	McPherson District

JOINT TRACK FACILITIES

LORRAINE—S.L.-S.F. trains will use A.T.&S.F. main and yard tracks between 750 feet east and 2200 feet west of S.L.-S.F. crossing.

WEST- WARD	TIME TABLE No. 19 July 12, 1971				EAST- WARD
Ruling Grade Ascending	STATIONS	Ruling Grade Ascending	Mile Post	Communications Turn Tables and Wyes	
Feet Per Mile		Feet Per Mile		Y C	
52.8	MANCHESTER YL 5.7	52.8		Y	
52.8	VINE CREEK 8.7	52.8	5.6		
52.8	WELLS 9.7	52.8	14.3		
0	MINNEAPOLIS YL 0.2	0	24.0	C	
0	U.P. Crossing ADA 10.0	0	24.2		
0	ADA 8.8	0	34.2	C	
	BARNARD YL		43.0	Y C	
	(43.1)				

Rule 99(D) in effect.
No switch lights on the Minneapolis District.

MAXIMUM AUTHORIZED SPEED FOR TRAINS

	MPH
Manchester to Barnard	20

SPEED RESTRICTIONS - RR CROSSINGS.

	MPH
RR Crossing M.P. 24.2 Stop. Rules 98, 98(A), 98(B), 98(D).	20

SWITCHES AND SIDINGS—MAXIMUM AUTHORIZED SPEED

Maximum authorized speed 10 MPH heading in or out over other than main track switches; 15 MPH heading in or out over main track switches.

Trains or engines using siding must not exceed maximum turnout speed for that siding.

JUNCTION SWITCHES Rule 98 (C)

LOCATION	NORMAL POSITION
Manchester	Strong City District

MIDDLE DIVISION

SALINA DISTRICT 19

Siding Capacity 50 Ft. Per Car	WEST- WARD	Ruling Grade Ascending	TIME TABLE		Ruling Grade Ascending	Mile Post	Communications Turn Tables and Wyes	EAST- WARD
			No. 19					
			July 12, 1971					
			STATIONS					
			0	ABILENE YL	0			T C R
			0	0.4 C.R.I. & P. JCT.	0			
			0	0.2 S.A. JCT.	0			
			0	0.3 WEST ABILENE YL	0			
			0	7.5 UP Ry.	0			
A.T.&S.F. Yard			0	SOLOMON	0			C
			0	12.6 EAST SALINA YL	0			
			0	0.4 A.B. JCT.	0	20.5		
			0	1.0 U.P. Crossing	0	21.5		
			0	0.1 U.P. Crossing	0	21.6		
			0	0.1 SALINA F.S. YL	0	21.7		R C
			0	0.4	0			
			14.2	SALINA U.S. YL	0	22.1		C
			39.9	0.6 U.P. Crossing	37.0	22.7		
42			47.7	7.4 HEDVILLE	30.0	30.1		
42			47.5	6.8 GLENDALE	42.2	36.9		
			47.5	5.3 JUNIATA	44.0	42.2		
			47.6	3.3 WESTFALL	42.2	45.5		
			47.5	3.5 EDALGO	42.2	49.0		
			39.6	6.2 BARTON	42.2	55.2		
			50.0	1.4 U.P. Crossing	50.2	56.6		
45			0	0.3 LINCOLN CENTER YL	0	56.9		C
			37.0	5.2 GOLDENROD	21.1	62.1		
			47.5	3.1 DENMARK	37.0	65.2		
			37.0	5.5 ASH GROVE	18.5	71.7		
			42.2	5.4	30.0			
			52.8	HUNTER	44.9	77.1		C
			55.4	8.9 TIPTON	50.0	86.0		C
			21.1	8.2 CORINTH	10.6	94.2		
			47.5	3.9 FORNEY	42.2	98.1		
				4.4 OSBORNE YL		102.5		Y C
				(103.4)				

MAXIMUM AUTHORIZED SPEED FOR TRAINS

		MPH
Salina U.S. to Osborne		30

SPEED RESTRICTIONS - CURVES AND RR CROSSINGS:

		MPH
RR Crossing M.P. 21.5	Stop. Rules 98, 98(A), 98(B), 98(D).	15
RR Crossing M.P. 21.6	Stop. Rules 98, 98(A), 98(B), 98(D).	15
RR Crossing M.P. 22.7	Gate mechanically connected to electric locked derails, normally across AT&SF tracks. Stop and be governed by instructions at crossing.	
Curve, M.P. 24.5 to 24.6		15
Curve, M.P. 25.1 to 25.2		15
2 Curves, M.P. 55.1 to 55.4		15
RR Crossing M.P. 56.6	Gate normally across AT&SF track. Stop, open and close gate.	
M.P. 88.5 to 91.5		20
Over bridge M.P. 101.1, Solomon River		10

SWITCHES AND SIDINGS - MAXIMUM AUTHORIZED SPEED

Maximum authorized speed 10 MPH heading in or out over all switches.
Trains or engines using siding must not exceed maximum turnout speed for that siding.

JUNCTION SWITCHES Rule 98(C)

LOCATION	NORMAL POSITION
C.R.I. & P. Jct.	Strong City District
S.A. Jct.	Strong City District
West Abilene	U.P. R.R.
East Salina	U.P. R.R.
A.B. Jct.	C.R.I. & P. R.R.

OVERHEAD OBSTRUCTIONS (Rule 761)

Mile Post	Name
Yard	Salina, Salina Terminal, canopy over tracks each side of elevator.
Yard	Salina, Gooch Mill, canopy over track on south side of mill.
25.2	CGF Elevator, canopy over tracks north and south side.
101.1	Solomon River Bridge.

JOINT TRACK FACILITIES

C.R.I. P. JCT.—WEST ABILENE—C.R.I. & P. trains use A.T. & S.F. main track and will be governed by A.T. & S.F. Time Table.

WEST ABILENE—EAST SALINA—A.T. & S.F. trains use U.P. R.R. main and yard tracks and be governed by U.P. time table, rules and regulations.

EAST SALINA—A.B. JCT.—C.R.I. & P. and A.T. & S.F. trains use C.R.I. & P. main track and will be governed by A.T. & S.F. Time Table.

INDUSTRY AND OTHER TRACKS BETWEEN STATIONS

Name	Location	Capacity
CGF spurs and switching tracks	M.P. 25.2	298 Cars

Rule 99(D) in effect between Salina F.S. and Osborne.

Eastward trains originating Salina secure UP clearance card Salina US before leaving.

Westward trains secure UP clearance card Abilene; also ATSF numbered clearance card at Salina F.S. when operator on duty.

Between Abilene and West Abilene, and between East Salina and Salina F.S., there is no superiority of trains. Trains and engines within these limits must move at restricted speed.

Siding Capacity 50 Ft. Per Car	WEST- WARD	Ruling Grade Ascending	TIME TABLE		Ruling Grade Ascending	Mile Post	Communications Turn Tables and Wyes	EAST- WARD
	↓		No. 19	July 12, 1971				↑
	Feet Per Mile		STATIONS	Feet Per Mile				
			NEVA YL					
			2.6	0				
			ROCKLAND			2.6		
			5.0	0				
34			HYMER			7.6		
			5.8	0				
20			DIAMOND SPRINGS			13.4	B	
			5.8	0				
29			BURDICK			19.2	B	
			6.3	41.2				
22			C.R.I. & P. Crossing LOST SPRINGS			25.5		
			5.4	49.1				
			C.R.I. & P. Crossing			30.9		
			5.9	49.1				
53			HOPE			36.8		
			0.3	0				
			Mo. Pac. Crossing			37.1		
			7.3	47.5				
27			NAVARRE			44.4		
			7.7	47.5				
30			ENTERPRISE			52.1		
			0.1	0				
			C.R.I. & P. Crossing			52.2		
			0.1	0				
			A.T. & S.F. Crossing			52.3		
			5.8	0				
			ABILENE YL			58.1	T C R	
			0.5	0				
			C.R.I. & P. Jct.			58.6		
			0.2	0				
			S.A. Jct.			58.8		
			0.2	0				
			U.P. Crossing			59.0		
			8.0	0				
31			TALMAGE YL			67.0	C	
			5.2	0				
32			MANCHESTER YL			72.8	Y B	
			5.5	52.7				
34			LONGFORD			78.4	C	
			5.3	52.8				
15			OAK HILL			83.7	B	
			9.3	37.0				
			MILTONVALE			93.0	C	
			9.1	52.7				
17			AURORA			102.1	C	
			5.9	52.7				
			HUSCHER			108.0		
			2.0	52.7				
			COOK			110.0		
			3.2	0				
			Mo. Pac. Crossing BN Crossing			113.2		
			0.3	0				
			CONCORDIA YL			113.5	C	
			5.6	0				
			Mo. Pac. Crossing			120.1		
			7.6	0				
			KACKLEY			127.7		
			6.0	23.5				
			C.R.I. & P. Crossing COURTLAND			133.7	C	
			7.5	52.7				
			LOVEWELL			141.2		
			5.8	0				
			WEBBER			147.0		
			4.9	52.8				
			State Line			151.9		
			0.7	0				
			Mo. Pac. Crossing			152.6		
			0.4	0				
			BN Crossing			153.0		
			0.8	0				
			SUPERIOR YL			153.8	T C	
			(153.8)					

Trains must secure numbered clearance card before leaving Superior and Concordia. Trains must secure clearance card before leaving Abilene when operator on duty.

Between Abilene Station and U.P. Crossing M.P. 59.0, there is no superiority of trains. Trains and engines within these limits must move at restricted speed.

Trains and engines will be governed by C.&N.W. Ry. Time Table between M.P. 151.9 and Superior, which provides:

"A.T.&S.F. trains and engines have authority to operate on main and yard tracks, Superior, Chicago & North Western and A.T.&S.F. trains and engines have no time table superiority and must proceed at restricted speed within the yard limits, Superior."

No switch lights on the Strong City District.

SWITCHES AND SIDINGS - MAXIMUM AUTHORIZED SPEED

Maximum authorized speed 10 MPH heading in or out over other than main track switches; 15 MPH heading in or out over main track switches.

Trains or engines using siding must not exceed maximum turnout speed for that siding.

JUNCTION SWITCHES Rule 98(C)

LOCATION	NORMAL POSITION
C.R.I. & P. Jct.	Strong City District
S.A. Jct.	Strong City District

JOINT TRACK FACILITIES

C.R.I. & P. JCT. — WEST ABILENE — C.R.I. & P. trains use A.T. & S.F. main track and will be governed by A.T. & S.F. Time Table.

SUPERIOR — A.T. & S.F. trains will use C.&N.W. main and yard tracks.

OVERHEAD OBSTRUCTIONS (Rule 761)

Mile Post	Name
Yard	Enterprise, Ersham spur, overhead doorway into building.
Yard	Abilene, Security Mill, canopy over two tracks.
Yard	Abilene, Abilene Alfalfa Mill, canopy over track.

MAXIMUM AUTHORIZED SPEED FOR TRAINS

	MPH
Neva to Courtland	35
Courtland to State Line	25
State Line to Superior	20

SPEED RESTRICTIONS - CURVES AND RR CROSSINGS:

	MPH
2 Curves, M.P. 4.2 to 4.8	30
7 Curves, M.P. 8.2 to 10.9	30
RR Crossing M.P. 25.5 (Auto. Interlocking)	20*
RR Crossing M.P. 30.9 (Auto. Interlocking)	20*
RR Crossing M.P. 37.1 (Auto. Interlocking)	20*
3 Curves, M.P. 50.7 to 51.9	30
RR Crossing M.P. 52.2 Gate normally across CRI & P track. Approach prepared to stop. If gate normal, observe maximum speed shown.	15
RR Crossing M.P. 52.3 Mill track lead—Gate normally across Mill track. Approach prepared to stop. If gate normal, observe maximum speed shown.	15
RR Crossing M.P. 59.0 Interlocking, signals and derails set normally against AT&SF. Be governed by instructions posted in signal house at crossing.	
Curve, M.P. 60.8 to 61.0	30
Curve, M.P. 62.7 to 62.9	30
Curve, M.P. 83.4 to 83.7	30
5 Curves, M.P. 88.7 to 90.0	30
4 Curves, M.P. 90.9 to 92.0	30
2 Curves, M.P. 92.7 to 93.4	20
2 Curves, M.P. 96.7 to 97.5	30
Curve, M.P. 108.5 to 108.7	30
2 Curves, M.P. 109.8 to 109.9	15
Curve, M.P. 111.1 to 111.3	30
RR Crossing M.P. 113.2 Stop. Rules 98, 98(A), 98(B), 98(D).	15
RR Crossing M.P. 120.1 Gate normally across Mo. Pac. track. Approach prepared to stop. If gate is normal, observe maximum speed shown.	35
RR Crossing M.P. 133.7 Electric locked gate normally across AT&SF track. Be governed by instructions in lock box. Stop, open and close gate.	
RR Crossing M.P. 152.6 Stop. Rules 98, 98(A), 98(B), 98(D).	20
RR Crossing M.P. 153.0 Stop. Rules 98, 98(A), 98(B), 98(D).	20

*Speed shown applies only until head end of train is through interlocking limits.

1. Except as otherwise provided, Eastward Trains are superior to Westward Trains of the same class.

2. REGISTER STATIONS RULE 83(A)

STATIONS LISTED BELOW ARE REGISTER STATIONS ONLY FOR TRAINS DESIGNATED:

Station	Designated Trains
Emporia—Emporia Yard	Originating or terminating either place.
Newton—Sand Creek	Originating or terminating either place.
Wellington—Wellington Yard	Originating or terminating either place.
McPherson	Originating or terminating.
Lyons	Originating or terminating.
Esau Jct.	When instructed by train order.

AT STATIONS LISTED BELOW TRAINS DESIGNATED WILL REGISTER BY FORM 903:

Emporia Trains on which engine or train crews do not change.

3. YARD LIMITS

Abilene	Marion	Osborne
Augusta	Manchester	Kiowa
Barnard (Minneapolis Dist.)	Minneapolis	Cherokee
Chase	Ellinwood	Blanton
CH Jct. (5th Dist. only)	Emporia	Enid
Concordia	Ponca City (Plains Division only)	Newkirk (Cushing Dist. only)
Conway	Guthrie (Enid District only)	Ralston
Dodge City	Oklahoma City (includes Two Tracks only between	Skedee (includes Esau Jct.)
El Dorado	Nowers M.P. 380.6 and Burnett M.P. 385.7)	Cushing
Galatia	McPherson	Shawnee
Great Bend	ND Jct.	Stillwater
Hillsboro	Ness City	Salina
Holyrood	Neva (Strong City Dist. only)	Scott City
Jetmore	Newton	Sterling
Kinsley	No. Wichita	Superior
Larned		Talmage
Lincoln Center		WN Jct. (Douglass Dist. only)
Little River		Ada, Okla.
Lorraine		Tupelo
Lyons		

4. BULLETIN BOOKS

Abilene	Great Bend	Ada, Okla.
Argentine RH	Kans City US	Sand Creek
Arkansas City	Cushing	Superior
Augusta	Shawnee	Way
Concordia	McPherson	Wellington
Guthrie	Newton	Ponca City
Nowers	No. Wichita	Kiowa
Oklahoma City	Osborne	Enid
Dodge City	Purcell	Cherokee
El Dorado	Salina F S	Lyons
Emporia		

5. STANDARD CLOCKS

Abilene	Ponca City	Ada, Okla.
Arkansas City	Newton	Scott City
Dodge City	No. Wichita	Way
Emporia	Sand Creek	Wellington
Great Bend	Purcell	Shawnee (Cushing Dist.)
Nowers	Cushing	Enid

6. (Rule 312) Home signals interlockings AG Tower, Wright, and Dodge City when displaying single yellow aspect, indicates—proceed prepared to enter turnout or stop short of train or obstruction.

7. MOVEMENTS OVER SUBMERGED TRACK—(Rule 817)

Equipment listed below must not be moved through water above top of rail greater than the depths and not in excess of the speeds shown:

Engines	Maximum Depth Above Top of Rail (Inches)	Maximum Speed (MPH)
6300-6348, 6600-6615, 7500-7519, 7900-7909, 8000-8005, 8500-8524, 9122-9148, 9800-9849	3	5
652-653	4	5
16C-47A, 200-289, 300-321, 325-344, 500-564, 1500-1537, 2258-2298, 2323-2399, 2404-2441, 2450, 2500-2899, 2900-2951, 3100-3174, 3200-3284, 3300-3460, 3500-3560, 4000-4019, 4500-4579, 5000-5019, 5500-5589, 5590-5624, 5900-5939, 5940-5948	5	5
Passenger Cars:		
Roller Bearings	8	5
Friction Bearings	12	5

8. DERRICKS, CRANES, SCALE TEST CARS.

Derricks, cranes, pile drivers, spreaders, and similar machinery moving on their own running gear, and scale test cars, must not be moved in trains except on authority of Trainmaster, and trains or engines handling such equipment must not exceed speed indicated below:

DISTRICT	Wrecking Derricks MPH	Pile Drivers AT 199454 AT 199455 AT 199457 AT 199458 Derrick AT 199720 and Jordan Spreaders MPH	Other machines including Derrick AT 199775 MPH
First, Second, Third, Fourth, Fifth, Oklahoma and Douglass	40	45	30
Cushing	24	24	24
Strong City, McPherson, Great Bend, Enid, Larned, and Stillwater	20	20	20
Little River, Minneapolis and Salina	15	15	15
OCAA	10	10	10

Derricks AT 199720 and AT 199775, and pile drivers must be handled in trains next to engine.

Santa Fe scale test cars AT 199913, AT 199914, and AT 199915, and all foreign line scale test cars must be handled in trains immediately ahead of caboose at speed not exceeding 50 MPH.

9. MAXIMUM SPEED OF ENGINES.

Diesels	Forward or Dead In Train MPH	Backing or When not Controlled From Leading Unit MPH
300LABC-314LABC, 315AB-321AB	90	45
5920-5948	79	45
16C-47A, 200-289, 325-344, 2500-2899, 2900-2951, 3100-3174, 3200-3284, 3300-3460, 3500-3560, 4000-4019, 4500-4579, 5000-5019, 5500-5589, 5590-5614, 5615-5624, 5900-5919, 6300-6348, 6600-6615, 7500-7519, 7900-7909, 8000-8005, 8500-8524, 9122-9149, 9800-9849	70	45
500-564, 652-653, 1500-1537, 2258-2298, 2323-2399, 2404-2441, 2450	45	45

EYE, EAR, NOSE AND THROAT SPECIALISTS

LOCATION	DOCTORS
Arkansas City	J. E. HILL (Eye Only)
"	S. L. ABBEY, O.D.
"	ALFRED AUCAR
Augusta	R. WHITTAKER (Eye Only)
"	D. CRUM (Eye Only)
Cushing	
Dodge City	E. W. SCHWARTZ, Ophthalmologist
El Dorado	J. H. JOHNSON (Eye Only)
"	G. CAMPBELL (Eye Only)
"	G. V. WILLIAMS (E.N.T.)
"	G. ABBOTT (Eye Only)
"	J. D. JOYCE (Eye Only)
Emporia	D. P. TRIMBLE
"	E. L. GANN
Enid	A. F. DOUGAN
"	W. J. BUVINGER
Great Bend	R. C. POLSON (Eye Only)
Guthrie	J. R. HENKE, Ophthalmologist
Halstead	RUTH M. SHORT
"	
Hutchinson	
"	V. R. MOORMAN
"	G. E. STONE
"	C. T. MCCOY (Ophthalmologist)
Newton	E. K. ENNS
"	J. H. ENNS (Eye Spec)
"	GARY K. ASH (Optometrist)
"	ROGER D. GRANT (Optometrist)
"	D. J. STANGLE (Optometrist)
Norman	D. W. MARSH
Oklahoma City	D. M. LOWRY
"	R. E. CAMPBELL (Eye Only)
"	W. D. HEATH, Ophthalmologist
Ponca City	W. W. MALL
Shawnee	A. M. WILLIAMS
Stillwater	W. H. GARNIER
Wichita	E. M. HARMS
"	E. E. TIPPIN, JR.
"	E. PARK, (Eye Only)
"	J. EATON (Eye Only)
"	R. D. WEAVERLING (Eye Only)

SURGEONS OF THE A.T.&S.F. EMPLOYEES' BENEFIT ASSOCIATION
DR. R. M. BROOKER, Chief Surgeon.....Topeka

LOCAL SURGEONS

LOCATION	DOCTORS
Abilene	D. C. CHAFFEE
"	D. C. RORABAUGH
"	K. E. CONKLIN
Ada, Kansas	C. D. WISEMAN
Arkansas City	R. F. MORTON
"	GEO. MEEK
"	G. L. CAMPBELL
"	N. C. SMITH
"	B. G. SMITH
Augusta	FRANK CVETKOVICH
"	J. L. BARBER
"	D. W. ANDERSON
"	W. N. HAFFNER
Bethany	L. N. GILBERT
Chandler	D. A. SEELIG
Cherokee	C. L. BENSON
Concordia	M. C. PEARSON
"	E. R. GELVIN
Cottonwood Falls	L. F. MCKEE
Cushing	C. M. BASSETT
"	G. R. SMITH, JR.
"	W. O. DAVIS
"	J. D. GREEN
Dighton	GEO. VON LAONROD
Dodge City	R. J. OHMAN
"	R. G. KLEIN
"	R. MCCOY
"	A. B. BUSCH
"	WM. VANTREKELL
Edmond	E. H. MURRAY
El Dorado	G. E. KASSEBAUM
"	R. M. BRIAN
"	GEO. W. HAMMEL
Ellinwood	FINDLEY LAW
Emporia	C. R. HOPPER
"	C. A. UNDERWOOD
"	E. CAMPBELL
"	D. A. GINAVAN
"	R. L. PETERSON
Enid	R. G. JACOBS
"	B. R. HINSON
Florence	J. C. SLIFER (Osteopath)
Great Bend	H. B. RUSSELL
"	D. G. SHIVEL
"	W. C. NIEDEREC
"	A. W. BEAHM
Guthrie	J. S. PETTY
Halstead	J. W. WELCH
Haysville	N. L. MORGAN, JR.
Hillsboro	A. C. EITZEN
Hutchinson	R. W. FERNIE
"	C. R. OPENSHAW
"	J. S. SPITZER
"	CHARLES T. MCCOY
Jetmore	J. G. O'SHEA
Kinsley	M. D. ATWOOD
"	W. L. MCKIM
Kiowa	L. PATZKOWSKY
Larned	W. R. BRENNER
Lincoln Center	H. L. SONGER
Little River	A. F. SCHMIDT
Lyons	R. A. SIEMENS
"	J. T. GRIMES
Marion	T. C. ENSEY
Marshall	J. F. W. DEWITT (Osteopath)
McPherson	A. H. DYCK

LOCATION	DOCTORS
Meeker	H. T. BAUGH
Midwest City	G. S. COLLINS, JR.
Minneapolis	E. DEAN BRAY
Ness City	D. B. PARKER
Newkirk	G. H. YEARY
Newton	J. W. HERTZLER
"	V. W. VOGT
"	H. R. SCHMIDT
"	F. A. ALLEN
"	E. T. OLSON
"	R. W. MYERS
"	D. V. PREHEIM
"	E. S. RICH
"	M. A. CLAASSEN
"	J. S. BENTON
"	ANDREW NACHTIGALL
"	HERBERT FRANSEN
Norman	CURTIS BERRY
"	O. M. WOODSON
"	Y. E. PARKHURST
Oklahoma City	J. N. CLYMER
"	I. C. MCLENDON
"	C. SHIELDS
"	J. N. PARKER
"	M. L. COX
"	T. E. VOGEL
"	W. L. BOWLAN
"	P. D. PATZKOWSKY
"	JOHN R. MCINNIS
"	H. A. MASTERS
"	WM. A. CROCKETT
Osborne	A. L. SCHERER
Pawnee	H. L. RATLIFF
Peabody	BETHEL CLINIC
Perkins	L. C. FREED
Perry	A. M. BROWN
"	A. M. EVANS
Ponca City	R. B. GIBSON
"	R. W. GIBSON
"	P. T. POWELL
Purcell	W. C. MCCURDY, JR.
"	W. G. LONG
"	W. T. STONE
"	J. G. ROLLINS
Salina	J. C. MITCHELL
"	C. E. SCOTT
"	W. K. NICKELL
Scott City	B. M. HOPKINS
"	G. W. FIELDS
"	J. H. LATHROP
Shawnee	PAUL GALLAHER
Spearville	G. H. HORT, D.O.
Stafford	O. W. LONGWOOD
Sterling	J. C. DYSART
Stillwater	A. B. SMITH
"	H. G. NELSON
"	H. R. SANDERS
St. John	R. P. QUACKENBUSH
Superior	P. J. HALLGRIMSON
"	T. C. KIEHAEFER
Wellington	J. L. MCGOVERN
"	W. M. COLE
"	J. L. DIACON
Wichita	D. M. THOMPSON
"	F. D. EVANS
"	HARRY HIDAKA
"	A. J. WRAY
"	E. B. WINCHESTER
" (Park City)	BETHEL CLINIC
Winfield	R. B. WHITE
"	L. R. KAUFMAN
"	M. W. WELLS



SANTA FE SAFETY FIRST



Every employee should report promptly to his Foreman, some member of the Safety Committee, or other proper person, all unsafe conditions or practices.

(See General Rules E and F, Book of Rules.)

CONDENSED SCHEDULES OF THROUGH FREIGHT TRAINS WESTWARD

		324	314	304	195	305 315	325	119 329 379	118 328 368 378	308	317	309	318	198	307
Emporia	LV	AM	PM	PM	AM	PM	PM	AM	AM	AM	PM	PM	PM	PM	PM
Wellington	AR	1215	700	825	1100	105	1000	110	215	900	100	420	530	725	800
								325	430	120	400	645	800	925	1100
								AM	AM	PM	PM	PM	PM	PM	PM
Arkansas City	LV				150	440	215								
Okla. City	LV					730	530								
Purcell	AR				600	850	700								
Sand Creek	LV	600	915	1100	PM	PM	AM								
Dodge City	AR	400	100	300											
		PM	AM	AM											

EASTWARD

		413	403	473	591	511	843	943	801	901	703 713	813 863	891	741 743	841	803
Dodge City	LV (CT)	AM	PM	PM												
Sand Creek	LV	400	445	1100												
		1000	1100	300												
					AM	PM										
Purcell	LV				120	430										
Okla. City	LV				245	600										
Arkansas City	LV				600	1000										
Wellington	LV						AM	AM	AM	AM	AM	PM	PM	PM	PM	PM
Emporia	AR	1230	245	500	845	215	340	455	555	655	1201	510	430	950	1010	1225
		PM	AM	AM	AM	AM	AM	AM	AM	AM	PM	PM	PM	PM	PM	AM

Note: The above schedules are shown for information only and confer no time table authority.