

COMPANY SURGEONS

- *Dr. Abbott Skinner, Chief Medical Officer,
Office CA 4-7408—Home MI 8-2650,
1360 Lowry Medical Arts Bldg.St. Paul, Minn.
- *Dr. Hugo F. Schroeckenstein, Asst. to Chief Medical Officer,
Office CA 4-7408—Home CA 6-6906,
1360 Lowry Medical Arts Bldg.St. Paul, Minn.
- *Dr. Darrell E. Westover,
215 Lowry Medical Arts Bldg.St. Paul, Minn.
- *Dr. John F. Alden,
1151 Lowry Medical Arts Bldg.St. Paul, Minn.
- *Dr. Robert S. Flom,
1151 Lowry Medical Arts Bldg.St. Paul, Minn.
- *Dr. Ernest R. Anderson,
Office FE 2-7508—Home TA 4-2671,
1849 Medical Arts Bldg.Minneapolis, Minn.
- *Designates also Examining Surgeon.

**OPHTHALMIC SURGEONS
(Eye Doctors)**

- Dr. Edward P. Burch,
852 Lowry Medical Arts Bldg.St. Paul, Minn.
- Dr. Donald C. Sterner,
852 Lowry Medical Arts Bldg.St. Paul, Minn.
- Dr. Malcolm A. McCannel,
325 Doctors Bldg.Minneapolis, Minn.
- Dr. Richard C. Horns,
1633 Medical Arts Bldg.Minneapolis, Minn.

ROENTGENOLOGISTS

- Dr. David A. Burlingame,
435 Lowry Medical Arts Bldg.St. Paul, Minn.
- Dr. Malcolm B. Hanson,
853 Medical Arts Bldg.Minneapolis, Minn.

D. W. HARTUNG,
Chief Dispatcher.

A. Q. FORD,
Traveling Engineer.

A. T. WALKER,
Master Mechanic.

T. C. WHITACRE,
Trainmaster.

M. M. DONAHUE,
Trainmaster.

J. H. BOYD,
Trainmaster.

F. L. HENRY,
Trainmaster.

GREAT NORTHERN RAILWAY COMPANY

TWIN CITY TERMINALS WILLMAR DIVISION

TIME TABLE 362

Effective 12:01 A. M. Central Standard Time.

Tuesday, September 3, 1963

J. G. TOOMEY, Asst. Superintendent.

E. F. OVIATT, Superintendent.

R. N. WHITMAN, General Manager.

H. J. SURLS,
General Superintendent Transportation.

Printed in U.S.A.

2 WESTWARD

FIRST SUBDIVISION—ST. PAUL TO LYNDALE JCT.

Time Table No. 362 Effective September 3, 1963		Distance from St. Paul via Passenger Tracks	FIRST CLASS												
			871	923	3	781	873	55	27	925	57				
STATIONS			N. Pac. No. 65	C. B. & Q. No. 47	G. N.	C. G. W. No. 14	N. Pac. No. 1	G. N. No. 24	G. N.	C. B. & Q. No. 21	G. N. No. 20				
		Daily	Daily	Daily	Daily	Daily	Daily	Daily	Daily	Daily	Daily				
AUTOMATIC SIGNALSSAINT PAUL.....		L 12.25Am	L 6.45Am	L 7.30Am	L 7.40Am	L 7.42Am	L 8.10Am	L 8.30Am	L 2.30Pm	L 4.30Pm				
	1.39WESTMINSTER ST. TOWER.★	1.39	12.28	6.48	7.33	7.43	7.45	8.13	8.33	2.33	4.33				
	9.18MINNEAPOLIS.....★	10.57	A 12.50Am	A 7.10Am	A 7.50Am	A 8.00Am	8.05 8.15	A 8.30Am	8.55 9.05	A 2.50Pm	A 4.52Pm				
	0.25FIRST STREET.....	10.82					A 8.17Am								
	1.35LYNDALE JCT.....★	12.17							A 9.09Am						

EASTWARD

FIRST SUBDIVISION—LYNDALE JCT. TO ST. PAUL

Time Table No. 362 Effective September 3, 1963		Distance from Lyndale Jct. via Passenger Tracks	FIRST CLASS												
			872	874	870	32	8	924	56	28	928				
STATIONS			N. Pac. No. 12	N. Pac. No. 4	N. Pac. No. 26	G. N.	G. N.	C. B. & Q. No. 22	G. N. No. 23	G. N.	C. B. & Q. No. 24				
		Mon. only	Daily Ex. Mon.	Daily	Daily	Daily	Daily	Daily	Daily	Daily	Daily	Daily			
AUTOMATIC SIGNALSSAINT PAUL.....	12.17	A 4.35Am	A 4.35Am	A 6.40Am	A 6.45Am	A 7.30Am	A 8.15Am	A 11.45Am	A 3.30Pm	A 3.50Pm				
	1.39WESTMINSTER ST. TOWER.★	10.78	4.22	4.22	6.27	6.32	7.17	8.07	11.32	3.12	3.42				
	9.18MINNEAPOLIS.....★	1.60	4.10 4.00	4.10 4.00	6.15 6.10	6.20 6.15	L 7.05Am	L 7.55Am	L 11.20Am	L 3.00Pm	L 3.30Pm				
	0.25FIRST STREET.....	1.35	L 3.58Am	L 3.58Am	L 6.08Am										
	1.35LYNDALE JCT.....★					L 6.05Am									

Westward trains are superior to eastward trains of the same class.

WESTWARD

SECOND SUBDIVISION
MINNEAPOLIS AND NORTHTOWN

EASTWARD

FIRST CLASS					Distance from Minneapolis	Time Table No. 362 Effective September 3, 1963		FIRST CLASS				
7	11	57	55	3				8	56	28	58	4
G. N.	G. N.	G. N. No. 20	G. N. No. 24	G. N.		STATIONS		G. N.	G. N. No. 23	G. N.	G. N. No. 19	G. N.
Daily	Daily	Daily	Daily	Daily				Daily	Daily	Daily	Daily	Daily
L 9.30Pm	L 5.55Pm	L 5.00Pm	L 8.35Am	L 7.55Am	AUTOMATIC SIGNALSMINNEAPOLIS.....★ 0.20BRIDGE SWITCH.... 1.37MPLS. JCT. WYE.... 2.29NORTHTOWN.....	A 7.00Am	A 11.15Am	A 2.50Pm	A 7.35Pm	A 8.01Pm
9.31	5.56	5.01	8.36	7.56	0.20			6.59	11.14	2.47	7.30	8.00
9.33	5.58	5.03	8.38	7.58	1.37			6.57	11.12	2.45	7.27	7.58
A 9.39Pm	A 6.04Pm	A 5.09Pm	A 8.44Am	A 8.04Am	2.29			L 6.51Am	L 11.06Am	L 2.39Pm	L 7.21Pm	L 7.53Pm
					3.86							

Westward trains are superior to eastward trains of the same class.

MAXIMUM
Between
St. Paul and Minneapolis
First St. North, Minneapolis, and
Northtown and Van Buren St. N.
Van Buren St. N. E. and Harrison
Minneapolis Jct. and First St. North

SPECIAL INSTRUCTIONS
ST. PAUL

Trains or Engines heading in or out of
Back up movement
Trains and engines on track between
tracks, St. Paul and connecting
commonly known as Thumbs-Up

SPECIAL INSTRUCTIONS
SUBDIVISIONS ON

FIRST SUBDIVISION—ST. PAUL TO LYNDALE JCT.

WESTWARD 2

FIRST CLASS

				11	875	7	31	877	879	929								
				G. N.	N. Pac. No. 25	G. N.	G. N.	N. Pac. No. 11	N. Pac. No. 3	C. B. & Q. No. 23								
				Daily	Daily	Daily	Daily	Sat. only	Daily Ex. Sat.	Daily								
				L 5.30Pm	L 7.20Pm	L 8.55Pm	L 9.50Pm	L 10.22Pm	L 10.22Pm	L 10.35Pm								
				5.33	7.23	8.58	9.53	10.25	10.25	10.38								
				A 5.50Pm	7.45 7.55	A 9.15Pm	10.15 10.20	10.50 11.15	10.50 11.15	A 11.00Pm								
					A 7.56Pm			A 11.17Pm	A 11.17Pm									
							A 10.24Pm											

FIRST SUBDIVISION—LYNDALE JCT. TO ST. PAUL

EASTWARD

FIRST CLASS

				58	4	788	876	14	930	878								
				G. N. No. 19	G. N.	C. G. W. No. 13	N. Pac. No. 2	G. N.	C. B. & Q. No. 48	N. Pac. No. 66								
				Daily	Daily	Daily	Daily	Daily	Daily	Daily								
				A 8.00Pm	A 8.30Pm	A 8.32Pm	A 9.20Pm	A 9.50Pm	A 9.50Pm	A 11.20Pm								
				7.52	8.20	8.22	9.07	9.37	9.42	11.02								
				L 7.40Pm	L 8.08Pm	L 8.10Pm	8.55 8.47	9.25 9.15	L 9.30Pm	L 10.50Pm								
							L 8.45Pm											
								L 9.10Pm										

eastward trains of the same class.

MAXIMUM PERMISSIBLE SPEED.

Between	Passenger	Freight
St. Paul and Minneapolis	55 M.P.H.	30 M.P.H.
St. Paul, Minneapolis, and Lyndale Junction	30 M.P.H.	30 M.P.H.
St. Paul and Van Buren St. N. E.	45 M.P.H.	30 M.P.H.
St. Paul, N. E. and Harrison St. N. E.	20 M.P.H.	20 M.P.H.
St. Paul Jct. and First St. North, Minneapolis	30 M.P.H.	20 M.P.H.

SPEED RESTRICTIONS.

ST. PAUL UNION DEPOT PROPERTY.

	Passenger	Freight
Engines heading in or out	10 M.P.H.	10 M.P.H.
Engines in movement	8 M.P.H.	8 M.P.H.
Engines on track between east end of freight track, St. Paul and connection with Depot tracks, known as Thumbs-Up	5 M.P.H.	5 M.P.H.

SPECIAL INSTRUCTIONS FIRST AND SECOND DIVISIONS ON PAGES THREE, FOUR AND FIVE.

SPEED RESTRICTIONS—Continued.

	Passenger	Freight
Eastward train and engine movements, on eastward passenger track, with or without cars, between Jackson St. overhead bridge and Third Street, St. Paul	30 M.P.H.	20 M.P.H.
Between East End Stone Arch Bridge and Minneapolis	30 M.P.H.	20 M.P.H.
Minneapolis Passenger Station, all tracks between Mill Pond Bridge, First St. North, C. & N. W. Ry. crossing, and CB&Q RR. crossing	Restricted Speed	Restricted Speed
Minneapolis Passenger Station wye track	8 M.P.H.	8 M.P.H.
For movements between Home Signals of Interlocking at Mulberry Street:		
With the current of traffic on Main Tracks	30 M.P.H.	15 M.P.H.
Against the current of traffic on main tracks and on other than main tracks	15 M.P.H.	15 M.P.H.
Unless conditions require a further speed restriction, trains or engines moving against current of traffic on double track through interlockings, or making diverging movements through switches and crossovers	15 M.P.H.	15 M.P.H.

SPECIAL INSTRUCTIONS

1. PASSENGER TRACKS:

Two right hand main tracks between Third Street, St. Paul, and St. Anthony Park.

Two left hand main tracks between St. Anthony Park and West end of Mill Pond Bridge.

FREIGHT TRACKS:

Two left hand main tracks between Third Street, St. Paul, and St. Anthony Park.

Two right hand main tracks between St. Anthony Park and Union Yard puzzles.

PASSENGER AND FREIGHT TRACKS:

Both main tracks between First Street North, Minneapolis, and Northtown, via Minneapolis Junction.

Five main tracks designated below between First Street North, Minneapolis, and Lyndale Junction:

No. 1, Switching lead—north track.

No. 2, Westward track for G. N. passenger and freight trains.

No. 3, Eastward track for G. N. passenger and freight trains.

No. 4, Westward track for freight trains.

No. 5, Eastward track for freight trains.

Trains using freight tracks Nos. 4 and 5 shall stop before passing over the Holden Street crossing and will not proceed until proper signal is received from switchtender.

ROUTING OF TRAINS AND ENGINES.

2. Switchtenders will route trains and engines at Minneapolis Passenger Station, First Street North, Second Street North, Holden Street, Lyndale Junction, Union Yard puzzles, West End Union "R" Yard, Minneapolis Junction East Wye, West Wye, Van Buren Street, and Northtown. Trains and engines will not proceed until proper signal is received from switchtenders to pass through or over switchtenders' territory, except one switchtender will handle switchtender's assignments at Second and First Streets North, Minneapolis, during the hours of 10:30 PM to 6:30 AM, and movements can be made through those territories on one proceed signal instead of two signals; and except at Van Buren Street between hours of 10:30 PM and 6:30 AM daily, all trains and engines moving through or into that switchtender's territory will be required to line up their own routes.

TRAIN REGISTER AND CLEARANCE EXCEPTIONS.

3. Northtown—Lyndale Junction—Trains originating at these points will not require clearance when train order signal indicates proceed.

Minneapolis Passenger Station—All trains register and receive clearance.

C. & N. W. Ry. westward passenger trains arriving at Westminster Street Tower via East St. Paul may proceed to Third Street, St. Paul, over eastward passenger track without Great Northern clearance.

REGISTER STATIONS

St. Paul Passenger trains.

Westminster St. Tower Freight trains.

Minneapolis Jct. Freight trains.

Minneapolis Passenger Station Passenger trains.

Northtown All trains, passenger trains may register by ticket.

MINNEAPOLIS PASSENGER STATION.

4. Minneapolis—All trackage within switchtenders' limits from west end of Mill Pond Bridge east of depot extending through to eastward main track west of depot, and between First Street North and east leg of wye, will be considered depot station tracks of the Minneapolis Passenger Station, and while within these limits it will not be necessary to observe Rule 99.

There is no superiority of trains on depot station tracks. All trains and engines, with or without cars, entering and leaving depot station tracks will move only on hand signal from switchtenders and must approach and proceed within these limits at restricted speed expecting to find track occupied and be pre-

pared to stop. A proceed signal from switchtender is no assurance that track ahead is clear.

Before starting westward train from Minneapolis Passenger Station, engineers will know way is clear at crossing beyond stop board before proceeding over the crossing, and the stop made by train in the west end of passenger station will be regarded as a stop for stop board at the west end of station.

5. Train, engines or cars must not be moved over Railroad Crossing of the C. & N. W. Ry. or the C. B. & Q. R. R. west of Minneapolis Passenger Station without flagman or member of crew in charge of movement first stationing themselves at crossing to prevent opposing movements. This rule not to apply to movements on freight tracks, which are covered by other rules.

MISCELLANEOUS

6. Between St. Paul and Minneapolis Passenger Station, employees will not permit any part of their person to project beyond the sides of moving engines or cars. On trains, engines or cars having windshields, windows, doors or ventilators that open outward same should be kept closed between St. Paul and Minneapolis.
7. On all trackage, Twin City Terminals, lighted fuses must not be used, except in cases of emergency, and then only when held in hand and must be extinguished before leaving; also, in this same area, the use of torpedoes is prohibited.
8. On westward passenger track, engineers on moving engines will keep engine bell ringing passing Great Northern Union Yard puzzle switches, located just west of St. Anthony Elevator, to 15th Avenue S.E.
9. Passenger extra trains may run ahead of first class trains between St. Paul and Minneapolis; between Minneapolis and Lyndale Jct.; and between Minneapolis and Northtown.
10. Employees are prohibited from riding or walking on the roof of any moving car, except when absolutely necessary in the passing of signals, and then only when they place themselves near the middle of the car.
11. Rule 2 of the Consolidated Code of Operating Rules is modified for Great Northern Railway Company employees to the extent that a watch certificate form is no longer required. Watches of employees will be inspected by Division Officers, Rules Examiners, and other designated officers. Rule 3(C) of the Consolidated Code of Operating Rules is amended as follows: Employees governed by time service rules must not wear wrist watches while on duty unless such watches are of an approved type. Approved type wrist watches are: Elgin, B. W. Raymond model, 13/0 size, 23 jewels; or Ball Official Standard, 1604-B, stainless steel 13/0 ligne, 21 jewels; or Bulova Accutron Railroad Approved Model; or Hamilton 505 R. R. Electric Special.
12. Regarding Consolidated Code Rule 103. In addition to complying with the provisions of this rule, members of a crew will be governed by the following: "When an engine, with or without cars, is about to move over a public crossing not protected by a watchman, by gates or by crossing signals in operation, a member of the crew must be on the ground at the crossing to provide protection."
13. Great Northern trains using the CB&Q interlocker at St. Paul Depot to back in, will not start their back-up movement until the rear brakeman is in the rear end of the rear car with the conductor to assist the conductor in observing the position of switches and signal indications.
14. All trains entering St. Paul Depot Company Trackage at Third Street will stop unless they receive a proceed signal from the Switchtender.
15. This is authority to honor passes of tenant lines railways' train and engine men between Twin Cities, except on Trains 31 and 32.
16. COMO AVENUE CROSSOVER MOVEMENTS. There is no superiority of trains on the two passenger main tracks between the following locations. Between signal 2.3 (on the westward passenger main track) located about 800 feet east of Rice Street overhead bridge and signal 4.4 (on eastward passenger main track) located on Lexington Ave. overhead

bridge. The portion of Consolidated Code Rule 93 reading—
 "Within Yard limits the main track may be used, clearing first
 class trains when due to leave the last station where time is
 shown"—does not apply between signal 2.3 and signal 4.4.

Before making a crossover movement at this location, a member
 of the crew must contact the operator at Westminster Tower
 and obtain his permission to make the movement. The switches
 then lined in their proper order following the instructions for
 the electric locked switches as posted at the electric lock.

MINNEAPOLIS.

17. Eastward freight trains at Lyndale Junction, and westward
 freight trains at First Street North, may run ahead of first class
 trains between those points after receiving proceed signal from
 switchtender.

18. Lyndale Junction — Eastward freight trains on Willmar line,
 having cars to set out at this point, will stop before passing east-
 ward Home Signal to make set-out.

19. Minneapolis Junction—Trains must stop before passing over the
 crossing of the N. P. Ry. Industry Track 460 feet East of Junction
 yard office, unless proceed signal is received from switch-
 tender.

20. The Laws of the Cities of St. Paul and Minneapolis prohibit the
 unnecessary use of the engine whistle within those limits.

21. Operation of Spring Switches. Spring switches of two different
 types are in use on this division.

Without facing point lock:

(a) East leg of wye at Mississippi Street to track leading to
 8th Street, St. Paul. Normal position is for west leg of
 wye.

(b) Four spring switches located at east end Minneapolis
 Junction Roundhouse.

(1) leading off Roundhouse lead to westward main line
 towards First St. North. Normal position is for main
 track.

(2) leading off Roundhouse lead to Main Line 4, opposite
 turn table. Normal position is for main track.

(3) leading off Roundhouse lead to Main Line 4, opposite
 yard office. Normal position is for main track.

(4) East end Roundhouse lead opposite yard office. Nor-
 mal position is for east lead #2.

With facing point lock:

(a) East end of eastward freight track near Fourth Street,
 St. Paul. Normal position is for westward freight track.

22. The normal position of a spring switch with facing point lock is
 identified by a color light type signal displaying a lunar white
 light for train or engine movements in a trailing point direction
 and for movements in facing point direction when conditions
 require.

23. The normal position of a spring switch without facing point lock
 is identified by a triangular yellow target on switch stand with
 letter "S" in black, and "lunar white" light in switch lamp in
 place of green light displayed in both directions through or over
 the switch.

24. Facing point locks on hand operated switches are indicated by a
 six inch yellow stripe painted on target staff. Be positive locking
 device is restored to normal position after using. A running
 switch must not be made through this type switch.

25. Loaded dump cars should not be handled on double track after
 dark, but if necessary to do so, close watch must be kept by
 trainmen and if a car dumps its load, train must be stopped and
 protection afforded on the opposite track.

26. Due to limited overhead clearance at tunnels and structures,
 employes are warned to keep off top of cars of extreme height
 and width when handled in trains and yards, except in emer-
 gency. In absence of previous advice on such cars, wire proper
 officer for instructions.

27. When any passenger car or cars are left on any track, the hand
 brakes must be adequately applied on each car. The brakes on
 one passenger car are not to be depended upon to hold other
 cars when coupled together.

YARD LIMITS

ST. PAUL-MINNEAPOLIS.

28. St. Paul to yard limit board west of the west Fridley yard
 switch; Minneapolis Jct. to yard limit board 2640 feet west of
 the new spur head block about 3 miles west of Hopkins Jct., in-
 cluding Hopkins Branch; and 5636 feet west of Junction
 Switch (Osseo Line).

Automatic Interlocking

29. MinneapolisMulberry Street with N. P. Ry.

If a train is stopped at a home signal and no immediate conflict-
 ing train movement is evident, trainman may signal train to
 proceed over crossing, after making certain that conflicting home
 signals indicate Stop.

30. To insure safe movement on descending grade, trains and en-
 gines using Eastward freight track at Westminster Street Inter-
 locking must stop at Eastward Home Signal located about 200
 feet West of Tower. This signal governs movement over safety
 derail and will not be changed to indicate Proceed until stop is
 made.

Manual Interlocking

31. St. Anthony Park.....St. Paul

Manual Interlocking with Dual Control Switches

32. Westminster StreetSt. Paul

15th Avenue S.E.Minneapolis

Boom IslandMinneapolis

Westminster Street—Between the home signal limits of West-
 minster Street Interlocking, train or engine movements may be
 made in either direction, ON EITHER PASSENGER TRACK,
 by signal indication.

For movements on the Passenger or Freight Tracks, the home
 signal limits, Rule 605, of Westminster Street Interlocking, in-
 clude all trackage between the eastward home signal located
 approximately 850 feet west of Mississippi Street overhead
 bridge and the westward home signal located approximately 900
 feet west of Third Street overhead bridge.

Telephones for communication are located at the home signals,
 in bungalows, and in Northern Pacific switchtender's shanty
 near Third Street.

15th Avenue S. E. is controlled from St. Anthony Park Inter-
 locking. Telephones for communication are located in booths
 near the east and west interlocking limits.

Semi-Automatic Interlockings

33. St. PaulFair Grounds Spur with N. P. Ry.

HopkinsM. & St. L. Div. of C. & N. W. Ry. Crossing.

St. Paul, Great Northern train movements over the crossing will
 be governed by manually operated gates together with standard
 interlocking dwarf signal indications. Great Northern routes
 over the crossing will be set manually after obtaining release of
 electric lock holding gates in "Stop" position. See instructions
 posted in box locked with a switch lock.

Hopkins, Great Northern train and engine movements over the
 crossing will be governed by "Stop" signs located each side of
 crossing, and by manually operated crossing gates, with red
 lights, normally set and electrically locked across G. N. track.
 See instructions posted in box locked with a switch lock.

ST. PAUL UNION DEPOT & MINNESOTA TRANSFER

34. The Consolidated Code of Operating Rules, Edition of 1959, in addition to the following instructions will govern Great Northern employes while operating on Minnesota Transfer Railway Co. and St. Paul Union Depot Company trackage:—

- (a) All trackage of the Minnesota Transfer Railway Company is defined as a system of tracks within yard limits over which movements must be made at restricted speed and are not authorized by timetable, or train order, but subject to prescribed signals and rules or special instructions. The limits of the Saint Paul Union Depot Company property extend from connection with the Northern Pacific Ry. and Great Northern Ry. tracks at Third Street and connection with the CMStP&P-CB&Q R.R. tracks opposite depot roundhouse, on the east, to connection with the CGW Ry. and CMStP&P R.R. tracks at Robert Street on the west.
- (b) The timetable of the Saint Paul Union Depot Company is for information only. Employes of railroads using the tracks of this Company will be governed by current timetable of their respective Companies only as to arriving and departing time of trains.
- (c) Where in the rules of the Consolidated Code reference is made to trains, such rules will also apply to yard movements and engines.
- (d) Under Rule 15, the use of torpedoes is prohibited.
- (e) Under Rule 11, burning fusees must not be used except in case of emergency and then only when held in hand and must be extinguished before leaving.

THE FOLLOWING RULES APPLY ONLY ON THE ST. PAUL UNION DEPOT COMPANY PROPERTY:

- (f) There is no superiority of trains within the limits of Saint Paul Union Depot Company property.
- (g) Within the limits of the Saint Paul Union Depot Company property trains and engines must move at restricted speed and must not exceed ten (10) miles per hour through crossovers, turnouts and puzzle switches. The entrance to and all movements on this property will be made only on authority of hand signals from switch tenders. No train or engine may foul any track or puzzle

switch without authority of hand signals from switch tenders in control of such movements, except that short interior switching movements may be made through crossovers connecting shed tracks when authorized by train director. Any lead or track may be used for the make-up of trains on authority of train director. The movement of trains should be given preference.

- (h) When indicated by the ringing of the bell, flashing of headlight, hand or light signal that a train or engine is ready to move, the switch tender in charge of the shed track on which the movement is standing will handle as follows: at west end of station the switch tender will control the movement by hand or light signal; at the east end of station the switch tender will inform the train director, who will route the movement by instructions over the public address system. Switch tenders will be governed by these instructions, relaying such instructions by hand or light signal to the next switch tender in the direction of the movement, each must receive an acknowledgment before signalling the movement. Signals must not be acknowledged or acted upon unless the signal corresponds with instructions from the train director and is definitely understood.
- (i) When backing, the back-up air brake valve on passenger trains must be operated by the conductor, except in the movement of empty equipment, it may be operated by a competent trainman or yardman. When practicable, conductors must see that trainmen are stationed so hand or light signals may be used, in case of any emergency. When backing a train, the engine brake valve must be in running position; an application of the brakes must be made with back-up brake valve before starting and it must be known that the brakes are in operative condition. Movement must not be started until the proper signal is given. A running test must be made with the back-up air brake valve before the train has moved 300 feet; if the running test is not made within 300 feet the engineer must stop the train and ascertain cause. The speed of train must not exceed eight (8) miles per hour and train must be under such control that it can be stopped short of train, or obstruction, and short of bumping post on stub tracks.
- (j) Headlights must be dimmed while on shed tracks.